

CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINES OR PUMPS

F01 MACHINES OR ENGINES IN GENERAL; ENGINE PLANTS IN GENERAL; STEAM ENGINES

F01D NON-POSITIVE DISPLACEMENT MACHINES OR ENGINES, e.g. STEAM TURBINES (machines or engines for liquids [F03](#); non-positive displacement pumps [F04D](#))

NOTES

- This subclass covers:
 - non-positive-displacement engines for elastic fluids, e.g. steam turbines;
 - non-positive-displacement engines for liquids and elastic fluids;
 - non-positive-displacement machines for elastic fluids;
 - non-positive-displacement machines for liquids and elastic fluids.
- Attention is drawn to the Notes preceding class [F01](#), especially as regards the definitions of "reaction type", e.g. with airfoil-like blades, and "impulse type", e.g. bucket turbines.

WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Non-positive-displacement machines or engines, e.g. steam turbines (wit working-fluid flows in opposite axial directions for balancing axial thrust F01D 3/02; with other than pure rotation F01D 23/00; turbines characterised by their use in special steam systems, cycles, or processes, regulating devices therefor F01K)	1/16	. . characterised by having both reaction stages and impulse stages
		1/18	. without stationary working-fluid guiding means; (F01D 1/24 , F01D 1/32 , F01D 1/34 take precedence; { with pressure-velocity transformation exclusively in rotor F01D 1/32 })
1/02	. with stationary working-fluid guiding means and bladed or like rotor, {e.g. multi-bladed impulse steam turbines} (F01D 1/24 takes precedence; without stationary working-fluid guiding means F01D 1/18)	1/20	. . traversed by the working-fluid substantially axially
		1/22	. . traversed by the working-fluid substantially radially
		1/24	. characterised by counter-rotating rotors subjected to same working fluid stream without intermediate stator blades or the like
1/023	. . {the working-fluid being divided into several separate flows (F01D 3/02 takes precedence); several separate fluid flows being united in a single flow; the machine or engine having provision for two or more different possible fluid flow paths}	1/26	. . traversed by the working-fluid substantially axially
		1/28	. . traversed by the working-fluid substantially radially
1/026	. . {Impact turbines with buckets, i.e. impulse turbines, e.g. Pelton turbines (F01D 1/16 , F01D 1/34 take precedence)}	1/30	. characterised by having a single rotor operable in either direction of rotation, e.g. by reversing of blades (combinations of machines or engines F01D 13/00)
1/04	. . traversed by the working-fluid substantially axially	1/32	. with pressure velocity transformation exclusively in rotor, e.g. the rotor rotating under the influence of jets issuing from the rotor, {e.g. Heron turbines (the working fluid being a combustion products F02C 3/165 ; jet propulsion plants per se F02K)}
1/06	. . traversed by the working-fluid substantially radially		
1/08	. . . having inward flow		
1/10	. . having two or more stages subjected to working-fluid flow without essential intermediate pressure change, i.e. with velocity stages (F01D 1/12 takes precedence)	1/34	. characterised by non-bladed rotor, e.g. with drilled holes (F01D 1/32 takes precedence; sirens G10K 7/00 {; impact turbines with buckets F01D 1/026 ; hand-held tools with a non-bladed rotor F01D 15/067 })
1/12	. . with repeated action on same blade ring		
1/14	. . . traversed by the working-fluid substantially radially	1/36	. . using fluid friction
		1/38	. . of the screw type

3/00	Machines or engines with axial-thrust balancing effected by working-fluid	5/088 {in a closed cavity}
3/02	. characterised by having one fluid flow in one axial direction and another fluid flow in the opposite direction	5/10	. . Anti- vibration means {(specially adapted for radial flow machines or engines F01D 5/04)}
3/025	. . {with a centrally disposed radial stage}	5/12	. Blades ({specially adapted for radial flow machines or engines F01D 5/04 }; blade roots F01D 5/30 ; rotors with blades adjustable in operation F01D 7/00 ; stator blades F01D 9/02)
3/04	. axial thrust being compensated by thrust-balancing dummy piston or the like	5/14	. . Form or construction (selecting particular materials, measures against erosion or corrosion F01D 5/28)
5/00	Blades; Blade-carrying members (nozzle boxes F01D 9/02); Heating, heat-insulating, cooling or antivibration means on the blades or the members {(special arrangements in rotors dealing with breaking off of part thereof F01D 21/045)}	5/141 {Shape, i.e. outer, aerodynamic form (F01D 5/148 - F01D 5/20 take precedence; blade construction F01D 5/147)}
5/005	. {Repairing methods or devices}	5/142 {of the blades of successive rotor or stator blade-rows}
5/02	. Blade-carrying members, e.g. rotors (rotors of non-bladed type F01D 1/34 ; stators F01D 9/00 ; selecting particular materials F01D 5/28)	5/143 {Contour of the outer or inner working fluid flow path wall, i.e. shroud or hub contour}
5/021	. . {for flow machines or engines with only one axial stage (for more than one stage F01D 5/06)}	5/145 {Means for influencing boundary layers or secondary circulations (for compressors F04D 29/68)}
5/022	. . {with concentric rows of axial blades}	5/146 {of blades with tandem configuration, split blades or slotted blades}
5/023	. . {of the screw type}	5/147 {Construction, i.e. structural features, e.g. of weight-saving hollow blades (F01D 5/148 , F01D 5/16 and F01D 5/20 take precedence; blade shape F01D 5/141 ; blades with cooling or heating channels or cavities F01D 5/18 ; heating, heat-insulating or cooling means on blades F01D 5/18)}
5/025	. . {Fixing blade carrying members on shafts (attachment of a member on a shaft in general F16D 1/06 ; for non-positive displacement pumps F04D 29/00)}	5/148 {Blades with variable camber, e.g. by ejection of fluid}
5/026	. . {Shaft to shaft connections}	5/16	. . . for counteracting blade vibration
5/027	. . {Arrangements for balancing (for balancing rotating bodies in general F16F 15/32 ; for compensating unbalance G01M 1/36)}	5/18	. . . Hollow blades, {i.e. blades with cooling or heating channels or cavities (structure of hollow blades in general F01D 5/147)}; Heating, heat-insulating or cooling means on blades
5/028	. . {the rotor disc being formed of sheet laminae (rotor blade aggregates of unitary construction F01D 5/34)}	5/181 {Blades having a closed internal cavity containing a cooling medium, e.g. sodium}
5/03	. . Annular blade-carrying members having blades on the inner periphery of the annulus and extending inwardly radially, i.e. inverted rotors	5/182 {Transpiration cooling}
5/04	. . for radial-flow machines or engines	5/183 {Blade walls being porous}
5/041	. . . {of the Ljungström type}	5/184 {Blade walls being made of perforated sheet laminae}
5/043	. . . {of the axial inlet- radial outlet, or <u>vice versa</u> , type}	5/185 {Liquid cooling (F01D 5/181 takes precedence)}
5/045 {the wheel comprising two adjacent bladed wheel portions, e.g. with interengaging blades for damping vibrations}	5/186 {Film cooling (F01D 5/187 takes precedence)}
5/046 {Heating, heat insulation or cooling means}	5/187 {Convection cooling}
5/048 {Form or construction}	5/188 {with an insert in the blade cavity to guide the cooling fluid, e.g. forming a separation wall}
5/06	. . Rotors for more than one axial stage, e.g. of drum or multiple disc type; Details thereof, e.g. shafts, shaft connections {(F01D 5/022 , F01D 5/023 take precedence)}	5/189 {the insert having a tubular cross-section, e.g. airfoil shape}
5/063	. . . {Welded rotors (welding <u>per se</u> B23K)}	5/20	. . . Specially-shaped blade tips to seal space between tips and stator {(F01D 5/225 takes precedence)}
5/066	. . . {Connecting means for joining rotor-discs or rotor-elements together, e.g. by a central bolt, by clamps}	5/22	. . Blade-to-blade connections, {e.g. for damping vibrations}
5/08	. . Heating, heat-insulating or cooling means {(specially adapted for radial flow machines or engines F01D 5/04)}	5/225	. . . {by shrouding}
5/081	. . . {Cooling fluid being directed on the side of the rotor disc or at the roots of the blades (F01D 5/087 takes precedence)}	5/24	. . . using wire or the like
5/082 {on the side of the rotor disc}	5/26	. . Antivibration means not restricted to blade form or construction or to blade-to-blade connections {or to the use of particular materials}
5/084 {the fluid circulating at the periphery of a multistage rotor, e.g. of drum type}		
5/085	. . . {cooling fluid circulating inside the rotor}		
5/087 {in the radial passages of the rotor disc}		

- 5/28 . . . Selecting particular materials; {Particular measures relating thereto;} Measures against erosion or corrosion
- 5/282 . . . {Selecting composite materials, e.g. blades with reinforcing filaments}
- 5/284 . . . {Selection of ceramic materials}
- 5/286 . . . {Particular treatment of blades, e.g. to increase durability or resistance against corrosion or erosion (F01D 5/288 takes precedence)}
- 5/288 . . . {Protective coatings for blades}
- 5/30 . . . Fixing blades to rotors; Blade roots {; Blade spacers}
- 5/3007 . . . {of axial insertion type}
- 5/3015 . . . {with side plates}
- 5/3023 . . . {of radial insertion type, e.g. in individual recesses}
- 5/303 . . . {in a circumferential slot}
- 5/3038 {the slot having inwardly directed abutment faces on both sides}
- 5/3046 . . . {the rotor having ribs around the circumference}
- 5/3053 . . . {by means of pins}
- 5/3061 . . . {by welding, brazing}
- 5/3069 . . . {between two discs or rings}
- 5/3076 . . . {Sheet metal discs}
- 5/3084 . . . {the blades being made of ceramics}
- 5/3092 . . . {Protective layers between blade root and rotor disc surfaces, e.g. anti-friction layers (F01D 5/288 takes precedence)}
- 5/32 . . . Locking, e.g. by final locking blades or keys
- 5/323 {Locking of axial insertion type blades by means of a key or the like parallel to the axis of the rotor}
- 5/326 {Locking of axial insertion type blades by other means}
- 5/34 . . . Rotor-blade aggregates of unitary construction {, e.g. formed of sheet laminae; (discs formed of sheet laminae F01D 5/028; ceramic materials F01D 5/284, composite materials F01D 5/282)}
- 7/00 Rotors with blades adjustable in operation; Control thereof (for reversing F01D 1/30)**
- 7/02 . . . having adjustment responsive to speed
- 9/00 Stators**
- 9/02 . . . Nozzles; Nozzle boxes; Stator blades; Guide conduits {, e.g. individual nozzles (nozzle boxes F01D 9/047)}
- 9/023 . . . {Transition ducts between combustor cans and first stage of the turbine in gas-turbine engines; their cooling or sealings}
- 9/026 . . . {Scrolls for radial machines or engines}
- 9/04 . . . forming ring or sector
- 9/041 {using blades (F01D 5/148 takes precedence)}
- 9/042 {fixing blades to stators (fixing stator-rings in the casing or to each other F01D 25/246)}
- 9/044 {permanently, e.g. by welding, brazing, casting or the like}
- 9/045 {for radial flow machines or engines}
- 9/047 {Nozzle boxes}
- 9/048 {for radial admission}
- 9/06 . . . Fluid supply conduits to nozzles or the like
- 9/065 . . . {Fluid supply or removal conduits traversing the working fluid flow, e.g. for lubrication-, cooling-, or sealing fluids (see also F01D 25/16, F01D 25/24 and F01D 25/26)}
- 11/00 Preventing or minimising internal leakage of working-fluid, e.g. between stages (sealings in general F16J {; sealing arrangements for transition ducts of combustor cans F01D 9/023)}**
- 11/001 . . . {for sealing space between stator blade and rotor}
- 11/003 . . . {by packing rings; Mechanical seals}
- 11/005 . . . {Sealing means between non relatively rotating elements}
- 11/006 . . . {Sealing the gap between rotor blades or blades and rotor}
- 11/008 {by spacer elements between the blades, e.g. independent interblade platforms}
- 11/02 . . . by non-contact sealings, e.g. of labyrinth type (for sealing space between rotor blade tips and stator F01D 11/08)
- 11/025 . . . {Seal clearance control; Floating assembly; Adaptation means to differential thermal dilatations}
- 11/04 . . . using sealing fluid, e.g. steam
- 11/06 Control thereof
- 11/08 . . . for sealing space between rotor blade tips and stator (specially-shaped blade tips therefor F01D 5/20)
- 11/10 . . . using sealing fluid, e.g. steam
- 11/12 . . . using a rubstrip, e.g. erodible. deformable or resiliently-biased part
- 11/122 {with erodable or abradable material (blades having cutting or grinding tips F01D 5/20)}
- 11/125 {with a reinforcing structure}
- 11/127 {with a deformable or crushable structure, e.g. honeycomb}
- 11/14 . . . Adjusting or regulating tip-clearance, i.e. distance between rotor-blade tips and stator casing (rotors with blades adjustable in operation F01D 7/00)
- 11/16 by self-adjusting means (F01D 11/12 takes precedence)
- 11/18 using stator or rotor components with predetermined thermal response, e.g. selective insulation, thermal inertia, differential expansion
- 11/20 Actively adjusting tip-clearance
- 11/22 by mechanically actuating the stator or rotor components, e.g. moving shroud sections relative to the rotor
- 11/24 by selectively cooling-heating stator or rotor components
- 13/00 Combinations of two or more machines or engines (F01D 15/00 takes precedence; combinations of two or more pumps F04; fluid gearing F16H)**
- 13/003 . . . {with at least two independent shafts, i.e. cross-compound}
- 13/006 . . . {one being a reverse turbine}
- 13/02 . . . Working-fluid interconnection of machines or engines
- 15/00 Adaptations of machines or engines for special use; Combinations of engines with devices driven thereby**
- 15/005 . . . {Adaptations for refrigeration plants}
- 15/02 . . . Adaptations for driving vehicles, e.g. locomotives

15/04	. . the vehicles being waterborne vessels	17/26	. . . fluid, e.g. hydraulic
15/045	. . . {Control thereof}	19/00	Starting of machines or engines; Regulating, controlling, or safety means in connection therewith (warming-up before starting F01D 25/10; turning or inching gear F01D 25/34)
15/06	. Adaptations for driving, or combinations with, hand-held tools or the like {control thereof}	19/02	. dependent on temperature of component parts, e.g. of turbine-casing
15/062	. . {Controlling means specially adapted therefor}	21/00	Shutting-down of machines or engines, e.g. in emergency; Regulating, controlling, or safety means not otherwise provided for
15/065	. . {with pressure-velocity transformation exclusively in rotor}	21/003	. {Arrangements for testing or measuring (for measuring vibrations G01H)}
15/067	. . {characterised by non-bladed rotor}	21/006	. {Arrangements of brakes (brakes per se F16D)}
15/08	. Adaptations for driving, or combinations with, pumps	21/02	. Shutting-down responsive to overspeed
15/10	. Adaptations for driving, or combinations with, electric generators	21/04	. responsive to undesired position of rotor relative to stator {or to breaking-off of a part of the rotor}, e.g. indicating such position
15/12	. Combinations with mechanical gearing (driven by multiple engines F01D 13/00)	21/045	. . {special arrangements in stators or in rotors dealing with breaking-off of part of rotor}
17/00	Regulating or controlling by varying flow (for reversing F01D 1/30; by varying rotor-blade position F01D 7/00; specially for starting F01D 19/00; shutting-down F01D 21/00; regulating or controlling in general G05 ; specially adapted for hand-held tools or the like F01D 15/06)	21/06	. . Shutting-down
17/02	. Arrangement of sensing elements	21/08	. . Restoring position
17/04	. . responsive to load	21/10	. responsive to unwanted deposits on blades, in working-fluid conduits or the like
17/06	. . responsive to speed	21/12	. responsive to temperature
17/08	. . responsive to condition of working-fluid, e.g. pressure	21/14	. responsive to other specific conditions
17/085	. . . {to temperature}	21/16	. Trip gear
17/10	. Final actuators (valves in general F16K {; blades with variable camber F01D 5/148 })	21/18	. . involving hydraulic means
17/105	. . {by passing part of the fluid}	21/20	. Checking operation of shut-down devices
17/12	. . arranged in stator parts	23/00	Non-positive-displacement machines or engines with movement other than pure rotation, e.g. of endless-chain type
17/14	. . . varying effective cross-sectional area of nozzles or guide conduits	25/00	Component parts, details, or accessories, not provided for in, or of interest apart from, other groups
17/141 {by means of shiftable members or valves obturating part of the flow path}	25/002	. {Cleaning of turbomachines}
17/143 {the shiftable member being a wall, or part thereof of a radial diffuser}	25/005	. {Selecting particular materials}
17/145 {by means of valves, e.g. for steam turbines (valves in general F16K)}	25/007	. {Preventing corrosion}
17/146 {by throttling the volute inlet of radial machines or engines}	25/02	. De-icing means for engines having icing phenomena
17/148 {by means of rotatable members, e.g. butterfly valves}	25/04	. Antivibration arrangements
17/16 by means of nozzle vanes	25/06	. . for preventing blade vibration (means on blade-carrying members or blades F01D 5/00)
17/162 {for axial flow, i.e. the vanes turning around axes which are essentially perpendicular to the rotor centre line (F01D 17/167 takes precedence)}	25/08	. Cooling (of machines or engines in general F01P); Heating; Heat-insulation (of blade-carrying members, of blades F01D 5/00)
17/165 {for radial flow, i.e. the vanes turning around axes which are essentially parallel to the rotor centre line (F01D 17/167 takes precedence)}	25/10	. . Heating, e.g. warming-up before starting
17/167 {of vanes moving in translation}	25/12	. . Cooling
17/18	. . . varying effective number of nozzles or guide conduits {, e.g. sequentially operable valves for steam turbines}	25/125	. . . {of bearings}
17/20	. Devices dealing with sensing elements or final actuators or transmitting means between them, e.g. power-assisted (sensing elements alone F01D 17/02 ; final actuators alone F01D 17/10)	25/14	. . Casings modified therefor (double casings F01D 25/26)
17/205	. . {Centrifugal governors directly linked to valves}	25/145	. . . {Thermally insulated casings}
17/22	. . the operation or power assistance being predominantly non-mechanical	25/16	. Arrangement of bearings; Supporting or mounting bearings in casings (bearings per se F16C)
17/24	. . . electrical	25/162	. . {Bearing supports}
		25/164	. . . {Flexible supports; Vibration damping means associated with the bearing}
		25/166	. . {Sliding contact bearing (gas bearings F01D 25/22)}
		25/168	. . . {for axial load mainly}
		25/18	. Lubricating arrangements (of machines or engines in general F01M)

F01D

- 25/183 . . {Sealing means}
- 25/186 . . . {for sliding contact bearing}
- 25/20 . . using lubrication pumps
- 25/22 . . using working-fluid or other gaseous fluid as lubricant
- 25/24 . Casings (modified for heating or cooling [FOID 25/14](#)); Casing parts, e.g. diaphragms, casing fastenings (casings for rotary machines or engines in general [F16M](#) {; special arrangements in stators dealing with breaking-off of part of rotor [FOID 21/045](#)})
- 25/243 . . {Flange connections; Bolting arrangements ([FOID 25/265](#) takes precedence)}
- 25/246 . . {Fastening of diaphragms or stator-rings}
- 25/26 . . Double casings; Measures against temperature strain in casings
- 25/265 . . . {Vertically split casings; Clamping arrangements therefor}
- 25/28 . Supporting or mounting arrangements, e.g. for turbine casing
- 25/285 . . {Temporary support structures, e.g. for testing, assembling, installing, repairing; Assembly methods using such structures}
- 25/30 . Exhaust heads, chambers, or the like
- 25/305 . . {with fluid, e.g. liquid injection}
- 25/32 . Collecting of condensation water; Drainage {; [Removing solid particles](#)}
- 25/34 . Turning or inching gear
- 25/36 . . using electric motors