

1	<b>METHODS</b>	31	..Blade slidable along plane of work surface
2	.With preliminary weakening	32	.Zigzag-folded supply package
3	.Longitudinally of direction of feed	33	.Separate blades usable alternatively or sequentially on same work supply
4	.Transversely of continuously fed work	34	.Plural supply sources
5	..Progressively to or from one side edge	35	..On turret-type support with single blade
6	<b>SEVERING BY MANUALLY FORCING AGAINST FIXED EDGE</b>	36	..With movable blade registrable selectively with each source
7	.With other type severing means	37	..With plural blades
8	.With timer-released means for preventing work feed-out	38	...With individual blade for each source
9	.Including means to effect bias cut	39	.With housing for work supply
10	.With feed-out of predetermined length from work supply	40	..Liquid-, gas-, or light-tight work passage
11	..Including means to select or adjust feed-out length	41	..With inspection window or transparent panel
12	..Including feed-out stop for manually pulled work	42	..With mounting means for housing
13	...Stop abuts work edge or work-mounted article	43	..Blade on pivoted closure for housing
14	...With feed-out of lead-end to aid initial grasping	44	..Sectional telescoping housing
15	..Merely to provide lead-end for manual grasping	45	...Including removable cap or sleeve enclosure for spooled work supply
16	..Manually operated feed-out mechanism	46	..Including special support for wound supply package
17	.With indicator	47	...Bearing or trunnions to engage package core
18	..Indicates length to be severed from supply	48	..Single blank container
19	.With blade-edge guard	49	...Blade unitary with container
20	..Movable	50	...With closure fastener
21	.Work stripped from blade by relatively movable means	51	..With brake or tensioner
22	..Including movable blade	52	...Restricted or restrictable work outlet
23	.With means to move work toward or into severing position	53	..With finger-access opening to facilitate work feed-out
24	..With means to strip adhering work therefrom	54	..With internal guide
25	.With work-immobilizing paster surface	55	.Blade carrier bodily and slidably supported on running length work
26	..With finger-access opening	56	.Blade mounted on hand-held wound package
27	.With means to hold pad or stack of individual sheets	57	..With lead-end stripper for tacky adhesive work
28	..With means to separate severed end of stub from supply package	58	..By resiliently embracing outer circumference of package
29	..With changeable blade-edge contour	59	..Work supply nonrotatably wound on flanged spool
30	...Slidable notcher	60	...Circumferentially movable blade radially retained by beaded or grooved flanges

- |    |   |      |  |
|----|---|------|--|
| 61 | ...Blade carrier supports hollow spool for rotation                   | 90   | .With means to facilitate lead-end grasping                    |
| 62 | ...Flange edge notched to provide or coact with cutter                | 91   | .Blades or severing devices                                    |
| 63 | ...With clamp for lead-end of strand-type work                        | 92   | ..Adjustable blade-edge contour                                |
| 64 | ...Strand clamped against flange                                      | 93   | <b>BREAKING OR TEARING APPARATUS</b>                           |
| 65 | ..By resiliently engaging package ends or interior of core            | 93.5 | .Including means to apply thermal shock to work                |
| 66 | ..Blade carrier supports package for rotation                         | 94   | .Combined with preliminary weakener or with nonbreaking cutter |
| 67 | .Movable blade continually biased toward wound web supply package     | 95   | ..Successively actuated sharp and dull tools                   |
| 68 | ..Including temporary bias-disabling means                            | 96   | ..Preliminary weakener   |
| 69 | ..Including stripper to separate lead-end from package                | 96.5 | ...With means to apply moment of force to weakened work        |
| 70 | ..Weight of bodily movable package contributes to blade-biasing force | 97   | .Plural breakers   |
| 71 | ..Blade slidably guided   | 98   | .Conveyer diverter for moving work                             |
| 72 | .Blade movable to severing position by moving work                    | 99   | ..Plural divergent work paths                                  |
| 73 | ..With simultaneous application of brake or clamp                     | 100  | .Work-parting pullers (burstors)                               |
| 74 | ...Applied to running length work                                     | 101  | ..Relatively movable clamps                                    |
| 75 | ...Opposed movable jaws   | 102  | .Axial twistors  |
| 76 | .Wound package bodily biased toward fixed blade                       | 103  | .Movable breaking tool   |
| 77 | .With fixed blade and support for wound package                       | 104  | ..Breaking tool intermediate spaced work supports              |
| 78 | ..Body- or belt-attached  | 105  | ...Clamping supports   |
| 79 | ..With brake applied to supply package                                | 106  | .Web restrainer  |
| 80 | ..With guide spaced from blade edge to provide lead-end therebetween  |      |  |
| 81 | .With work-abutment stop  |      |  |
| 82 | .With brake or clamp  |      |  |
| 83 | ..Thread cutter and clamp attachment for sewing machine presser foot  |      |  |
| 84 | ..Applied to running length work                                      |      |  |
| 85 | ...Spaced from blade edge to provide lead-end therebetween            |      |  |
| 86 | ...Blade manually movable to expose lead-end                          |      |  |
| 87 | ..Manually applied, spring returned                                   |      |  |
| 88 | .With guide for running length work                                   |      |  |
| 89 | .Blade manually movable to or from severing position                  |      |  |

**FOREIGN ART COLLECTIONS**FOR 000 **CLASS-RELATED FOREIGN DOCUMENTS**