

B60G

VEHICLE SUSPENSION ARRANGEMENTS (air-cushion vehicles [B60V](#); {cycle suspensions [B62K 25/00](#)})

Definition statement

This place covers:

Suspension for vehicle with a limitation to the type of vehicle:

Car, truck, agricultural vehicle and their trailers.

References

Limiting references

This place does not cover:

Rail vehicle suspensions	B61F
Cycle suspensions	B62K 25/00

Informative references

Attention is drawn to the following places, which may be of interest for search:

Vehicle wheels; castors; axles; increasing wheel adhesion	B60B 1/00 - B60B 39/12
Vehicles adapted for load transportation	B60P 1/00
Conjoint control of vehicle sub-units	B60W
Steering	B62D 1/00 - B62D 7/00
Chassis understructures	B62D 21/00 - B62D 67/00
Cycles	B62K
Bearings	F16C
Springs; Shock-absorbers; Means for damping vibration	F16F

Special rules of classification

For the whole [B60G](#) range, consider the indexing range [B60G 2200/00](#) – [B60G 2800/00](#)

B60G 9/00

Resilient suspensions of a rigid axle or axle housing for two or more wheels
 {(the axle being a part of a set of tandem axles [B60G 5/00](#)-[B60G 5/065](#); with leaf springs [B60G 11/02](#)-[B60G 11/08](#))}

Definition statement

This place covers:

Resilient suspensions of a rigid axle or axle housing for two or more wheels

References

Limiting references

This place does not cover:

Twist beam axles or semi-rigid axles	B60G 21/051
--------------------------------------	-----------------------------