CPC COOPERATIVE PATENT CLASSIFICATION

A HUMAN NECESSITIES

PERSONAL OR DOMESTIC ARTICLES

A44 HABERDASHERY; JEWELLERY

A44B BUTTONS, PINS, BUCKLES, SLIDE FASTENERS, OR THE LIKE (fastenings specially adapted for footwear A43C)

NOTE

This subclass covers buckles or slide fasteners whether used as haberdashery or otherwise.

WARNINGS

1. The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:

A44B 1/16 covered by <u>A44B 1/14</u>

2. In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

| 1/00 | Buttons | 3/08 | • with head and base separable |
|--------|---|--------|---|
| 1/02 | characterised by their material | | • |
| 1/04 | Ornamental buttons | 5/00 | Sleeve-links |
| 1/06 | • Assembling of buttons (covering by braiding <u>D04D</u>) | 5/002 | • {with head tiltable as a whole} |
| 1/08 | • Constructional characteristics | 5/005 | • {formed as two tiltable flaps} |
| 1/10 | • • washable | 5/007 | • {concealing a sewed-on button (buttons with |
| 1/12 | covered by fabric | | replaceable coverings <u>A44B 1/14</u>)} |
| 1/123 | • • • {with a removable fabric covering} | 5/02 | • with separable parts |
| 1/126 | • • {Manufacture not otherwise provided for} | 6/00 | Retainers or tethers for neckties, cravats, |
| 1/14 | with replaceable {or protective} coverings | | neckerchiefs, or the like, e.g. tie-clips, spring |
| 1, 1 . | {(removable fabric coverings A44B 1/123; | | clips with attached tie-tethers, woggles, pins |
| | sleeve-links concealing a sewed-on button | | with associated sheathing members tetherable |
| | <u>A44B 5/007</u>)} | | to clothing (tie-pins A44B 9/08; decorative or |
| 1/18 | adapted for special ways of fastening | | ornamental aspects <u>A44C</u>) |
| 1/185 | • • {with quick, thread-like, anchoring means avoiding the use of a separate needle and thread} | 7/00 | Cards for buttons, collar-studs, or sleeve-links |
| 1/20 | attached by thread visible to the front | 9/00 | Hat, scarf, or safety pins or the like (decorative |
| | $\{(\underline{A44B \ 1/185} \ takes \ precedence)\}$ | | or ornamental aspect A44C; hair pins A45D 8/02; |
| 1/22 | attached by thread not visible to the front | | sewing needles <u>D05B 85/00</u>) |
| | $\{(\underline{A44B \ 1/185} \ takes \ precedence)\}$ | 9/02 | Simple pins |
| 1/24 | Eye-buttons | 9/04 | Ordinary pins |
| 1/26 | • • with resilient shank | 9/06 | • • Hat-pins (other fastening means for head |
| 1/28 | • • with shank and counterpiece | | coverings <u>A42B 7/00</u>) |
| 1/30 | Screw-buttons | 9/08 | • • Tie-pins (pins with associated sheathing members |
| 1/32 | Shank inserted into counterpiece and locked by | | tetherable to clothing A44B 6/00) |
| | sliding or rotating | 9/10 | Safety devices |
| 1/34 | • • • with snap-action counterpiece | 9/12 | • Safety-pins |
| 1/36 | • • • with counterpiece in the form of cotter, split- | 9/125 | • • {made of plastics} |
| | pin, or the like | 9/14 | Ordinary safety-pins |
| 1/38 | Clamping by spring action | 9/16 | Brooches; Breast-pins |
| 1/40 | with helical wire-shank screwed into material | 9/18 | Hinges; Locking devices |
| 1/42 | with deformable prongs | 9/20 | Attaching heads of glass or the like to pin shafts |
| 1/44 | • with deformable counterpiece | 11/00 | Buckles; Similar fasteners for interconnecting straps or the like, e.g. for safety belts |
| 3/00 | Collar-studs | 11/001 | • {Ornamental buckles} |
| 3/02 | . completely rigid | 11/001 | , |
| 3/04 | with head tiltable as a whole | 11/003 | {covered with cloth or other material; Making thereof} |
| 3/06 | . with head formed as two tiltable flaps | | thereon y |

CPC - 2024.05

| 11/005 | • {Buckles combined with other articles, e.g. with receptacles} | 11/2573 | • • • {Locking means preventing an unauthorised opening, e.g. by children} |
|---------|--|---------|---|
| 11/006 | • {Attachment of buckle to strap (for safety buckles | 11/2576 | {Buckle covers} |
| | <u>A44B 11/2553</u>)} | 11/258 | • • {fastening by superposing one part on top of the |
| 11/008 | • • {extensible} | 11/2504 | other (A44B 11/2503 takes precedence)} |
| 11/02 | frictionally engaging surface of straps | 11/2584 | . (followed by sliding in the main plane of the buckle) |
| 11/04 | • • without movable parts | 11/2588 | • • {combined with one buckle element rotating or |
| 11/06 | • with clamping devices | 11/2388 | pivoting} |
| 11/065 | • • • {with strap tightening means (A44B 11/125 takes precedence; tighteners for securing of | 11/2592 | • • {fastening by sliding in the main plane or a |
| | load on vehicles B60P 7/0823; buckles attached to the end of a strap for bundling articles | 11/23/2 | plane parallel to the main plane of the buckle (A44B 11/2503, A44B 11/2584 take precedence) |
| | <u>B65D 63/16</u>)} | 11/2596 | • • • {the movement being transverse to the |
| 11/08 | roller displaceable in wedge-shaped slot | | longitudinal direction of the strap or chain} |
| 11/10 | sliding wedge | 11/26 | • with push-button fastenings {(A44B 11/2507 |
| 11/12 | turnable clamp | | takes precedence; press-button fasteners |
| 11/125 | • • • { with strap tightening means } | | <u>A44B 17/00</u>)} |
| 11/14 | with snap-action | 11/263 | • • • { with a push-button acting perpendicularly to |
| 11/16 | Strap held by spring action | | the main plane of the buckle} |
| 11/18 | Strap held by threading through linked rings | 11/266 | • • • { with at least one push-button acting |
| 11/20 | • engaging holes or the like in strap | | parallel to the main plane of the buckle and |
| 11/22 | Buckle with fixed prong | | perpendicularly to the direction of the fastening |
| 11/223 | • • • {fixed on a movable element} | 11/20 | action} |
| 11/226 | • • {with cover plate} | 11/28 | with hooks engaging end-pieces on the strap |
| 11/24 | Buckle with movable prong | | $\{(\underline{A44B\ 11/2503}\ takes\ precedence)\}$ |
| 11/25 | • with two or more separable parts | 13/00 | Hook or eye fasteners |
| 11/2503 | • • {Safety buckles (safety belts in vehicles | 13/0005 | • {characterised by their material (A44B 13/0052 and |
| 11,2000 | <u>B60R 22/00</u> ; safety belts for aircraft <u>B64D 25/02</u>)} | 13/0011 | A44B 13/0058 take precedence)} • {made of wire} |
| 11/2507 | • • {actuated by a push-button} | 13/0011 | . {made of whe} {made of metal plate} |
| 11/2507 | • • • {actuated by a push-button} • • • • {acting perpendicularly to the main plane of | 13/0017 | . {made of plastics} |
| 11/2311 | the buckle, e.g. placed on the front face of | 13/0023 | • {characterised by their way of fastening to the |
| 11/2515 | the buckle} • • • {acting parallel to the main plane of the | 13/0029 | support (<u>A44B 13/0052</u> and <u>A44B 13/0058</u> take precedence)} |
| 11/2313 | buckle and perpendicularly to the direction | 13/0035 | • {using prongs} |
| | of the fastening action} | 13/0041 | • • (asing prongs) • • • (and a backing element on which prongs are |
| 11/2519 | • • • • { with two buttons acting in opposite directions } | 13/0047 | bent over} • {welded or moulded} |
| 11/2523 | • • • {acting parallel to the main plane of the | 13/0047 | |
| 11/2323 | buckle and in the same direction as the | | . {Strips of hook or eye fasteners} |
| | fastening action} | 13/0058 | {Eyelets or grommets} {characterised by their material} |
| 11/2526 | • • · { with an operating lever} | 13/0064 | • |
| 11/253 | • • • (acting in the same plane or in a plane | 13/007 | • • {made of plastics} |
| | parallel to the main plane of the buckle} | 13/0076 | {characterised by their way of fastening to the support} |
| 11/2534 | • { with the sliding motion of the buckle providing the opening or closing action} | 13/0082 | • • {by riveting} |
| 11/2538 | • • • { with a pivoting bar retaining a loop of the | 13/0088 | • • • {by separable snap connection} |
| 11/2330 | strap itself} | 13/0094 | • • • {welded or moulded} |
| 11/2542 | • • • {actuated by a rotatable element, e.g. combined | 13/02 | with spring closure of hook |
| 11/0546 | with other actuating means} | 15/00 | Key-rings |
| 11/2546 | {Details} | 15/002 | • {Separable rings} |
| 11/2549 | • • • {Fastening of other buckle elements to | 15/005 | • {Fobs} |
| | the main buckle (buckles with several tongues released by the same mechanism | 15/007 | • {Openers} |
| | A44B 11/2507 - A44B 11/2542)} | 17/00 | Press-button or snap fasteners |
| 11/2553 | • • • {Attachment of buckle to strap} | 17/0005 | • {Fastening of press-button fasteners (A44B 17/0017 |
| 11/2557 | • • • • {Attachment of buckle to strap} • • • • • {with strap length adjustment} | | and A44B 17/0035 take precedence)} |
| 11/2557 | {With strap religin adjustment} {Tongue elements} | 17/0011 | • {Press-button fasteners in which the elastic retaining |
| 11/2565 | { I foligue elements } { Illuminated buckles } | | action is obtained by a spring working in the plane |
| | | | of the fastener} |
| 11/2569 | • • • {Safety measures (buckles for releasing in a vehicle emergency <u>B60R 22/32</u> ; control, alarm, | 17/0017 | • • {Their fastening} |
| | or interlock systems for the correct application | 17/0023 | • {Press-button fasteners in which the elastic retaining |
| | of safety belt buckles in vehicles <u>B60R 22/48</u>)} | | action is obtained by the own elasticity of the material constituting the fastener} |

CPC - 2024.05

| 17/0029 | • {Press-button fasteners made of plastics} | 19/04 | • • Stringers arranged edge-to-edge when fastened {, |
|---------|--|--------|---|
| 17/0035 | {Their fastening} | 10/06 | e.g. abutting stringers} |
| 17/0041 | • {Press-button fasteners consisting of two parts (A44B 17/0029 takes precedence)} | 19/06 | with substantially rectangular members having interlocking projections and pieces |
| 17/0047 | | 19/08 | Stringers arranged side-by-side when fastened, |
| 17/0047 | • {Press-button fasteners consisting of three parts (A44B 17/0029 takes precedence)} | 19/08 | e.g. at least partially superposed stringers |
| 17/0052 | • {Press-button fasteners consisting of four parts | 19/10 | with a one-piece interlocking member on each |
| 17/0032 | (A44B 17/0029 takes precedence) | 17/10 | stringer tape |
| 17/0058 | • {Strips of press-button fasteners} | 19/12 | . Interlocking member in the shape of a continuous |
| 17/0064 | • {Surps of press-button fasteners} • {Details} | 13,12 | helix |
| 17/007 | • {Stud-member} | 19/14 | Interlocking member formed by a profiled or |
| 17/007 | • {Socket member} | | castellated edge |
| 17/0070 | • {Socket member} • . {Decoration} | 19/16 | Interlocking member having uniform section |
| 17/0082 | . {made from sheet metal} | | throughout the length of the stringer {(for sacks |
| 17/0094 | • {made from solid metal} | | or bags <u>B65D 33/2508</u>)} |
| 17/00/7 | • • (made from some metal) | 19/18 | . with a third member or members, other than the |
| 18/00 | Fasteners of the touch-and-close type; Making | | slider, connected to the edges of adjacent stringers |
| | such fasteners | | when closed, e.g. third member moved into position |
| 18/0003 | • {Fastener constructions (<u>A44B 18/0023</u> , | | by a slider |
| | A44B 18/0046 take precedence)} | 19/20 | the third member being embraced by the stringers |
| 18/0007 | • • {in which each part has similar elements} | 19/22 | the third member embracing the stringers |
| 18/0011 | • • {Female or loop elements (<u>A44B 18/0007</u> takes | 19/24 | . Details |
| | precedence)} | 19/26 | Sliders |
| 18/0015 | • • {Male or hook elements (<u>A44B 18/0007</u> takes | 19/262 | • • • {Pull members; Ornamental attachments for |
| | precedence)} | | sliders} |
| 18/0019 | • • · { of a mushroom type } | 19/265 | • • • {with means for preventing the accidental |
| 18/0023 | • {Woven or knitted fasteners} | | intrusion of material into the slider body, e.g. |
| 18/0026 | • • {Devices for cutting loops into hooks (cutting pile | 10/07 | with shield or guard} |
| 10/002 | loops <u>D06C 13/08</u>)} | 19/267 | • • • {for slide fasteners with edges of stringers having uniform section throughout the length |
| 18/003 | • • {in which each part has similar elements} | | thereof (for sacks or bags <u>B65D 33/2508</u>)} |
| 18/0034 | • • {Female or loop elements (A44B 18/003 takes | 19/28 | constructed to be removable from at least one |
| 18/0038 | precedence)} • • {Male or hook elements (<u>A44B 18/003</u> takes | 17/20 | stringer {; Sliders with movable parts to permit |
| 10/0030 | precedence)} | | releasing of the slider in the event of jamming |
| 18/0042 | • • {of a mushroom type} | | or obstruction} |
| 18/0046 | • {Fasteners made integrally of plastics} | 19/285 | {Tools for opening or closing slide |
| 18/0049 | (obtained by moulding processes (compression) | | fasteners} |
| 10/0042 | moulding or articles of indefinite length | 19/30 | • • • with means for locking in position |
| | characterised by the shape of the surface | 19/301 | • • • {at the end of their upward travel with any |
| | <u>B29C 43/222</u> ; screen moulding <u>B29C 67/08</u>)} | | suitable device, e.g. pull member combined |
| 18/0053 | • • {in which each part has similar elements} | | with a press-button, a hook, a key-operated |
| 18/0057 | • • {Female or loop elements (A44B 18/0053 takes | | lock} |
| | precedence)} | 19/303 | {Self-locking sliders, e.g. slider body |
| 18/0061 | • • {Male or hook elements (<u>A44B 18/0053</u> takes | | provided with locking projection or groove, |
| | precedence)} | 19/305 | friction means} {in the form of a locking prong protuding |
| 18/0065 | {of a mushroom type} | 19/303 | from the pull member |
| 18/0069 | • {Details} | 19/306 | {in the form of a locking spring member |
| 18/0073 | • • {Attaching means} | 17/300 | actuated by the pull member} |
| 18/0076 | {Adaptations for being fixed to a moulded article | 19/308 | • • • • {in the form of a spring-actuated locking |
| | during moulding} | 17,300 | member actuated by the pull member} |
| 18/008 | • • {Hooks or loops provided with means to | 19/32 | Means for making slide fasteners gas or |
| | reinforce the attachment, e.g. by adhesive | | watertight |
| | means (tab fastener elements for absorbent pads | 19/34 | • Stringer tapes (A44B 19/40 takes precedence); |
| | combining adhesive and mechanical fastening A61F 13/581)} | | Flaps secured to stringers for covering the |
| 18/0084 | • {Double-sided} | | interlocking members (A44B 19/32 takes |
| 18/0088 | . {Double-sided}. {Mixed male and female members} | | precedence {; setting slide or glide fastener |
| 18/0092 | {Induct male and remain members} {flame retardant} | | elements on garments <u>A41H 37/06</u> }) |
| 18/0092 | . {frame retardant}. {Shape memory materials} | 19/343 | {Knitted stringer tapes} |
| | | 19/346 | {Woven stringer tapes (weaving of tapes |
| 19/00 | Slide fasteners | 10/01 | D03D 1/00)} |
| 19/02 | • with a series of separate interlocking members | 19/36 | Means for permanently uniting the stringers at the |
| | secured to each stringer tape | | end; Means for stopping movement of slider at the end |
| | | | the one |

CPC - 2024.05

| 19/38 | • • Means at the end of stringer by which the slider can be freed from one stringer, e.g. stringers can be completely separated from each other |
|--------|---|
| 19/382 | • • • {"Two-way" or "double-acting" separable slide fasteners} |
| 19/384 | • • • {Separable slide fasteners with quick opening devices} |
| 19/386 | • • • {Top end stop means for quick opening slide fasteners} |
| 19/388 | • • • {Bottom end stop means for quick opening slide fasteners} |
| 19/40 | • Connection of separate, or one-piece, interlocking members to stringer tapes; Reinforcing such connections, e.g. by stitching |
| 19/403 | • • • {Connection of separate interlocking members} |
| 19/406 | • • • {Connection of one-piece interlocking members} |
| 19/42 | Making by processes not fully provided for in |
| | one other class, e.g. <u>B21D 53/50</u> , <u>B21F 45/18</u> , |
| | B22D 17/16, B29D 5/00 {(attaching closure |
| | devices, e.g. slide fasteners, to bags <u>B31B 70/813</u> ; |
| | making package opening by applying or incorporating profile strips, e.g. for reclosable bags |
| | <u>B65B 61/188)</u> } |
| 19/44 | Securing metal interlocking members to ready- |
| | made stringer tapes (making metal slide fastener parts combined with attaching B21D 53/52) |
| 19/46 | Securing separate interlocking members |
| 19/48 | Arranging interlocking members before |
| | securing (article handling devices associated |
| | with conveyors in general <u>B65G 47/00</u> , e.g. |
| 10/50 | <u>B65G 47/14</u>) |
| 19/50 | Securing one-piece interlocking members |
| 19/52 | Securing the interlocking members to stringer |
| 19/54 | tapes while making the latter while weaving the stringer tapes |
| 19/54 | while weaving the stringer tapeswhile knitting the stringer tapes |
| 19/58 | while kinding the stringer tapes Removing interlocking members to produce gaps |
| 19/58 | Applying end stops upon stringer tapes |
| 19/62 | Assembling sliders in position on stringer tapes |
| 19/64 | Slider holders for assemblage of slide fasteners |
| 99/00 | Subject matter not provided for in other groups of |
| | this subclass |
| 99/005 | • {Turn-button fasteners} |

CPC - 2024.05