CPC COOPERATIVE PATENT CLASSIFICATION

B PERFORMING OPERATIONS; TRANSPORTING

(NOTES omitted)

TRANSPORTING

B62 LAND VEHICLES FOR TRAVELLING OTHERWISE THAN ON RAILS

B62D MOTOR VEHICLES; TRAILERS (steering, or guiding on a desired track, of agricultural machines or implements A01B 69/00; wheels, castors, axles, increasing wheel adhesion B60B; vehicle tyres, tyre inflation or tyre changing <u>B60C</u>; connections between vehicles of a train or the like B60D; vehicles for use on rail and road, amphibious or convertible vehicles B60F; suspension arrangements B60G; heating, cooling, ventilating or other air treating devices B60H; windows, windscreens, non-fixed roofs, doors or similar devices, protective coverings for vehicles not in use <u>B60J</u>; propulsion plant arrangements, auxiliary drives, transmissions, controls, instrumentation or dashboards B60K; electric equipment or propulsion of electricallypropelled vehicles <u>B60L</u>; power supply for electrically-propelled vehicles <u>B60M</u>; passenger accommodation not otherwise provided for B60N; adaptations for load transportation or to carry special loads or objects B60P; arrangement of signalling or lighting devices, the mounting or supporting thereof or circuits therefor, for vehicles in general B60Q; vehicles, vehicle fittings or vehicle parts not otherwise provided for <u>B60R</u>; servicing, cleaning, repairing, supporting, lifting, or manoeuvring, not otherwise provided for, B60S; brake arrangements, brake control systems or parts thereof <u>B60T</u>; air-cushion vehicles <u>B60V</u>; motor-cycles, accessories therefor <u>B</u>62J, B62K; testing of vehicles **G01M**)

NOTE

In this subclass, the following terms are used with the meanings indicated:

- "vehicles" include motor vehicles and trailers;
- "trailers" include forecars or sidecars.

WARNINGS

1. The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:

 B62D 25/13
 covered by
 B60J 1/20, B60R 13/07

 B62D 25/22
 covered by
 B60R 3/00

 B62D 65/08
 covered by
 B60J 10/45

B62D 101/00-B62D 137/00 covered by B62D 6/00 - B62D 6/008

2. In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

Steering of motor vehicles or trailers		1/065	{Steering wheels with heating and
1/00	Steering controls, i.e. means for initiating a change of direction of the vehicle		ventilating means (heating and ventilation of steering wheel when connected to vehicle HVAC <u>B60H 1/00292</u>)}
1/02	 vehicle-mounted 	1/08	• • • Spokes, e.g. resilient (B62D 1/11 takes
1/04	Hand wheels		precedence)
1/043	• • { with a device allowing single-hand operation of the steering wheel }	1/10	• • Hubs; Connecting hubs to steering columns, e.g. adjustable (B62D 1/11 takes precedence)
1/046	• • • {Adaptations on rotatable parts of the steering wheel for accommodation of switches}	1/105	• • • {Non-rotatable hubs, e.g. the central part of the steering wheel not rotating}
1/06	Rims, e.g. with heating means; Rim covers (B62D 1/11 takes precedence)	1/11	e.g. by being yieldable or collapsible (padded linings associated with the steering wheel <u>B60R 21/05</u> ; shock absorbers using plastic deformation of members in general <u>F16F 7/12</u>)

1/12	Hand levers	3/123	{characterised by pressure yokes}
1/14	Tillers, i.e. hand levers operating on steering	3/126	{characterised by the rack}
	columns	3/14	. hydraulic
1/16	Steering columns	5/00	Power-assisted or power-driven steering (for
1/163	• • {Part of the steering column replaced by flexible means, e.g. cable or belt}	5/00	non-deflectable wheels <u>B62D 11/00</u> ; fluid-pressure
1/166	• • • {Means changing the transfer ratio between steering wheel and steering gear}	5/001	servomotors in general F15B) • {Mechanical components or aspects of steer-by-
1/18	yieldable or adjustable, e.g. tiltable (padded linings associated with the steering column		wire systems, not otherwise provided for in this maingroup}
	B60R 21/05)	5/003	• • {Backup systems, e.g. for manual steering (B62D 5/30 takes precedence)}
	NOTE	5/005	• • {means for generating torque on steering wheel or
	Group <u>B62D 1/181</u> takes precedence over	5 /00 <	input member, e.g. feedback}
	groups <u>B62D 1/183</u> - <u>B62D 1/187</u> .	5/006	• • {power actuated}
1/181	• • • with power actuated adjustment, e.g. with position memory	5/008	• {Changing the transfer ratio between the steering wheel and the steering gear by variable supply of
1/183	adjustable between in-use and out-of-use	5.400	energy, e.g. by using a superposition gear}
1/103	positions, e.g. to improve access	5/02	• mechanical, e.g. using a power-take-off mechanism
1/184	Mechanisms for locking columns at selected positions	~ /o /	for taking power from a rotating shaft of the vehicle and applying it to the steering gear
1/185	•	5/04	• electrical, e.g. using an electric servo-motor
1/103	telescopically (<u>B62D 1/183</u> , <u>B62D 1/187</u> ,	5/0402	connected to, or forming part of, the steering gear
	B62D 1/19 take precedence)	5/0403	 {characterised by constructional features, e.g. common housing for motor and gear box}
1/187	• • • with tilt adjustment; with tilt and axial	5/0406	• • { including housing for electronic control unit }
1,10,	adjustment (B62D 1/183, B62D 1/19 takes		. { Electric motor acting on the steering column }
	precedence)	5/0409	
1/189	the entire column being tiltable as a unit	5/0412	. • {the axes of motor and steering column being parallel}
1/19	incorporating energy-absorbing	5/0415	• • • {the axes being coaxial}
	arrangements, e.g. by being yieldable	5/0413	{ the axes being coaxiar} { Electric motor acting on road wheel carriers }
	or collapsible (shock absorbers using	5/0418	
	plastic deformation of members in general		• • {Electric motor acting on or near steering gear}
	<u>F16F 7/12</u>)	5/0424	{the axes of motor and final driven element of
1/192	• • • • { Yieldable or collapsible columns}	5/0427	steering gear, e.g. rack, being parallel} {the axes being coaxial}
1/195	• • • • { Yieldable supports for the steering	5/043	{characterised by clutch means between driving
1/197	column} {incorporating devices for preventing	3/043	element, e.g. motor, and driven element, e.g.
	ingress of the steering column into the	5/0.422	steering column or steering gear}
	passengers space in case of accident}	5/0433	• • • {the clutch being of on-off type}
1/20	Connecting steering column to steering gear	5/0436	• • • • {the clutch being a controlled emergency
1/22	 Alternative steering-control elements, e.g. for teaching purposes 		clutch, e.g. for disconnecting at motor break- down}
1/24	 not vehicle-mounted 	5/0439	• • • {Controllable friction clutches (<u>B62D 5/0436</u>
1/26	mechanical, e.g. by a non-load-bearing guide (railways B61)	5/0442	takes precedence)} {Conversion of rotational into longitudinal
1/265	• • • {especially adapted for guiding road vehicles		movement}
1/203	carrying loads or passengers, e.g. in urban	5/0445	• • • {Screw drives}
	networks for public transportation}	5/0448	• • • • {Ball nuts}
1/28	• • non-mechanical {, e.g. following a line or other	5/0451	• • • {Roller spindle drives}
1/20	known markers}	5/0454	• • {Worm gears}
1/283	• • • {for unmanned vehicles}	5/0457	• • {characterised by control features of the drive
1/286	• • {Systems for interrupting non-mechanical		means as such}
1,200	steering due to driver intervention}	5/046	• • • {Controlling the motor}
3/00	Steering gears (power assisted or power driven	5/0463	• • • • {calculating assisting torque from the motor based on driver input}
	B62D 5/00; steering linkages B62D 7/00; for non-	5/0466	• • • { for returning the steering wheel to neutral
	deflectable wheels <u>B62D 11/00</u> ; gearing in general		position}
	<u>F16H</u>)	5/0469	• • • {End-of-stroke control}
3/02	. mechanical	5/0472	• • • { for damping vibrations }
3/04	• of worm type	5/0475	• • • {Controlling other elements}
3/06	with screw and nut	5/0478	· · · · {Clutches}
3/08	using intermediate balls or the like	5/0481	• • • {monitoring the steering system, e.g. failures}
3/10	with worm engaging in sector or roller gear	5/0484	• • • { for reaction to failures, e.g. limp home }
3/12	• of rack-and-pinion type		

5/0487	• • • {detecting motor faults (<u>B62D 5/0496</u> takes precedence)}	6/00	Arrangements for automatically controlling steering depending on driving conditions sensed
5/049	{detecting sensor failures}		and responded to, e.g. control circuits (means for
5/0493	• • • {detecting processor errors, e.g. plausibility		initiating a change in direction <u>B62D 1/00</u> ; steering
	of steering direction}		valves <u>B62D 5/06</u> ; combined with means for inclining
5/0496	• • • {by using a temperature sensor}		the vehicle body or wheels on bends <u>B62D 9/00</u>)
5/06	 fluid, i.e. using a pressurised fluid for most or all the force required for steering a vehicle 		NOTE
5/061	 • {provided with effort, steering lock, or end-of- stroke limiters} 		When classifying in this group, classification is also made in the appropriate one of groups B62D 1/00 - B62D 5/00 or
5/062	• • {Details, component parts}		$\frac{B62D 7/00}{B62D 19/00} = \frac{B62D 19/00}{B62D 19/00}$ if other aspects of the
5/063	• • {Pump driven by vehicle engine (<u>B62D 5/065</u> takes precedence)}		steering system are of interest
5/064	• • • {Pump driven independently from vehicle engine, e.g. electric driven pump (<u>B62D 5/065</u> takes precedence)}	6/001 6/002	 {the torque NOT being among the input parameters} {computing target steering angles for front or rear
5/065	characterised by specially adapted means for	0/002	wheels (B62D 7/159 takes precedence)}
	varying pressurised fluid supply based on need,	6/003	• • {in order to control vehicle yaw movement,
	e.g. on-demand, variable assist		i.e. around a vertical axis (B62D 6/007 takes
5/07	Supply of pressurised fluid for steering also		precedence)}
5/075	<pre>supplying other consumers {; control thereof} {using priority valves}</pre>	6/005	 • { treating sensor outputs to obtain the actual yaw rate}
5/08	 (using priority varves) characterised by type of {steering} valve used	6/006	• • {using a measured or estimated road friction
3/00	(valves in general F16K)	0/000	coefficient}
5/081	• • • {Seat valves}	6/007	• {adjustable by the driver, e.g. sport mode}
5/083	Rotary valves	6/008	• {Control of feed-back to the steering input
5/0832	• • { with elastic means other than a torsion bar,e.g. leaf springs}		member, e.g. simulating road feel in steer-by-wire applications}
5/0835	{characterised by means for actively	6/02	 responsive only to vehicle speed
	influencing the deflection angle of the valve, e.g. depending on driving parameters}	6/04	• responsive only to forces disturbing the intended course of the vehicle, e.g. forces acting transversely
5/0837	• • • Characterised by the shape of the control	- 10 -	to the direction of vehicle travel
	edges, e.g. to reduce noise}	6/06	• responsive only to vehicle vibration dampening
5/087	Sliding spool valves		arrangements (steering dampers for cycles B62K 21/08)
5/09	characterised by means for actuating valves	6/00	
5/091	• • • {Hydraulic steer-by-wire systems, e.g. the	6/08	• responsive only to {driver} input torque
5 /00 2	valve being actuated by an electric motor}	6/10	 characterised by means for sensing {or determining} torque
5/092	• • • { the electric motor being connected to the		determining) torque
	final driven element of the steering gear, e.g. rack}	7/00	Steering linkage; Stub axles or their mountings
5/093	Telemotor driven by steering wheel movement		(<u>B62D 13/00</u> takes precedence; power-assisted or
	(hydraulic steering gear <u>B62D 3/14</u>)	7/02	power-driven steering <u>B62D 5/00</u>)
5/097	gerotor type	7/02	• for pivoted bogies
5/10	characterised by type of power unit	7/023	• • {Steering turntables}
5/12	Piston and cylinder	7/026	• • {characterised by comprising more than one
5/14	Rotary motor		bogie, e.g. situated in more than one plane
5/16	Expansible chamber with flexible wall		transversal to the longitudinal centre line of the vehicle}
5/18	characterised by power transmitting means	7/04	• • with more than one wheel
5/20	specially adapted for particular type of steering	7/04	 for individually-pivoted wheels, e.g. on king-pins
0,20	gear or particular application (steering gears per	7/08	 to individually-pivoted wheels, e.g. on king-pins the pivotal axes being situated in a single plane
	se <u>B62D 3/00</u> ; steering linkages not characterised by being power-assisted or power-driven	7/08	transverse to the longitudinal centre line of the vehicle
5/22	B62D 7/00) for rack-and-pinion type	7/09	characterised by means varying the ratio
	for worm type		between the steering angles of the steered
5/24 5/26	for pivoted exles		wheels (varying the ratio automatically
5/26 5/28	for pivoted axles	7/10	depending on driving conditions <u>B62D 6/00</u>)
5/28	Sofety devices a gulternate emergency power	7/10	• • with single-output steering gear
5/30	Safety devices, e.g. alternate emergency power	7/12	• • with twin-output steering gear
5/22	supply or transmission means to ensure steering upon failure of the primary steering means	7/14	• • the pivotal axes being situated in more than one plane transverse to the longitudinal centre line of
5/32	• • • for telemotor systems	7/1 40	the vehicle, e.g. all-wheel steering
		7/142	 { specially adapted for particular vehicles, e.g. tractors, carts, earth-moving vehicles, trucks}

7/144	• • • { for vehicles with more than two axles }	11/00	Steering non-deflectable wheels; Steering endless
7/146	 {characterised by comprising means for steering by acting on the suspension system, 		tracks or the like <u>NOTE</u>
	e.g. on the mountings of the suspension arms}		
7/148	• • • {provided with safety devices}		Gearings of interest apart from this application are
7/15	 characterised by means varying the ratio between the steering angles of the steered 		also classified in the relevant group of subclass F16H covering gearings per se
7/1509	wheels {(<u>B62D 7/148</u> takes precedence)} {with different steering modes, e.g. crab-	11/001	• {control systems ($\underline{B62D \ 11/183}$ takes precedence)}
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	steering, or steering specially adapted for		NOTE
7/1518 7/1527	reversing of the vehicle} {comprising a mechanical interconnecting system between the steering control means of the different axles} {comprising only mechanical parts, i.e.		{When classifying in this group, classification is also made in the appropriate one of groups B62D 11/02 - B62D 11/24 if other aspects of the steering system are of interest}
	without assistance means}	11/003	• • {Electric or electronic control systems}
7/1536	• • • • {provided with hydraulic assistance}	11/005	• • {Hydraulic control systems}
7/1545	• • • • {provided with electrical assistance}	11/006	• • {Mechanical control systems}
7/1554	• • • {comprising a fluid interconnecting system	11/008	• • {Pneumatic control systems}
	between the steering control means of the different axles}	11/02	 by differentially driving ground-engaging elements on opposite vehicle sides
7/1563	• • • • {provided with fluid control means	11/04	by means of separate power sources
	$(\underline{B62D7/1572} \text{ takes precedence})$	11/06	by means of a single main power source
7/1572	• • • • {provided with electro-hydraulic control means}	11/08	• • using brakes or clutches as main steering- effecting means
7/1581	 {characterised by comprising an electrical interconnecting system between the steering control means of the different axles} 	11/10	 using gearings with differential power outputs on opposite sides, e.g. twin-differential or epicyclic gears
7/159	• • • • (characterised by computing methods or stabilisation processes or systems, e.g. responding to yaw rate, lateral wind, load,	11/105	• • • {using variable ratio belt and pulley gearings}
	road condition}	11/12	using separate change-speed gearings
7/16	Arrangement of linkage connections (pivots per se F16C)	11/14	 differential power outputs being effected by additional power supply to one side, e.g. power originating from secondary power
7/163	{substantially in axial direction, e.g. between rack bar and tie-rod}	11/16	source
7/166	{substantially perpendicular, e.g. between tie-rod and steering knuckle}	11/16	the additional power supply being supplied mechanically
7/18	. Steering knuckles; King pins	11/18	• • • • the additional power supply being supplied hydraulically
7/20	 Links, e.g. track rods (means for adjusting camber, 	11/183	{Control systems therefor}
7/22	castor, or toe-in <u>B62D 17/00</u>) Arrangements for reducing or eliminating reaction,	11/186	• • • • • {Uncoupling devices for the hydraulic motors, e.g. to allow towing}
	e.g. vibration, from parts, e.g. wheels, of the steering system	11/20	 Endless-track steering having pivoted bogie
7/222	• {acting on the steering wheel}	11/22	carrying track (<u>B62D 11/02</u> takes precedence) • Endless track steering being effected by deflecting
7/224	{acting between the steering wheel and the		endless track rollers or the like
7/226	steering gear, e.g. on the steering column} {acting on the steering gear}	11/24	• Endless track steering specially adapted for vehicles having both steerable wheels and endless track
7/228	• • {acting between the steering gear and the road		
0/00	wheels, e.g. on tie-rod}	12/00	Steering specially adapted for vehicles operating in tandem or having pivotally connected frames
9/00	Steering deflectable wheels not otherwise provided for (steering positon indicators <u>B62D 15/02</u>)		(steering endless tracks or the like <u>B62D 11/00</u> ; steering specially adapted for trailers <u>B62D 13/00</u>)
9/002	• {combined with means for differentially distributing power on the deflectable wheels during cornering}	12/02	for vehicles operating in tandem
9/005	• {Emergency systems using brakes for steering}	13/00	Steering specially adapted for trailers (combined
9/007	• {Emergency systems using the steering system for	13/005	traction and steering hitches <u>B60D</u>) • {operated from tractor steering system}
	braking}		
9/02	 combined with means for inwardly inclining vehicle body on bends 	13/02 13/025	 for centrally-pivoted axles {the pivoted movement being initiated by the
9/04	 combined with means for {inwardly} inclining 	10/04	coupling means between tractor and trailer}
	wheels on bends (<u>B62D 9/02</u> takes precedence)	13/04 13/06	for individually-pivoted wheelsfor backing a normally drawn trailer
		15/00	Steering not otherwise provided for

15/02	 Steering position indicators {; Steering position determination; Steering aids} 	21/06	 of X-shaped or fork-shaped construction, i.e. having members which form an X or fork as the frame is
15/0205	 {Mechanical indicators, e.g. in or near steering wheel} 	21/07	seen in plan view • wide-hipped frame type, i.e. a wide box-shaped mid
15/021	. {Determination of steering angle}	21/07	portion with narrower sections extending from said
15/0215	• {by measuring on the steering column}		mid portion in both fore and aft directions
15/022	• • • { on or near the connection between the	21/08	 built up with interlaced cross members
	steering wheel and steering column}	21/09	 Means for mounting load bearing surfaces
15/0225	• • • {by measuring on a steering gear element, e.g.	21/10	• in which the main member is plate-like
1.7.10.00	on a rack bar}	21/11	• with resilient means for suspension {, e.g. of wheels
15/023	• • {by measuring on the king pin}		or engine; sub-frames for mounting engine or suspensions}
15/0235	• • • {by measuring or deriving directly at the electric power steering motor}		
15/024	• • • {Other means for determination of steering		<u>NOTE</u>
10, 02	angle without directly measuring it, e.g. deriving from wheel speeds on different sides of the car}		This group <u>does not cover</u> subject matter primarily relating to the suspension, with only a nominal recitation of frame structure, which are
15/0245	• • { Means or methods for determination of the		covered by subclass <u>B60G</u>
	central position of the steering system, e.g.	21/12	. assembled from readily detachable parts
15/025	straight ahead position}	21/14	• of adjustable length or width
15/025	{Active steering aids, e.g. helping the driver by actively influencing the steering system	21/15	 having impact absorbing means, e.g. a frame
	after environment evaluation (<u>B62D 1/28</u> takes precedence)}		designed to permanently or temporarily change shape or dimension upon impact with another body (bumpers <u>B60R 19/02</u> ; shock absorbers in general
15/0255	• • • {Automatic changing of lane, e.g. for passing		<u>F16F</u>)
15/026	another vehicle}	21/152	• • {Front or rear frames}
15/026	 {combined with automatic distance control, i.e. electronic tow bar} 	21/155	• • • {Sub-frames or underguards}
15/0265	{Automatic obstacle avoidance by steering}	21/157	• • {for side impacts}
15/027	• {Parking aids, e.g. instruction means}	21/16	having fluid storage compartment
15/0275	• • • {by overlaying a vehicle path based on present steering angle over an image without	21/17	 forming fluid or electrical conduit means or having other means to accommodate the transmission of a force or signal
15/028	processing that image}• {Guided parking by providing commands to the driver, e.g. acoustically or optically}	21/18	• characterised by the vehicle type and not provided for in groups $\underline{B62D\ 21/02}$ - $\underline{B62D\ 21/17}$
15/0285	• • {Parking performed automatically}	21/183	• • {specially adapted for sports vehicles, e.g.
15/029	Steering assistants using warnings or proposing		race, dune buggies, go-karts (tubular skeleton B62D 23/005)}
	actions to the driver without influencing the steering system}	21/186	• • {for building site vehicles or multi-purpose tractors (tracked vehicles <u>B62D 55/10</u> ; tractors
15/0295	• • • {by overlaying a vehicle path based on present steering angle over an image without		in general <u>B62D 49/00</u> ; building site vehicles in general <u>E02F</u> ; lift-trucks <u>B66F</u>)}
	processing that image}	21/20	• trailer type, i.e. a frame specifically constructed for use in a non-powered vehicle
17/00	Means on vehicles for adjusting camber, castor, or	23/00	Combined superstructure and frame, i.e. monocoque constructions ({having impact absorbing
	toe-in		means <u>B62D 21/15</u> ; } superstructure {or monocoque
19/00	Radius rods, i.e. distance members		structure} sub-units {or parts or details thereof} <u>B62D 25/00</u> {; characterised by the material thereof
derstructu	<u>ures; Superstructures; Vehicle bodies</u>	23/005	B62D 29/00})
21/00	Understructures, i.e. chassis frame on which a vehicle body may be mounted (combined frame	23/003	• {with integrated chassis in the whole shell, e.g. meshwork, tubes, or the like (<u>B62D 33/044</u> takes precedence)}
21/02	and vehicle body $\underline{B62D\ 23/00}$ {; characterised by the material thereof $\underline{B62D\ 29/00}$ })	24/00	Connections between vehicle body and vehicle frame (B62D 23/00, B62D 33/077 take precedence)
21/02	comprising longitudinally or transversely arranged frame members	24/02	. Vehicle body, not intended to move relatively to the
21/03	transverse members providing body support		vehicle frame, and mounted on vibration absorbing
21/04	single longitudinal type	0.1/0.1	mountings, e.g. rubber pads
21/05	pinched frame type, i.e. formed of at least two longitudinal frame sections connected by other longitudinal frame sections of lesser transverse dimension	24/04	Vehicle body mounted on resilient suspension for movement relative to the vehicle frame

25/00	Superstructure {or monocoque structure} sub- units; Parts or details thereof not otherwise provided for {(having impact absorbing means	25/20	• Floors or bottom sub-units {(sub-frames for mounting engine or suspensions <u>B62D 21/11</u> ; drip trays <u>F16N 31/006</u>)}
	B62D 21/15; running-boards, steps, or the like as superstructure sub-unit B60R 3/00)}	25/2009	{in connection with other superstructure subunits}
25/02	• Side panels {(<u>B62D 33/046</u> takes precedence;	25/2018	• • • {the subunits being front structures}
	sideboards for open load compartments	25/2027	• • • {the subunits being rear structures}
25/025	<u>B62D 33/023</u>)}	25/2036	• • • {the subunits being side panels, sills or pillars
25/025	• • {Side sills thereof}		(B62D 21/157 takes precedence)
25/04	• Door pillars {; windshield pillars}	25/2045	• • • {the subunits being fire walls}
25/06	• Fixed roofs (non-fixed roofs or like shelters B60J 7/00; roof liners B60R 13/02; insulating	25/2054	• • {Load carrying floors for commercial vehicles}
	elements <u>B60R 13/08</u>)	25/2063	• • {Floor elements for repairs}
25/07	having water drainage or guide means integral	25/2072	• • {Floor protection, e.g. from corrosion or scratching (floor mats <u>B60N 3/04</u> , armour
	with roof structure		F41H 7/042, insulation <u>B60R 13/08</u> , streamlining
25/08	• Front or rear portions {(sub-frames for mounting		B62D 35/02)}
	engine or suspensions <u>B62D 21/11</u>)}	25/2081	• • {Jack receiving devices}
25/081	• • {Cowls (ventilating openings situated directly in	25/209	• • { Arrangements for the mounting of vehicle
25/002	front of the vehicle front window <u>B60H 1/28</u>)}		hitches (vehicle connections in general <u>B60D</u>)}
25/082	• • {Engine compartments}	25/24	• Superstructure sub-units with access {or drainage}
25/084 25/085	 {Radiator supports} {Front-end modules}		openings having movable or removable closures;
25/083	{Tront-end modules} {Luggage compartments}		{Sealing means therefor}(inlet covers for vehicle fuel tanks B60K 15/05)
25/087	. {Euggage compartments}. {Details of structures as upper supports for		
23/000	springs or dampers}	27/00	Connections between superstructure {or
25/10	. Bonnets or lids {, e.g. for trucks, tractors, busses,		understructure} sub-units {(B62D 33/0207, B62D 33/044 take precedence; between sub-
	work vehicles (for truck beds B60J 7/1607; for		units predominently made of synthetic material
	boats <u>B63B 19/12</u> ; doors arranged at the vehicle		B62D 29/048)}
	rear <u>B60J 5/10</u> ; inlet covers for vehicle fuel tanks	27/02	· rigid
	<u>B60K 15/05</u> ; for protecting non-occupants of a vehicle <u>B60R 21/38</u>)}	27/023	• • {Assembly of structural joints}
25/105	• • {for motor cars}	27/026	• • {Connections by glue bonding (in general
25/103	• Parts or details thereof (locks <u>E05B</u> ,		<u>F16B 11/00</u> ; processes <u>C09J 5/00</u>)}
23/12	{E05B 83/16; devices for holding open	27/04	 resilient
	E05C 17/00, e.g. while carrying oversize	27/06	 readily releasable
	objects <u>E05C 17/042</u> }; hinges <u>E05D</u> ;	27/065	• • {using screwthread (connection of crossbeam to
	counterbalancing means <u>E05F</u> ; {checks, stops,		A- pillars <u>B62D 25/147</u> ; mounting load bearing surfaces <u>B62D 21/09</u> ; securing mudguards
	buffers <u>E05F 5/00</u> ; } springs, {e.g. pneumatic springs} <u>F16F</u>)		B62D 25/163; connections for synthetic parts
25/14	. Dashboards as superstructure sub-units (other		<u>B62D 29/048</u>)}
25/14	Dashboards as superstructure sub-units (other dashboard aspects B60K)	20/00	
25/14 25/142	 Dashboards as superstructure sub-units (other dashboard aspects <u>B60K</u>) {having ventilation channels incorporated 	29/00	Superstructures, {understructures, or sub-units
	dashboard aspects B60K)	29/00	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof
	 dashboard aspects B60K) {having ventilation channels incorporated therein} {having a crossbeam incorporated therein} 		Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)}
25/142 25/145 25/147	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} 	29/00 29/001	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof
25/142 25/145	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • • Mud-guards or wings; Wheel cover panels 		Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} • {characterised by combining metal and synthetic material} • • {a foamable synthetic material or metal being
25/142 25/145 25/147	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres 	29/001	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} . {characterised by combining metal and synthetic material} {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic
25/142 25/145 25/147 25/16	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) 	29/001 29/002	 Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} {characterised by combining metal and synthetic material} • {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)}
25/142 25/145 25/147	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • {Mud-guards made of non-conventional 	29/001	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} · {characterised by combining metal and synthetic material} · · {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} · · {the metal being over-moulded by the synthetic
25/142 25/145 25/147 25/16	 dashboard aspects B60K) • • {having ventilation channels incorporated therein} • • {having a crossbeam incorporated therein} • • • {with adjustable connection to the A-pillars} • • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • • {Mud-guards made of non-conventional material, e.g. rubber, plastics} 	29/001 29/002 29/004	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} · {characterised by combining metal and synthetic material} · · {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} · · {the metal being over-moulded by the synthetic material, e.g. in a mould}
25/142 25/145 25/147 25/16	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • • {Mud-guards made of non-conventional material, e.g. rubber, plastics} • • {Mounting devices} 	29/001 29/002	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} · {characterised by combining metal and synthetic material} · · {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} · · {the metal being over-moulded by the synthetic material, e.g. in a mould} · · {preformed metal and synthetic material elements
25/142 25/145 25/147 25/16 25/161 25/163	 dashboard aspects B60K) • • {having ventilation channels incorporated therein} • • {having a crossbeam incorporated therein} • • • {with adjustable connection to the A-pillars} • • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • • {Mud-guards made of non-conventional material, e.g. rubber, plastics} 	29/001 29/002 29/004	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} • {characterised by combining metal and synthetic material} • • {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} • • {the metal being over-moulded by the synthetic material, e.g. in a mould}
25/142 25/145 25/147 25/16 25/161 25/163 25/165	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • • {Mud-guards made of non-conventional material, e.g. rubber, plastics} • • {Mounting devices} • • {including sealing devices} 	29/001 29/002 29/004 29/005	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} · {characterised by combining metal and synthetic material} · · {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} · · {the metal being over-moulded by the synthetic material, e.g. in a mould} · · {preformed metal and synthetic material elements being joined together, e.g. by adhesives}
25/142 25/145 25/147 25/16 25/161 25/163 25/165 25/166 25/168 25/18	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • • {Mud-guards made of non-conventional material, e.g. rubber, plastics} • • {Mounting devices} • • {including sealing devices} • • {by rods or other distance-keeping devices} • • {Mud guards for utility vehicles} • • Parts or details thereof, e.g. mudguard flaps 	29/001 29/002 29/004 29/005 29/007	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} • {characterised by combining metal and synthetic material} • • {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} • • {the metal being over-moulded by the synthetic material, e.g. in a mould} • • {preformed metal and synthetic material elements being joined together, e.g. by adhesives} • {predominantly of special steel or specially treated steel, e.g. stainless steel or locally surface hardened steel}
25/142 25/145 25/147 25/16 25/161 25/163 25/165 25/166 25/168	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • • {Mud-guards made of non-conventional material, e.g. rubber, plastics} • • {Mounting devices} • • {including sealing devices} • • {by rods or other distance-keeping devices} • • {Mud guards for utility vehicles} • • Parts or details thereof, e.g. mudguard flaps • • {Movable mudguards, or mudguards 	29/001 29/002 29/004 29/005 29/007	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} · {characterised by combining metal and synthetic material} · {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} · {the metal being over-moulded by the synthetic material, e.g. in a mould} · {preformed metal and synthetic material elements being joined together, e.g. by adhesives} · {predominantly of special steel or specially treated steel, e.g. stainless steel or locally surface hardened steel} · {predominantly of light alloys, e.g. extruded}
25/142 25/145 25/147 25/16 25/161 25/163 25/165 25/166 25/168 25/18	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • • {Mud-guards made of non-conventional material, e.g. rubber, plastics} • • {Mounting devices} • • {including sealing devices} • • • {by rods or other distance-keeping devices} • • {Mud guards for utility vehicles} • • Parts or details thereof, e.g. mudguard flaps • • {Movable mudguards, or mudguards comprising movable or detachable parts 	29/001 29/002 29/004 29/005 29/007 29/008 29/02	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} · {characterised by combining metal and synthetic material} · · {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} · · {the metal being over-moulded by the synthetic material, e.g. in a mould} · · {preformed metal and synthetic material elements being joined together, e.g. by adhesives} · {predominantly of special steel or specially treated steel, e.g. stainless steel or locally surface hardened steel} · {predominantly of light alloys, e.g. extruded} · predominantly of wood
25/142 25/145 25/147 25/16 25/161 25/163 25/165 25/166 25/168 25/18 25/182	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • • {Mud-guards made of non-conventional material, e.g. rubber, plastics} • • {Mounting devices} • • {including sealing devices} • • {by rods or other distance-keeping devices} • • {Mud guards for utility vehicles} • • Parts or details thereof, e.g. mudguard flaps • • {Movable mudguards, or mudguards comprising movable or detachable parts (B62D 25/188 takes precedence)} 	29/001 29/002 29/004 29/005 29/007	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} · {characterised by combining metal and synthetic material} · · {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} · · {the metal being over-moulded by the synthetic material, e.g. in a mould} · · {preformed metal and synthetic material elements being joined together, e.g. by adhesives} · {predominantly of special steel or specially treated steel, e.g. stainless steel or locally surface hardened steel} · {predominantly of light alloys, e.g. extruded} · predominantly of wood · predominantly of synthetic material (working of
25/142 25/145 25/147 25/16 25/161 25/163 25/165 25/166 25/168 25/182 25/182	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • {Mud-guards made of non-conventional material, e.g. rubber, plastics} • {Mounting devices} • • {including sealing devices} • • {by rods or other distance-keeping devices} • • {Mud guards for utility vehicles} • • Parts or details thereof, e.g. mudguard flaps • • {Movable mudguards, or mudguards comprising movable or detachable parts (B62D 25/188 takes precedence)} • • {to facilitate access to wheels} 	29/001 29/002 29/004 29/005 29/007 29/008 29/02 29/04	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} · {characterised by combining metal and synthetic material} · {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} · {the metal being over-moulded by the synthetic material, e.g. in a mould} · {preformed metal and synthetic material elements being joined together, e.g. by adhesives} · {predominantly of special steel or specially treated steel, e.g. stainless steel or locally surface hardened steel} · {predominantly of light alloys, e.g. extruded} · predominantly of synthetic material (working of plastics or substances in a plastic state B29)
25/142 25/145 25/147 25/16 25/161 25/163 25/165 25/166 25/168 25/18 25/182	dashboard aspects B60K) • • {having ventilation channels incorporated therein} • • {having a crossbeam incorporated therein} • • • {with adjustable connection to the A-pillars} • • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • • {Mud-guards made of non-conventional material, e.g. rubber, plastics} • • {Mounting devices} • • • {including sealing devices} • • • {by rods or other distance-keeping devices} • • • {Mud guards for utility vehicles} • • • Parts or details thereof, e.g. mudguard flaps • • • {Movable mudguards, or mudguards comprising movable or detachable parts (B62D 25/188 takes precedence)} • • • { to facilitate access to wheels} • • • { being attached or suspended laterally	29/001 29/002 29/004 29/005 29/007 29/008 29/02 29/04 29/041	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} · {characterised by combining metal and synthetic material} · {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} · {the metal being over-moulded by the synthetic material, e.g. in a mould} · {preformed metal and synthetic material elements being joined together, e.g. by adhesives} · {predominantly of special steel or specially treated steel, e.g. stainless steel or locally surface hardened steel} · {predominantly of light alloys, e.g. extruded} · predominantly of synthetic material (working of plastics or substances in a plastic state B29) · {Understructures}
25/142 25/145 25/147 25/16 25/161 25/163 25/165 25/166 25/168 25/182 25/182	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • {Mud-guards made of non-conventional material, e.g. rubber, plastics} • {Mounting devices} • • {including sealing devices} • • {by rods or other distance-keeping devices} • • {Mud guards for utility vehicles} • • Parts or details thereof, e.g. mudguard flaps • • {Movable mudguards, or mudguards comprising movable or detachable parts (B62D 25/188 takes precedence)} • • {to facilitate access to wheels} 	29/001 29/002 29/004 29/005 29/007 29/008 29/02 29/04	 Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} {characterised by combining metal and synthetic material} {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} {the metal being over-moulded by the synthetic material, e.g. in a mould} {preformed metal and synthetic material elements being joined together, e.g. by adhesives} {predominantly of special steel or specially treated steel, e.g. stainless steel or locally surface hardened steel} {predominantly of light alloys, e.g. extruded} predominantly of synthetic material (working of plastics or substances in a plastic state B29) {Understructures} {Superstructures (B62D 25/161 takes
25/142 25/145 25/147 25/16 25/161 25/163 25/165 25/166 25/168 25/182 25/182	 dashboard aspects B60K) • {having ventilation channels incorporated therein} • {having a crossbeam incorporated therein} • • {with adjustable connection to the A-pillars} • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S) • {Mud-guards made of non-conventional material, e.g. rubber, plastics} • {Mounting devices} • • {including sealing devices} • • {by rods or other distance-keeping devices} • • {Mud guards for utility vehicles} • • Parts or details thereof, e.g. mudguard flaps • • {Movable mudguards, or mudguards comprising movable or detachable parts (B62D 25/188 takes precedence)} • • • {to facilitate access to wheels} • • {being attached or suspended laterally from the wheel (B62D 25/184 takes 	29/001 29/002 29/004 29/005 29/007 29/008 29/02 29/04 29/041	Superstructures, {understructures, or sub-units thereof,} characterised by the material thereof {(B62D 33/044, B62D 33/048 take precedence)} · {characterised by combining metal and synthetic material} · {a foamable synthetic material or metal being added in situ (shaping of substances in a plastic state by foaming, in general B29C 44/00)} · {the metal being over-moulded by the synthetic material, e.g. in a mould} · {preformed metal and synthetic material elements being joined together, e.g. by adhesives} · {predominantly of special steel or specially treated steel, e.g. stainless steel or locally surface hardened steel} · {predominantly of light alloys, e.g. extruded} · predominantly of synthetic material (working of plastics or substances in a plastic state B29) · {Understructures}

29/046	• • {Combined superstructure and frame, i.e.	33/0604	• • {Cabs insulated against vibrations or noise, e.g.
29/048	monocoque constructions} • {Connections therefor, e.g. joints (<u>B62D 29/045</u>)		with elastic suspension (resilient connections between superstructure sub-units <u>B62D 27/04</u> ;
	takes precedence)}		damping noise in general <u>G10K 11/00</u> ; for vehicles in general <u>B60R 13/08</u>)}
31/00	Superstructures for passenger vehicles (passenger	33/0608	• • • {pneumatic or hydraulic suspension}
	vehicles specially adapted to co-operate with aircraft or terminal buildings <u>B64F 1/31</u>)	33/0612	• • {Cabins with living accommodation, especially
31/003	• {compact cars, e.g. city cars}		for long distance road vehicles, i.e. sleeping,
31/005	• {compact cars, e.g. city cars} • • {foldable (droppable <u>B60F 5/006</u>)}		cooking, or other facilities (beds in general
31/000	• for carrying large numbers of passengers, e.g.		adapted to be used in vahicles <u>A47C 17/80</u> ; sanitation devices in vehicles in general
31/02	omnibus		B60R 15/00; living accommodation in vehicles in
31/025	• • {having modular sections}		general <u>B60P 3/32</u> ; passenger fittings in general
31/04	• with more than one deck		B60N 3/00)}
22/00		33/0617	• • {for tractors or off-the-road vehicles (protective
33/00	Superstructures for load-carrying vehicles		devices for drivers in case of overturning of
	({having impact absorbing means <u>B62D 21/15</u> ; } in which a load-carrying element is movable <u>B60P</u> ;		tractors <u>B60R 21/131</u>)}
	liners B60R 13/00 {; joining sheets or plates to	33/0621	• • • {able to be dismantled, folding}
	one another or to strips or bars parallel to them	33/0625	{open}
	<u>F16B 5/00</u> })	33/063	• movable from one position into at least one other
33/02	• Platforms; Open load compartments {(flat wagons		position, e.g. tiltable, pivotable about a vertical
	including posts or standards <u>B61D 3/08</u>)}		axis, displaceable from one side of the vehicle to the other
33/0207	• • {Connections of movable or detachable racks or	33/0633	• • {pivotable about a vertical axis}
	stanchions to platforms}	33/0636	{displaceable along a linear path}
33/0215	• • • { for log hauling vehicles (vehicles for log	33/067	tiltable
22/0222	transport in general <u>B60P 3/41</u>)}	33/07	characterised by the device for locking the
33/0222	 {Connecting elements between stanchions, e.g. roof supporting elements, stiffeners (non-fixed 		cab in the tilted or in the driving position
	roofs <u>B60J 7/00</u> ; securing and covering of load	33/071	{Locking devices for cabins in driving
	B60P 7/00)}		position; Shock and vibration absorbing
33/023	Sideboard or tailgate structures {(vehicle side)		devices therefor}
	panels in general B62D 25/02)}	33/073	characterised by special adaptations of vehicle
33/027	movable	22/077	control devices
33/0273	• • • • {Movable tailboards for vehicles comprising	33/077	 characterised by the connection of the superstructure to the vehicle frame {(B62D 33/06)
	non-movable sideboards, e.g. pick-up trucks		takes precedence)}
22/0276	$\frac{\text{(B62D 33/037)}}{\text{takes precedence)}}$	33/08	• comprising adjustable means (<u>B62D 33/10</u> takes
33/0276	• • • {by vertical translation (<u>B62D 33/0273</u> takes precedence)}		precedence)
33/03	by swinging down {(B62D 33/0273 takes	33/10	• • comprising means for the suspension of the
	precedence)}		superstructure on the frame
33/033	• • • removable {(<u>B62D 33/0273</u> takes	35/00	Vehicle bodies characterised by streamlining
	precedence)}	35/001	• {For commercial vehicles or tractor-trailer
33/037	Latching means therefor		combinations, e.g. caravans}
33/04	• Enclosed load compartments {; Frameworks	35/002	• • {for caravans ($\underline{B62D \ 35/004}$ takes precedence)}
	for movable panels, tarpaulins or side curtains	35/004	• • {Inflatable nose or rear cones}
	(side curtains <u>per se B60J 5/065</u> ; tarpaulins <u>per se B60J 7/00</u> , <u>B60P 7/04</u>)}	35/005	• {Front spoilers (<u>B62D 35/001</u> takes precedence)}
33/042	• { divided into compartments (movable bulk heads	35/007	• {Rear spoilers (<u>B62D 35/001</u> takes precedence)}
33/012	B60P 7/14; cattle transport B60P 3/04; bottled	35/008	• {Side spoilers (<u>B62D 35/001</u> takes precedence)}
	liquids <u>B60P 3/22</u>)}	35/02	• Streamlining the undersurfaces {(B62D 35/005,
33/044	• • {built up with profiles of constant elongated		<u>B62D 35/007</u> , <u>B62D 35/008</u> take precedence)}
	shape, e.g. extruded, mechanically interconnected	37/00	Stabilising vehicle bodies without controlling
	by coupling members, e.g. by clamping, riveting		suspension arrangements
22/045	or bolting}	37/02	by aerodynamic means
33/046	• • {built up with flat self-supporting panels; Fixed	37/04	• by means of movable masses
	connections between panels (<u>B62D 29/045</u> , <u>B62D 33/048</u> take precedence)}	37/06	• using gyroscopes
33/048	• {for refrigerated goods vehicles}	39/00	Vehicle bodies not otherwise provided for {, e.g.
33/06	 Drivers' cabs {(overhead guards, e.g. against loads 		safety vehicles (safety equipment <u>B60R 21/00</u>)}
	falling down <u>B60R 21/11</u> ; roll-over protection	41/00	Fittings for identifying vehicles in case of collision;
	<u>B60R 21/13</u>)}	F1/00	Fittings for marking or recording collision areas
		42/00	
		43/00	Spare wheel stowing, holding, or mounting arrangements
			arrangements

43/002	• {Handling devices, mainly for heavy wheels (via	49/0657	{Asymmetrical tractors}
	cables and chains <u>B62D 43/045</u>)}	49/0664	• • {Light, simple, and economical tractors
43/005	• {Protective coverings for spare wheels}		$(\underline{B62D \ 49/002} \ takes \ precedence)$
43/007	• {Anti-theft devices for spare wheels}	49/0671	• • • {the driver riding on the tractor}
43/02	 external to the vehicle body 	49/0678	• • {Tractors of variable track width or wheel
43/04	 attached beneath the vehicle body 		base (for vehicles in general <u>B60B 23/12</u> and
43/045	{the wheel or its cradle being attached to one or	10/0505	<u>B60B 35/10</u>)}
10/04	more chains or cables for handling}	49/0685	• • {Reversible tractors adapted for shuttle work}
43/06	• within the vehicle body	49/0692	• Characterised by the particular arrangement of control devices, e.g. having more than one control
43/08	and arranged substantially vertically		stand, operable from vehicle extension (control
43/10	and arranged substantially horizontally les or trailers classified according to type; Parts or		devices or systems characterised by mechanical features only)}
	hereof (frames for vehicles of special type B62D 21/18)	49/08	 having means for preventing overturning or tipping
47/00	Motor vehicles or trailers predominantly for		(safety devices for propulsion-unit control, specially adapted for, or arranged in, vehicles <u>B60K 28/00</u>)
	carrying passengers (superstructures <u>B62D 31/00</u>)	49/085	• {Counterweight}
47/003	• {convertible in order to modify the number of seats	49/063	• • (Counterweight)
	(foldable compact cars <u>B62D 31/006</u> ; convertible	51/00	Motor vehicles characterised by the driver not
	from one use to a different one $\underline{B60P 3/42}$)		being seated {(wheeled carriers for golf bags
47/006	• {Vehicles which can be divided in sub-vehicles;	71/001	A63B 55/60)}
	nestable vehicles}	51/001	{characterised by the vehicle control device (mechanical features of control devices in general
47/02	• for large numbers of passengers, e.g. omnibus		G05G; arrangements of vehicle control devices in
47/025	• • {articulated buses with interconnecting		general <u>B60K 20/00</u> , <u>B60K 23/00</u> , <u>B60K 26/00</u>)}
	passageway, e.g. bellows (coupling aspects B60D 5/00)}	51/002	• • {comprising safety arrangements (safety devices
	<u>B00D 5/00</u>)}		for vehicle propulsion unit control <u>B60K 28/00</u>)}
49/00	Tractors (of walk type <u>B62D 51/04</u> ; endless- track	51/004	• {characterised by the transmission (arrangements or
	features <u>B62D 55/00</u> {; transport specially adapted for		mounting of transmissions in vehicles <u>B60K 17/00</u> ;
40,1000	underground galleries <u>E21F 13/02</u> })		gearing in general <u>F16H</u>)}
49/002	• {characterised by being of the low ground pressure	51/005	• {Vehicular characteristics of load handling vehicles,
40/005	type}	-1.100-	e.g. pedestrian trucks (fork-lift trucks <u>B66F 9/06</u>)}
49/005	• {Tractors for semi-trailers (combinations of tractor plus semi- trailer <u>B62D 53/06</u>)}	51/007	• {the vehicle being of the endless track type (endless
49/007	• • {Tractors for handling trailers, e.g. roll-trailers in	51/008	track vehicles in general <u>B62D 55/00</u>)
47/007	terminals}	31/008	 {characterised by the vehicle being formed by articulated or separable units (road trains
49/02	 modified to take lifting devices 		$\frac{B62D}{53/00}$
49/04	 modified to take pushing devices 	51/02	• the driver standing in the vehicle
49/06	adapted for multi-purpose use	51/04	the driver walking
49/0607	{Straddle tractors, used for instance above vine	51/06	Uniaxle walk-type tractors
	stocks, rows of bushes, or the like}	51/065	{the vehicle baving only one wheel}
49/0614	• • {equipped with visual aids for positioning	53/00	Tuestan tueilan aambinations. Dood tueina (tuestion
	implements or to control working condition	53/00	Tractor-trailer combinations; Road trains (traction couplings other than fifth wheel coupling <u>B60D</u> {;
	(optical signalling for vehicles in general		tracked vehicles comprising at least two articulated
49/0621	B60Q 1/26)} {comprising traction increasing arrangements,		parts <u>B62D 55/0655</u> })
49/0021	e.g. all-wheel traction devices, multiple-	53/005	• {Combinations with at least three axles and
	axle traction arrangements, auxiliary traction		comprising two or more articulated parts
	increasing devices (anti-skid or anti-slip devices		(articulated buses <u>B62D 47/025</u>)}
	fitted onto the wheels <u>B60B 15/02</u> , <u>B60B 39/12</u> ;	53/02	 comprising a uniaxle tractor unit and a uniaxle
	arrangements of transmission for driving both		trailer unit $\{(\underline{\text{see}} \ \underline{\text{B60B } 11/00} - \underline{\text{B60B } 11/08})\}$
	front and rear wheels or tandem wheels of	53/021	• . (comprising a universal coupling joint)
10/0 - 20	vehicles <u>B60K 17/34</u> , <u>B60K 17/36</u>)}	53/023	• • {with two or more coupling joints allowing
49/0628	• • • {using detachable weights (counterweights	52/025	staggering of the units from a central plane}
	against overturning <u>B62D 49/085</u> ; movable	53/025	• • {Comprising a transmission shaft passing
49/0635	stabilisation masses <u>B62D 37/04</u>)} {using additional ground engaging means, e.g.		through the coupling joints (B62D 53/021 takes precedence; trailers with powered axles
47/0033	endless tracks (vehicles with endless tracks and		B62D 59/00)}
	either additional or alternative ground wheels	53/026	• • • {With all wheels powered}
	B62D 55/02, B62D 55/04)}	53/028	Having only coupling joints other than
49/0642	• • · {by coupling of tractors}	55,020	directional (articulated frames B62D 21/186 and
49/065	• • {Coupling of multi-purpose tractors with		B62D 55/10)}
	equipment (towing bars B60D; with load transfer	53/04	. comprising a vehicle carrying an essential part of
	<u>B62D 53/08</u> ; power take-off <u>B60K</u> ; with lifting		the other vehicle's load by having supporting means
	devices <u>B62D 49/02</u> ; pushing gear <u>B62D 49/04</u>)}		for the front or rear part of the other vehicle

53/045	• • {with rigid linkage in the horizontal plane (luggage trailers <u>B62D 63/064</u> - <u>B62D 63/067</u>)}	55/00	Endless track vehicles (steering aspects <u>B62D 11/00</u> ; {characterised by the driver not being seated
53/06	Semi-trailers		B62D 51/007})
53/061	• • • {of flat bed or low loader type or fitted	55/02	• with tracks and additional ground wheels {(for
	with swan necks (detachable swan necks	55/OA	multi-purpose tractors <u>B62D 49/0635</u>)}
	B62D 53/065; swan neck-fifth wheel couplings B62D 53/08)}	55/04	 with tracks and alternative ground wheels, e.g. changeable from endless track vehicle into wheeled
53/062	• • • {having inclinable, lowerable platforms;		vehicle and <u>vice versa</u> {(for multi-purpose tractors
33/002	Lift bed trailers; Straddle trailers (lifting		B62D 49/0635)}
	coupling saddles <u>B62D 53/0821</u> ; crane	55/06	with tracks without ground wheels
	vehicles <u>B60P 3/28</u>)}	55/062	{Tracked vehicles of great dimensions adapted
53/064	• • • • {inclining platforms by detachable bogies}		for moving bulky loads or gear}
53/065	• • • • {inclining platforms by detachable or	55/065	Multi-track vehicles, i.e. more than two tracks
	folding swan necks}		{(soil-shifting machines <u>E02F</u> ; mining machines
53/067	• • • {Multi-purpose, convertible or extendable load		<u>E21C</u>)}
	surface semi-trailers (for container transport	55/0655	{Articulated endless track vehicles (steering
	<u>B60P 1/6418</u> ; convertible road transport vehicles in general <u>B60P 3/42</u>)}		specially adapted for trailers <u>B62D 13/00</u> ; articulated buses B62D 47/025; tractor-trailer
53/068	• • • {having devices to equalise or modify the		combinations or road trains comprising a uni-
33/008	load between the fifth wheel and the rear		axle unit and a uni-axle trailer <u>B62D 53/02</u>)
	wheels (adjustable couping saddles per se	55/07	Mono-track vehicles
	B62D 53/0807; load transfer devices to permit	55/075	Tracked vehicles for ascending or
	coupling or uncoupling B62D 53/0857; anti		descending stairs, {steep slopes or vertical
	jack-knifing devices <u>B62D 53/0871</u>)}		surfaces}(magnetic or pneumatic ground-
53/08	• Fifth wheel traction couplings {(tractors for		engaging parts <u>B62D 55/265</u> ; chairs or multi-
£2/0907	handling trailers in terminals <u>B62D 49/007</u>)}		track cycles specially adapted for invalids A61G 5/00)
53/0807	 . • {adjustable coupling saddles mounted on sub- frames; Mounting plates therefor} 	55/08	• Endless track units; Parts thereof
53/0814	• • • { with adjustment of the clearance between	55/084	Endless track units, raits thereof Endless-track units or carriages mounted
33/0011	the tractor or the trailer (devices modifying	33/004	separably, adjustably or extensibly on vehicles,
	the load in tractor-trailer combinations		e.g. portable track units (<u>B62D 55/07</u> takes
	<u>B62D 53/068</u>)}		precedence)
53/0821	• • • {Lifting saddles, i.e. to lift the trailer front	55/0842	• • • {Tracked vehicle with track carriages
70 (0.000	(tilting body constructions <u>B60P</u>)		suspended on three points, e.g. by an equaliser
53/0828	• • • • (Removable or fold-away traction couplings	55/0045	bar}
53/0835	for non-specialised tractor vehicles } {Coupling saddles able to rock in all	55/0845 55/0847	 {Protection devices} {Track blocking devices mounted on the frame;
33/0033	directions, e.g. for use in rough terrain}	33/0047	Track guides}
53/0842	{King pins}	55/088	• • with means to exclude or remove foreign matter,
53/085	• • • • {fitted with anti-coupling devices, pivotal		e.g. sealing means, self-cleaning track links or
	or retractable king pins, e.g. to prevent		sprockets, deflector plates or scrapers
	theft (vehicle fittings for preventing theft in	55/0882	• • • {Track or sprocket cleaning devices mounted
52/0055	general <u>B60R 25/00</u>)}		on the frame (wheel cleaning devices in general
53/0857	• • • {Auxiliary semi-trailer handling or loading	55/0005	<u>B60S</u>)}
53/0864	equipment, e.g. ramps, rigs, coupling supports} {Dollies for fifth wheel coupling}	55/0885	 {Self-cleaning sprockets} {Track-articulation sealings against dust,
53/0804	• • { With stabilising means, e.g. to prevent jack-	55/0887	water, mud or the like (sealing of bearings in
33/00/1	knifing, pitching, rolling, buck jumping		general <u>F16C 33/72</u> ; chain bushings in general
	(stabilising in general <u>B62D 37/00</u> ; tractors		F16G 15/00)}
	<u>B62D 49/08</u>)}	55/092	with lubrication means (lubricating in general
53/0878	• • • { the fifth wheel coupling incorporating		<u>F16N</u>)
	braking or restraining means}	55/096	with noise reducing means
53/0885	{Comprising devices to limit or to compensate	55/0963	• • • {Anti-noise driving sprockets}
	for wear or excessive play; Lubricating, shock absorbing, bearing devices, or the like}	55/0966	• • • {Low noise rollers, e.g. with antivibration
53/0892	• • {comprising power transmission shafts (trailers		means (elastic wheel rims in general B60B 9/00)}
22,0072	with driven ground wheels <u>B62D 59/00</u>)}	55/10	Bogies; Frames (track-tensioning means)
53/10	with means for preventing accidental	2-7-0	B62D 55/30)
	uncoupling	55/104	Suspension devices for wheels, rollers, bogies or
53/12	engaging automatically		frames (vehicle suspension in general <u>B60G</u>)
53/125	• • • { with simultaneous coupling of the service	55/108	• • • with mechanical springs, e.g. torsion bars
	lines}	55/1083	• • • {Torsion-bar springs}
		55/1086	• • • {Rubber springs}
		55/112	• • • with fluid springs, e.g. hydraulic pneumatic

55/1125	• • • {Hydro-pneumatic or pneumatic, e.g. air-cushioned}	57/02	 with ground-engaging propulsion means, e.g. walking members
55/116	• • Attitude or position control of chassis by action on suspension, e.g. to compensate for a slope	57/021	• • {the ground engaging means being sequentially inflatable bags for peristaltic movement
55/12	 Arrangement, location, or adaptation of driving sprockets 	57/022	(B62D 57/024 takes precedence)} • • {consisting of members having both rotational}
55/125	Final drives		and walking movements}
55/13	readily interchangeable modular type	57/024	specially adapted for moving on inclined or
55/135	with dismountable driving crown		vertical surfaces (endless-track vehicles for ascending or descending stairs B62D 55/075;
55/14	. Arrangement, location, or adaptation of rollers		hand-carts with provision for travelling up or
55/145	• • • {Rollers with replaceable wear rings or rims		down stairs B62B 5/02)
	(driving sprockets with replaceable rims B62D 55/12)}	57/028	• having wheels and mechanical legs (B62D 57/024
55/15	Mounting devices, e.g. bushings, axles, bearings, sealings {(with lubrication means})		takes precedence; ground-engaging vehicle fittings for supporting, lifting or manoeuvring the
	B62D 55/092)}		vehicle, wholly or in part <u>B60S 9/00</u>)
55/18	• Tracks (self-cleaning track links <u>B62D 55/088</u>)	57/032	• with alternately or sequentially lifted supporting
55/20	• • • of articulated type, e.g. chains {(with		base and legs; with alternately or sequentially lifted feet or skid (B62D 57/024 takes
	lubrication means <u>B62D 55/092</u>)}		precedence)
55/202	• • • • Wheel engaging parts; Wheel guides on	57/036	• screw type, e.g. Archimedian screw {(amphibious
55/005	links}		vehicles comprising screw-type ground-engaging
55/205	Connections between track links		means <u>B60F 3/0023</u>)}
55/21 55/211	Links connected by transverse pivot pins	57/04	 having other than ground-engaging propulsion
55/211	{Bitubular chain links assembled by pins and double connectors}		means, e.g. having propellers (arrangement of jet-
55/213	{Master track links}		propulsion units <u>B60K</u>)
55/215	Resilient connections between links	59/00	Trailers with driven ground wheels or the like
55/22	Arrangements for preventing or modifying	59/02	 driven from external propulsion unit
	back-flexing	59/04	 driven from propulsion unit on trailer
55/24	• • of continuously flexible type, e.g. rubber belts	61/00	Motor vehicles or trailers, characterised by the
55/242	• • • {The flexible band being semi-rigid for	01/00	arrangement or number of wheels, not otherwise
	resisting back-flexing and contributing to		provided for, e.g. four wheels in diamond pattern
55/244	spring the vehicle}	61/02	. with two road wheels in tandem on the longitudinal
33/244	• • • • {Moulded in one piece, with either smooth surfaces or surfaces having projections, e.g.		centre line of the vehicle
	incorporating reinforcing elements}	61/04	with two other wheels which are coaxial
55/247	Gas filled or inflatable flexible tracks	61/06	• with only three wheels
	(connection of valves to inflatable elastic	61/065	• • {with single rear wheel}
	bodies <u>B60C 29/00</u>)	61/08	with single front wheelwith more than four wheels {(tractors of the low
55/253	having elements interconnected by one or	61/10	ground pressure type <u>B62D 49/002</u>)}
55/06	more cables or like elements	61/12	• with variable number of ground engaging wheels,
55/26	 Ground engaging parts or elements {(tracks specially adapted for amphibious vehicles 	01/12	e.g. with some wheels arranged higher than others,
	B60F 3/0015)}		or with retractable wheels (for manoeuvring
55/265	having magnetic or pneumatic adhesion		purposes only <u>B60S</u>)
55/27	having different types of crampons for	61/125	• • {the retractable wheel being a part of a set of
	progression over varying ground		tandem wheels (resilient suspension for a single
55/275	with street plate, i.e. means to prevent tread		set of tandem wheels <u>B60G 5/00</u>)}
	from cutting into road surface	63/00	Motor vehicles or trailers not otherwise provided
55/28	detachable		for
55/283	{and movable, e.g. around an axis or	63/02	• Motor vehicles
55/286	perpendicularly to the track} {For soft grounds, e.g. consisting of snow}	63/025	 {Modular vehicles (superstructures for busses having modular sections <u>B62D 31/025</u>)}
33/200	or swamp}	63/04	
55/30	Track-tensioning means	63/04	 Component parts or accessories Trailers (vehicles comprising living accommodation
55/305	• • {acting on pivotably mounted idlers}	03/00	for people, e.g. caravans, camping or like vehicles
55/32	Assembly, disassembly, repair or servicing of		B60P 3/32)
	endless-track systems	63/061	• • {Foldable, extensible or yielding trailers (foldable
57/00	Vehicles characterised by having other propulsion		caravans <u>B60P 3/34</u> ; adjustable chassis frames
37/00	or other ground- engaging means than wheels or		<u>B62D 21/14</u>)}
	endless track, alone or in addition to wheels or	63/062	• • {Trailers with one axle or two wheels (semi-
	endless track (sledges <u>B62B</u> ; motor sledges <u>B62M</u>)		trailers <u>B62D 53/06</u>)}

63/064	• • • {light luggage or equipment trailers, e.g. for batteries, gas generators, gas bottles, stretchers (luggage carriers per se B60R)}
63/065	 (luggage carriers <u>per se Book</u>) . • {forming an extension of the towing vehicle, i.e. with two point fixation}
63/067	• • • { single wheeled (rigid or semi-rigid couping) }
63/068	• • {with more than two axles or more than four wheels (vehicles with more than four wheels in general B62D 61/10)}
63/08	Component parts or accessories
65/00	Designing, manufacturing, e.g. assembling, facilitating disassembly, or structurally modifying
	motor vehicles or trailers, not otherwise provided for
65/005	• {Inspection and final control devices}
65/02	 Joining sub-units or components to, or positioning sub-units or components with respect to, body shell or other sub-units or components
65/022	• • {Transferring or handling sub-units or
	components, e.g. in work stations or between workstations and transportation systems}
65/024	 {Positioning of sub-units or components with respect to body shell or other sub-units or components}
65/026	• • • {by using a jig or the like; Positioning of the jig}
65/028	• • • {by determining relative positions by measurement}
65/04	 Joining preassembled modular units composed of sub-units performing diverse functions, e.g. engine and bonnet (<u>B62D 65/06</u> - <u>B62D 65/16</u> take precedence)
65/06	 the sub-units or components being doors, windows, openable roofs, lids, bonnets, or weather strips or seals therefor {(assembling sealing arrangements with vehicle parts, e.g. doors, windows <u>B60J 10/45</u>)}
65/10	 the sub-units or components being engines, clutches or transmissions
65/12	 the sub-units or components being suspensions, brakes or wheel units
65/14	 the sub-units or components being passenger compartment fittings, e.g. seats, linings, trim, instrument panels
65/16	• • the sub-units or components being exterior fittings, e.g. bumpers, lights, wipers {, exhausts}
65/18	 Transportation, conveyor or haulage systems specially adapted for motor vehicle or trailer assembly lines {(conveyors and haulage in general <u>B65G</u>)}
67/00	Systematic disassembly of vehicles for recovery of salvageable components, e.g. for recycling (for disposal of vehicles by destroying or transformation B09B 3/00, B09B 5/00 {; general arrangement of separating plants B03B 9/00; recovery of plastics B29B 17/00})