CPC COOPERATIVE PATENT CLASSIFICATION

E FIXED CONSTRUCTIONS

BUILDING

E03 WATER SUPPLY; SEWERAGE

E03C DOMESTIC PLUMBING INSTALLATIONS FOR FRESH WATER OR WASTE

WATER (not connected to either water-supply main or to waste pipe <u>A47K</u>; devices of the kind used in the ground <u>E03B</u>, <u>E03F</u>); **SINKS**

WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

| 1/00 | Domestic plumbing installations for fresh water or |
|-----------|--|
| | waste water; Sinks {(work tops A47B 77/022)} |
| 2001/005 | • {Installations allowing recovery of heat from waste |
| | water for warming up fresh water} |
| 1/01 | . for combinations of baths, showers, sinks, wash- |
| | basins, closets, urinals, or the like {(combinations |
| | of baths, douches, or the like, <u>A47K 4/00</u> ; cell-like |
| | units for special technical purposes <u>E04B 1/34869;</u> |
| | panels adapted for locating conduits E04C 2/52; |
| 1/02 | ducts for installation lines E04F 17/08)} |
| 1/02 | • Plumbing installations for fresh water |
| 1/021 | • • {Devices for positioning or connecting of |
| | water supply lines (connection to the tap body |
| 1/022 | <u>E03C 1/0403</u>)} |
| 1/023 | • • {with flow distribution, e.g. diverters} |
| 1/025 | • {Water supply lines as such, e.g. shower hoses} |
| 2001/026 | • {with flow restricting devices} |
| 2001/028 | • • {Alignment aids for plumbing installations} |
| 1/04 | • Water-basin installations specially adapted to wash-basins or baths (valves, faucets, mixing |
| | valves, taps $\underline{F16K}$) |
| 1/0401 | • • • {Fixing a tap to the sanitary appliance or to an |
| 1/0401 | associated mounting surface, e.g. a countertop} |
| 1/0402 | • • • • { with mounting from only one side } |
| 1/0402 | . {Connecting the supply lines to the tap body} |
| 1/0403 | Constructional or functional features of the |
| 1/0404 | spout} |
| 1/0405 | • • • {enabling multiple spray patterns} |
| 1/0407 | • • • {Spouts for unpressurized outflow of water} |
| 1/0408 | • • • {Water installations especially for showers |
| 1,0100 | $(\underline{E03C 1/06} \text{ takes precedence; shower heads})$ |
| | B05B 1/18)} |
| 1/0409 | • • • {Shower handles} |
| 1/041 | • • {having provisions against scalding, e.g. |
| | temperature limiting devices, external covers} |
| 1/0411 | • • • {Taps specially designed for dispensing boiling |
| | water} |
| 1/0412 | • • • {Constructional or functional features of the |
| | faucet handle (valve actuating members as such |
| | <u>F16K 31/60</u>)} |
| 2001/0414 | • • • {allowing different orientations of the spout or |
| | the outlet nozzle} |
| 2001/0415 | • • • {having an extendable water outlet} |
| 2001/0416 | • • • {using a socket for mounting of faucet} |
| | |

| 2001/0417 | • • {having space-saving features, e.g. retractable, demountable} |
|-------------------|--|
| 2001/0418 | • • • {having temperature indicating means} |
| 1/042 | • • • Arrangements on taps for wash-basins or baths |
| 1/012 | for connecting to the wall |
| 1/044 | • • • having a heating or cooling apparatus in the supply line (water heaters, e.g. with continuous flow, F24H) |
| 1/046 | • • • Adding soap, disinfectant, or the like in the supply line {or at the water outlet}(preventing contamination of drinking-water pipes <u>E03C 1/10</u>) |
| 1/0465 | • • • {by mounting an independent soap dispenser to outlet of tap} |
| 1/048 | • • • supplying water through two or more openings around or along one side of the water-basin |
| 1/05 | • Arrangements of devices on wash-basins, baths, sinks, or the like for remote control of taps (remote control of taps or the like <u>per se F16K</u>) |
| 1/052 | • • {Mechanical devices not being part of the tap, e.g. foot pedals} |
| 1/055 | • • {Electrical control devices, e.g. with push buttons, control panels or the like} |
| 1/057 | • • • {touchless, i.e. using sensors} |
| 1/06 | Devices for suspending or supporting the supply pipe or supply hose of a shower-bath {(showers per se A47K 3/28)} |
| 1/063 | • • • {with reciprocating mechanisms (reciprocating mechanisms for massage, other than showers <u>A61H 2201/1669</u>)} |
| 1/066 | • • {allowing height adjustment of shower head} |
| 1/08 | • Jet regulators {or jet guides}, e.g. anti-splash devices |
| 2001/082 | |
| 2001/082 1/084 | {Outlets connected by an universal joint} . Jet regulators with aerating means |
| | |
| 1/086 | Jet regulators or jet guides, easily mountable on the outlet of taps |
| 1/10 | • Devices for preventing contamination of drinking-water pipes, e.g. means for aerating self-closing flushing valves (vacuum-breakers in general <u>F16K</u> , <u>F16L</u>) |
| 1/102 | • • • {using an air gap device} |
| 1/104 | • • { using a single check valve } |
| 1/106 | {using two or more check valves} |
| | |

E03C

| 1/108 | • • • {having an aerating valve} |
|--------------|---|
| 1/12 | • Plumbing installations for waste water; Basins |
| | or fountains connected thereto (drainage devices |
| | in floors <u>E03F 5/04</u>); Sinks {(wash-basins not connected to the waste-pipe <u>A47K 1/04</u>)} |
| 2001/1206 | Pipes with specific features for influencing flow |
| 2001/1200 | characteristics} |
| 2001/1213 | • • {Constructional features of bidet bowls; adapters |
| 1/122 | for using other sanitary appliances as bidet} |
| 1/122 | • Pipe-line systems for waste water in building (pipe-line systems in general <u>F17D</u>) |
| 1/1222 | • • {Arrangements of devices in domestic waste |
| | water pipe-line systems} |
| 1/1225 | • • • {of air admittance valves (structural details of air admittance valves <u>F16K 24/06</u>)} |
| 1/1227 | • • • {of pumps for facilitating drawing off} |
| 1/126 | Installations for disinfecting or deodorising |
| | waste-water plumbing installations |
| 1/14 | • Wash-basins connected to the waste-pipe |
| 1/16 1/18 | • Wash-fountains connected to the waste-pipe |
| 1/18 | Sinks, whether or not connected to the waste-pipe Anti-splash devices in sinks, e.g. splash guards |
| 1/101 | (jet regulators <u>E03C 1/08</u>) |
| 1/182 | connected to the waste-pipe |
| 1/184 | adapted for attachment of washing machines |
| | or heating or cooling devices (washing machines for attachment D06F 7/00) |
| 1/186 | Separate partition walls, lids, protecting |
| | borders, or the like, for sinks |
| 1/20 | . Connecting baths or bidets to the wastepipe |
| 1/22 | • Outlet devices mounted in basins, baths, or sinks (stoppers <u>A47K 1/14</u>) |
| 1/23 | • • • with mechanical closure mechanisms |
| 1/2302 | • • • • {the actuation force being transmitted to the |
| | plug via rigid elements} |
| 1/2304 | •••• {the actuation force being transmitted to the plug via flexible elements, e.g. chain, |
| | Bowden cable} |
| 1/2306 | • • • • {the plug being operated by hand contact} |
| 1/2308 | • • • • {actuated by rotating the wash-basin} |
| 2001/2311 | • • • • {the actuation force being magnetic or |
| 2001/2313 | electromagnetic }the actuation force being pneumatic or |
| 2001/2010 | hydraulic} |
| 2001/2315 | • • • { the actuation force created by a turning |
| 2001/2317 | movement of a handle }transmission of actuation force involves a |
| 2001/2317 | {transmission of actuation force involves a spring} |
| 1/232 | combined with overflow devices (overflow |
| | devices for basins or baths per se E03C 1/24) |
| 1/24 | • Overflow devices for basins or baths (E03C 1/232 takes precedence) |
| 2001/2406 | • • {Overflow alarm devices} |
| 2001/2413 | • • {Covers for temporarily closing off overflow |
| | outlets} |
| 1/242 | automatically actuating supply or draining valves |
| 1/244 | . Separate devices to be placed on the outlet |
| | opening |
| 1/26 | . Object-catching inserts or similar devices |
| | for waste pipes or outlets (<u>E03C 1/28</u> takes precedence) |
| 1/262 | combined with outlet stoppers |
| | · · · · · · · · · · · · · · · · · · · |

| 1/264 | Separate sieves or similar object-catching inserts |
|----------|---|
| 1/266 | • • Arrangement of disintegrating apparatus in waste pipes or outlets; Disintegrating apparatus specially adapted for installation in waste pipes or outlets |
| 1/2665 | •••• {Disintegrating apparatus specially adapted for installation in waste pipes or outlets (disintegrating apparatus <u>per se B02C</u>)} |
| 1/28 | • • Odour seals |
| 1/281 | • • {using other sealants than water} |
| 1/282 | combined with additional object-catching |
| | devices |
| 1/284 | • • • having U-shaped trap |
| 1/286 | • • • having hand-operated valves against return of waste water |
| 1/288 | • • • having non-return valves against return of waste water (E03C 1/286 takes precedence) |
| 1/29 | • • • having housing containing dividing wall, e.g. tubular |
| 1/292 | • • • having elastic housing |
| 1/294 | • • • with provisions against loss of water lock |
| 1/295 | • • • using air-supply valves |
| 1/296 | using water-supply valves |
| 1/298 | consisting only of non-return valve |
| 1/30 | • Devices to facilitate removing of obstructions in |
| | waste-pipes or sinks {(for use in sewer pipes or both in waste and sewer pipes <u>E03F 9/00</u>)} |
| 1/302 | using devices moved through the pipes {(and simultaneously rotated by means of a cable or rods E03F 9/005)} |
| 1/304 | • • • using fluid under pressure |
| 1/306 | • • • by means of a tube connected to the water mains |
| 1/308 | •••• by means of a pumping device |
| 1/32 | • Holders or supports for basins |
| 2001/321 | • • • {Siphon or angle valve covers} |
| 1/322 | connected to the wall only |
| 1/324 | adjustable |
| 1/326 | • • • resting on the floor |
| 1/328 | • • • • adjustable |
| 1/33 | Fastening sinks or basins in an apertured |
| | support |
| 1/335 | {the fastening means comprising a screw} |
| 2201/00 | Details, devices or methods not otherwise provided |
| | for |
| 2201/30 | • Diverter valves in faucets or taps |
| 2201/40 | . Arrangement of water treatment devices in domestic |
| | plumbing installations |
| 2201/45 | • • for carbonated water |
| 2201/50 | • Constructional features of escutcheons for domestic |
| | plumbing installations |
| 2201/60 | • Reducing noise in plumbing systems |
| 2201/70 | • Reducing or removing limescale at spout outlet |
| 2201/80 | . Combined water inlet and outlet devices |
| 2201/90 | Basins movable between several positions |
| | - |