

CPC COOPERATIVE PATENT CLASSIFICATION

E FIXED CONSTRUCTIONS

BUILDING

E05 LOCKS; KEYS; WINDOW OR DOOR FITTINGS; SAFES

(NOTE omitted)

E05C BOLTS OR FASTENING DEVICES FOR WINGS, SPECIALLY FOR DOORS OR WINDOWS (latching means for sideboard or tailgate structures for vehicles [B62D](#), {[B62D 33/02](#)}; fastening devices for constructional or engineering elements [E04](#), [F16B](#); locks, fastening devices structurally or operatively combined or having significant cooperation with locks [E05B](#); means for operating or controlling wing fasteners in conjunction with mechanisms for moving the wing [E05F](#))

NOTES

1. In this subclass only the movement essential for securing the wing is considered, e.g. a sliding bolt which is rotated on its axis to prevent its withdrawal is classified as having only a sliding movement.
2. Attention is drawn to the definition following the title of class [E05](#).

WARNINGS

1. The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:

E05C 3/32	covered by	E05C 3/30
E05C 17/06	covered by	E05C 17/04
E05C 17/10	covered by	E05C 17/04
E05C 21/02	covered by	E05C 21/00
2. In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

Bolts, latches, or equivalent wing-fastening devices, characterised by special way of movement, e.g. moving rectilinearly, pivotally or rotatively (devices released automatically by pull or pressure on the wing [E05C 19/02](#); hasps [E05C 19/08](#); hook fastenings [E05C 19/10](#))

<p>1/00 Fastening devices with bolts moving rectilinearly</p> <p>1/002 . {perpendicular to the surface on which the fastener is mounted}</p> <p>1/004 . {parallel to the surface on which the fastener is mounted}</p> <p>1/006 . . {parallel to the wing edge}</p> <p>2001/008 . {the axis of the bolt movement forming an oblique angle with the surface from which the bolt protrudes, e.g. the wing edge}</p> <p>1/02 . without latching action</p> <p>1/04 . . with operating handle or equivalent member rigid with the bolt</p> <p>1/06 . . with operating handle or equivalent member moving otherwise than rigidly with the bolt</p> <p>1/065 . . . {flush}</p> <p>1/08 . with latching action</p> <p>1/085 . . {With means for assisting depression of the latch bolt during latching}</p> <p>1/10 . . with operating handle or equivalent member rigid with the latch</p> <p>1/12 . . with operating handle or equivalent member moving otherwise than rigidly with the latch</p>	<p>1/14 . . . the handle or member moving essentially towards or away from the plane of the wing or frame</p> <p>1/145 {flush}</p> <p>1/16 . . . the handle or member moving essentially in a plane substantially parallel to the wing or frame</p> <p>1/163 {Cylindrical or tubular latches}</p> <p>1/166 {with sliding handle}</p> <p>3/00 Fastening devices with bolts moving pivotally or rotatively</p> <p>3/002 . {sliding in an arcuate guide or the like (locks with circular bolts E05B 63/123)}</p> <p>3/004 . {about an axis perpendicular to the surface on which the fastener is mounted}</p> <p>3/006 . {about an axis parallel to the surface on which the fastener is mounted}</p> <p>3/008 . . {parallel to the wing edge}</p> <p>3/02 . without latching action</p> <p>3/04 . . with operating handle or equivalent member rigid with the bolt</p> <p>3/041 . . . {rotating about an axis perpendicular to the surface on which the fastener is mounted}</p> <p>3/042 {the handle being at one side, the bolt at the other side or inside the wing}</p> <p>3/043 {the pivot being between bolt and handle (E05C 3/042 takes precedence)}</p>
---	---

3/044 {the bolt and handle being at the same side of the pivot (E05C 3/045 , E05C 3/046 take precedence)}	3/38 with bolts engaging a hooked keeper (E05C 3/24 , E05C 3/30 , E05C 3/36 take precedence)
3/045 {in the form of a hook (hook-like fastenings E05C 19/10)}	3/40 with bolts engaging a stud-like keeper (E05C 3/24 , E05C 3/30 , E05C 3/36 take precedence)
3/046 {in the form of a crescent-shaped cam (hooks E05C 3/045)}	5/00	Fastening devices with bolts moving otherwise than only rectilinearly and only pivotally or rotatively {(E05C 9/1883 , E05C 19/009 , E05B 63/125 , E05B 63/126 , E05B 63/127 take precedence; pivotally-mounted hooks-like fastenings with toggle action E05C 19/14 ; bayonet-type locks E05B 63/125 ; locks for sliding wings, with additional movement E05B 65/0817)}
3/047	. . . {rotating about an axis parallel to the surface on which the fastener is mounted}		
3/048 {parallel to the wing edge}		
3/06	. . with operating handle or equivalent member moving otherwise than rigidly with the bolt		
3/08	. . . the handle or member moving essentially towards or away from the plane of the wing or frame		
3/10	. . . the handle or member moving essentially in a plane substantially parallel to the wing {or frame}	2005/005	. {Pivoting bolts or catches being able to move in an additional direction, e.g. by sliding or by pivoting about an additional axis, in order to allow closing of the wing even if the bolt or catch is in its locked position}
3/12	. with latching action (devices in which the securing part is formed or merely carried by a spring and moves only by distortion of the spring, e.g. snaps, E05C 19/06 ; tilt-plate latches E05C 19/007)	5/02	. both moving axially and turning about their axis to secure the wing
3/122	. . {flush}	5/04	. . performing both movements simultaneously, e.g. screwing into a keeper
3/124	. . {with latch under compression force between its pivot and the striker (E05C 3/122 , E05C 3/14 , E05C 3/16 and E05B 65/0852 take precedence)}	7/00	Fastening devices specially adapted for two wings
2003/126	. . {Only part of the latch movable for latching}		NOTE
2003/128	. . {Pendulum-type bolt}		If a fastening device merely secures one wing to another wing which is already closed it is not regarded as specially adapted for two wings
3/14	. . with operating handle or equivalent member rigid with the latch {(E05C 3/122 takes precedence)}	7/002	. {for sluice doors (for nuclear reactors G21C 13/0285)}
3/145	. . . {pivoting about an axis perpendicular to the wing}	7/005	. {for "Dutch doors", i.e. upper and lower wings}
3/16	. . with operating handle or equivalent member moving otherwise than rigidly with the latch {(E05C 3/122 takes precedence)}	2007/007	. {for a double-wing sliding door or window, i.e. where both wings are slidable}
3/162	. . . {the handle or member moving essentially towards or away of the plane of the wing or frame (E05C 3/167 takes precedence)}	7/02	. for wings which lie one behind the other when closed {(E05C 7/002 takes precedence)}
3/165	. . . {the handle or member moving substantially parallel to the wing or frame (E05C 3/167 takes precedence)}	7/04	. for wings which abut when closed {(pillarless vehicle doors E05B 83/38)}
3/167	. . . {the latch pivoting about an axis perpendicular to the wing}	7/045	. . {Sliding bolts mounted on or in the edge of a normally closed wing of a double-door or -window}
3/22	. . . the bolt being spring controlled	7/06	. . a fastening device for one wing being actuated or controlled by closing another wing {(locking one vehicle door by shutting another E05B 77/52)}
3/24 in the form of a bifurcated member {(automatic catches with a bifurcated latch E05C 19/024 ; locks with a bifurcated bolt E05B 65/0046 , E05B 85/243)}	9/00	Arrangements of simultaneously actuated bolts or other securing devices at well-separated positions on the same wing ((Locking, cross or security bars E05C 19/003 ; locks for safes or the like E05B 65/0075 ; of the vertical-rod type for panic or emergency doors E05B 65/1006); similar constructions for engineering closures F16J 13/08)
3/26 engaging a stud-like keeper (stud-like keepers per se E05B 2015/0235)	9/002	. {with arrangements allowing the wing to be slam-shut, e.g. by securing elements with latching action (E05B 63/20 , E05B 63/24 take precedence)}
3/28 with simultaneously operating double bolts {(vehicle locks with a pair of bifurcated bolts E05B 85/245)}	9/004	. {Faceplates (for other locks or fasteners E05B 9/002); Fixing the faceplates to the wing}
3/30 in the form of a hook {(hook-like fastenings E05C 19/10 ; locks for sliding wings with pivoting bolts E05B 65/0811 , E05B 65/0835)}	9/006	. {Details of bars}
3/34 with simultaneously operating double bolts {(locks for sliding wings with bolts pivoting about an axis parallel to the wings E05B 65/0835 , comprising simultaneously pivoting double hook-like locking members E05B 65/0858)}	9/008	. {mounted in an elongate casing on the surface of the wing}
3/36 in the form of a rotary gear {(vehicle door locks E05B 85/28)}	9/02	. with one sliding bar for fastening when moved in one direction and unfastening when moved in opposite direction; with two sliding bars moved in the same direction when fastening or unfastening

9/021	. . {with rack and pinion mechanism}	9/24	. Means for transmitting movements between vertical and horizontal sliding bars, rods or cables {for the fastening of wings}, e.g. corner guides (means for transmitting movements between vertical and horizontal sliding bars, rods or cables, for moving wings into open or closed position E05F 7/08)
9/023	. . . {between a lock cylinder and the bar}		
9/025	. . {with pins engaging slots}		
9/026	. . {comprising key-operated locks, e.g. a lock cylinder to drive auxiliary deadbolts or latch bolts (E05C 9/023 takes precedence)}		
9/028	. . {externally mounted on the wing, i.e. surface mounted (E05C 9/008 takes precedence)}	17/00	Devices for holding wings open; Devices for limiting opening of wings or for holding wings open by a movable member extending between frame and wing; Braking devices, stops or buffers, combined therewith (combined with hinges E05D 11/00; combined with operating apparatus for wings E05F; other braking devices, stops, buffers E05F 5/00)
9/04	. with two sliding bars moved in opposite directions when fastening or unfastening		
9/041	. . {with rack and pinion mechanism}		
9/042	. . {with pins engaging slots}		
9/043	. . {with crank pins and connecting rods}		
9/045	. . {with inclined surfaces, e.g. spiral or helicoidal}		
9/046	. . {with two interconnected mechanisms each driving one rod}	17/003	. {Power-actuated devices for limiting the opening of vehicle doors}
9/047	. . {comprising key-operated locks, e.g. a lock cylinder to drive auxiliary deadbolts or latch bolts (E05C 9/041 takes precedence)}	17/006	. . {with means for detecting obstacles outside the doors}
9/048	. . {externally mounted on the wing, i.e. surface mounted (E05C 9/008 takes precedence)}	17/02	. by mechanical means (E05C 17/60 takes precedence)
9/06	. with three or more sliding bars {(for watertight doors in bulkheads of vessels B63B 43/24 , B63B 43/32 ; for safe doors E05B 65/0075 ; covers or similar closures for pressure vessels F16J 13/00)}	17/025	. . {Means acting between hinged edge and frame (E05C 17/203 takes precedence)}
9/063	. . {extending along three or more sides of the wing or frame (means for transmitting movements between vertical and horizontal bars E05F 7/08)}	17/04	. . with a movable bar or equivalent member extending between frame and wing
9/066	. . . {Locks for windows or doors specially adapted for tilt and turn}	17/042	. . . {for anchoring the trunk lid of a car while carrying oversize objects (E05C 17/36 takes precedence)}
9/08	. with a rotary bar for actuating the fastening means {(E05B 83/10 and E05B 65/468 take precedence; for a plurality of drawers E05B 65/465)}	17/045	. . . {Hinges for the movable bar (E05C 17/163 , E05C 17/26 , E05C 17/345 take precedence; hinges in general F16C 11/04 , E05D)}
9/085	. . {pivoting about an axis perpendicular to the door (locking bars or the like pivoted about an axis perpendicular to the plane of the wing E05C 19/005)}	17/047	. . . {Portable bars or the like, i.e. completely removable (E05C 17/042 takes precedence)}
9/10	. Actuating mechanisms for bars {(E05C 9/02 - E05C 9/06 take precedence)}	17/08	. . . with special means for release, e.g. automatic release by further opening
9/12	. . with rack and pinion mechanism {(E05C 9/021 , E05C 9/041 take precedence)}	17/085 {automatic release by further opening}
9/14	. . with pins engaging slots {(E05C 9/025 , E05C 9/042 take precedence)}	17/12	. . . consisting of a single rod
9/16	. . with crank pins and connecting rods {(E05C 9/043 takes precedence)}	17/14 Hook and eye, or equivalent
9/18	. Details of fastening means or of fixed retaining means for the ends of bars	17/16 pivoted only at one end and having an elongated slot
9/1808	. . {Keepers}	17/163 {with clamping or securing means at the pivot, e.g. friction hinge}
2009/1816	. . . {snap-mounted without screw fasteners}	17/166 {Security devices}
9/1825	. . {Fastening means}	17/18 pivoted only at one end having a row of holes, notches, or pins
9/1833	. . . {performing sliding movements}	17/20 sliding through a guide (E05C 17/18 takes precedence)
9/1841 {perpendicular to actuating bar}	17/203 {concealed, e.g. for vehicles}
9/185 {parallel with actuating bar}	17/206 {with elastomeric springs to hold wing open}
9/1858 {of the roller bolt type}	17/22 with braking, clamping or securing means in the guide {(E05C 17/203 takes precedence)}
2009/1866 {of the keyhole slot type}	17/24 pivoted at one end, and with the other end running along a guide member
9/1875	. . . {performing pivoting movements (E05C 9/08 takes precedence)}	17/26 with braking, clamping or securing means at the pivot of the rod
9/1883 {pivotally mounted on the actuation bar}	17/28 with braking, clamping or securing means at the connection to the guide member
9/1891 {pivoting around an axis parallel to the bar}	17/30	. . . of extensible, e.g. telescopic, construction (flexible members E05C 17/36 ; locking of telescopic systems in general F16B 7/10 ; lockable telescopic gas springs F16F 9/0254)
9/20	. Coupling means for sliding bars, rods, or cables {(connecting means between actuating rods for vehicle door locks E05B 79/14)}	17/305 {with hydraulic locks}
9/22	. Guides for sliding bars, rods or cables	17/32	. . . consisting of two or more pivoted rods

17/34 with means for holding in more than one position	19/008	. . {Tilt-plate latches}
17/345 {using friction, e.g. friction hinge}	19/009	. {Latches with floating bolts, e.g. rings, balls}
17/36	. . . comprising a flexible member, e.g. chains	19/02	. Automatic catches, i.e. released by pull or pressure on the wing (E05C 19/06 takes precedence {; with locking means E05B 63/22})
17/365 {Security chains}		
17/38	. . with a curved rail rigid with the frame for engagement with means on the wing, or <u>vice versa</u>	19/022	. . {Released by pushing in the closing direction}
		19/024	. . {with a bifurcated latch}
		19/026	. . {with a keeper caught between two pivoting bolts}
17/40	. . Bars or like parts connecting a right wing with a left wing which move against each other when being closed	19/028	. . {with sliding bolt(s)}
		19/04	. . Ball or roller catches
17/42	. . connecting exterior and interior wings	19/06	. in which the securing part if formed or carried by a spring and moves only by distortion of the spring, e.g. snaps
17/44	. . with a device carried on the wing for frictional or like engagement with a fixed flat surface, e.g. {for holding wings open or closed by} retractable feet {(with wedging action between the wing and a flat surface E05C 17/54)}	19/063	. . {Released by pull or pressure on the wing (E05C 19/022 takes precedence)}
		19/066	. . . {made of plastics, e.g. hook-and-loop type fastener}
17/443	. . . {of the pivoted lever or eccentric type, e.g. for sliding windows}	19/08	. Hasps; Hasp fastenings; Spring catches therefor
17/446	. . . {of the retractable sliding feet type (similar devices for sliding wings E05C 17/64)}	19/10	. Hook fastenings; Fastenings in which a link engages a fixed hook-like member
17/46	. . in which the wing or a member fixed thereon is engaged by a movable fastening member in a fixed position; in which a movable fastening member mounted on the wing engages a stationary member	19/105	. . {Butterfly latches}
		19/12	. . pivotally mounted {around an axis (E05C 3/045, E05C 3/40 take precedence)}
		19/14	. . . with toggle action
17/48	. . . comprising a sliding securing member	19/145 {flush}
17/50	. . . comprising a single pivoted securing member	19/16	. Devices holding the wing by magnetic or electromagnetic attraction {(E05C 17/56 takes precedence)}
17/505 {acting directly on the knob or handle}		
17/52	. . . comprising a snap, catch, or the like	19/161	. . {magnetic gaskets}
17/525 {comprising a suction cup}	19/163	. . {a movable bolt being held in the striker by a permanent magnet}
17/54	. . Portable devices, e.g. wedges; wedges for holding wings open or closed (E05C 17/047 takes precedence)	19/165	. . {released by pushing in the closing direction}
		19/166	. . {electromagnetic}
17/56	. . by magnetic or electromagnetic attraction {or operated by electric or electromagnetic means (for closed wings E05C 19/16)}; (operation of locks or fasteners by electric or magnetic means E05B 47/00)	19/168	. . . {a movable bolt being electromagnetically held in the striker by electromagnetic attraction}
		19/18	. Portable devices specially adapted for securing wings {(E05C 17/54, E05C 19/003, E05B 65/0894, E05B 67/00 take precedence); preventing operation of handles E05B 13/00}
17/58	. . operated or controlled from a distance {, e.g. pneumatically (E05C 17/56 takes precedence)}		
17/60	. . holding sliding wings open {(E05C 17/443, E05C 17/54 take precedence)}	19/182	. . {insertable in the gap between the wing and the frame or in the gap between a lock and its striker, e.g. for cooperation with the striker}
17/62	. . using notches	19/184	. . {a portable member cooperating with a fixed member or an opening on the wing or the frame, for locking the wing}
17/64	. . by friction		
19/00	Other devices specially designed for securing wings, {e.g. with suction cups}(movable draft sealings additionally used for bolting E06B 7/18)	19/186	. . {with a pair of hooks, which are movable towards each other for grasping of an element on the wing, respectively on the frame, or for grasping of an element on each of the wings forming a double door}
19/001	. . {with bolts extending over a considerable extent, e.g. nearly along the whole length of at least one side of the wing (movable sealing strips E06B 7/18)}	19/188	. . {Removably mounted securing devices, e.g. devices clamped to the wing or the frame (E05C 19/182 - E05C 19/186 take precedence)}
19/002	. . {Rotating about a longitudinal axis}		
19/003	. . {Locking bars, cross bars, security bars (for sliding wings E05B 65/0888; for a plurality of drawers E05B 65/467)}	21/00	Arrangements or combinations of wing fastening, securing, or holding devices, not covered by a single preceding main group; {Locking kits}
19/004	. . {at an angle between door and floor or wall}		
19/005	. . {pivoted about an axis on the wing, perpendicular to the plane of the wing}	21/005	. {Provisional arrangements between door and frame for holding vehicle doors closed or partially open during manufacturing or maintenance}
19/006	. . {by displacement of the wing substantially in its own plane (E05F 7/02 takes precedence)}		
19/007	. . {Latches with wedging action (wedges between wing itself and fixed surface E05C 17/54)}		