CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINES OR PUMPS

F03 MACHINES OR ENGINES FOR LIQUIDS; WIND, SPRING, OR WEIGHT MOTORS; PRODUCING MECHANICAL POWER OR A REACTIVE PROPULSIVE THRUST, NOT OTHERWISE PROVIDED FOR

F03C POSITIVE-DISPLACEMENT ENGINES DRIVEN BY LIQUIDS (positive- displacement engines for liquids and elastic fluids <u>F01</u>; positive- displacement machines for liquids <u>F04</u>; fluid-pressure actuators <u>F15B</u>; fluid gearing <u>F16H</u>)

NOTE

Attention is drawn to the notes preceding class <u>F01</u>, especially as regards the meanings of "positive displacement", "rotarypiston machines", "oscillating-piston machines", "rotary-piston", "co-operating members", "movement of co-operating members", "teeth or tooth-equivalents", and "internal axis".

WARNINGS

1. The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:

0		
F03C 1/253	covered by	<u>F03C 1/06</u>
F03C 1/28	covered by	F03C 1/0406, F03C 1/0605
F03C 1/30	covered by	F03C 1/0409, F03C 1/0631, F03C 1/0668
F03C 1/32	covered by	F03C 1/0415, F03C 1/0626, F03C 1/0652
F03C 1/34	covered by	F03C 1/0435, F03C 1/0615, F03C 1/0655
F03C 1/36	covered by	F03C 1/0435, F03C 1/0615, F03C 1/0655
F03C 1/38	covered by	F03C 1/0435, F03C 1/0615, F03C 1/0655
F03C 1/40	covered by	F03C 1/0447, F03C 1/0678

2. In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Reciprocating-piston liquid engines
1/001	 {the movement in two directions being obtained by two or more double-acting piston liquid motors}
1/002	• {details; components parts}
1/003	• {controlling}
1/004	• • {speed-control}
1/005	• • {motor piston stroke control}
1/007	• with single cylinder, double-acting piston
1/0073	• • {one side of the double-acting piston being
	always under the influence of the liquid under pressure}
1/0076	 { the liquid under pressure being continuously delivered to one cylinder chamber through a valve in the piston for actuating the return stroke }
1/013	• with single cylinder, single-acting piston
1/0135	• • {with actuation of the return stroke by gravity}
1/02	• with multiple-cylinders, characterised by the number or arrangement of cylinders (with movable cylinders <u>F03C 1/22</u> ; of flexible-wall type F03C 7/00)
1/03	• with movement in two directions being obtained by two single-acting piston liquid engines, each acting in one direction

1/035	• • {one single-acting piston being always under the influence of the liquid under pressure}
1/04	• with cylinders in star or fan arrangement
	$\{(\underline{F03C \ 1/22} \text{ takes precedence})\}$
1/0403	• • {Details, component parts specially adapted of
	such engines }
1/0406	• • • • {Pistons}
1/0409	•••• {Cams}
1/0412	{consisting of several cylindrical elements,
	e.g. rollers}
1/0415	{Cylinders}
1/0419	• • • • {Arrangements for pressing or connecting
	the pistons against the actuated cam}
1/0422	• • • • • {hydraulically}
1/0425	{Disconnecting the pistons from the actuated
	cam (in general <u>F01B 31/24</u>)}
1/0428	• • • • {Supporting and guiding means for the
	pistons}
1/0431	• • • {Draining of the engine housing;
	arrangements dealing with leakage fluid}
1/0435	• • • • {Particularities relating to the distribution
	members (F03C 1/0472, F03C 1/0531, and
	F03C 1/0538 take precedence)}
1/0438	•••• {to cylindrical distribution members}
1/0441	••••• {to conical distribution members}

F03C

1/0444	•••• {to plate-like distribution members}
1/0447	{Controlling}
1/045	• • • • {by using a valve in a system with several
	pump or motor chambers, wherein the flow
	path through the chambers can be changed,
	e.g. series-parallel}
1/0454	• • • • {by changing the effective cross sectional
	piston working surface}
1/0457	• • • {by changing the effective piston stroke}
1/046	• • • • {by changing the excentricity of one
1/040	element relative to another element}
1/0463	• • • {by changing the phase relationship between
1/0403	
1/0466	two actuated cams}
1/0466	• • • {by changing the phase relationship between
	the actuated cam and the distributing means}
1/047	• • • the pistons co-operating with an actuated
	element at the outer ends of the cylinders
1/0472	• • • { with cam-actuated distribution members }
1/0474	• • • • {with two or more radial piston/cylinder
	units in series}
1/0476	••••• {directly located side by side}
1/0478	•••• {having several cylinder barrels coupled
	together}
1/053	• • • the pistons co-operating with an actuated
1/055	element at the inner ends of the cylinders
1/0531	• • • { with cam-actuated distribution members }
1/0533	
1/0555	• • • • {each piston being provided with channels
	coacting with the cylinder and being used
	as a distribution member for another
1 10 50 5	cylinder}
1/0535	• • • { with two or more radial piston/cylinder
	units in series}
	(directly located side by side)
1/0536	• • • • {directly located side by side}
1/0536 1/0538	• • • { the piston-driven cams being provided with
1/0538	• • • { the piston-driven cams being provided with inlets or outlets }
	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or
1/0538 1/06	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis
1/0538 1/06 1/0602	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details}
1/0538 1/06	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons
1/0538 1/06 1/0602 1/0605	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis . {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)}
1/0538 1/06 1/0602	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means}
1/0538 1/06 1/0602 1/0605	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis . {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)}
1/0538 1/06 1/0602 1/0605 1/0607	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means}
1/0538 1/06 1/0602 1/0605 1/0607 1/061	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders}
1/0538 1/06 1/0602 1/0605 1/0607 1/061	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having two or more sets of cylinders or
1/0538 1/06 1/0602 1/0605 1/0607 1/061 1/0613	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having two or more sets of cylinders or pistons}
1/0538 1/06 1/0602 1/0605 1/0605 1/0617 1/0613 1/0615	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {distributing members} {cylindrical distribution members}
1/0538 1/06 1/0602 1/0605 1/0605 1/0617 1/0613 1/0615 1/0618	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {distributing members} {cylindrical distribution members} {conical distribution members}
1/0538 1/06 1/0602 1/0605 1/0607 1/061 1/0613 1/0615 1/0618 1/0621 1/0623	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {distributing members} {conical distribution members} {Details, component parts}
1/0538 1/06 1/0602 1/0605 1/0607 1/061 1/0613 1/0615 1/0615 1/0618 1/0621 1/0623 1/0626	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {distributing members} {conical distribution members} {Details, component parts} {Cylinders}
1/0538 1/06 1/0602 1/0605 1/0605 1/061 1/0613 1/0615 1/0618 1/0621 1/0623 1/0626 1/0628	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {distributing members} {conical distribution members} {Details, component parts} {Cylinders} {Cylinders} {Cylinders} {Casings, housings}
1/0538 1/06 1/0602 1/0605 1/0605 1/0613 1/0613 1/0615 1/0618 1/0621 1/0623 1/0626 1/0628 1/0631	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having two or more sets of cylinders or pistons} {conical distribution members} {Conical distribution members} {Cylinders} {Cylinders} {Casings, housings} {Wobbler or actuated element}
1/0538 1/06 1/0602 1/0605 1/0605 1/061 1/0613 1/0615 1/0618 1/0621 1/0623 1/0626 1/0628	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having two or more sets of cylinders or pistons} {conical distribution members} {Conical distribution members} {Cylinders} {Cylinders} {Cusings, housings} {Actuated element}
1/0538 1/06 1/0602 1/0605 1/0605 1/0613 1/0615 1/0613 1/0615 1/0618 1/0621 1/0623 1/0626 1/0628 1/0631 1/0634	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having two or more sets of cylinders or pistons} {cylindrical distribution members} {Conical distribution members} {Cylinders} {Cylinders} {Kotuated element}
1/0538 1/06 1/0602 1/0605 1/0605 1/0613 1/0615 1/0615 1/0618 1/0621 1/0623 1/0626 1/0628 1/0631 1/0634	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having two or more sets of cylinders or pistons} {conical distribution members} {Conical distribution members} {Cylinders} {Cylinders}
1/0538 1/06 1/0602 1/0605 1/0605 1/0613 1/0615 1/0613 1/0615 1/0618 1/0621 1/0623 1/0626 1/0628 1/0631 1/0634	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having two or more sets of cylinders or pistons} {conical distribution members} {Cotical distribution members} {Cylinders} {Cylinders} {Actuated element bearing means or driven axis bearing means} {having rotary cylinder block} {having two or more sets of cylinders or pistons}
1/0538 1/06 1/0602 1/0605 1/0607 1/061 1/0613 1/0615 1/0618 1/0618 1/0621 1/0623 1/0626 1/0628 1/0631 1/0634 1/0636 1/0639	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having two or more sets of cylinders or pistons} {conical distribution members} {Cylindrical distribution members} {Cylinders} {Cylinders} {Actuated element bearing means or driven axis bearing means} {having two or more sets of cylinders or pistons}
1/0538 1/06 1/0602 1/0605 1/0607 1/061 1/0613 1/0615 1/0618 1/0621 1/0623 1/0626 1/0628 1/0634 1/0634 1/0636 1/0639 1/0642	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having two or more sets of cylinders or pistons} {cylindrical distribution members} {Conical distribution members} {Cylinders} {Cylinders} {Actuated element bearing means or driven axis bearing means} {having two or more sets of cylinders or pistons}
1/0538 1/06 1/0602 1/0605 1/0607 1/061 1/0613 1/0615 1/0618 1/0621 1/0623 1/0626 1/0628 1/0634 1/0634 1/0636 1/0639 1/0642 1/0642 1/0644	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {baving stationary cylinders} {having two or more sets of cylinders or pistons} {conical distribution members} {Culindrical distribution members} {Culinders} {Culinders} {Actuated element} {Actuated element bearing means or driven axis bearing means} {having two or more sets of cylinders or pistons}
1/0538 1/06 1/0602 1/0605 1/0607 1/061 1/0613 1/0615 1/0618 1/0621 1/0623 1/0626 1/0628 1/0634 1/0634 1/0636 1/0639 1/0642	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {Driven means} {having stationary cylinders} {distributing members} {conical distribution members} {Corical distribution members} {Cylindrical distribution members} {Cylinders} {Cylinders} {Actuated element bearing means or driven axis bearing means} {having two or more sets of cylinders or pistons} {Actuated or more sets of cylinders or driven axis bearing means} {Actuated or more sets of cylinders or driven axis bearing means}
1/0538 1/06 1/0602 1/0605 1/0605 1/0613 1/0613 1/0615 1/0613 1/0615 1/0628 1/0628 1/0628 1/0628 1/0631 1/0634 1/0636 1/0639 1/0642 1/0644 1/0647	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {baving stationary cylinders} {having two or more sets of cylinders or pistons} {conical distribution members} {Colical distribution members} {Cylindrical distribution members} {Cylinders} {Cylinders} {Cylinders}
1/0538 1/06 1/0602 1/0605 1/0605 1/0613 1/0615 1/0613 1/0615 1/0618 1/0623 1/0623 1/0623 1/0628 1/0631 1/0634 1/0636 1/0639 1/0642 1/0644 1/0647 1/0649	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having stationary cylinders} {distributing members} {cylindrical distribution members} {Conical distribution members} {Cylinders} {Cylinders} {Cylinders} {Actuated element bearing means or driven axis bearing means} {having two or more sets of cylinders or pistons} {Particularities in the contacting area between cylinder barrel and valve plate} {Bearing means}
1/0538 1/06 1/0602 1/0605 1/0605 1/0613 1/0615 1/0613 1/0615 1/0618 1/0623 1/0623 1/0628 1/0631 1/0634 1/0634 1/0636 1/0639 1/0642 1/0644 1/0647 1/0649 1/0652	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having stationary cylinders} {having two or more sets of cylinders or pistons} {cylindrical distribution members} {Conical distribution members} {Cylinders} {Cylinders} {Cylinders} {Actuated element bearing means or driven axis bearing means} {having two or more sets of cylinders or pistons} {Component parts} {Inclined on main shaft axis} {Particularities in the contacting area between cylinder barrel and valve plate} {Bearing means} {Cylinders}
1/0538 1/06 1/0602 1/0605 1/0605 1/0613 1/0615 1/0613 1/0615 1/0618 1/0623 1/0623 1/0623 1/0628 1/0631 1/0634 1/0636 1/0639 1/0642 1/0644 1/0647 1/0649	 {the piston-driven cams being provided with inlets or outlets} . with cylinder axes generally coaxial with, or parallel or inclined to, main shaft axis {Component parts, details} {Adaptations of pistons (pump pistons F04B 1/124, F04B 53/14)} {Driven means} {having stationary cylinders} {having stationary cylinders} {distributing members} {cylindrical distribution members} {Cylinders} {Cylinders} {Cylinders} {Actuated element bearing means or driven axis bearing means} {having two or more sets of cylinders or pistons} {Cylinder or actuated element} {Actuated on main shaft axis} {Component parts} {Component parts}

1/0657	
	••••• {Cylindrical valve means}
1/066	••••• {Conical valve means}
1/0663	••••• {Casings, housings}
1/0665	••••• {Cylinder barrel bearing means}
1/0668	••••• {Swash or actuated plate}
1/0671	••••• {Swash or actuated plate bearing means or driven axis bearing means}
1/0673	•••• {Connection between rotating cylinder and rotating inclined swash plate}
1/0676	• • • {Arrangement for pressing the cylinder barrel against the valve plate}
1/0678	• • • {Control}
1/0681	•••• {using a valve in a system with several motor chambers, wherein the flow path through the chambers can be changed}
1/0684	• • • • {using a by-pass valve}
1/0686	• • • {by changing the inclination of the swash
1/0690	plate}
1/0689 1/0692	 {using wedges} {by changing the phase relationship between
1/0092	the actuated element and the distribution means, e.g. turning the valve plate; turning the swash plate }
1/0694	 {by changing the inclination of the axis of the cylinder barrel in relation to the axis of the actuated element}
1/0697	• • • {responsive to the speed}
1/08	 Distributing valve-gear peculiar thereto (for engines)
1/00	with positive-displacement in general <u>F01L</u> ; { <u>F03C 1/06</u> takes precedence})
1/10	actuated by piston or piston-rod
1/12	mechanically
1/14	• • by driving liquid of engine
1/16	• • Speed controlling, equalising or cushioning
1/20	• specially adapted for engines generating vibration only
1/22	• with movable cylinders {or cylinder}
1/223	• • {having cylinders in star or fan arrangement,
	the connection of the pistons with an actuated element being at the inner ends of the cylinders}
1/226	element being at the inner ends of the cylinders}
1/226 1/24	
	element being at the inner ends of the cylinders}. { with cam actuated distribution members}. in which the liquid exclusively displaces one or
	 element being at the inner ends of the cylinders } . { with cam actuated distribution members } . in which the liquid exclusively displaces one or more pistons reciprocating in rotary cylinders {(F03C 1/0636 takes precedence)} . { having cylinders in star or fan arrangement, the connection of the pistons with an actuated element being at the outer ends of the
1/24 1/2407	 element being at the inner ends of the cylinders} . { with cam actuated distribution members } . in which the liquid exclusively displaces one or more pistons reciprocating in rotary cylinders {(F03C 1/0636 takes precedence)} . { having cylinders in star or fan arrangement, the connection of the pistons with an actuated element being at the outer ends of the cylinders}
1/24	 element being at the inner ends of the cylinders} . { with cam actuated distribution members } . in which the liquid exclusively displaces one or more pistons reciprocating in rotary cylinders {(F03C 1/0636 takes precedence)} . { having cylinders in star or fan arrangement, the connection of the pistons with an actuated element being at the outer ends of the cylinders} { cylinder block and actuated cam both rotating (F03C 1/2431 and F03C 1/2446 take
1/24 1/2407	 element being at the inner ends of the cylinders} . {with cam actuated distribution members} . in which the liquid exclusively displaces one or more pistons reciprocating in rotary cylinders {(F03C 1/0636 takes precedence)} . {having cylinders in star or fan arrangement, the connection of the pistons with an actuated element being at the outer ends of the cylinders} {cylinder block and actuated cam both rotating (F03C 1/2431 and F03C 1/2446 take precedence)} {with two or more series radial piston-
1/24 1/2407 1/2415	 element being at the inner ends of the cylinders} . {with cam actuated distribution members} . in which the liquid exclusively displaces one or more pistons reciprocating in rotary cylinders {(F03C 1/0636 takes precedence)} . {having cylinders in star or fan arrangement, the connection of the pistons with an actuated element being at the outer ends of the cylinders} {cylinder block and actuated cam both rotating (F03C 1/2431 and F03C 1/2446 take precedence)} {with two or more series radial piston-cylinder units} {cylinder block and actuated cam both
1/24 1/2407 1/2415 1/2423 1/2431	 element being at the inner ends of the cylinders} . {with cam actuated distribution members} . in which the liquid exclusively displaces one or more pistons reciprocating in rotary cylinders {(F03C 1/0636 takes precedence)} . {having cylinders in star or fan arrangement, the connection of the pistons with an actuated element being at the outer ends of the cylinders} {cylinder block and actuated cam both rotating (F03C 1/2431 and F03C 1/2446 take precedence)} {with two or more series radial piston-cylinder units} {cylinder block and actuated cam both rotating (F03C 1/2446 take precedence)}
1/24 1/2407 1/2415 1/2423	 element being at the inner ends of the cylinders} . {with cam actuated distribution members} . in which the liquid exclusively displaces one or more pistons reciprocating in rotary cylinders {(F03C 1/0636 takes precedence)} . {having cylinders in star or fan arrangement, the connection of the pistons with an actuated element being at the outer ends of the cylinders} {cylinder block and actuated cam both rotating (F03C 1/2431 and F03C 1/2446 take precedence)} {with two or more series radial piston-cylinder units} {cylinder block and actuated cam both rotating (F03C 1/2446 takes precedence)} {directly located side by side}
1/24 1/2407 1/2415 1/2423 1/2431 1/2438	 element being at the inner ends of the cylinders} . {with cam actuated distribution members} . in which the liquid exclusively displaces one or more pistons reciprocating in rotary cylinders {(F03C 1/0636 takes precedence)} . {having cylinders in star or fan arrangement, the connection of the pistons with an actuated element being at the outer ends of the cylinders} {cylinder block and actuated cam both rotating (F03C 1/2431 and F03C 1/2446 take precedence)} { with two or more series radial piston-cylinder units} {cylinder block and actuated cam both rotating (F03C 1/2446 takes precedence)} {cylinder block and actuated cam both rotating (F03C 1/2446 takes precedence)} {cylinder block and actuated cam both rotating (F03C 1/2446 takes precedence)} {cylinder block and actuated cam both rotating (F03C 1/2446 takes precedence)} {cylinder block and actuated cam both rotating (F03C 1/2446 takes precedence)}
1/24 1/2407 1/2415 1/2423 1/2431 1/2438 1/2446	 element being at the inner ends of the cylinders} . {with cam actuated distribution members} . in which the liquid exclusively displaces one or more pistons reciprocating in rotary cylinders {(F03C 1/0636 takes precedence)} . {having cylinders in star or fan arrangement, the connection of the pistons with an actuated element being at the outer ends of the cylinders} {cylinder block and actuated cam both rotating (F03C 1/2431 and F03C 1/2446 take precedence)} {with two or more series radial piston-cylinder units} {cylinder block and actuated cam both rotating (F03C 1/2446 takes precedence)} {cylinder block and actuated cam both rotating (F03C 1/2446 takes precedence)} {cylinder block and actuated cam both rotating (F03C 1/2446 takes precedence)} {cylinder block and actuated cam both rotating (F03C 1/2446 takes precedence)} {cylinder block and actuated cam both rotating (F03C 1/2446 takes precedence)}

F03C

1/247	 with cylinders in star- or fan-arrangement the connection of the pistons with an
1/26	• adapted for special use or combined with apparatus driven thereby
2/00	Rotary-piston engines (in which the liquid exclusively displaces one or more piston reciprocating in rotary cylinders <u>F03C 1/24</u>)
	NOTE
	Group <u>F03C 2/30</u> takes precedence over groups F03C 2/02 - F03C 2/24.
2/02	• of arcuate-engagement type, i.e. with circular translatory movement of co-operating members, each member having the same number of teeth or tooth-equivalents
2/08	 of intermeshing-engagement type, i.e. with engagement of co- operating members similar to that of toothed gearing
2/22	• of internal-axis type with equidirectional movement of co-operating members at the points of engagement, or with one of the co-operating members being stationary, the inner member having more teeth or tooth- equivalents than the outer member
2/24	 of counter-engagement type, i.e. the movement of co-operating members at the points of engagement being in opposite directions
2/30	 having the characteristics covered by two or more of groups F03C 2/02, F03C 2/08, F03C 2/22, F03C 2/24 or having the characteristics covered by one of these groups together with some other type of movement between co-operating members
2/302	• {having both the movements defined in sub- groups <u>F03C 2/02</u> and relative reciprocation between members}
2/304	• {having both the movements defined in sub- group <u>F03C 2/08</u> or <u>F03C 2/22</u> and relative reciprocation between members}
2/306	• • {having both the movements defined in sub- groups <u>F03C 2/22</u> and <u>F03C 2/24</u> }
2/308	• • {having the movement defined in F03C 2/08 and having a hinged member}
4/00	Oscillating-piston engines
7/00	Engines of flexible-wall type
99/00	Subject matter not provided for in other groups of this subclass
99/005	• {Free-piston type engines}