

## H04W

**WIRELESS COMMUNICATION NETWORKS (broadcast communication [H04H](#); communication systems using wireless links for non-selective communication, e.g. wireless extensions [H04M 1/72](#))**

### Definition statement

*This place covers:*

- Communication networks deploying an infrastructure for mobility management of wireless users connected thereto, e.g. cellular networks, wireless LANs.
- Self organizing wireless communication networks, e.g. ad-hoc networks.
- Wireless access networks e.g. Wireless Local Loop.
- Said networks being used for selectively establishing one or a plurality of communication links between a desired number of users or between users and network equipments for the purpose of transferring information via these communication links.
- Arrangements or techniques for planning, deploying wireless networks.
- Arrangements or techniques specially adapted for wireless service provisioning.
- Arrangements or techniques specially adapted for wireless network operation.

### References

#### Limiting references

*This place does not cover:*

Broadcast communication	<a href="#">H04H</a>
Communication systems using wireless links for non-selective communication, e.g. wireless extensions	<a href="#">H04M 1/72</a>

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Arrangements for programme control, e.g. control unit	<a href="#">G06F 9/00</a>
Wireless sensing of record carriers	<a href="#">G06K 7/10</a>
Signalling or calling systems	<a href="#">G08B</a>
Traffic control systems	<a href="#">G08G</a>
Transceivers, i.e. devices in which transmitter and receiver form a structural unit and in which at least one part is used for functions of transmitting and receiving	<a href="#">H04B 1/38</a>
Spread spectrum techniques in general	<a href="#">H04B 1/69</a>
Near-field transmission systems, e.g. inductive loop type	<a href="#">H04B 5/00</a>
Control of transmission; Equalising	<a href="#">H04B 7/005</a>
Diversity systems	<a href="#">H04B 7/02</a>
Space-based or airborne stations	<a href="#">H04B 7/185</a>
For communication between two or more posts at least one of which is mobile	<a href="#">H04B 7/26</a>
Transmission systems employing electromagnetic waves other than radio waves	<a href="#">H04B 10/00</a>

Transmission systems employing sonic, ultrasonic or infrasonic waves	<a href="#">H04B 11/00</a>
Transmission systems characterised by the medium used for transmission	<a href="#">H04B 13/00</a>
Multiplex communication	<a href="#">H04J</a>
Arrangements for detection or preventing errors in the information received	<a href="#">H04L 1/00</a>
Arrangements affording multiple use of the transmission path	<a href="#">H04L 5/00</a>
Arrangements for synchronising receiver with transmitter	<a href="#">H04L 7/00</a>
Data switching networks	<a href="#">H04L 12/00</a>
Modulated-carrier systems	<a href="#">H04L 27/00</a>
Communication control or processing characterised by a protocol	<a href="#">H04L 29/06</a>
Telephonic communication	<a href="#">H04M</a>
Telephonic substation equipment	<a href="#">H04M 1/00</a>
Telephonic automatic or semi-automatic exchanges	<a href="#">H04M 3/00</a>
Metering arrangements; Time controlling arrangements; Time- indicating arrangements	<a href="#">H04M 15/00</a>
Prepayment telephone systems	<a href="#">H04M 17/00</a>
Arrangements using wireless links for the sole purpose of telecontrol or telemetry systems	<a href="#">H04Q 9/00</a>

## Glossary of terms

*In this place, the following terms or expressions are used with the meaning indicated:*

Access point	means an equipment providing wireless user access to a backbone network by terminating a radio link.
BSC	Base Station Controller
BTS	Base Transceiver Station
Backbone network	designates equipment(s) for connecting one or several wireless access points to a wired or wireless infrastructure in order to allow communication(s) between users' inside or outside the wireless network.
Care-of-address	designates the termination point of a tunnel toward a mobile node, for datagrams forwarded to the mobile node while it is away from home.
Cellular	an infrastructure deployment involving partitioning geographical areas in a plurality of sub-areas (cells) for the purpose of reusing wireless resources.
Communication link	means a physical or logical connection selectively established for the purpose of conveying messages or information between users or networks.
Connection	means network resource(s) allocated or reserved for an affiliated user.

Connected state	designates the state of a user/terminal having active i.e. allocated logical traffic/control channel, dormant or suspended, i.e. without allocated logical channels but with maintained service instances. It also incorporates context (PDP context), User Plane, Control Plane operations.
Control channel	transports control information used to control the function of the network element. ("signalling channel", e.g. paging channel, broadcast channel, pilot channel).
Core network, CN	3GPP standard terminology. PLMN architecture is divided into Core Network (CN) and Access Network (AN). Whereas Access Network comprises GERAN (BSS for GSM), UTRAN (RNS) and E-UTRAN, Core Network is logically subdivided into a Circuit Switched (CS) domain, a Packet Switched (PS) domain and an IP Multimedia (IM) subsystem.
Correspondent node	a peer with which a mobile node is communicating. A correspondent node may be either mobile or stationary.
Data network PoA [Point of Attachment]	entity within wireless network or mobility management infrastructure providing access to a data network for a wireless user.
Direct mode	establishing a direct communication link between user/terminal; the link can be established using an intermediate node.
Domain;CS domain, PS domain	3GPP standard terminology. Circuit Switched domain (CS domain) refers to the set of all core network entities offering "circuit switched type of connection" for user traffic and for the related signalling. Dedicated network resources are allocated at connection establishment and released at connection release. Entities specific to the CS domain are: MSC, GMSC, VLR. The Packet Switched domain (PS domain, Packet domain) refers to the set of all core network entities offering "packet switched type of connection" for user traffic and for supporting the related signalling. Transports user information using autonomous concatenation of bits called packets: each packet can be routed independently from the previous one. PS domain includes General Packet Radio Service (GPRS) and Evolved Packet Core (EPC). Entities specific to the PS domain are: SGSN, GGSN, PDN GW, S-GW, MME, HSS, HLR. CS and PS domains also have common network entities: e.g. HSS, HLR
Downlink	means the wireless link from a wireless access point or network towards the user or terminal equipment (see also "uplink").
Fixed allocation (of a dedicated resource)	allocation of a resource that is not changed with each frame or time slot. It is also named "persistent or semi-persistent scheduling".
Hand-off, handover	a change of radio link or data network point of attachment, while a connection is ongoing.
Home network	designates the network performing functions at a permanent location regardless of the location of the user's access point. The home network is responsible for subscription information management and for specific services not provided by the serving network; dedicated equipment used therefore is designed by HLR (Home Location Register); also Home Agent, Home Subscriber Server.

Idle state	designates the state of a user/terminal having no active traffic/ control channel and no active service instances but being affiliated to the network. (See also "null state")
Mobility binding	designates the association of a home address with a care-of address, along with the remaining lifetime of that association.
Mobility data	information obtained by the network or exchanged by network components, in particular user affiliation or location data, to be used in providing a network service
Mobility management	designates techniques or arrangements allowing operation of, or services to be provided to, a user capable of selecting or changing his point of attachment to the network.
Mobility server	A network functional entity acting as an established reference point in location registration operations by (or on behalf of) a mobile user/terminal.
Mobile node	designates a host or router that changes its point of attachment from one network or subnetwork to another, without changing its constant home IP address.
Multi-call	means a plurality of communication links established over one or a plurality of networks for transferring information to one user/ terminal.
Multiplexing	sorting packets of flows onto one or several channels in time, frequency, code and space division. better or space division.
Network	means the physical or logical entities involved in providing communication services to users.
Network security	(see Tanenbaum) roughly means the four intertwined areas: secrecy, authentication, nonrepudiation and integrity control for a interconnected collection of autonomous nodes, e.g, computers
Null state	designates the state of a user/terminal having no active traffic/ control channel and no active service instances.
Originating	means a user/terminal acting as a requester for communication towards a wireless access point.
Packet domain PLMN backbone network	The 3GPP standard terminology defines two kinds of packet domain PLMN backbone networks: The intra-PLMN backbone network is the IP network comprising routers interconnecting ps domain(s) within the same PLMN. The inter-PLMN backbone network is the IP network comprising routers interconnecting ps domain(s) of different PLMNs.
Paging	Notifying a terminating user of a communication event.
Paging service	one-way selective calling service.
Partitioning	means distributing/committing specific resources to a particular/ specific network component.
Polling	questioning for needed transmission resources and according instant allocation for immediate transmission.
Private networks	designates networks owned and operated by non-public authorities.
QoS	Quality of Service
Resource allocation	means allocation of a resource to a communication.

Resource distribution	means committing a resource to an entity for future allocation thereof for communication.
RNC	Radio Network Controller
Scheduling	means establishing an order of transmission of communication information based on precedence or priority policies.
Scheduled access	access to a wireless resource follows a schedule or is performed in a defined order.
Scheduled allocation	resource allocation is continuously changed or adapted during a connection according to a transmission schedule. This requires the usage of a shared channel.
(semi-) persistent scheduling	allocation of resources that is persistent for a number of (consecutive) time slots or frames according to a transmission schedule. This requires the usage of a shared channel.
Serving network	designate the part of the network to which the access point providing user's access is connected. The serving network is responsible for path finding and transport of users data; dedicated equipment used therefore is designed by VLR (Visitor Location Register; also Foreign Agent, Visiting Subscriber Server).
SLA	Service Level Agreement
Subscriber	means an entity recognized and authorized as user.
Terminal	means the equipment acting as/or on behalf of a user.
Terminating	means a user/terminal specified as a recipient for communication from within or via a wireless network.
Tracking	monitoring a user or terminal activity in the network for purposes of gathering, e.g. location, activity or status information.
Traffic channel	transports communication information (user data) to and from one or several users.
Trigger, triggering	the act of initiating an action. This could be caused by certain criteria or events or involve the exchange of information.
(transmission) scheduling	defines an order of transmission of one or several data flows in time, frequency, code and space dimension.
Uplink	means the wireless link from the user or terminal equipment towards a wireless network or access point (see also "Downlink").
User	means an entity acting as an information source (sender, transmitter, server) or information sink (recipient, receiver, client).
Wireless extension	means equipment using a pre-defined dedicated wireless link.
Wireless link	means a communication link established via radio, infra-red, inductive or other electromagnetic radiation.
Wireless resource	means a communication link using a specific frequency, time, code or space (or combination thereof).
Zoned	designates an infrastructure deployment involving partitioning geographical areas in a plurality of sub-areas (zones, cells) for the purpose of reusing wireless resources.

## H04W 4/00

### Services specially adapted for wireless communication networks; Facilities therefor

#### Definition statement

*This place covers:*

Providing wireless communication services by or via one or a plurality of network equipment to one or a plurality of affiliated user or terminal equipment.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Wireless network security	<a href="#">H04W 12/00</a>
Charging, metering arrangements	<a href="#">H04L 12/14</a> , <a href="#">H04M 15/00</a> , <a href="#">H04M 17/00</a>
Broadcast or conference in data switching networks	<a href="#">H04L 12/18</a>
Message switching systems	<a href="#">H04L 51/00</a>
Network arrangements or protocols	<a href="#">H04L 61/00</a>
Network architectures or network communications	<a href="#">H04L 63/00</a>
Network arrangements or protocols in real time	<a href="#">H04L 65/00</a>
Network arrangements or communication protocols for networked applications	<a href="#">H04L 67/00</a>
Application independent communication protocol aspects	<a href="#">H04L 69/00</a>
Telephonic communication, substation extension arrangements, cordless telephones, portable communication terminals with improved user interface to control a main telephone operation mode or to indicate the communication status	<a href="#">H04M 1/72403</a>
Telephonic communication systems providing special services or facilities to subscriber	<a href="#">H04M 3/42</a>

#### Glossary of terms

*In this place, the following terms or expressions are used with the meaning indicated:*

Affiliated	means a user or terminal being recognized by a network and/or authorized to use network resources
------------	---

## H04W 4/06

**Selective distribution of broadcast services, e.g. multimedia broadcast multicast service [MBMS]; Services to user groups; One-way selective calling services**

### References

#### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Resource management for broadcast services	<a href="#">H04W 72/005</a>
Connection management for selective distribution or broadcast	<a href="#">H04W 76/40</a>

## H04W 4/10

**Push-to-Talk [PTT] or Push-On-Call services**

### References

#### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Connection management for Push-to-Talk [PTT] or Push-to-Talk over cellular [PoC] services	<a href="#">H04W 76/45</a>
Arrangements for real-time multimedia Push-to-X-Services	<a href="#">H04L 65/4061</a>

## H04W 8/00

**Network data management**

### Definition statement

*This place covers:*

Managing network data, e.g. storing, updating, transferring, obtaining or exchanging operation data, mobility data, user service data or terminal service data.

### References

#### *Limiting references*

*This place does not cover:*

Connection management, e.g. connection set-up, manipulation or release.	<a href="#">H04W 76/00</a>
---	----------------------------

## H04W 8/005

**{Discovery of network devices, e.g. terminals}**

### Definition statement

*This place covers:*

(RE-)scanning for and (re-)discovery of terminals or devices; inquiry methods

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Connectivity information management, e.g. connectivity discovery or update	<a href="#">H04W 40/24</a>
Discovering, processing access restriction or access information	<a href="#">H04W 48/16</a>
Arrangements for service discovery, e.g. Service Location Protocol	<a href="#">H04L 29/08648</a>
Protocols for network applications involving the display to the application user of network conditions affecting the network application	<a href="#">H04L 29/0899</a>
Network service discovery by a Service Manager	<a href="#">H04L 41/5058</a>

## H04W 8/02

**Processing of mobility data, e.g. registration information at HLR [Home Location Register] or VLR [Visitor Location Register]; Transfer of mobility data, e.g. between HLR, VLR or external networks**

### Definition statement

*This place covers:*

Processing, e.g. storing, updating of mobility data; Transfer of mobility data.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Network layer protocols, e.g. mobile IP [Internet Protocol]	<a href="#">H04W 80/04</a>
---	----------------------------

## H04W 8/04

**Registration at HLR or HSS [Home Subscriber Server]**

### Definition statement

*This place covers:*

Registration of user or terminal affiliation or location information.

## H04W 8/06

**Registration at serving network Location Register, VLR or user mobility server**

### Definition statement

*This place covers:*

Temporary or semi-permanent registration of user or terminal mobility data at a user mobility server not being the permanent reference point for mobile data queries.



**H04W 8/065****{involving selection of the user mobility server}****Definition statement***This place covers:*

Selecting a user mobility server for registration.

**H04W 8/08****Mobility data transfer****Definition statement***This place covers:*

Transfer of mobility data, e.g. to network components or external parties.

**H04W 8/082****{for traffic bypassing of mobility servers, e.g. location registers, home PLMNs or home agents}****Definition statement***This place covers:*

Transfer of mobility data to forward traffic data directly to the mobile node without having to detour traffic data through the home network e.g. route optimization, local breakout

**H04W 8/085****{involving hierarchical organized mobility servers, e.g. hierarchical mobile IP [HMIP]}****Definition statement***This place covers:*

Transfer of mobility data in a network, wherein mobility servers are hierarchical components of a mobility management scheme.

**H04W 8/087****{for preserving data network PoA address despite hand-offs}****Definition statement***This place covers:*

Transfer of mobility data on the basis of a localised network-based mobility management scheme, where the user terminal preserves its data network address, e.g. HAWAII and NETLMM.

**References****Informative references***Attention is drawn to the following places, which may be of interest for search:*

Modification of an existing route due to handover	<a href="#">H04W 40/36</a>
---	----------------------------

## H04W 8/10

### between location register and external networks

#### Definition statement

*This place covers:*

Transfer of mobility data between external networks and a location register or mobility server, e.g. HSS.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Interfaces specially adapted for wireless communication networks, inter-networking arrangements	<a href="#">H04W 92/02</a>
---	----------------------------

## H04W 8/12

### between location registers or mobility servers

#### Definition statement

*This place covers:*

Transfer of mobility data between location registers or mobility servers e.g. for the purpose of sharing the load between mobility servers, or for supporting roaming.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Interfaces specially adapted for wireless communication networks, interfaces between backbone network devices	<a href="#">H04W 92/24</a>
---	----------------------------

## H04W 8/14

### between corresponding nodes

#### Definition statement

*This place covers:*

Transfer of mobility data between corresponding nodes, e.g. among communicating users or terminals.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Interfaces specially adapted for wireless communication networks, interfaces between hierarchical similar devices	<a href="#">H04W 92/16</a>
---	----------------------------

## H04W 8/16

### selectively restricting mobility {data} tracking

#### Definition statement

*This place covers:*

Selectively restricting the tracking of mobility data by the network or user, e.g. restricting the transmission of affiliation or location information, or restricting the transfer of tracking information.

## H04W 8/18

### Processing of user or subscriber data, e.g. subscribed services, user preferences or user profiles; Transfer of user or subscriber data

#### Definition statement

*This place covers:*

Processing or transferring of user data, e.g. storing, updating, deleting, and transferring user profiles, service data, and preferences; Processing or transferring of subscriber data, e.g. data concerning subscribed services, subscriber profiles.

Storage arrangements therefore including dedicated record carriers.

#### References

##### Limiting references

*This place does not cover:*

Devices for signalling identity of wanted subscriber with provision for storing more than one subscriber number at a time using static electronic memories	<a href="#">H04M 1/2745</a>
--	-----------------------------

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Registration, e.g. affiliation to network; De-registration, e.g. terminating affiliation	<a href="#">H04W 60/00</a>
Protocols for network applications involving profiles	<a href="#">H04L 29/08918</a>

## H04W 8/183

### {Processing at user equipment or user record carrier}

#### Definition statement

*This place covers:*

Processing, e.g. storing, updating, deleting, at user equipment or record carrier; logical bundling of record carrier and subscriber equipment, e.g. SIM-lock.

## References

### *Informative references*

Attention is drawn to the following places, which may be of interest for search:

Fraud detection as security arrangement	<a href="#">H04W 12/12</a>
---	----------------------------

## H04W 8/186

### {Processing of subscriber group data}

#### Definition statement

*This place covers:*

- Affiliation of subscribers to a group
- De-affiliation of subscribers from a group
- Creation and administration of subscriber groups
- Transfer, processing, and update of subscriber group information

This subgroup covers all kinds of subscriber groups.

Network addressing or numbering for mobility support	<a href="#">H04W 8/26</a>
Self-organizing networks, e.g. ad-hoc networks or sensor networks	<a href="#">H04W 84/18</a>

## H04W 8/20

### Transfer of user or subscriber data

#### Definition statement

*This place covers:*

Arrangements for transfer of user data or subscriber data, e.g. between network databases, subscriber equipment or between network databases and authorized 3d parties.

## H04W 8/205

### {Transfer to or from user equipment or user record carrier}

#### Definition statement

*This place covers:*

Transfer is performed to or from user equipment or between user equipment and user record carrier.

## H04W 8/22

### Processing or transfer of terminal data, e.g. status or physical capabilities

#### Definition statement

*This place covers:*

Processing terminal data, e.g. storing, updating, deleting.

Transferring terminal data, e.g. data related to condition, physical capabilities. Transferring terminal status, e.g. lost, stolen.

## References

### Limiting references

*This place does not cover:*

Devices for signalling identity of wanted subscriber with provision for storing more than one subscriber number at a time using static electronic memories	<a href="#">H04M 1/2745</a>
--	-----------------------------

### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Allocation plan definition, set-up or creation based on terminal or device properties	<a href="#">H04W 72/048</a>
Protocols for network applications adapted for proprietary or special purpose networking environments, involving the management of devices over a network	<a href="#">H04L 29/08567</a>

## H04W 8/24

### Transfer of terminal data

#### Definition statement

*This place covers:*

Transfer of terminal data, e.g. between network and terminal equipment.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Programme loading or initiating <a href="#">G06F 9/445</a> ; Power saving arrangements <a href="#">H04W 52/02</a> ; De-registration or Detaching	<a href="#">H04W 60/06</a>
Portable communication terminals with means for supporting locally a plurality of applications to increase the functionality provided by software upgrading or downloading	<a href="#">H04M 1/72406</a>

## H04W 8/245

### {from a network towards a terminal}

#### Definition statement

*This place covers:*

Transfer of terminal data from a network towards a terminal, e.g. downloading terminal equipment software, remotely activating or deactivating terminals.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Protocols for network applications involving the movement of software and/or configuration parameters	<a href="#">H04L 29/08981</a>
Cordless phones with means for supporting locally a plurality of applications to increase the functionality provided by software upgrading or downloading	<a href="#">H04M 1/72406</a>

## H04W 8/26

### Network addressing or numbering for mobility support

#### Definition statement

*This place covers:*

Allocating address(es) to network components, services or other logical entities, for the purpose of handling mobility or establishing communication(s) using said address(es);

De-allocating, reclaiming of address(es); Action(s) making use of addresses.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Assignment or use of connection identifiers when establishing a connection	<a href="#">H04W 76/11</a>
Address allocation involving portability aspects in data networks	<a href="#">H04L 29/12311</a>
Additional connecting arrangements for providing access to frequently-wanted subscribers, e.g. abbreviated dialling	<a href="#">H04M 3/44</a>

## H04W 8/265

### {for initial activation of new user}

#### Definition statement

*This place covers:*

Allocation of network address or number at initial activation of a user

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Access control characterised by a protocol	<a href="#">H04L 29/06823</a>
--	-------------------------------

## H04W 8/28

### Number portability {; Network address portability}

#### Definition statement

*This place covers:*

Network addressing is carried out independently of a user's subscription data.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Personal communications services for intelligent networking, e.g. provisions for portability of subscriber numbers	<a href="#">H04Q 3/005</a>
--	----------------------------

## H04W 8/30

### Network data restoration; {Network data reliability; Network data fault tolerance}

#### Definition statement

*This place covers:*

Providing for reliability and fault tolerance of network data; Restoring network data after accidental loss or network malfunction.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Arrangements for maintaining operational condition	<a href="#">H04W 24/04</a>
Error control	<a href="#">H04W 28/04</a>
Counter-measures to a fault	<a href="#">H04L 29/14</a>

## H04W 12/00

### Security arrangements; Authentication; Protecting privacy or anonymity

#### Definition statement

*This place covers:*

Security arrangements for wireless communications networks, e.g. wireless sensor networks, self-organizing wireless networks, wireless local loop, and for near field communication [NFC] networks.

It covers:

- protecting privacy or anonymity
- protecting confidentiality
- key management
- authentication
- access security

## Definition statement

- integrity
- fraud detection and prevention
- mobile application security
- using identity modules
- secure pairing of devices
- context-dependent security
- lawful interception

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Security arrangements for protecting computers against unauthorised activity	<a href="#">G06F 21/00</a>
Arrangements for secret or secure communication	<a href="#">H04L 9/00</a>

### Special rules of classification

When allocating subgroups [H04W 12/30](#) - [H04W 12/80](#) to documents, attention should be made to check whether other subgroups from [H04W 12/02](#) - [H04W 12/12](#) need to be allocated too for a complete classification.

### Synonyms and Keywords

In patent documents, the following abbreviations are often used:

2G	Second Generation
3G	Third Generation
3GPP	Third Generation Partnership Project
4G	Fourth Generation
5G	Fifth Generation
ACL	Access Control List
AP	Access Point
API	Application Programming Interface
botnet	Robot Network
Cell ID	Cell IDentity
DoS	Denial Of Service
DDoS	Distributed Denial Of Service
EAP	Extensible Authentication Protocol
EAP-AKA	Extensible Authentication Protocol-Authentication and Key Agreement
EAP-SIM	Extensible Authentication Protocol-Subscriber Identity Module
EAP-TLS	Extensible Authentication Protocol-Transport Layer Security
eSIM	Embedded Subscriber Identity Module
eSE	Embedded Secure Element
eSSID	Extended Service Set IDentifier
eUICC	Embedded Universal Integrated Circuit Card



GBA	Generic Bootstrapping Architecture
GSM-AKA	Global System for Mobile Communications-Authentication and Key Agreement
ID	IDentity or IDentifier
IEEE	Institute of Electrical and Electronics Engineers
IEEE 802.1x	Institute of Electrical and Electronics Engineers standard 802.1x.
ICC-ID	Integrated Circuit Card IDentifier
IMEI	International Mobile Equipment Identifier
IMSI	International Mobile Subscriber IDentity
ISIM	IMS (IP Multimedia Subsystem) Subscriber Identity Module
LI	Lawful or Legal Interception
M2M	Machine to Machine
MCIM	Machine-to-machine Communication Identity Module
MEID	Mobile Equipment IDentifier
MITM	Man-In-The-Middle
MSIN	Mobile Station Identity Number
MSISDN	Mobile Station International Subscriber Directory Number
Multi-SIM	Multiple SIMs
MTM	Mobile Trusted Module
NAS	Non-Access Stratum
NFC	Near Field Communication
OAuth	Open Authorisation
OpenID	Open Identity
OOB	out of band
OTAR	Over-The-Air Rekey
P2P	peer-to-peer
PCID	Provisional Connectivity IDentity
PII	Personally Identifiable Information
QR	Quick Response
RBAC	Role Based Access Control
RF	Radio Frequency
RFID	Radio Frequency IDentifier
RRC	Radio Resource Control
RTT	Round Trip Time
RUIM	Removable Universal Identity Module
SE	Secure Element
SIM	Subscriber Identity Module
SMS	Short Message Service
SSID	Service Set IDentifier
TMSI	Temporary Mobile Station Identity

UICC	Universal Integrated Circuit Card
UMTS-AKA	Universal Mobile Telecommunications System-Authentication and Key Agreement
USB	Universal Serial Bus
USIM	Universal Subscriber Identity Module
WEP	Wired Equivalent Privacy
Wi-Fi	Wireless Fidelity
WLAN	Wireless Local Area Network
WPA	Wi-Fi Protected Access
WPS	Wi-Fi Protected Setup

## H04W 12/009

{specially adapted for networks, e.g. wireless sensor networks, ad-hoc networks, RFID networks or cloud networks}

### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communications networks specially adapted for networks such as wireless sensor networks, ad-hoc networks, RFID networks or cloud networks.

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Self-organising networks	<a href="#">H04W 84/18</a>
--------------------------	----------------------------

### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

RFID	Radio Frequency IDentification
------	--------------------------------

## H04W 12/02

Protecting privacy or anonymity, e.g. protecting personally identifiable information [PII]

### Definition statement

*This place covers:*

Security arrangements specifically adapted for wireless communication networks for protecting privacy and anonymity comprising, for example:

- identity privacy, e.g. aliases, pseudonyms or temporary identities,
- data privacy, e.g. by defining which of the owner's data are visible to other parties, or
- protecting personally identifiable information [PII], e.g. by using privacy policies or levels, by anonymising or obfuscating or blurring user data like location, by hiding browsing or movement history.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Selectively restricting mobility data tracking	<a href="#">H04W 8/16</a>
Security arrangements for protecting computers, components thereof, programs or data against unauthorised activity; Protecting Data	<a href="#">G06F 21/60</a>
Call monitoring; Call tracing; Detection or prevention of malicious calls	<a href="#">H04M 3/2281</a>

## Synonyms and Keywords

In patent documents, the following abbreviations are often used:

PII	Personally Identifiable Information
-----	-------------------------------------

## H04W 12/03

### Protecting confidentiality, e.g. by encryption

#### Definition statement

This place covers:

Security arrangements specifically adapted for wireless communication networks for protecting confidentiality of information, e.g. by encryption or ciphering.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Security arrangements for protecting computers, components thereof, programs or data against unauthorised activity; Protecting Data	<a href="#">G06F 21/60</a>
Arrangements for secret or secure communication, the encryption apparatus using shift registers or memories for blockwise coding	<a href="#">H04L 9/06</a>
Arrangements for secret or secure communication; Public key	<a href="#">H04L 9/30</a>

## H04W 12/033

### of the user plane, e.g. user's traffic

#### Definition statement

This place covers:

Security arrangements specifically adapted for wireless communication networks for protecting confidentiality of user plane, e.g. encrypting user traffic such as SMS, voice, web or application traffic.

## Synonyms and Keywords

In patent documents, the following abbreviations are often used:

SMS	Short Message Service
-----	-----------------------

## H04W 12/037

### of the control plane, e.g. signalling traffic

#### Definition statement

*This place covers:*

Security arrangements specifically adapted for wireless communication networks for confidentiality of control plane, i.e. signalling traffic such as NAS, RRC, Over-The-Air Rekey [OTAR] traffic or M2M trigger traffic.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

NAS	Non-Access Stratum
RRC	Radio Resource Control
OTAR	Over-The-Air Rekey
M2M	Machine to Machine

## H04W 12/04

### Key management, e.g. using generic bootstrapping architecture [GBA]

#### Definition statement

*This place covers:*

Security arrangements specifically adapted for wireless communication networks for key management comprising negotiating, distributing, exchanging, transmitting and validating security keys or credentials.

Typical examples are:

- Key management by Generic Bootstrapping Architecture (GBA),
- EAP-AKA for cellular network,
- EAP-SIM or EAP-TLS for 3GPP-WLAN interworking,
- OpenID or Liberty Alliance and GBA interworking,
- Key agreement via IEEE 802.11x WEP or WPA or WPS push button, e.g. for secure pairing between wireless devices, or
- Key agreement using reduced power transmission like NFC, graphical codes, infra-red or audio channels, e.g. for the secure pairing between wireless devices.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Secure pairing between wireless devices	<a href="#">H04W 12/50</a>
Hand-off or reselection arrangements	<a href="#">H04W 36/00</a>
Arrangements for secret or secure communication; Key distribution	<a href="#">H04L 9/08</a>

## Synonyms and Keywords

In patent documents, the following abbreviations are often used:

GBA	Generic Bootstrapping Architecture
EAP	Extensible Authentication Protocol
EAP-AKA	Extensible Authentication Protocol-Authentication and Key Agreement
EAP-SIM	Extensible Authentication Protocol-Subscriber Identity Module
EAP-TLS	Extensible Authentication Protocol-Transport Layer Security
3GPP	Third Generation Partnership Project
WEP	Wired Equivalent Privacy
WPA	Wi-Fi Protected Access
WPS	Wi-Fi Protected Setup
NFC	Near Field Communication
IEEE	Institute of Electrical and Electronics Engineers

## H04W 12/041

### Key generation or derivation

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for key generation or derivation, for example:

- Key derivation for forward and/or backward security for example for securing vertical or horizontal handovers,
- Horizontal key derivation, or
- Vertical key derivations.

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Handoff or reselection arrangements	<a href="#">H04W 36/00</a>
-------------------------------------	----------------------------

## H04W 12/043

### using a trusted network node as an anchor

#### Definition statement

*This place covers:*

Key management using a trusted network node as anchor, for example:

- Key agreement for handover via EAP-SIM or EAP-AKA or EAP-TLS for 3GPP-WLAN interworking,
- OpenID and generic bootstrapping architecture [GBA interworking],
- Liberty alliance and GBA interworking.

## Synonyms and Keywords

In patent documents, the following abbreviations are often used:

GBA	Generic Bootstrapping Architecture
EAP	Extensible Authentication Protocol
EAP-AKA	Extensible Authentication Protocol-Authentication and Key Agreement
EAP-SIM	Extensible Authentication Protocol-Subscriber Identity Module
EAP-TLS	Extended Authenticated Protocol-Transport Layer Security
3GPP	Third Generation Partnership Project
WLAN	Wireless Local Area Network
OpenID	Open Identity

## H04W 12/0431

### Key distribution or pre-distribution; Key agreement

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for key distribution using a trusted network node as anchor, e.g. key pre-distribution or key agreement.

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Arrangements for secret or secure communication, Key distribution	<a href="#">H04L 9/08</a>
---	---------------------------

## H04W 12/047

### without using a trusted network node as an anchor

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for key management without using a trusted network node as anchor, for example:

- Key exchange or agreement via Wi-Fi protected setup [WPS],
- Key exchange using short range communication, e.g. near field communication [NFC],
- Key exchange out-of-band [OOB] methods such as graphical codes, barcodes or Quick Response [QR] codes, infrared, audio waves, light wave, USB dongle, etc. or
- Peer-to-peer [P2P] key exchange or agreement.

## Synonyms and Keywords

In patent documents, the following abbreviations are often used:

Wi-Fi	Wireless Fidelity
WPS	Wi-Fi protected setup

OOB	out of band
QR	Quick Response
NFC	near field communication
USB	Universal Serial Bus
P2P	peer-to-peer

## H04W 12/06

### Authentication

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for authentication, including authenticating entities such as, e.g. human user(s), device(s), service(s), after consulting network stored entity data or checking their credentials (e.g. GSM-AKA, UMTS-AKA, pre-authentication, continuous authentication, authentication using credential vaults or password managers).

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Security arrangements for protecting computers, components thereof, programs or data against unauthorised activity, Authentication	<a href="#">G06F 21/30</a>
Payment architectures, schemes or protocols, Authorisation	<a href="#">G06Q 20/40</a>
Arrangements for secret or secure communication including means for verifying the identity or authority of a user of the system	<a href="#">H04L 9/32</a>

### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

GSM-AKA	Global System for Mobile communications-Authentication and Key Agreement
UMTS-AKA	Universal Mobile Telecommunications System-Authentication and Key Agreement

## H04W 12/062

### Pre-authentication

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for performing pre-authentication, e.g. pre-caching and verification of credentials for faster login or IEEE 802.1x pre-authentication in advance to connection setup.

## Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

IEEE 802.1x	Institute of Electrical and Electronics Engineers standard 802.1x.
-------------	--

## H04W 12/065

### Continuous authentication

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for performing continuous authentication or implicit authentication, i.e. continuous identity recognition and authentication using, e.g. behavioural biometrics and without explicitly asking the user to provide credentials.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Context-dependent security, gesture-dependent or behaviour-dependent	<a href="#">H04W 12/68</a>
--	----------------------------

## H04W 12/068

**{using credential vaults, e.g. password manager applications or one time password [OTP] applications}**

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for performing authentication, using credential vaults, or password management applications or OTP applications.

Examples are: generating credentials via device movements or gestures, behaviormetrics for authentication using a learned user behaviour, such as typing or touching or gripping characteristics.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Network security architectures or protocols for supporting authentication in a packet data network	<a href="#">H04L 63/08</a>
--	----------------------------

## Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

OTP	One Time Password
-----	-------------------



## H04W 12/08

### Access security

#### Definition statement

*This place covers:*

Security arrangements specifically adapted for wireless communications network for access security comprising access authorisation to wireless network resources for example using:

- Authorisation based on an entity's identity, e.g. Access Control Lists ACL, whitelists, blacklists,
- Authorisation based on profile or attributes assigned to an entity, e.g. verifying current profile against expected one, age attribute verification,
- Authorisation based on a group or role, e.g. Role Based Access Control [RBAC],
- Authorisation based security level,
- Authorisation based on the trust score or the reputation of an entity,
- Authorisation based on location, e.g. proximity to other entities, allowed locations,
- Authorisation based on time, e.g. limited time window, within a time range,
- Revocation of authorisation, e.g. secure disconnect, remote kill or suspend or lock or wipe command,
- Delegation of authorisation, e.g. OAuth, user centric management of access rights, user consent or approval,
- Authorisation based on security domains, e.g. controlling access to enterprise security domain or private data security domains, authorisation based on application security domains, e.g. Global Platform domains or authorisation using packet filters or packet firewalls, e.g. SMS Firewalls, NFC or SIM packet filtering.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

ACL	Access Control List
RBAC	Role Based Access Control
SMS	Short Message Service
NFC	Near Field Communication
SIM	Subscriber Identity Module

## H04W 12/082

### using revocation of authorisation

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communications network comprising access authorisation to wireless network resources using revocation of authorisation, for example:

- Secure disconnect,
- Remote kill command, or
- Remote lock or remote wipe command.

## H04W 12/084

using delegated authorisation, e.g. open authorisation [OAuth] protocol

### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communications network for access authorisation delegation comprising giving authorisation to wireless network resources without sharing credentials, for example:

- Delegating access or authorisation token, e.g. using OAuth protocol, or
- Distributing authorisation tokens after user's consent or approval.

### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

OAuth	Open Authorisation
-------	--------------------

## H04W 12/086

using security domains

### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communications network comprising access authorisation to wireless network resources based on security domains, for example:

- Controlling access to enterprise security domain or private security domain,
- Access control based on machine to machine [M2M] security domains, or
- Authorisation based on application security domains (e.g. Global Platform domains).

### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

M2M	Machine-to-Machine
-----	--------------------

## H04W 12/088

using filters or firewalls

### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communications network comprising access authorisation to wireless network resources using filters or firewalls, for example:

- Wireless packet firewalls,
- SMS firewall,
- NFC packets filters, or
- SIM packets filters.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Arrangements for monitoring and testing packet switching networks	<a href="#">H04L 43/00</a>
Network architectures or network communication protocols for separating internal from external traffic, e.g. firewalls	<a href="#">H04L 63/02</a>

## Synonyms and Keywords

In patent documents, the following abbreviations are often used:

SMS	Short Message Service
NFC	Near Field Communications
SIM	Subscriber Identity Module

## H04W 12/10

### Integrity

#### Definition statement

*This place covers:*

Verifying information received.

### References

#### Informative references

Attention is drawn to the following places, which may be of interest for search:

Protecting data integrity, e.g. using checksums, certificates or signatures	<a href="#">G06F 21/64</a>
Network security architectures or protocols for verifying the received information	<a href="#">H04L 63/12</a>

## H04W 12/102

### Route integrity, e.g. using trusted paths

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for verifying or ensuring wireless paths or wireless routes' integrity, e.g. using signatures such as Message Authentication Codes or hash chains.

## H04W 12/104

### Location integrity, e.g. secure geotagging

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for verifying or ensuring location integrity, e.g. using secure geotagging, trusted wireless cell tagging, or wireless location signatures.

## H04W 12/106

### Packet or message integrity

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for verifying or ensuring packet integrity, e.g. using packet signatures such as Message Authentication Codes.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Coding, decoding or code conversion, for error detection or error correction; Coding theory basic assumptions; Coding bounds; Error probability evaluation methods; Channel models; Simulation or testing of codes	<a href="#">H03M 13/00</a>
--	----------------------------

## H04W 12/108

### Source integrity

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for verifying or ensuring source (i.e. sender) integrity, e.g. using signatures such as Message Authentication Codes to verify the source (i.e. sender).

## H04W 12/12

### Detection or prevention of fraud

#### Definition statement

*This place covers:*

Security arrangements specifically adapted for wireless communication networks for fraud detection or prevention, comprising

- protecting against rogue devices, e.g. bidding down or downgrading attacks, rogue device or rogue AP or NFC device, selfish nodes,
- wireless intrusion detection and prevention,
- protecting against power exhaustion attacks, e.g. power depletion, starvation attack or sleep deprivation attack,

## Definition statement

- anti-theft arrangements, e.g. protection against identity or service or device theft like SIM cloning or machine to machine M2M displacement,
- anti-malware arrangements, e.g. protection against SMS fraud or mobile malware,
- detecting or preventing attacks on wireless networks or entities (e.g. Denial of Service DoS, DDoS, botnet) or
- vulnerability assessment of wireless networks or entities.

## References

*Informative references*

Attention is drawn to the following places, which may be of interest for search:

Detecting local intrusion or implementing counter-measures	<a href="#">G06F 21/55</a>
Monitoring arrangements; testing arrangements	<a href="#">H04L 43/00</a>

## Synonyms and Keywords

In patent documents, the following abbreviations are often used:

AP	Access Point
NFC	Near Field Communications
DoS	Denial of Service
DDoS	Distributed Denial of Service
SMS	Short Message Service
botnet	Robot Network

## H04W 12/121

## Wireless intrusion detection systems [WIDS]; Wireless intrusion prevention systems [WIPS]

## Definition statement

This place covers:

Security arrangements specially adapted for wireless communication networks for wireless intrusion detection and protection, comprising:

- Detecting or preventing intrusions using identifiers in general for example a MAC address, or a Bluetooth address, or
- Detecting or preventing intrusions using radio fingerprints identifiers.

## References

*Informative references*

Attention is drawn to the following places, which may be of interest for search:

Context-dependent security, identity-dependent	<a href="#">H04W 12/69</a>
Context-dependent security, radio fingerprint	<a href="#">H04W 12/79</a>

## H04W 12/122

### Counter-measures against attacks; Protection against rogue devices

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for countermeasures against attacks, e.g. to protect against rogue devices, comprising:

- Protecting against bidding down or downgrading attacks,
- Protecting against rogue WLAN AP or cellular Base Station spoofing legitimate APs or base stations,
- Protecting against wireless short range (e.g. RFID, NFC, Bluetooth) man-in-the-middle [MITM] or wireless relay attacks,
- Protecting against selfish nodes dropping legitimate packets or impersonating other nodes,
- Isolating malicious wireless devices or malicious wireless traffic or
- Quarantining malicious wireless devices or dropping malicious wireless traffic.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

WLAN	Wireless Local Area Network
AP	Access Point
NFC	Near Field Communications
RFID	Radio Frequency IDentifier
MITM	Man-in-the-Middle

## H04W 12/126

### Anti-theft arrangements, e.g. protection against subscriber identity module [SIM] cloning

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks comprising:

- Anti-theft arrangements, e.g. protection against identity or service or device theft like SIM cloning or machine to machine [M2M] displacement,
- Anti-malware arrangements, e.g. protection against SMS fraud or mobile malware,
- Detecting or preventing of attacks on wireless networks or entities, e.g. denial of service [DoS], distributed denial of service [DDoS] or botnet, or
- Vulnerability assessment of wireless networks or entities.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

M2M	Machine-to-Machine
SIM	Subscriber Identity Module

## H04W 12/128

### Anti-malware arrangements, e.g. protection against SMS fraud or mobile malware

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks comprising anti-malware arrangements, for example:

- Protection against SMS fraud, such as premium SMS malware or
- Protection against mobile malware, e.g. viruses or worms propagating via wireless networks or attacking wireless networks or wireless services.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Computer malware detection or handling, e.g. Anti-Virus arrangements	<a href="#">G06F 21/56</a>
--	----------------------------

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

SMS	Short Message Service
-----	-----------------------

## H04W 12/30

### Security of mobile devices; Security of mobile applications

#### Definition statement

*This place covers:*

Security arrangements specifically adapted for wireless communications networks for mobile device security or mobile application security, for example:

- Securing mobile application or mobile service provisioning, securing SIM application provisioning,
- Securing mobile application download, protecting update thereof, or
- Managing security policies for mobile applications or mobile devices.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

SIM	Subscriber Identity Module
-----	----------------------------

## H04W 12/33

### using wearable devices, e.g. using a smartwatch or smart-glasses

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communications networks for protecting application or service provisioning using wearables, for example:

## Definition statement

- Automatic access to entities such as mobile devices, e.g. unlocking mobile devices using wirelessly enabled wearable devices or
- Securing mobile applications or services executable or connectable to using wirelessly enabled wearable devices, such as wireless smartwatches, headphones, bracelets, rings, necklaces, smart-glasses, wristbands.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Identity modules using near field communication	<a href="#">H04W 12/47</a>
Wireless network protocols or protocol adaptations to wireless operations	<a href="#">H04W 80/00</a>

## H04W 12/35

### {Protecting application or service provisioning, e.g. securing SIM application provisioning}

#### Definition statement

This place covers:

Security arrangements specially adapted for wireless communications networks for protecting application or service provisioning, for example:

- Securing SIM application provisioning.
- Securing mobile application download, protecting update thereof.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Power saving arrangements	<a href="#">H04W 52/02</a>
Network security architectures or protocols for detecting or protecting against malicious traffic	<a href="#">H04L 63/14</a>

## Synonyms and Keywords

In patent documents, the following abbreviations are often used:

SIM	Subscriber Identity Module
-----	----------------------------

## H04W 12/37

### Managing security policies for mobile devices or for controlling mobile applications

#### Definition statement

This place covers:

Security arrangements specially adapted for wireless communications networks for managing security policies for mobile applications or mobile devices, for example:

- Managing security policies for mobile applications or devices, using remote mobile device management tools,



## Definition statement

- Parents managing child security policies for wireless devices or mobile applications, or
- Employers managing employees' security policies for wireless devices or for mobile applications.

**H04W 12/40****Security arrangements using identity modules****Definition statement**

*This place covers:*

Security arrangements specifically adapted for wireless communication networks using identity modules for protecting wireless traffic, comprising

- Using subscriber identity modules SIM, USIM, RUIM, MCIM, ISIM, Secure Element [SE], NFC module, Mobile Trusted Module [MTM],
- Virtual identity modules, e.g. virtual SIMs or downloadable SIMs for running on an embedded Secure Element [eSE] or embedded Universal Integrated Circuit [eUICC] or embedded SIM [eSIM],
- Shared identity modules, e.g. shared SIMs,
- Multiple identity modules, e.g. multi-sim, dual-sim,
- Near field communication [NFC] enabled identity modules for protecting wireless traffic, e.g. NFC tags, smart tag or radio frequency identification [RFID] module, or
- Secure binding of identity modules, e.g. securely binding identity modules to a device or a service or an application like Simlock or subsidy lock, binding an SIM to a Relay Node, binding an App to UICC.

**References****Informative references**

*Attention is drawn to the following places, which may be of interest for search:*

Network data management, processing of user or subscriber data	<a href="#">H04W 8/18</a>
Context-dependent security, identity-dependent	<a href="#">H04W 12/69</a>
Payment schemes or models using cards	<a href="#">G06Q 20/34</a>

**Special rules of classification**

When allocating subgroup [H04W 12/40](#), attention should be made to check whether other subgroups, e.g. [H04W 12/06](#) (using SIM for authentication) or [H04W 12/08](#) (using SIM for access security) need to be allocated too for a complete classification.

**Synonyms and Keywords**

*In patent documents, the following abbreviations are often used:*

SIM	Subscriber Identity Module
USIM	Universal Subscriber Identity Module
RUIM	Removable Universal Identity Module
MCIM	Machine-to-machine Communication Identity Module
ISIM	IMS (IP Multimedia Subsystem) Subscriber Identity Module
UICC	Universal Integrated Circuit Card
SE	Secure Element
eSIM	Embedded Subscriber Identity Module

eUICC	Embedded Universal Integrated Circuit Card
eSE	Embedded Secure Element
MTM	Mobile Trusted Module
NFC	Near Field Communication
RFID	Radio Frequency IDentification

## H04W 12/42

### using virtual identity modules

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks using virtual identity modules for protecting wireless traffic, comprising

- Virtual SIMs or downloadable SIMs for running on an embedded Secure Element [eSE] or embedded Universal Integrated Circuit [eUICC] or embedded SIM [eSIM].

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Network data management, processing of user or subscriber data	<a href="#">H04W 8/18</a>
Payment schemes or models using cards	<a href="#">G06Q 20/34</a>

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

SIM	Subscriber Identity Module
eSIM	Embedded Subscriber Identity Module
eUICC	Embedded Universal Integrated Circuit Card
eSE	Embedded Secure Element

## H04W 12/43

### using shared identity modules, e.g. SIM sharing

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks using shared identity modules, e.g. SIM sharing between tethered devices and between a SIMless devices and device equipment with a SIM or UICC.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

SIM	Subscriber Identity Module
UICC	Universal Integrated Circuit Card

## H04W 12/45

### using multiple identity modules

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks using multiple identity modules for protecting wireless traffic, e.g. multi-sim, dual-sim.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

SIM	Subscriber Identity Module
Multi-SIM	Multiple SIMs

## H04W 12/47

### using near field communication [NFC] or radio frequency identification [RFID] modules

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks using near field communication [NFC] enabled identity modules for protecting wireless traffic, e.g. NFC tags, smart tag or radio frequency identification [RFID] module, or NFC enabled SIM or UICC cards.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

NFC	Near Field Communication
RFID	Radio Frequency Identification
SIM	Subscriber Identity Module

## H04W 12/48

### using secure binding, e.g. securely binding identity modules to devices, services or applications

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks for the secure binding of identity modules, e.g. securely binding identity modules to a device or a service or an application like Simlock or subsidy lock, binding an SIM to a Relay Node, and binding an App to UICC.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Network data management for processing of user or subscriber data	<a href="#">H04W 8/18</a>
---	---------------------------

## Synonyms and Keywords

In patent documents, the following abbreviations are often used:

SIM	Subscriber Identity Module
UICC	Universal Integrated Circuit Card

## H04W 12/50

### Secure pairing of devices

#### Definition statement

*This place covers:*

Security arrangements specifically adapted for wireless communication networks for securing pairing of wireless devices, for example:

- Bootstrapping a secure communication link between pairing terminals or
- Secure socializing by establishing a secure wireless link between terminals and their respective mobile social network applications, for examples between mobile terminals of friends, family members, guests.

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Affiliation to network using triggered events	<a href="#">H04W 60/04</a>
---	----------------------------

## H04W 12/55

### involving three or more devices, e.g. group pairing

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communications networks for securing pairing of wireless devices involving three or more devices, e.g. group pairing, securely joining wireless ad-hoc networks.

## H04W 12/61

### Time-dependent

#### Definition statement

*This place covers:*

Time-dependent security arrangements specially adapted for wireless communication networks, e.g. using timestamps, time delays like Round Trip Time RTT or time windows.

## Synonyms and Keywords

In patent documents, the following abbreviations are often used:

RTT	Round Trip Time
-----	-----------------

## H04W 12/63

### Location-dependent; Proximity-dependent

#### Definition statement

*This place covers:*

Location-dependent or proximity-dependent security arrangements specially adapted for wireless communication networks, e.g. using absolute location or proximity to other devices measured using received signal strength RSS.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Services making use of location information	<a href="#">H04W 4/02</a>
---	---------------------------

## H04W 12/64

### using geofenced areas

#### Definition statement

*This place covers:*

Geofenced location aware security arrangements specially adapted for wireless communication networks, e.g. using fenced areas.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Services making use of location information, services related to particular areas	<a href="#">H04W 4/02</a>
---	---------------------------

## H04W 12/65

### Environment-dependent, e.g. using captured environmental data

#### Definition statement

*This place covers:*

Environment-dependent security arrangements specially adapted for wireless communication networks, e.g. using captured environmental data like audio, image, media or temperature.

## H04W 12/67

### Risk-dependent, e.g. selecting a security level depending on risk profiles

#### Definition statement

*This place covers:*

Risk-dependent security arrangements specially adapted for wireless communication networks, e.g. arrangements based on risk profiles, risk scores or trust scores derived from social networks (e.g. from

mobile friends or buddy lists), or arrangements based on trust scores determined by trusted third party servers.

## H04W 12/68

### Gesture-dependent or behaviour-dependent

#### Definition statement

*This place covers:*

Gesture-dependent or behaviour-dependent security arrangements specially adapted for wireless communication networks, e.g. using gestures or device movement.

Examples are: generating credentials via device movements or gestures, behaviormetrics for authentication using a learned user behaviour, such as typing or touching or gripping characteristics.

## H04W 12/71

### Hardware identity

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks using wireless hardware identities, e.g. IMEI, MEID, ICC-ID.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

IMEI	International Mobile Equipment Identifier
MEID	Mobile Equipment Identifier
ICC-ID	Integrated Circuit Card Identifier

## H04W 12/72

### Subscriber identity

#### Definition statement

*This place covers:*

Security arrangements specifically adapted for wireless communication networks using wireless subscriber identities, e.g. MSISDN, IMSI or MSIN.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

MSISDN	Mobile Station International Subscriber Directory Number
IMSI	International Mobile Subscriber Identity
MSIN	Mobile Station Identity Number

## H04W 12/73

### Access point logical identity

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks using wireless access point logical identities, e.g. AP SSID, ESSID or Base station Cell ID.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

AP	Access Point
SSID	Service Set Identifier
eSSID	Extended Service Set Identifier
Cell ID	Cell Identity

## H04W 12/75

### Temporary identity

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks using temporary identities, e.g. TMSI, PCID, pseudonym or alias, random or one-time ID, rolling ID, session ID or anonymous ID.

#### Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

TMSI	Temporary Mobile Station Identity
PCID	Provisional Connectivity IDentity
ID	IDentity or IDentifier

## H04W 12/76

### Group identity

#### Definition statement

*This place covers:*

Security arrangements specifically adapted for wireless communication networks using group identities, e.g. group ID, group IMSI, shared identity, pool of identities.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Network data management, mobility data transfer	<a href="#">H04W 8/08</a>
---	---------------------------

## Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

IMSI	International Mobile Station Identity
ID	IDentity or IDentifier

## H04W 12/77

### Graphical identity

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks using graphical identities, e.g. graphical codes, barcodes or QR codes.

## Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

QR	Quick Response
----	----------------

## H04W 12/79

### Radio fingerprint

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communication networks using radio fingerprints, e.g. electromagnetic signature or RF fingerprint.

## Synonyms and Keywords

*In patent documents, the following abbreviations are often used:*

RF	Radio Frequency
----	-----------------

## H04W 12/80

### Arrangements enabling lawful interception [LI]

#### Definition statement

*This place covers:*

Security arrangements specially adapted for wireless communications networks for lawful or legal interception.

Note: This group should only be allocated when the technical aspects relate to security arrangements for wireless networks for managing "lawful interception"

#### Special rules of classification

When allocating subgroup [H04W 12/80](#) to documents, attention should be made to check whether other subgroups from [H04W 12/02](#) - [H04W 12/128](#) need to be allocated too for a complete classification.



## H04W 16/00

**Network planning, e.g. coverage or traffic planning tools; Network deployment, e.g. resource partitioning or cells structures**

### Definition statement

*This place covers:*

- Arrangements and techniques for determining traffic capacity for network equipments and/or linking infrastructure.
- Distribution of spectral resources at deployment stage, i.e. distributing wireless channels to access points; Re-distribution of said resources during operation on basis of predicted or predefined traffic patterns.
- Providing wireless coverage by special arrangements of service areas or shape, e.g. cell structures.

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Network traffic or resource management	<a href="#">H04W 28/00</a>
Local resource management	<a href="#">H04W 72/00</a>

## H04W 16/02

**Resource partitioning among network components, e.g. reuse partitioning**

### Definition statement

*This place covers:*

- Distribution, at initial stage of deployment, of spectral resources, e.g. channels among access points in a network.
- Defining spectral resources to be re-distributed.
- Sizing network equipments or network equipment links for the purpose of handling expected traffic.
- Distribution of pilot channels

## H04W 16/04

**Traffic adaptive resource partitioning**

### Definition statement

*This place covers:*

Part of the spectral resources can be re-distributed to the access points in order to autonomously optimize performance using long or short term variations in traffic, i.e. the network does not revert to the original distribution.

## H04W 16/06

### Hybrid resource partitioning, e.g. channel borrowing

#### Definition statement

*This place covers:*

Part of the spectral resources distributed to an access point can be relinquished to adjacent access points to avoid communication drops or regulate traffic load. When not longer needed, the relinquished resources are returned to the original access point.

## H04W 16/08

### Load shedding arrangements

#### Definition statement

*This place covers:*

The expected traffic load is regulated by controlling the size of a service area by controlling the transmission power of an access point.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Hand-off or reselecting arrangements for handling the traffic	<a href="#">H04W 36/22</a>
Transmission power control management, i.e. sharing limited amount of power among users or channels or data types, taking into account loading or congestion level	<a href="#">H04W 52/343</a>

## H04W 16/10

### Dynamic resource partitioning

#### Definition statement

*This place covers:*

- Partitioning of all spectral resources is performed autonomously among the access points normally on a interference limiting criteria.
- Dynamic channel partitioning as such.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Wireless resource selection or allocation	<a href="#">H04W 72/04</a>
---	----------------------------

## H04W 16/12

### Fixed resource partitioning

#### Definition statement

*This place covers:*

All of the available spectral resources are assigned in a fixed manner among the network's access points.

Cluster reuse wherein one or more reuse patterns are assigned to at least one access point.

## H04W 16/14

### Spectrum sharing arrangements {between different networks}

#### Definition statement

*This place covers:*

Service area(s) belonging to different wireless networks have at least one of their allocated or cooperatively used spectral resources in common.

Techniques and arrangements for avoiding simultaneous use of the resource, e.g. for detecting interference-free channels in overlap areas.

Covers overlap sharing, i.e. filling voids or gaps in used or allocated resources. Covers also underlay sharing, i.e. using the resources of an overlaid system in an underlay system while staying within an agreed noise floor. Covers the detection and cooperative use of licensed spectrum resources or their detection for interference free operation of unlicensed networks;

Covers also spectrum sharing aspects of cognitive radio systems.

Interference avoidance for communication to/from terminal.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Wireless resource selection or allocation	<a href="#">H04W 72/04</a>
Dynamic wireless traffic scheduling; Dynamically scheduled allocation on shared channel	<a href="#">H04W 72/12</a>
Auxiliary means for detecting or identifying radar signals or the like	<a href="#">G01S 7/021</a>
Assessment of spectral gaps suitable for allocating digitally modulated signals in multi-carrier systems, e.g. for carrier allocation in cognitive radio	<a href="#">H04L 27/0006</a>

## H04W 16/16

### for PBS [Private Base Station] arrangements

#### Definition statement

*This place covers:*

One of the networks being of small scale for non-public usage.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Public Land Mobile Systems, e.g. cellular systems, using private Base Stations, e.g. femto Base Stations, home Node B	<a href="#">H04W 84/045</a>
Small scale networks, flat hierarchical networks, PBS [Private Base Station] network	<a href="#">H04W 84/105</a>

## H04W 16/18

### Network planning tools

#### Definition statement

This place covers:

- Coverage prediction tools or models.
- Use of field measurements for network deployment, use of test access points for determining optimal or optimized locations for network deployment.
- Arrangements and techniques for providing initial network coverage at network deployment or additional coverage at subsequent re-deployment stage. This additional coverage at subsequent re-deployment stage refers to a planned system upgrade, i.e. is not an adaptation of a running system.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Measuring electromagnetic field characteristics	<a href="#">G01R 29/08</a>
Arrangements for maintenance or administration of data switching networks, hardware and software tools for network design, e.g. with integrated simulation and design testing	<a href="#">H04L 41/145</a>

## H04W 16/22

### Traffic simulation tools or models

#### Definition statement

This place covers:

Arrangements and techniques for predicting equipment or system link capacity or system performance

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Arrangements for maintenance or administration of data switching networks, hardware and software tools for network design, e.g. with integrated simulation and design testing	<a href="#">H04L 41/145</a>
---	-----------------------------

## H04W 16/24

### Cell structures

#### Definition statement

*This place covers:*

Arrangements where wireless coverage is provided by special arrangements of service areas (cells) or shape thereof.

## H04W 16/26

### Cell enhancers {or enhancement}, e.g. for tunnels, building shadow

#### Definition statement

*This place covers:*

Techniques and arrangements where the service area is extended by dedicated repeating equipment, Network coordinated processing for cell enhancements. This subgroup contains the use of repeaters to extend the coverage, i.e. the repeater is essentially at fixed position and under direct control of the wireless network.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Public Land Mobile Systems using dedicated repeater stations	<a href="#">H04W 84/047</a>
Terminal device adapted for relaying to or from another terminal or user	<a href="#">H04W 88/04</a>
Active relay systems	<a href="#">H04B 7/15</a>
Radio transmission arrangements for base station coverage control, e.g. by using relays in tunnels	<a href="#">H04B 7/2606</a>

## H04W 16/28

### using beam steering

#### Definition statement

*This place covers:*

The service area is defined by a focused beam in a desired generally variable direction of transmission or reception, e.g. electric antenna tilting or beam forming.

#### References

##### Limiting references

*This place does not cover:*

Arrangements for changing or varying the orientation or the shape of the directional pattern of the waves radiated from an aerial or aerial system	<a href="#">H01Q 3/00</a>
--	---------------------------

**Informative references**

Attention is drawn to the following places, which may be of interest for search:

Control of transmission	<a href="#">H04B 7/005</a>
-------------------------	----------------------------

**H04W 16/30****Special cell shapes, e.g. doughnuts or ring cells****Definition statement**

*This place covers:*

The service area differs substantially from a normally polygonal or sectorized shape, e.g. the outer borders of the ring are defined by preset values of an access point's transmission power.

**References****Informative references**

Attention is drawn to the following places, which may be of interest for search:

Load shedding arrangements	<a href="#">H04W 16/08</a>
Transmission power control management, i.e. sharing limited amount of power among users or channels or data types, taking into account loading or congestion level	<a href="#">H04W 52/343</a>

**H04W 16/32****Hierarchical cell structures****Definition statement**

*This place covers:*

Partitioning spectral resources among access areas organized into ranks, each subordinate to the one above it. Macro cell, microcell overlays.

**H04W 24/00****Supervisory, monitoring or testing arrangements****Definition statement**

*This place covers:*

- Arrangements for supervising performance of a deployed network.
- Testing or monitoring arrangements specially adapted for wireless networks.
- Arrangements for evaluating network performance under real or simulated traffic conditions.
- System equipment reconfiguration or upgrades in order to improve overall network performance.

This group relates also to testing of network components and the monitoring of connections for performance assessment.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Monitoring; testing	<a href="#">H04B 17/00</a>
Arrangements for maintenance or administration of data switching networks	<a href="#">H04L 41/00</a>
Details of data switching networks, monitoring arrangements, testing arrangement	<a href="#">H04L 41/06</a>
Network Service management	<a href="#">H04L 41/50</a>
Supervisory, monitoring or testing arrangements for automatic or semiautomatic exchanges	<a href="#">H04M 3/22</a>

## H04W 24/02

### Arrangements for optimising operational condition

#### Definition statement

*This place covers:*

Automatic configuration of system equipment, reconfiguration or upgrades in order to improve overall network performance. The permanent deployment of additional, i.e. not initially planned, equipment or resources for performance improvement.

Generation, update or management of Neighbour Cell Lists for network management

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Network planning tools	<a href="#">H04W 16/18</a>
Determination of parameters used for hand-off e.g. generation or modification of neighbour cell lists	<a href="#">H04W 36/0083</a>
Service support, Network management device	<a href="#">H04W 88/18</a>
Configuration optimization of network or network elements in data switching networks	<a href="#">H04L 41/0823</a>

## H04W 24/04

### Arrangements for maintaining operational condition

#### Definition statement

*This place covers:*

Reliability aspects, stand-by arrangements, back-up or redundant systems or system components in a network.

## References

### Limiting references

*This place does not cover:*

Details of transmission systems for increasing reliability, e.g. using redundant or spare channels or apparatus	<a href="#">H04B 1/74</a>
---	---------------------------

### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Network data restoration	<a href="#">H04W 8/30</a>
Details of data switching networks, arrangements for maintenance or administration involving automatic restoration of network faults	<a href="#">H04L 41/0654</a>

## H04W 24/06

### Testing, {supervising or monitoring} using simulated traffic

#### Definition statement

*This place covers:*

The operational condition of the network or network nodes is assessed using data generated outside normal operation or by self-testing operation, e.g. loop-back operation.

## References

### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Hardware and software tools for network design, e.g. with integrated simulation and design testing in data switching networks	<a href="#">H04L 41/145</a>
Monitoring arrangements for data switching networks	<a href="#">H04L 43/00</a>

## H04W 24/08

### Testing, {supervising or monitoring} using real traffic

#### Definition statement

*This place covers:*

The operational condition of the network or network nodes is assessed with data collected during normal operation.

## References

### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Network Planning tools	<a href="#">H04W 16/18</a>
Hardware and software tools for network design, e.g. with integrated simulation and design testing in data switching networks	<a href="#">H04L 41/145</a>
Monitoring arrangements for data switching networks	<a href="#">H04L 43/00</a>



## H04W 24/10

### Scheduling measurement reports {; Arrangements for measurement reports}

#### Definition statement

*This place covers:*

Generating measurement requests to monitoring equipment; measuring/collecting/receiving data at/ from reporting equipment.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Discovery of network devices, e.g. terminals	<a href="#">H04W 8/005</a>
Generation, update or management of Neighbour Cell Lists for network management	<a href="#">H04W 24/02</a>
Hand-off or reselecting arrangements	<a href="#">H04W 36/00</a>
Generation, update or management of Neighbour Cell Lists for the purpose of hand-off	<a href="#">H04W 36/0083</a>
Determination of parameters used for hand-off, scheduling hand-off measurements	<a href="#">H04W 36/0088</a>
Connectivity information management, e.g. connectivity discovery or update	<a href="#">H04W 40/24</a>
Power headroom reporting	<a href="#">H04W 52/365</a>
Wireless resource selection or allocation based on quality criteria	<a href="#">H04W 72/08</a>
Processing of captured monitoring data, report generation in data switching networks	<a href="#">H04L 43/06</a>

## H04W 28/00

### Network traffic or resource management

#### Definition statement

*This place covers:*

Arrangements or techniques for central control, by a network component, of traffic or admission policies for the purpose of, e.g. ensuring fair use of network resources among users or terminals or guarantying implicit or negotiated service level or quality agreements. Management of negotiated local resources for further allocation.

This group together with its subgroups cover all reservation and resource negotiation activities (both central and local).

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Local resource management, e.g. wireless traffic scheduling or selection or allocation of wireless resources	<a href="#">H04W 72/00</a>
--	----------------------------

## H04W 28/02

### Traffic management, e.g. flow control or congestion control

#### Definition statement

*This place covers:*

Avoiding or regulating an actual or potential traffic overload condition

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Flow control in the network	<a href="#">H04W 28/10</a>
-----------------------------	----------------------------

## H04W 28/04

### Error control

#### Definition statement

*This place covers:*

Arrangements for preventing, detecting, or correcting errors in the information received in wireless networks.

#### Relationships with other classification places

Arrangements for detecting or preventing errors in the information received in general, i.e. including in wireless networks, is classified in [H04L 1/00](#).

## H04W 28/06

**Optimizing {the usage of the radio link}, e.g. header compression, information sizing {, discarding information (system modifying transmission characteristic according to link quality by modifying frame length [H04L 1/0007](#); dynamic adaptation of the packet size for flow control or congestion control [H04L 47/365](#))}**

#### Definition statement

*This place covers:*

Techniques or arrangements whereby the amount of information transmitted over a wireless link is optimized by:

- Reducing the amount of associated control information.
- Performing information sizing across a wireless interface, e.g. adapting the length of a packet to carry one or more information blocks without bit stuffing.
- Discarding information.

#### References

##### Limiting references

*This place does not cover:*

Systems modifying transmission characteristic according to link quality by modifying the frame length	<a href="#">H04L 1/0007</a>
---	-----------------------------

Dynamic adaptation of the packet size for flow control or congestion control	<a href="#">H04L 47/365</a>
--	-----------------------------

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Customizing content of application services or information format or content conversion, e.g. adaptation by the network of the transmitted or received information for the purpose of wireless delivery to users or terminals	<a href="#">H04W 4/18</a>
Compression; Expansion; Suppression of unnecessary data, e.g. redundancy reduction	<a href="#">H03M 7/30</a>
Systems modifying transmission characteristics according to link quality by adapting the source coding	<a href="#">H04L 1/0014</a>
Protocols for data compression not specifically aiming the wireless interface	<a href="#">H04L 69/04</a>
High level architectural aspects of 7-layer open systems interconnection [OSI] type protocol stacks	<a href="#">H04L 69/32</a>

## H04W 28/065

{using assembly or disassembly of packets}

### Definition statement

*This place covers:*

Adaptation of traffic data packets received from higher layers onto packet transmission requirements of lower layer, e.g. SDU onto PDU, by fragmentation or aggregation.

### References

#### Informative references

Attention is drawn to the following places, which may be of interest for search:

Queuing arrangements for supporting packet reassembly or resequencing	<a href="#">H04L 49/9057</a>
High level architectural aspects of 7-layer open systems interconnection [OSI] type protocol stack	<a href="#">H04L 69/32</a>

### Synonyms and Keywords

*In patent documents, the following words/expressions are often used as synonyms:*

- "fragmentation", and "segmentation"
- "aggregation", and "concatenation"

## H04W 28/08

### Load balancing or load distribution

#### Definition statement

*This place covers:*

Techniques and arrangements where communication information is transmitted over alternate transmission paths for balancing the load in the system or when a preferred or desired path is unavailable due to excessive traffic carried over said path, e.g. load shedding/sharing involving alternative entities.

Emphasis is put on "alternate" here to distinguish from flow control; e.g. load shedding/sharing involving alternative entities will be covered here.

Typical example: different paths in the backbone network.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Hand-off or reselecting arrangements for handling the traffic	<a href="#">H04W 36/22</a>
Communication route or path selection based on wireless node resources	<a href="#">H04W 40/04</a>
Access restriction based on traffic conditions	<a href="#">H04W 48/06</a>
Load balancing in packet switching networks	<a href="#">H04L 47/125</a>

## H04W 28/10

### Flow control {between communication endpoints}

#### Definition statement

*This place covers:*

Techniques and arrangements to regulate the amount of communication information in the network.

In this subgroup flow control is seen from a network point of view, i.e. involving backbone network entities which can communicate to perform flow control. This covers up and downlink.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Local resource management with wireless traffic scheduling	<a href="#">H04W 72/12</a>
Flow control in packet switching networks	<a href="#">H04L 47/10</a>

## H04W 28/12

### using signalling between network elements

#### Definition statement

*This place covers:*

Supervisory or control information is exchanged between equipments involved in information transmission.

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Flow Control and congestion control in packet switching networks using signalling	<a href="#">H04L 47/26</a> , <a href="#">H04L 47/33</a>
---	---

## H04W 28/14

### using intermediate storage

#### Definition statement

*This place covers:*

The information is temporarily stored, buffered, queued for transmission.

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Buffering or recovering information during reselection	<a href="#">H04W 36/02</a>
Schedule definition, set-up, creation based on age of data to be sent	<a href="#">H04W 72/1221</a>
Flow Control and congestion control in packet switching networks using information about buffer occupancy at either end or transit nodes	<a href="#">H04L 47/30</a>

## H04W 28/16

### Central resource management; Negotiation of resources or communication parameters, e.g. negotiating bandwidth or QoS [Quality of Service]

#### Definition statement

*This place covers:*

- Central management of wireless communication resources, i.e. management of wireless communication resources in the access network, e.g. between a central communication resource manager and an access point
- (Re)Negotiating communication parameters of connections involving at least one wireless communication link over which information is to be delivered with a requesting user/terminal from within or outside the system.
- Grant or denial of requests from new users/terminals via access points and conditions under which such requests are granted in view of keeping respectively meeting negotiated or implicit requirements for serviced users or terminals. Establishment of communication parameters

through actions other than negotiation (e.g. delegating or commanding the use of pre-established parameters; determining by a device itself the set of parameters to use).

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Services or facilities specially adapted for wireless communication networks	<a href="#">H04W 4/00</a>
Security arrangements, e.g. access security or fraud detection, Authentication, e.g. verifying user identity or authorisation, Protecting privacy or anonymity	<a href="#">H04W 12/00</a>
Local resource management	<a href="#">H04W 72/00</a>
Admission Control and Resource allocation in packet switching networks	<a href="#">H04L 47/70</a>

## H04W 28/18

### Negotiating wireless communication parameters

#### Definition statement

*This place covers:*

Determining the wireless resources or parameters to be used to achieve an agreed SLA, QoS, etc.

The resources can be provided by/in different networks.

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Arrangements for detecting or preventing errors in the information received, modifying transmission characteristics according to link quality	<a href="#">H04L 1/0001</a>
---	-----------------------------

## H04W 28/20

### Negotiating bandwidth

#### Definition statement

*This place covers:*

(Re)negotiating bandwidth of connection(s) via one or more communication links.

The negotiated bandwidth may be provided via one or more communication links.

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Details of data switching networks, arrangements for maintenance or administration, involving configuration of the network and network elements, bandwidth and capacity management, i.e. automatically increasing or decreasing capacities, e.g. bandwidth on demand	<a href="#">H04L 41/0896</a>
--	------------------------------

## Glossary of terms

In this place, the following terms or expressions are used with the meaning indicated:

Bandwidth	transmission capacity available for communication as provided by a suitable combination of communication links of predefined capacity
-----------	---

## H04W 28/22

### Negotiating communication rate

#### Definition statement

This place covers:

(Re)negotiating transmission rate of connection.

## Glossary of terms

In this place, the following terms or expressions are used with the meaning indicated:

Communication rate	information rate available for communication provided by a suitable combination of information coding and/or modulation techniques
--------------------	--

## H04W 28/24

### Negotiating SLA [Service Level Agreement]; Negotiating QoS [Quality of Service]

#### Definition statement

This place covers:

Determining or negotiating the SLA or QoS. Allowing temporary "graceful degradation" in order to maximize general network capacity.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Data switching networks, stored and forward switching systems, packet switching systems, flow control, access or admission control, e.g. network resource reservation	<a href="#">H04L 47/18</a>
Selecting arrangements, arrangements providing connection between exchanges, provisions for network management, bandwidth allocation or management	<a href="#">H04Q 3/0066</a>

## H04W 28/26

### Resource reservation

#### Definition statement

This place covers:

- Reservation of resources in backbone network; reservation of wireless resources to be allocated by local controller.

- Reservation based on predicted user or terminal behaviour, e.g. moving direction or speed.

Resources are reserved not for immediate but for future use.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Wireless resource selection or allocation	<a href="#">H04W 72/04</a>
---	----------------------------

## H04W 36/00

### Hand-off or reselection arrangements

#### Definition statement

*This place covers:*

Transferring ongoing connection(s) of a user or terminal in connected state to different network resource(s) or administrative domains with the purpose of avoiding or limiting loss or degradation of said connection(s) due to user mobility, wireless link conditions or system loading.

The reselection can take place at the user and/or system initiative based on fixed or agreed criteria and can be performed for all or part of the assigned resources.

Generation, update or management of Neighbour Cell Lists; temporary storage, buffering of connection data during reselection, performing registration, binding or location updates at reselection of network equipments or administrative domains

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Arrangements for detecting or preventing errors in the information received	<a href="#">H04L 1/00</a>
Supervisory, monitoring or testing arrangements	<a href="#">H04W 24/00</a>
Transmission Power Control during macro-diversity or soft handoff	<a href="#">H04W 52/40</a>
Registration, e.g. affiliation to network; De-registration, e.g. terminating affiliation	<a href="#">H04W 60/00</a>
Resource management for broadcast services	<a href="#">H04W 72/005</a>
"Idle hand-off", i.e. reselection while user terminal is in an idle, non-connected state	<a href="#">H04W 48/18</a> , <a href="#">H04W 48/20</a> .

## Special rules of classification

In this main group, local priority rules supersede first-place priority rule (FPPR) classification.



**H04W 36/0005****{Control or signalling for completing the hand-off}****Definition statement***This place covers:*

Exchange of information for controlling the realisation of the hand-off

**H04W 36/0007****{for multicast or broadcast services, e.g. MBMS (multicast or broadcast application services [H04W 4/06](#); resource management for broadcast services [H04W 72/005](#); connection management for selective distribution or broadcast [H04W 76/40](#))}****Definition statement***This place covers:*

Transmission and use of control information, e.g. hand-off signalling messages, including trigger messages which initiates connection(s) hand-off of MBMS services provided in the cell.

**References****Limiting references***This place does not cover:*

Selective distribution or broadcast services to user groups	<a href="#">H04W 4/06</a>
Resource management for broadcast services	<a href="#">H04W 72/005</a>
Connection management for selective distribution or broadcast	<a href="#">H04W 76/40</a>

**H04W 36/0009****{for a plurality of users or terminals, e.g. group communication or moving wireless networks (user group management [H04W 4/08](#); processing of subscriber group data [H04W 8/186](#))}****Definition statement***This place covers:*

Transmission and use of control information, e.g. hand-off signalling messages, including trigger messages which initiates connection(s) hand-off of group communication(s), e.g. for moving wireless networks, hand-off of a group of terminals.

**References****Limiting references***This place does not cover:*

User group management	<a href="#">H04W 4/08</a>
Processing of subscriber group data	<a href="#">H04W 8/186</a>

## H04W 36/0011

**{for data session or connection}**

### Definition statement

*This place covers:*

Transmission and use of control information, e.g. hand-off signalling messages, including trigger messages which initiate data session or connection hand-off

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Connection manipulation	<a href="#">H04W 76/20</a>
Real-time multimedia communications - Session control	<a href="#">H04L 29/06319</a>

## H04W 36/0016

**{for hand-off preparation}**

### Definition statement

*This place covers:*

Preparing data session or connection hand-off (e.g. by using binding update messages) carried out during or prior to lower layer hand-off events (e.g. radio link hand-off)

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Resource reservation	<a href="#">H04W 28/26</a>
----------------------	----------------------------

## H04W 36/0022

**{for transferring sessions between adjacent core network technologies}**

### Definition statement

*This place covers:*

Facilitating access network mobility through handovers between at least two core network domains, either in one or in both directions. Involves change from one core network technology, e.g. from PS [Packet Switched] domain, to a different core network technology, to e.g. CS [Circuit Switched] domain, to CS fallback in EPS [Evolved Packet System].

Used, e.g., in VCC [Voice Call Continuity], SRVCC [Single Radio VCC], VoLGA [Voice over LTE Generic Access].

**H04W 36/0027**

**{for a plurality of sessions or connections, e.g. multi-call, multi-bearer connections}**

**Definition statement**

*This place covers:*

Exchange of information for selecting a particular session to be handed off

**H04W 36/0033**

**{with transfer of context information}**

**Definition statement**

*This place covers:*

Existing context information e.g. PDP context is provided to the hand-off target, e.g., using hand-off signalling between source and target node

**H04W 36/0038**

**{of security context information}**

**Definition statement**

*This place covers:*

Transparent transfer of whole security contexts or parts of a security context, e.g., using hand-off signalling between source and destination node. Solely the transport but not the particular content of the context information is essential. For earlier or in-time availability of established security contexts in connection with hand-offs.

**References****Informative references**

*Attention is drawn to the following places, which may be of interest for search:*

Security arrangements; authentication; protecting privacy or anonymity	<a href="#">H04W 12/00</a>
Arrangements for Network Security characterised by a protocol	<a href="#">H04L 29/06551</a>

**Special rules of classification**

The use of [H04W 12/04](#) code for additional information is mandatory.

**H04W 36/0044**

**{of quality context information}**

**Definition statement**

*This place covers:*

Transparent transfer of data session or connection quality contexts or parameters, e.g. using hand-off signalling between source and target node. Solely the transport but not the particular content of the context information is essential. For earlier or in-time availability of established quality contexts in connection with hand-offs.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Central resource management; Negotiation of resources, e.g. negotiating bandwidth or QoS [Quality of Service]	<a href="#">H04W 28/16</a>
Flow control in packet switching systems	<a href="#">H04L 47/10</a>

## H04W 36/005

{involving radio access media independent information, e.g. MIH [Media independent Hand-off]}

### Definition statement

This place covers:

Radio network independent, universal signalling methods are used to control hand-off in different radio networks, e.g., IEEE 802.21 Media Independent Handoff

## H04W 36/0055

{Transmission and use of information for re-establishing the radio link}

### Definition statement

This place covers:

Transmission and use of capacity information of neighbouring cells; Transmission and use of configuration information to be applied in the target cell; Transmission and use of information to assist the MT to retrieve neighbour cell information;

Transmission and use of the configuration information of the links associated with the terminal realising the hand-off; Transmission and use of specific resource information which are used to transmit a handover message.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Load balancing or load distribution	<a href="#">H04W 28/08</a>
Central resource management, Negotiation of resources, e.g. negotiating bandwidth or QoS [Quality of Service]	<a href="#">H04W 28/16</a>
Access restriction or access information delivery, e.g. discovery data delivery	<a href="#">H04W 48/08</a>
Control information exchange between nodes	<a href="#">H04W 72/0406</a>

**H04W 36/0058**

**{Transmission of hand-off measurement information, e.g. measurement reports}**

**Definition statement**

*This place covers:*

Transmission and use of control information, e.g. hand-off signalling messages, including trigger messages which initiates connection(s) hand-off of MBMS services provided in the cell.

**H04W 36/0061**

**{of neighbor cell information}**

**Definition statement**

*This place covers:*

Transmission and use of cell information, e.g. cell ID, neighbour cell lists or service capabilities.

**H04W 36/0066**

**{of control information between different types of networks in order to establish a new radio link in the target network}**

**Definition statement**

*This place covers:*

Transmission of information between different types of networks in order to establish a new radio link.

**H04W 36/0069**

**{in case of dual connectivity, e.g. CoMP, decoupled uplink/downlink or carrier aggregation (allocation of physical resources in CoMP or in carrier aggregation [H04L 5/0035](#))}**

**Definition statement**

*This place covers:*

Transmission and use of information for hand-off of radio link(s) in case of RRC diversity, decoupled uplink/downlink, aggregation of macro anchor carrier and low power node data booster, CoMP, carrier aggregation, unbalanced uplink/downlink.

**References****Limiting references**

*This place does not cover:*

Allocation of physical resources in a cooperative multipoint environment	<a href="#">H04L 5/0035</a>
--	-----------------------------

**H04W 36/0072****{of resource information of target access point}****Definition statement***This place covers:*

Notifying the terminal about resources assigned to the target access point or to be used by the terminal; Notification of timing information of a target cell.

**References****Informative references**

Attention is drawn to the following places, which may be of interest for search:

Compensating for timing error of reception due to propagation delay by altering transmission time	<a href="#">H04W 56/0045</a>
---	------------------------------

**H04W 36/0077****{of access information of target access point}****Definition statement***This place covers:*

Transmission of random access codes to be used for accessing the destination cell; Transmission of ranging codes.

**H04W 36/0079****{in case of hand-off failure or rejection}****Definition statement***This place covers:*

Transmission and use of information for retry strategies in case of hand-off failure or rejection.

**H04W 36/0083****{Determination of parameters used for hand-off, e.g. generation or modification of neighbour cell lists}****Definition statement***This place covers:*

Scanning for hand-off; generation of neighbour cell lists; determination of threshold for signal level reception upon which reporting should be done or upon which hand-off is triggered; update of neighbouring cell list; Determination of the resource that shall be used in the neighbouring cell; Provision of measurements reports in connection with hand-off.

**References****Informative references**

Attention is drawn to the following places, which may be of interest for search:

Discovering; Processing access restriction or access information	<a href="#">H04W 48/16</a>
--	----------------------------

**H04W 36/00835****{Determination of the neighbour cell list}****Definition statement**

*This place covers:*

Generation or update of neighbour cell lists; determination of target BS priorities in the neighbour cell lists; determination of a target neighbour cell.

**H04W 36/00837****{Determination of triggering parameters for hand-off}****Definition statement**

*This place covers:*

Determination of thresholds values or any other type of values for which hand-off is triggered, determination of time when hand-off is triggered.

**H04W 36/0085****{Hand-off measurements}****Definition statement**

*This place covers:*

Scanning for hand-off; determination of the time at which measurement shall be performed; arrangements and techniques for defining and determining parameters required for hand-off measurements, determination of thresholds for triggering hand-off measurements.

**H04W 36/0088****{Scheduling hand-off measurements}****Definition statement**

*This place covers:*

Determination of the time at which measures shall be performed.

**References****Informative references**

*Attention is drawn to the following places, which may be of interest for search:*

Scheduling measurement reports; Arrangements for measurements reports	<a href="#">H04W 24/10</a>
---	----------------------------

**H04W 36/0094****{Definition of hand-off measurement parameters}****Definition statement**

*This place covers:*

Arrangements and techniques for defining parameters required for neighbour cell measurements.

## H04W 36/02

**Buffering or recovering information during reselection {; Modification of the traffic flow during hand-off}**

### Definition statement

*This place covers:*

Sending data to a buffer during hand-off; reading data from a buffer during hand-off and sending the data to one or more access points; Sending the same data to several access points during handoff.

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Flow control in the network	<a href="#">H04W 28/10</a>
-----------------------------	----------------------------

## H04W 36/023

**{Buffering or recovering information during reselection}**

### Definition statement

*This place covers:*

Sending data to a buffer during hand-off; reading data from a buffer during hand-off and sending the data to one or more access points

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Modification of an existing route due to handover	<a href="#">H04W 40/36</a>
Sequence integrity	<a href="#">H04L 47/34</a>

## H04W 36/026

**{Multicasting of data during hand-off}**

### Definition statement

*This place covers:*

Sending the same data to several access points during handoff.

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Site diversity, e.g. macro-diversity for radio transmission systems	<a href="#">H04B 7/022</a>
---	----------------------------



## H04W 36/03

### {Reselecting a link using a direct mode connection}

#### Definition statement

*This place covers:*

Hand-off of a pre-established connection through an access point to a direct mode connection; Hand-off of a direct mode connection; wherein the direct mode connection is established in a pre-organized network or is established independently, e.g. ad hoc.

## H04W 36/04

### Reselecting a cell layer in multi-layered cells

#### Definition statement

*This place covers:*

The connection is transferred between access points providing communication in areas of significantly different coverage. Macrocell/microcell hand-off, with the following features: hand-off within the same network authority and using the same air interface.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Reselecting a different type of service backbone for heterogeneous networks	<a href="#">H04W 36/125</a>
---	-----------------------------

## H04W 36/06

### Reselecting a communication resource in the serving access point

#### Definition statement

*This place covers:*

Arrangements where wireless communication(s) channel(s) are locally re-arranged without altering the fixed network connection(s); e.g. intra-cell hand-off, hand-off between sectors of one access point.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Wireless resource selection or (re-)allocation within a cell without exchange of handoff signalling messages	<a href="#">H04W 72/04</a>
--	----------------------------

## H04W 36/08

### Reselecting an access point

#### Definition statement

*This place covers:*

Arrangements where a different access point is selected, e.g. Intra BSC/RNC hand-off. In case of failure the previous access point can be reselected.

## H04W 36/10

### Reselecting an access point controller

#### Definition statement

*This place covers:*

Arrangements where the reselected access point(s) belongs to a different access controller, e.g. inter BSC/RNC hand-off.

## H04W 36/12

### Reselecting a serving backbone network switching or routing node

#### Definition statement

*This place covers:*

The connection is transferred between serving nodes in the backbone network e.g. inter-MSR, inter-SGSN.

## H04W 36/125

### {involving different types of service backbone}

#### Definition statement

*This place covers:*

Reselecting a different type of service backbone for heterogeneous networks, e.g. between macro and femto cells; Reselecting a service backbone involving a service backbone bypassing mobility servers e.g. for local breakout in LIPA or for selected IP traffic offload SIPTO.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Reselecting a cell layer in multi-layer cells providing the same type of service backbone	<a href="#">H04W 36/04</a>
---	----------------------------

## H04W 36/14

### Reselecting a network or an air interface

#### Definition statement

*This place covers:*

The connection is transferred to a different network or authority, e.g. inter-operator, inter-system hand-off.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Control or signalling for completing the hand-off	<a href="#">H04W 36/0005</a>
---	------------------------------

## H04W 36/16

### Performing reselection for specific purposes

#### Definition statement

*This place covers:*

Event causing a hand-off initiation

## H04W 36/165

{for improving the overall network performance ([H04W 36/18](#) - [H04W 36/22](#) take precedence)}

#### Definition statement

*This place covers:*

Hand-off of terminals for improving the overall network performance, e.g. reducing overall network power consumption or interference.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Performing selection for specific purposes	<a href="#">H04W 36/18</a> - <a href="#">H04W 36/22</a>
--	--

#### Special rules of classification

In practice, all documents falling under coverage of [H04W 36/165](#) are all classified in [H04W 36/165](#) unless they fit at least into one of the groups [H04W 36/18](#) - [H04W 36/22](#).

## H04W 36/18

for allowing seamless reselection, e.g. soft reselection

### Definition statement

*This place covers:*

Wireless links or data associations are temporarily added or deleted in such a manner that the terminal has at least one wireless link connected or one data association. The primary and the temporarily added wireless link carry the same content. This group covers temporarily established parallel radio links or data associations for the purpose of maintaining a connection during a hand-off.

Data associations cover mobility data e.g. IP addresses.

### References

#### Limiting references

*This place does not cover:*

Diversity systems, i.e. using permanently existing parallel connections for improving the robustness of the wireless connection	<a href="#">H04B 7/02</a>
Diversity systems, Cooperative use of antennas of several nodes, e.g. in coordinated multipoint or cooperative MIMO	<a href="#">H04B 7/024</a>

## H04W 36/20

for optimising the interference level

### Definition statement

*This place covers:*

Transferring connections in order to avoid interference to/from neighbouring cells, e.g. confinement hand-off.

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Allocation of wireless resources based on quality criteria	<a href="#">H04W 72/08</a>
--	----------------------------

## H04W 36/22

for handling the traffic

### Definition statement

*This place covers:*

Transferring connections in order to distribute the traffic to neighbouring cells, e.g. load shedding hand-off.

## References

### *Informative references*

Attention is drawn to the following places, which may be of interest for search:

Load shedding arrangements	<a href="#">H04W 16/08</a>
Load balancing or load distribution	<a href="#">H04W 28/08</a>

## H04W 36/245

{by historical data}

### Definition statement

*This place covers:*

The hand-off criteria are derived / calculated from recorded network data. Preventing hand-off to target cells for which a short dwell time is expected.

## H04W 36/26

by agreed or negotiated communication parameters

### Definition statement

*This place covers:*

The reselection is performed in order to meet service level agreements.

## References

### *Informative references*

Attention is drawn to the following places, which may be of interest for search:

Negotiating wireless communication parameters	<a href="#">H04W 28/18</a>
---	----------------------------

## H04W 36/28

involving a plurality of connections, e.g. multi-call, multi-bearer connections

### Definition statement

*This place covers:*

The reselection may be performed for selected parts of a plurality of connections of an user or terminal.

## H04W 36/305

{Reselection due to radio link failure (control signalling for hand-off failure [H04W 36/0079](#))}

### Definition statement

*This place covers:*

Triggering the reselection if failure of the current radio link.

## References

### Limiting references

*This place does not cover:*

Control signalling for hand-off failure or rejection	<a href="#">H04W 36/0079</a>
--	------------------------------

## H04W 36/365

**{by manual user interaction}**

### Definition statement

*This place covers:*

The user's opinion on whether the hand-off should be carried out is requested or the user pre-configures under which conditions a hand-off is to be carried out.

## H04W 36/385

**{of the core network}**

### Definition statement

*This place covers:*

E.g. under control of PCRF, MSC, HSS, HLR

## H04W 40/00

**Communication routing or communication path finding**

### Definition statement

*This place covers:*

Techniques and arrangements for selectively establishing one or a plurality of communication paths involving at least one wireless path, from information sources to information sinks, over which information is communicated.

Techniques and arrangements for discovering, establishing, maintaining connectivity information among affiliated wireless equipment, e.g. routing lists.

Techniques and arrangements for path selection, path optimisation in network.

## References

### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Packet switching systems	<a href="#">H04L 12/56</a>
--------------------------	----------------------------

## H04W 48/00

### Access restriction (access security to prevent unauthorised access [H04W 12/08](#)); Network selection; Access point selection

#### Definition statement

*This place covers:*

Techniques or arrangements for preventing user or terminal affiliation or for preventing use of network or access point resources or services.

Techniques or arrangements for selecting one or a plurality of networks, access points, or PoAs.

Techniques or arrangements for network or access point information delivery, e.g. discovery information delivery.

Access restriction is considered as restricting network access for any reason except security, performed without affiliation of a terminal. It can be implemented because of contract between user and provider, for the purpose of avoiding congestion, etc.

#### References

##### Limiting references

*This place does not cover:*

Access security to prevent unauthorised access	<a href="#">H04W 12/08</a>
--	----------------------------

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Security arrangements	<a href="#">H04W 12/00</a>
Hand-off or reselecting arrangements	<a href="#">H04W 36/00</a>
Registration, e.g. affiliation to network, De-registration, e.g. terminating affiliation	<a href="#">H04W 60/00</a>
Local resource management	<a href="#">H04W 72/00</a>
Wireless channel access	<a href="#">H04W 74/00</a>

## H04W 48/02

### Access restriction performed under specific conditions

#### Definition statement

*This place covers:*

Techniques or arrangements for preventing one or a plurality of users or terminals to affiliate to a selected network or access point, or to use network or access point resources or services, e.g. by jamming broadcast, using barring information.

Preventing or restricting access to service.

This group also covers terminal data consulting, e.g. IMEI data consulting.

## References

### *Informative references*

Attention is drawn to the following places, which may be of interest for search:

Access security	<a href="#">H04W 12/08</a>
Fraud detection	<a href="#">H04W 12/12</a>
Central resource management	<a href="#">H04W 28/16</a>
Local resource management	<a href="#">H04W 72/00</a>
Jamming of communication, Counter-measures	<a href="#">H04K 3/00</a>

## H04W 48/04

**based on user or terminal location or mobility data, e.g. moving direction, speed**

### Definition statement

*This place covers:*

Affiliation, access or use is prevented or restricted in specific areas e.g. hospitals, or makes use of user or terminal behaviour information.

Access restriction to avoid influencing systems outside the network.

## H04W 48/06

**based on traffic conditions**

### Definition statement

*This place covers:*

Affiliation, access or use is prevented or restricted in response to or to avoid a congestion situation, e.g. cell barring.

## H04W 48/08

**Access restriction or access information delivery, e.g. discovery data delivery (signalling during connection [H04W 76/00](#))**

### Definition statement

*This place covers:*

Distribution, by network equipment to a user or terminal, of information e.g. for the purpose of selecting a network, a network service, a data network PoA or an access point. This group contains downlink delivery of discovery data.

## References

### *Limiting references*

*This place does not cover:*

Signalling during connection	<a href="#">H04W 76/00</a>
------------------------------	----------------------------



**Informative references**

Attention is drawn to the following places, which may be of interest for search:

Connectivity information management, e.g. connectivity discovery or update	<a href="#">H04W 40/24</a>
--	----------------------------

**H04W 48/10****using broadcasted information****Definition statement**

*This place covers:*

The information is distributed by network equipment or by separate equipment on a channel which is distinct from a network communication or control channel e.g. bulletin board. This group contains broadcasting of network (discovery, access...) data for other networks.

**H04W 48/12****using downlink control channel****Definition statement**

*This place covers:*

Using part of/or a network control channel, e.g. beacon channel. This group contains broadcasting of network (discovery, access...) data by the network on a downlink control channel.

**References****Informative references**

Attention is drawn to the following places, which may be of interest for search:

Dynamic Wireless traffic scheduling; Dynamically scheduled allocation on shared channel using a grant channel	<a href="#">H04W 72/14</a>
Non-scheduled or contention based access, e.g. random access, ALOHA, CSMA [Carrier Sense Multiple Access] using a dedicated channel for access	<a href="#">H04W 74/0866</a>
Pilot transmitters or receivers for control of transmission or for equalising	<a href="#">H04B 1/76</a>

**H04W 48/14****using user query {or user detection}****Definition statement**

*This place covers:*

The information is sent by the network or access point in response to a user query or user presence detection.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Discovery of network devices, e.g. terminals	<a href="#">H04W 8/005</a>
--	----------------------------

## H04W 48/16

### Discovering, processing access restriction or access information

#### Definition statement

*This place covers:*

Searching for available networks, access points and/or communication services they provide; receiving provided discovery information.

Storage, updating, processing discovery information, generally at terminal or user equipment.

Covers also the discovery of the data network PoA

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Spread spectrum techniques in general for transmission systems using direct sequence modulation with code acquisition	<a href="#">H04B 1/7075</a>
---	-----------------------------

## H04W 48/17

### {Selecting a data network PoA [Point of Attachment]}

#### Definition statement

*This place covers:*

Selecting, based on processed network information, communication service information, or user defined criteria, one or a plurality of data network PoA device(s) within wireless network infrastructure (e.g. PDSN [Packet Date Switching Node] device for immediate or deferred access or affiliation request.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Reselecting a Data Network Point of Attachment	<a href="#">H04W 36/0011</a>
Network selection for access arrangements in wide area data switching networks characterised by path configuration	<a href="#">H04L 12/5691</a>

## H04W 48/18

### Selecting a network or a communication service

#### Definition statement

*This place covers:*

Based on processed network information, communication service information, or user defined criteria, one or a plurality of networks is (are) (re-)selected for immediate or deferred access or affiliation request. Selection of an air interface within a network, or selection of a service, or selection of a network domain in the core network. This group also covers selection between CS and PS domain, preferred PLMN, Home area, Localized Service Area selection.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Selecting a backbone service provider; Access to open networks	<a href="#">H04L 12/5691</a>
--	------------------------------

## H04W 48/20

### Selecting an access point

#### Definition statement

*This place covers:*

Based on processed access point information, or user defined criteria, one or a plurality of access points is (are) (re-)selected for immediate or deferred access or affiliation request. Selection of a cell served by an access point.

## H04W 52/00

### Power management, e.g. TPC [Transmission Power Control], power saving or power classes {(gain control in transmitters or power amplifiers [H03G 3/3042](#))}

#### Definition statement

*This place covers:*

Techniques and arrangements for optimizing network or terminal performance by regulating the amount of power used by a wireless terminal or network equipment.

## H04W 56/00

### Synchronisation arrangements

#### Definition statement

*This place covers:*

Techniques and arrangements for establishing or maintaining a predetermined synchronisation relationship between wireless terminal and network equipment or among wireless network equipment, e.g. time synchronisation or frequency synchronisation.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Synchronising arrangements in time-division multiplex systems	<a href="#">H04J 3/06</a>
Arrangements for synchronising receiver with transmitter	<a href="#">H04L 7/00</a>

## H04W 60/00

### Affiliation to network, e.g. registration; Terminating affiliation with the network, e.g. de-registration

#### Definition statement

This place covers:

- Registering, affiliating of an authorized user or terminal to a network
- Re-registration of subscribers or terminals in the network
- De-registration of subscribers or terminals from the network
- Tracking a subscriber or terminal by monitoring transmitted information e.g. location updates, communication information from the user or terminal either in response of a network's query, trigger event, periodical request or of his own volition, e.g. periodic registration
- Structure of location areas
- Mobility database structures therefor"

This group covers all registration procedures caused by the mobility of a terminal which are not induced by a hand-off.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Network data management	<a href="#">H04W 8/00</a>
Network addressing or numbering for mobility support for initial activation of new users	<a href="#">H04W 8/265</a>
Tracking of users for legal interception	<a href="#">H04W 12/02</a>
"Idle hand-off", i.e. reselection while user terminal is in an idle, non-connected state	<a href="#">H04W 48/18</a> , <a href="#">H04W 48/20</a>

## H04W 60/005

### {Multiple registrations, e.g. multihoming}

#### Definition statement

This place covers:

Multiple affiliations to one or multiple networks or network domains e.g. Multiple WLAN affiliations, parallel affiliations to GSM and UMTS networks, simultaneous registration of more than one binding in one or several location register.

## H04W 60/02

### by periodical registration

#### Definition statement

*This place covers:*

The user or terminal is requested to transmit registration information at scheduled intervals.

## H04W 60/04

### using triggered events

#### Definition statement

*This place covers:*

The registration information is transmitted upon occurrence of specific events, e.g. change of location or routing area, network query. Also changing from idle to active mode at terminal in response to such queries.

## H04W 60/06

### De-registration or detaching

#### Definition statement

*This place covers:*

Indication to the network, access point, user or terminal that affiliation will cease immediately or in a deferred manner; the indication may include information for maintaining or resuming affiliation.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Transfer of terminal data from a network towards a terminal	<a href="#">H04W 8/245</a>
---	----------------------------

## H04W 64/00

### Locating users or terminals {or network equipment} for network management purposes, e.g. mobility management

#### Definition statement

*This place covers:*

Locating user or terminal or network equipment for the purpose of network management or for providing network services to the user or terminal.

## References

### Limiting references

*This place does not cover:*

Radio direction finding, determining distance or velocity by use of radio waves	<a href="#">G01S</a>
Beacon or beacon systems transmitting signals having a characteristic or characteristics capable of being detected by non-directional receivers and defining directions, positions, or position lines fixed relatively to the beacon transmitters or receivers co-operating therewith	<a href="#">G01S 1/00</a>
Direction-finders for determining the direction from which electromagnetic waves, not having a directional significance, are being received	<a href="#">G01S 3/00</a>
Position-fixing by co-ordinating in general	<a href="#">G01S 5/00</a>

## H04W 64/003

**{locating network equipment}**

### Definition statement

*This place covers:*

Locating network equipment for the purpose of network management or for providing network services to the user or terminal.

## H04W 64/006

**{with additional information processing, e.g. for direction or speed determination}**

### Definition statement

*This place covers:*

The measurements on the wireless network links are used to derive additional information, e.g. mobility data.

## References

### Limiting references

*This place does not cover:*

Systems for determining distance or velocity using radio waves	<a href="#">G01S 11/02</a>
--	----------------------------

## H04W 68/00

**User notification, e.g. alerting and paging, for incoming communication, change of service or the like**

### Definition statement

*This place covers:*

Notifying one or a plurality of users specified as recipients of an incoming communication or changes in provided services. Selectively performing notifying in parts of the network, e.g. paging strategies. Techniques to increase efficiency of the notification channel. The notification uses specific wireless

channel(s) reserved/allocated for this purpose; Arrangements and techniques for defining/optimizing paging areas.

Notification, paging strategies based on established location update areas.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Messaging; Mailboxes; Announcements	<a href="#">H04W 4/12</a>
-------------------------------------	---------------------------

## H04W 68/005

{Transmission of information for alerting of incoming communication}

### Definition statement

*This place covers:*

Dedicated structure of paging channels (uplink, downlink, or both). This group covers paging channel structures and paging signalling

## H04W 68/02

Arrangements for increasing efficiency of notification or paging channel

### Definition statement

*This place covers:*

Techniques for enhancing notification attempts, e.g. changing the characteristics of the transmitted notification signal or notification channel(s) between unsuccessful attempts.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Transmission Power Control during retransmission after error or non-acknowledgment	<a href="#">H04W 52/48</a>
--	----------------------------

## H04W 68/025

{Indirect paging}

### Definition statement

*This place covers:*

Indirect paging, whereby a first paging message containing references to the actual paging information is transmitted, e.g. quick paging.

## H04W 68/04

### multi-step notification using statistical or historical mobility data

#### Definition statement

*This place covers:*

The notification is performed using several attempts in an order based on user's habits or recent network interaction data. Notification based on mobility data, e.g. direction of move, speed.

## H04W 68/06

### using multi-step notification by changing the notification area

#### Definition statement

*This place covers:*

The notification is performed using several attempts involving different network areas between unsuccessful attempts.

## H04W 68/08

### using multi-step notification by increasing the notification area

#### Definition statement

*This place covers:*

The notification is performed using several attempts and increasing the initial area by including surrounding network areas between unsuccessful attempts.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Arrangements for increasing efficiency of notification or paging channel	<a href="#">H04W 68/02</a>
--	----------------------------

## H04W 68/10

### using simulcast notification

#### Definition statement

*This place covers:*

The incoming communication is notified over the whole network.



## H04W 68/12

### Inter-network notification

#### Definition statement

*This place covers:*

The notification is conducted simultaneously or sequentially in a plurality of networks. Notification over other subscribed networks when user is unreachable/idle; Using notification associated with different services provided by one (the same) network.

## H04W 72/00

### Local resource management, e.g. wireless traffic scheduling or selection or allocation of wireless resources

#### Definition statement

*This place covers:*

Processing originating user or terminal resource requests for the purpose of allocating one or a plurality of local wireless resources to the user or terminal. Allocating one or a plurality of local wireless resources in response to a terminating user or terminal communication request.

Controlling wireless resource requests (grant or denial) and wireless resource allocation among contending users or terminals.

Selection of wireless resources by user or terminal.

Allocation one or a plurality of local wireless resources based on certain criteria or to fulfil certain requirements. In this group, a relaying equipment is considered as local access point for the requester. This group implicitly includes deallocation of resources.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Central resource management	<a href="#">H04W 28/16</a>
Negotiating wireless communication parameters	<a href="#">H04W 28/18</a>
Resource reservation	<a href="#">H04W 28/26</a>
Arrangements affording multiple use of the transmission path	<a href="#">H04L 5/00</a>

#### Special rules of classification

In this main group, local priority rules supersede first-place priority rule (FPPR) classification.

## H04W 72/005

### {Resource management for broadcast services}

#### Definition statement

*This place covers:*

Allocation of specific resources for broadcast/multicast purposes; reselection of preferred frequency layers (reselecting a different broadcast carrier when service is interrupted on the one in use).

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Central resource management	<a href="#">H04W 28/16</a>
Local resource management	<a href="#">H04W 72/00</a>

## H04W 72/02

### Selection of wireless resources by user or terminal

#### Definition statement

*This place covers:*

The user or terminal decides on the resources to be choose

## H04W 72/04

### Wireless resource allocation

#### Definition statement

*This place covers:*

Allocation of wireless resources or adaptation of assigned wireless resources of an access point or of a regulating authority of a self-organizing network for the purpose of communication with user or terminal; (Semi-) persistent scheduling; Allocation of channels to users.

Semi-persistent scheduling is understood as resource allocation, because the allocation of resources is not changed every transmission frame or slot. Re-allocation, i.e. a modification of an existing allocation plan is included, in case it does not involve handover signalling procedures.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Network deployment, e.g. resource partitioning or cells structures	<a href="#">H04W 16/00</a>
Reselecting a communication resource in the serving access point	<a href="#">H04W 36/06</a>
Scheduling is applied when selected data flows are multiplexed onto a wireless resource, the necessary allocation is implicitly executed	<a href="#">H04W 72/12</a>
Cooperative use of antennas of several nodes, e.g. in coordinated multipoint or cooperative MIMO [Multiple Input Multiple Output]	<a href="#">H04B 7/024</a>
Arrangements for detecting or preventing errors in the information received, modifying transmission characteristics according to link quality	<a href="#">H04L 1/0001</a>
Arrangements affording multiple use of the transmission path	<a href="#">H04L 5/00</a>

## H04W 72/0406

{involving control information exchange between nodes}

### Definition statement

*This place covers:*

Allocation-related communication among nodes, e.g. mobile stations, access points, leading to a transfer of control information e.g. a request for or an assignment of resources as well as descriptive information needed therefore. Control information exchanged via multiple interfaces or directions of similar importance. Resource allocation for control channels.

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Transfer of user or subscriber data	<a href="#">H04W 8/20</a>
Transmission and use of information for re-establishing the radio link of resource information of target access point	<a href="#">H04W 36/0072</a>

### Special rules of classification

Resource allocation for control channels should be classified with a code in [H04W 72/0406](#) and an additional code for the specific resource allocation aspect.

## H04W 72/0413

{in uplink direction of a wireless link, i.e. towards network}

### Definition statement

*This place covers:*

Allocation-related communication from a mobile station to an access point, from a mobile station to a relay node, or from a relay node to an access point. The allocation-related communication comprise e.g. requesting an allocation, or other allocation related issues.

## H04W 72/042

{in downlink direction of a wireless link, i.e. towards terminal}

### Definition statement

*This place covers:*

Allocation-related communication from an access point to a mobile station, from an access point to a relay node, or from a relay node to a mobile station. The allocation-related communication comprises e.g. transmission of the allocation plan, or other allocation related issues.

## H04W 72/0426

**{between access points}**

### Definition statement

*This place covers:*

Allocation-related communication between access points, e.g. notifying the next access point about the resources allocated at the present access point.

## H04W 72/0433

**{between access point and access point controlling device}**

### Definition statement

*This place covers:*

Allocation related communication between an access point and a device controlling the access point, e.g. parameter settings to be applied by the access point

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Central resource management; Negotiating of resources	<a href="#">H04W 28/16</a>
---	----------------------------

## H04W 72/044

**{where an allocation plan is defined based on the type of the allocated resource}**

### Definition statement

*This place covers:*

Allocation plan is based on a particular type of wireless resources to a user or terminal. Allocating complex or combinational resources, e.g. resource blocks in time-frequency domain.

## H04W 72/0446

**{the resource being a slot, sub-slot or frame}**

### Definition statement

*This place covers:*

Allocation of wireless resources to a user or terminal, where the resource allocated is a specified section of a time-based resource. The allocated resource can be specified indicating the start and stop times, or by indicating the identity of a known time-specified resource unit (e.g. slot)

**H04W 72/0453****{the resource being a frequency, carrier or frequency band}****Definition statement***This place covers:*

The resource allocated is a specified portion of a frequency-based resource. The resource can be specified e.g. by indicating the top/bottom frequencies, or by indicating the identity of a known frequency-specified resource unit (e.g. carrier)].

**H04W 72/046****{the resource being in the space domain, e.g. beams}****Definition statement***This place covers:*

The resource allocated is a specified portion of a space-based resource. The resource can be specified by indicating the sector or area where an operation may take place, or by indicating the identity of a known spatially-specified resource unit, e.g. sector, area.

**References****Informative references***Attention is drawn to the following places, which may be of interest for search:*

Cell structures using beam steering	<a href="#">H04W 16/28</a>
-------------------------------------	----------------------------

**H04W 72/0466****{the resource being a scrambling code}****Definition statement***This place covers:*

The resource allocated is a code.

**References****Informative references***Attention is drawn to the following places, which may be of interest for search:*

Orthogonal multiplex systems	<a href="#">H04J 11/00</a>
Code multiplex systems	<a href="#">H04J 13/00</a>

**H04W 72/0473****{the resource being transmission power}****Definition statement***This place covers:*

The resource allocated is defined in terms of transmission power.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Transmission power control management, i.e. sharing limited amount of power among users or channels or data types, e.g. cell loading	<a href="#">H04W 52/34</a>
--	----------------------------

## H04W 72/048

{where an allocation plan is defined based on terminal or device properties}

### Definition statement

*This place covers:*

Allocation of resources on the basis of properties related to the terminal/device to which resources are to be allocated e.g. location, mobility status, operating applications.

Properties either are known by or reported to the instance making the allocation decision.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Processing or transfer of terminal data, e.g. status or physical capabilities	<a href="#">H04W 8/22</a>
---	---------------------------

## H04W 72/0486

{where an allocation plan is defined based on load}

### Definition statement

*This place covers:*

Allocation of resources on the basis of loading of the stations involved or level of usage of resources.

## H04W 72/0493

{where an allocation plan is defined based on a resource usage policy}

### Definition statement

*This place covers:*

Allocation of resources making use of explicit instructions/regulations, whose application directly leads to a specified and well defined allocation plan

## H04W 72/06

{where an allocation plan is defined} based on a ranking criteria of the wireless resources

### Definition statement

*This place covers:*

Allocation of resources on the basis of ranking criteria of the wireless resources, e.g. preferred channel list. Usually a ranking criteria exist before a decision on allocation is made.

## H04W 72/08

{where an allocation plan is defined} based on quality criteria

### Definition statement

*This place covers:*

Allocation of resources on the basis of quality of communication provided by the links or stations involved

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Definition of hand-off measurement parameters; Arrangements and techniques for reducing the perturbation due to measuring activities performed for neighbour cell list measurements e.g. compressed mode	<a href="#">H04W 36/0094</a>
--	------------------------------

## H04W 72/082

{using the level of interference}

### Definition statement

*This place covers:*

Allocation of resources on the basis of interference on the air interface or faced by the stations involved, e.g. co-channel interference; Arrangements and techniques for measuring or sensing the primary network in a cognitive radio, e.g. "quiet period".

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Spectrum sharing arrangements between different networks	<a href="#">H04W 16/14</a>
--	----------------------------

### Special rules of classification

Defining or using a "quiet period" for sensing for the primary network in cognitive radio should be classified in [H04W 72/082](#) with an additional code in [H04W 16/14](#).

## H04W 72/085

{using measured or perceived quality}

### Definition statement

*This place covers:*

Allocation of resources on the basis of the measured quality of communication provided by the air interface or stations involved, e.g. C/I, BER

**H04W 72/087****{using requested quality}****Definition statement***This place covers:*

Allocation of resources on the basis of the requested quality of communication provided by the air interface or stations involved

**H04W 72/10****{where an allocation plan is defined} based on priority criteria****Definition statement***This place covers:*

Allocation of resources on the basis of priority of the traffic communicated, or the priority of the stations involved.

**H04W 72/12****{Dynamic} Wireless traffic scheduling {; Dynamically scheduled allocation on shared channel}****Definition statement***This place covers:*

Techniques and arrangements for:

- establishing the order of transmission of pending traffic information over one or a plurality of the access point's wireless resources. The order of transmission is based on precedence/priority of the information, priority of the information source or recipient or defined resource usage policy.
- notifying user(s) of granted transmission request(s).
- assigning traffic (of one or more users) to existing channels.
- wireless multiplexing of several flows into one single stream on the wireless interface. It applies to up- and downlink.
- scheduled allocation of resources, allocation change can be signalled and changed every transmission frame or slot, i.e. scheduling is applied when selected data flows are multiplexed onto a wireless resource; the necessary allocation is implicitly executed.

**References****Informative references**

Attention is drawn to the following places, which may be of interest for search:

Adaptation of traffic data packets received from higher layers onto packet transmission requirements of lower layer, e.g. SDU onto PDU"	<a href="#">H04W 28/065</a>
Flow control in the network	<a href="#">H04W 28/10</a>
Power saving arrangements using pre-established activity schedule	<a href="#">H04W 52/0216</a>
Semi-persistent scheduling is understood as resource allocation, because the allocation of resources is not changed every transmission frame, slot	<a href="#">H04W 72/04</a>
Discontinuous transmission or reception	<a href="#">H04W 76/28</a>
Arrangements for detecting or preventing errors in the information received, modifying transmission characteristics according to link quality	<a href="#">H04L 1/0001</a>



Flow control in packet switching networks	<a href="#">H04L 47/10</a>
---	----------------------------

## H04W 72/1205

{Schedule definition, set-up or creation}

### Definition statement

*This place covers:*

Definition of a transmission schedule for pending traffic data in a single or multidimensional resource, e.g. frequency and time in case of OFDMA. A transmission schedule is defined depending on e.g. depending on terminal capability

## H04W 72/121

{for groups of terminals or users}

### Definition statement

*This place covers:*

Schedule is established jointly for a group of users; Definition of scheduling group; Assigning group identifier

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

User group management	<a href="#">H04W 4/08</a>
-----------------------	---------------------------

## H04W 72/1215

{for collaboration of different radio technologies}

### Definition statement

*This place covers:*

Schedule is defined to provide for a disturbance free usage of different radio technologies by one network element

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Spectrum sharing arrangements [between different networks	<a href="#">H04W 16/14</a>
Terminal device adapted for operation in multiple networks, e.g. multi-mode terminals	<a href="#">H04W 88/06</a>
Access point device adapted for operation in multiple networks, e.g. multi-mode access points	<a href="#">H04W 88/10</a>
Programme switching, task transfer initiation or dispatching by program, scheduling strategies for dispatcher	<a href="#">G06F 9/4881</a>
Allocation of resources to service a request, the resources being hardware resources other than CPUs, Servers and Terminals	<a href="#">G06F 9/5011</a>

## Special rules of classification

Collaborative techniques,

- in terminals should receive the [H04W 88/06](#) code as additional information
- in base stations should receive the [H04W 88/10](#) code as additional information.

## H04W 72/1221

{based on age of data to be sent}

### Definition statement

*This place covers:*

Schedule definition is based on the time traffic data has been already waiting for transport e.g. in a terminal or base station buffer

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Flow control in the network using intermediate storage	<a href="#">H04W 28/14</a>
Schedule definition, set-up or creation based on load	<a href="#">H04W 72/1252</a>

## H04W 72/1226

{based on channel quality criteria, e.g. channel state dependent scheduling}

### Definition statement

*This place covers:*

Schedule definition is based on a quality criteria of a channel involved in transmission of the traffic data

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Definition of hand-off measurement parameters	<a href="#">H04W 36/0094</a>
Arrangements and techniques for reducing the perturbation due to measuring activities performed for neighbour cell list measurements e.g. compressed mode	<a href="#">H04W 36/0094</a>

## H04W 72/1231

{using measured or perceived quality}

### Definition statement

*This place covers:*

Schedule definition is based on a measured channel quality parameter related to an entity involved in transmission of the traffic data; e.g. measured interference, quality, throughput

**H04W 72/1236****{using requested quality}****Definition statement***This place covers:*

Schedule definition is based on a requested channel quality parameter related to an entity involved in transmission of the traffic data; e.g. requested data or transmission rate or throughput, delay, bandwidth

This group covers also the preferred transmission of packets with earliest deadline or due time.

**H04W 72/1242****{based on precedence or priority of the traffic information}****Definition statement***This place covers:*

Schedule definition is based on a precedence or priority of the data to be transmitted

**H04W 72/1247****{based on priority of the information source or recipient}****Definition statement***This place covers:*

Schedule definition is based on a priority attached to the source or recipient of the traffic data to be transmitted

**H04W 72/1252****{based on load}****Definition statement***This place covers:*

Schedule definition is based on a load status of a resource or entity involved in one of transmission of the traffic data, actual throughput, transmitted amount of data

**References****Informative references**

Attention is drawn to the following places, which may be of interest for search:

Schedule definition, set-up or creation based on age of data to be sent	<a href="#">H04W 72/1221</a>
---	------------------------------

**H04W 72/1257****{based on resource usage policy}****Definition statement***This place covers:*

Schedule definition based on a usage policy related to a resource or entity involved in transmission of the traffic data, e.g. fairness of transmission opportunity, opportunistic scheduling, synchronised switch between uplink and downlink transmission.

**H04W 72/1263****{Schedule usage, i.e. actual mapping of traffic onto schedule; Multiplexing of flows into one or several streams; Mapping aspects; Scheduled allocation}****Definition statement***This place covers:*

Application of a (pre-defined) schedule to accomplish the transport of traffic data over a wireless link. Mapping of traffic data onto a schedule pattern which is defined by the physical parameters used for quantising the wireless medium, e.g. a combination of a frequency and time slots in OFDMA. Also covers cases where scheduling effectively leads to a (temporary) allocation of resources.

**H04W 72/1268****{of uplink data flows}****Definition statement***This place covers:*

Schedule usage for uplink data flows.

**H04W 72/1273****{of downlink data flows}****Definition statement***This place covers:*

Schedule usage for downlink data flows

**H04W 72/1278****{Transmission of control information for scheduling}****Definition statement***This place covers:*

Transmission of information related to the control of scheduling, e.g. requesting of and notification about scheduling, provision of scheduling relevant information

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Transfer of user or subscriber data	<a href="#">H04W 8/20</a>
Transmission of channel access control information	<a href="#">H04W 74/002</a>

## H04W 72/1284

{in the uplink, i.e. from terminal to network}

### Definition statement

*This place covers:*

Transmission of scheduling control information on uplink, e.g. informing about terminal buffer status

## H04W 72/1289

{in the downlink, i.e. towards the terminal}

### Definition statement

*This place covers:*

Transmission of scheduling control information on downlink, e.g. providing scheduling notification information

## H04W 72/1294

{using a grant or specific channel ([H04W 72/14](#) takes precedence)}

### Definition statement

*This place covers:*

Transmission of downlink control information is sent over a specific channel, e.g. downlink control channel. The information signalled may not only be a grant but other control information sent over the channel.

## References

### Limiting references

*This place does not cover:*

Transmission of control information for scheduling in the downlink using a grant channel	<a href="#">H04W 72/14</a>
--	----------------------------

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Flow control in the network using signalling between network elements	<a href="#">H04W 28/12</a>
---	----------------------------

### Special rules of classification

[H04W 72/14](#) is an IPC class; all documents which would be classified in [H04W 72/1294](#) have to be classified into [H04W 72/14](#) instead.

## H04W 72/14

### using a grant {or specific} channel

#### Definition statement

*This place covers:*

Transmission of downlink control information is sent over a specific channel, e.g. downlink control channel. The information signalled may not only be a grant but other control information sent over the channel.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Flow control in the network using signalling between network elements	<a href="#">H04W 28/12</a>
---	----------------------------

## H04W 74/00

### Wireless channel access, e.g. scheduled or random access

#### Definition statement

*This place covers:*

Techniques or arrangements for managing user or terminal requests for access to a channel.  
Techniques or arrangements for arbitration of access between contending users

## H04W 74/002

### {Transmission of channel access control information}

#### Definition statement

*This place covers:*

Channel access related information is transmitted between access point and user or terminal.  
Exchange of information relevant for a random access procedure between nodes. Covers structures of control channels for access; transmission of access information to be used for access channels; access information format.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Transmission and use of information for re-establishing the radio link of access information of target access points	<a href="#">H04W 36/0077</a>
Access restriction or access information delivery, e.g. discovery data delivery	<a href="#">H04W 48/08</a>
Non-scheduled or contention based access with exchange of random access related information	<a href="#">H04W 74/0833</a>

## H04W 74/004

{in the uplink, i.e. towards network}

### Definition statement

*This place covers:*

Channel access related information is sent by a user or terminal towards an access point. A user equipment signals random access information to a radio base station, e.g. RA [Random Access] request, M1 message in LTE [Long Term Evolution].

## H04W 74/006

{in the downlink, i.e. towards the terminal}

### Definition statement

*This place covers:*

Channel access related information is send from access point to user or terminal. A radio base station signals random access information to a user equipment, e.g. RA [Random Access] request response, M2 message in LTE [Long Term Evolution], parameter provisioning)

## H04W 74/008

{with additional processing of random access related information at receiving side}

### Definition statement

*This place covers:*

Parameters relevant for random access, which are exchanged between the involved nodes are additionally processed at the receiving side

## H04W 74/02

**Hybrid access techniques**

### Definition statement

*This place covers:*

Automatic selection of an access technique, e.g. scheduled or non-scheduled with respect to network, user(s) requirements or channel conditions

## H04W 74/04

**Scheduled {or contention-free} access ([H04W 74/02](#) takes precedence)**

### Definition statement

*This place covers:*

Access techniques whereby access a shared media is established for one or a plurality of user's in an orderly fashion generally by a controller. Covers also Slotted access

## References

### Limiting references

*This place does not cover:*

Hybrid access techniques	<a href="#">H04W 74/02</a>
--------------------------	----------------------------

## H04W 74/06

### using polling

#### Definition statement

*This place covers:*

Users or terminals are polled for their immediate transmission requirements and channel access is granted accordingly. Invitation for transmission. Covers also Slotted polling

## H04W 74/08

**Non-scheduled {or contention based} access, e.g. random access, ALOHA, CSMA [Carrier Sense Multiple Access] ([H04W 74/02](#) takes precedence)**

#### Definition statement

*This place covers:*

Access to the shared wireless channel is performed without full awareness of other users' or channel state. This group covers the random access as such. Covers also Slotted ALOHA

## References

### Limiting references

*This place does not cover:*

Hybrid access techniques	<a href="#">H04W 74/02</a>
--------------------------	----------------------------

## H04W 74/0808

**{using carrier sensing, e.g. as in CSMA}**

#### Definition statement

*This place covers:*

Before transmission, the sender listens to the shared medium to detect transmissions by others. Covers also Slotted CSMA

## H04W 74/0816

**{carrier sensing with collision avoidance}**

#### Definition statement

*This place covers:*

Besides listening to the shared medium additional measures are taken in order to avoid collisions, e.g. notifying other senders of an intended transmission, RTS / CTS. Covers also Slotted CSMA



## H04W 74/0825

**{carrier sensing with collision detection}**

### Definition statement

*This place covers:*

If, despite performing carrier sensing, collisions can not be completely avoided, their occurrence is at least detected. Covers also Slotted CSMA

## H04W 74/0833

**{using a random access procedure}**

### Definition statement

*This place covers:*

In the framework of a given (multiple) access scheme the actual access to the shared medium takes place at a random instance without prior carrier sensing.

## H04W 74/0841

**{with collision treatment}**

### Definition statement

*This place covers:*

Given the intrinsic risk of a collision between multiple random access attempts, additional measures are taken for collision treatment of potential further collisions.

## H04W 74/085

**{collision avoidance}**

### Definition statement

*This place covers:*

Measures are taken in order to avoid further collisions, e.g. applying a time back-off for retransmissions.

## H04W 74/0858

**{collision detection}**

### Definition statement

*This place covers:*

In cases where collisions can not be avoided, their occurrence is at least detected.]

**H04W 74/0866****{using a dedicated channel for access}****Definition statement***This place covers:*

Access requests are transmitted on a distinct channel, normally allocated or defined by a controlling entity, e.g. an access point. This group covers the usage of an uplink control channel, i.e. a frequency, a code, a time slot, a frame section.

**H04W 74/0875****{with assigned priorities based access}****Definition statement***This place covers:*

Users access the dedicated channel in an order established by a controlling entity, e.g. an access point

**H04W 74/0883****{for un-synchronized access}****Definition statement***This place covers:*

Access to the dedicated channel is performed at random time, e.g. no frame structure exist or is respected.

**H04W 74/0891****{for synchronized access}****Definition statement***This place covers:*

Access to the dedicated channel is performed respecting a time structure on the channel, e.g. a frame or slot structure.

**H04W 76/00****Connection management****Definition statement***This place covers:*

Techniques and arrangements for selecting and establishing one or a plurality of connections (e.g. tunnels), recovering or reconnecting accidentally lost connections.

Switching or re-directing connection or control function.

De-allocating, re-claiming one or a plurality of established communication resources no longer in use.

Signalling arrangements therefore.

Connection state management, e.g. idle mode; allocation of reserved affiliation/binding connection identifiers associated with one or a plurality of the managed connections.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Communication routing or communication path finding	<a href="#">H04W 40/00</a>
Arrangements for connection and session management	<a href="#">H04L 29/08576</a>

## H04W 76/11

### Allocation or use of connection identifiers

#### Definition statement

*This place covers:*

Assignment or use of one or a plurality of connection identifiers when establishing a connection.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Network addressing or numbering for mobility support	<a href="#">H04W 8/26</a>
Arrangements for addressing and naming in data networks characterized by the data terminal	<a href="#">H04L 29/12009</a>

## H04W 76/12

### Setup of transport tunnels

#### Definition statement

*This place covers:*

Techniques and arrangements for establishing a tunnel connection for transport in the network, e.g. PDP Context establishment.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Protecting privacy or anonymity	<a href="#">H04W 12/02</a>
Arrangements for network security	<a href="#">H04L 29/06551</a>

## H04W 76/14

### Direct-mode setup

#### Definition statement

*This place covers:*

Setup of a direct mode connection in a hierarchical pre-organized network whereby the establishment is done either directly between users/terminals or via relaying equipment, e.g. establishment of a wireless connection between two peers.

The user/terminal equipment establishes a direct communication with another user/terminal equipment on a communication channel defined or negotiated via the network. The direct connection between regular members of a network must be a special mode of operation.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Set up of a connection, e.g. between Bluetooth terminals or between terminals belonging to self-organizing networks, e.g. ad-hoc networks or sensor, mesh networks	<a href="#">H04W 84/18</a>
--	----------------------------

## H04W 76/15

### Setup of multiple wireless link connections

#### Definition statement

*This place covers:*

Techniques and arrangements for establishing a plurality of wireless communication links for transferring information to one user/terminal, i.e. multi-call, multi-bearer connection.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Multichannel or multilink protocols	<a href="#">H04L 29/06088</a>
-------------------------------------	-------------------------------

## H04W 76/16

### Involving different core network technologies, e.g. a packet-switched [PS] bearer in combination with a circuit-switched [CS] bearer

#### Definition statement

*This place covers:*

The mobile network correlates establishment of multiple bearers across at least two different core network domain technologies in parallel for one and the same end user session. The mobile network introduces a certain level of cooperation between, e.g., a PS bearer and a CS bearer or CS over EPS bearer. Used, e.g., in IMS Centralized Services ICS, Combining Circuit Switched and IMS services CSI.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Control or signalling for completing the hand-off for transferring sessions between adjacent core network technologies	<a href="#">H04W 36/0022</a>
Reselecting a network or an air interface	<a href="#">H04W 36/14</a>

## H04W 76/18

### Management of setup rejection or failure

#### Definition statement

*This place covers:*

Techniques and arrangements for the purpose of establishing an alternate connection after the initial connection request being unsuccessful, e.g. retry strategies after rejection or after no response. Rejection of a request for establishing a connection.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Network traffic or resource management, Error control	<a href="#">H04W 28/04</a>
Access restriction performed under specific conditions	<a href="#">H04W 48/02</a>
Reactions to resource unavailability in packet switching systems	<a href="#">H04L 47/74</a>

## H04W 76/19

### Connection re-establishment

#### Definition statement

*This place covers:*

Recovering or reconnecting an accidentally lost connection.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Control or signalling for completing the hand-off for data session or connection with transfer of context information	<a href="#">H04W 36/0033</a>
---	------------------------------

## H04W 76/20

### Manipulation of established connections

#### Definition statement

*This place covers:*

- Switching, re-routing connection or control function in addition to those necessary to establish or maintain connection between users or terminals.
- In-connection signalling, notification, connection state transition to and from e.g. hibernation or dormant mode.
- Connection manipulation aspects of DTX or DRX not related to power saving arrangements.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Hand-off or reselecting arrangements	<a href="#">H04W 36/00</a>
Modification of an existing route due to handover	<a href="#">H04W 40/36</a>
Power saving arrangements	<a href="#">H04W 52/02</a>

## H04W 76/22

### Manipulation of transport tunnels

#### Definition statement

*This place covers:*

Techniques and arrangements for redefining a transport tunnel connection in the network, e.g. PDP context modification.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Control or signalling for completing the hand-off for data session or connection for hand-off preparation	<a href="#">H04W 36/0016</a>
---	------------------------------

## H04W 76/23

### Manipulation of direct-mode connections

#### Definition statement

*This place covers:*

Transition in a hierarchical pre-organized network between direct mode and via third parties mode. Release of non-active connection legs after the transition.

## H04W 76/25

### Maintenance of established connections

#### Definition statement

*This place covers:*

Techniques and arrangements for maintaining an already established connection and avoiding the release of the resources, e.g. transmitting a "keep-alive" packet over the packet protocol context so as to maintain the packet protocol context.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Arrangements for connection and session management at the data link level	<a href="#">H04L 29/08576</a>
---	-------------------------------

## H04W 76/27

### Transitions between radio resource control [RRC] states

#### Definition statement

*This place covers:*

Transitions between RRC states which reflect the level of user equipment connection and which transport channels can be used by the user equipment, e.g. transition between IDLE, CELL\_FACH, CELL\_DCH, CELL\_PCH and URA\_PCH states.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Connection setup	<a href="#">H04W 76/10</a>
------------------	----------------------------

## H04W 76/28

### Discontinuous transmission [DTX]; Discontinuous reception [DRX]

#### Definition statement

*This place covers:*

Connection manipulation aspects of DTX or DRX.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Determination of parameters used for hand-off, e.g. generation or modification of neighbour cell lists	<a href="#">H04W 36/0083</a>
Power saving arrangements	<a href="#">H04W 52/02</a>

## H04W 76/30

### Connection release

#### Definition statement

*This place covers:*

- De-allocating one or a plurality of established connections.
- Signalling therefor.

## H04W 76/32

### Release of transport tunnels

#### Definition statement

*This place covers:*

Techniques and arrangements for releasing a transport tunnel connection in the network, e.g. PDP Context deactivation.

## H04W 76/34

### Selective release of ongoing connections

#### Definition statement

*This place covers:*

Techniques and arrangements for partially releasing connections of one or a plurality of users. Also release of one or a plurality of connections involved in a multi-call.

## H04W 76/36

### for reassigning the resources associated with the released connections

#### Definition statement

*This place covers:*

Techniques and arrangements for forcibly releasing one or a plurality of the ongoing connections according to criteria like the priority of the users, priority of the information to be transmitted or activity related factors for the purpose of re-assigning the released resources. e.g. call pre-emption.

## H04W 76/38

### triggered by timers

#### Definition statement

*This place covers:*

Techniques and arrangements for releasing connections according to inactivity timers.



## H04W 76/40

### for selective distribution or broadcast

#### Definition statement

*This place covers:*

Connection set up for allowing a plurality of users or terminals to be included in a single communication. Connection set up for special broadcast or group call services, e.g. emergency broadcast, CUG, VPN, PTT, PoC (PTT on Cellular), P<sub>2C</sub> (Press to Connect).

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Broadcast or conference, e.g. multicast	<a href="#">H04L 12/18</a>
Arrangements for connecting several subscribers to a common circuit, i.e. affording conference facilities	<a href="#">H04M 3/56</a>

## H04W 76/45

### for Push-to-Talk [PTT] or Push-to-Talk over cellular [PoC] services

#### Definition statement

*This place covers:*

Communication is established among members of a predefined group by an active user with a talk request over usually a half-duplex channel.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Trunked mobile radio systems	<a href="#">H04W 84/08</a>
Arrangements for real-time multimedia communications - Push-to-X services	<a href="#">H04L 29/06442</a>

## H04W 76/50

### for emergency connections

#### Definition statement

*This place covers:*

- Connection set up requiring an urgent or hazardous situation; emergency connection set up techniques wherein an originating terminal creates an emergency communication to a central;
- Connection set up in disastrous scenarios wherein a central creates an emergency communication to a terminating terminal or a group of terminals.

## References

### Informative references

Attention is drawn to the following places, which may be of interest for search:

Alarm systems in which the location of the alarm condition is signalled to a central station, e.g. fire or police telegraphic systems, characterised by the transmission medium, using wireless transmission systems	<a href="#">G08B 25/10</a>
Cordless telephones for supporting an emergency service	<a href="#">H04M 1/72418</a>
Centralised call answering arrangements requiring operator intervention for emergency applications	<a href="#">H04M 3/5116</a>

## H04W 80/00

### Wireless network protocols or protocol adaptations to wireless operation

#### Definition statement

*This place covers:*

Generic data protocols for operation of wireless media and implemented at particular network layers.

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Communication control or communication processing characterised by a protocol	<a href="#">H04L 29/06</a>
---	----------------------------

## H04W 84/00

### Network topologies

#### Definition statement

*This place covers:*

Networks characterized by a specific organisation of network equipments, e.g. wireless access points, or linking infrastructure thereof.

#### References

##### Limiting references

*This place does not cover:*

Active relay systems	<a href="#">H04B 7/15</a>
----------------------	---------------------------

#### Special rules of classification

In this main group, local priority rules supersede first-place priority rule (FPPR) classification.

Classification symbols of this group should preferably only be allocated as "additional information".

**H04W 84/005****{Moving wireless networks}****Definition statement***This place covers:*

The wireless network(s) with their affiliated terminals or users are moving with respect to a linked overlaying wireless network(s)

**H04W 84/02****Hierarchically pre-organised networks, e.g. paging networks, cellular networks, WLAN [Wireless Local Area Network] or WLL [Wireless Local Loop]****Definition statement***This place covers:*

Networks with a pre-established organization i.e. users are normally not responsible for or network configuration or management.

**H04W 84/027****{providing paging services}****Definition statement***This place covers:*

Providing paging services to users

**H04W 84/04****Large scale networks; Deep hierarchical networks****Definition statement***This place covers:*

Networks of large scale, e.g. nationwide, using a plurality of hierarchically

interconnected selecting equipments for path finding or routing communication(s) within the network from/to a wireless user. The communication(s) can originate or terminate from/in an external network e.g. cellular systems.

**H04W 84/045****{using private Base Stations, e.g. femto Base Stations, home Node B}****Definition statement***This place covers:*

PLMS [Public Land Mobile systems] where additional access points are deployed by a private entity and operated under the control of the public network operator/administrator for providing exclusive private services and/or additional coverage or enhanced communication services to affiliated PLMS network users.

## H04W 84/047

{using dedicated repeater stations}

### Definition statement

*This place covers:*

PLMN using dedicated relay/repeater stations (not relaying terminals)

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Cell enhancers or enhancement, e.g. for tunnels, building shadow	<a href="#">H04W 16/26</a>
Self organising networks with access to wired networks	<a href="#">H04W 84/22</a>
Terminal devices adapted for relaying to or from another terminal or user	<a href="#">H04W 88/04</a>

## H04W 84/06

Airborne or Satellite Networks (space-based or airborne stations [H04B 7/185](#))

### References

#### Limiting references

*This place does not cover:*

Space-based or airborne stations	<a href="#">H04B 7/185</a>
----------------------------------	----------------------------

## H04W 84/08

Trunked mobile radio systems

### Definition statement

*This place covers:*

Dedicated systems in which, generally a half duplex communication channel is shared among a predefined group of users.

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Push-to-Talk or Push-on-Call services	<a href="#">H04W 4/10</a>
---------------------------------------	---------------------------

## H04W 84/10

### Small scale networks; Flat hierarchical networks

#### Definition statement

*This place covers:*

Networks of small, local or limited size with a wired or wireless backbone connected to access points, e.g. private, corporate networks.

## H04W 84/105

{PBS [Private Base Station] network ([H04W 84/12](#) - [H04W 84/16](#) take precedence)}

#### Definition statement

*This place covers:*

Access point owned and operated by a private entity, i.e. non-public operator for its own exclusive use. The PBS remains in, or forms on its own, a separate network or is connected to a PBX

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Small scale networks; Flat hierarchical network	<a href="#">H04W 84/12</a> - <a href="#">H04W 84/16</a>
Access point device	<a href="#">H04W 88/08</a>

#### Special rules of classification

In practice, all documents falling under coverage of [H04W 84/105](#) are all classified in [H04W 84/105](#) unless they fit at least into one of the groups [H04W 84/12](#) - [H04W 84/16](#).

## H04W 84/14

### WLL [Wireless Local Loop]; RLL [Radio Local Loop]

#### Definition statement

*This place covers:*

Networks in which subscribers with zero or limited mobility have wireless access to a public network.

Networks in which fixed subscribers have wireless access to a public network.

Radio concentration equipment for subscriber premises.

#### References

##### Informative references

Attention is drawn to the following places, which may be of interest for search:

Terminal device adapted for Wireless Local Loop operation	<a href="#">H04W 88/021</a>
---	-----------------------------

## H04W 84/16

### WPBX [Wireless Private Branch Exchange]

#### Definition statement

*This place covers:*

Networks in which wireless subscribers are connected by a Private Branch Exchange (PBX).

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Substation extension arrangements; Mobile telephones; Cordless telephones	<a href="#">H04M 1/71</a> ; <a href="#">H04M 1/72</a>
---	---

## H04W 84/18

### Self-organising networks, e.g. ad-hoc networks or sensor networks

#### Definition statement

*This place covers:*

- User-based networks without hierarchical organisation.
- Users define network(s), affiliation(s), can elect a regulating authority (master), can act as relaying device on behalf of other users.
- Affiliation of users to network(s) and user's roles in the network(s) can be dynamically changed.
- Creation and termination of user-defined networks.
- Single-hop or multi-hop networks for communication between network nodes having no predetermined connectivity and no pre-defined central control.
- Responsibilities for establishing, maintaining and controlling the network's organisation are distributed among the nodes dynamically.
- The nodes are either capable of relaying messages between pairs of nodes not having a direct communication link (multi-hop networks) or they communicate directly without having a specific pre-defined association (single hop).
- Membership in the ad-hoc network may be dynamic.
- Interrogation networks are considered self-organizing networks.
- Master-slave aspects as part of the ad-hoc network.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Arrangements for peer-to-peer networking in which application tasks are distributed across nodes	<a href="#">H04L 29/08306</a>
Arrangements for proprietary or special purpose networking environments, e.g. medical networks, sensor networks, networks in a car involving the management of devices over a network	<a href="#">H04L 29/08567</a>

## H04W 84/20

### Master-slave {selection or change} arrangements

#### Definition statement

*This place covers:*

Techniques and arrangements to (re-)elect a user as regulating authority.

This group covers only the (re-)election of a master (also "transfer" of master role).

## H04W 84/22

### with access to wired networks

#### Definition statement

*This place covers:*

Techniques and arrangements for connection of a self-organizing network to a wired network through an access point.

## H04W 88/00

### Devices specially adapted for wireless communication networks, e.g. terminals, base stations or access point devices

#### Definition statement

*This place covers:*

Devices specially adapted for wireless communication networks, e.g. terminal equipment;

Wireless access network equipment e.g. access point, access point controllers;

Switching or routing equipment in wireless backbone networks,

gateways, service support - and network management equipment.

#### References

##### Limiting references

*This place does not cover:*

Casings, cabinets or drawers for electric apparatus	<a href="#">H05K 5/00</a>
---	---------------------------

## H04W 88/005

### {Data network PoA devices}

#### Definition statement

*This place covers:*

Logical entity within wireless network or mobility management infrastructure providing access to a data network for a wireless user.

## H04W 88/02

### Terminal devices

#### Definition statement

*This place covers:*

Physical equipment acting as/on behalf of a user, thereby behaving as an endpoint of a network functionality.

#### References

##### Limiting references

*This place does not cover:*

Portable computers with a single-body enclosure integrating a flat display, e.g. personal digital assistants	<a href="#">G06F 1/1626</a>
Transceivers, i.e. devices in which transmitter and receiver form a structural unit and in which at least one part is used for functions of transmitting and receiving	<a href="#">H04B 1/38</a>
Substation equipment for telephonic communication	<a href="#">H04M 1/00</a>

## H04W 88/025

### {Selective call decoders}

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Network addressing or numbering for mobility support	<a href="#">H04W 8/26</a>
--	---------------------------

## H04W 88/04

### adapted for relaying to or from another terminal or user

#### Definition statement

*This place covers:*

Terminal device providing the additional functionality of acting as a relay e.g. on behalf of a different terminal, forwarding information to/from said terminal.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Cell enhancers or enhancement, e.g. for tunnels, building shadow	<a href="#">H04W 16/26</a>
Public land mobile networks using dedicated repeater stations	<a href="#">H04W 84/047</a>
Active relay systems	<a href="#">H04B 7/15</a>



## H04W 88/06

**adapted for operation in multiple networks {or having at least two operational modes}, e.g. multi-mode terminals**

### Definition statement

*This place covers:*

Terminal equipment able to operate using at least two different communication technologies or standards, or different versions of a standard in a single network or multiple networks, e.g. packet-switched and circuit-switched operation, analog-digital, WLAN-cellular, GSM900-GSM1800.

Terminal equipment with at least two operational modes; multiple operational modes are understood to mean significantly different operations, which would be equivalent to deeming the operations to take place in two different networks.

### References

#### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Power saving arrangements	<a href="#">H04W 52/02</a>
Hybrid wireless channel access techniques	<a href="#">H04W 74/02</a>
Connection manipulation, discontinuous transmission or reception	<a href="#">H04W 76/28</a>
Transceivers with more than one transmission mode	<a href="#">H04B 1/406</a>

## H04W 88/08

### Access point devices

#### Definition statement

*This place covers:*

Access points. Equipment providing wireless coverage and selective access to/from wireless access network.

### References

#### Limiting references

*This place does not cover:*

Transceivers, i.e. devices in which transmitter and receiver form a structural unit and in which at least one part is used for functions of transmitting and receiving	<a href="#">H04B 1/38</a>
Active relay systems	<a href="#">H04B 7/15</a>
Cordless telephones	<a href="#">H04M 1/72</a>
Casings, cabinets or drawers for electric apparatus	<a href="#">H05K 5/00</a>
Constructional details common to different types of electric apparatus	<a href="#">H05K 7/00</a>

## H04W 88/085

### {Access point devices with remote components}

#### Definition statement

*This place covers:*

Access point devices, where components of the access point device (e.g. transceiver and antenna) are located remote from the main body of the access point device, and the remote components are connected to the main body by cable, e.g. CATV or optical fibre.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Radio through fibre	<a href="#">H04B 10/2575</a>
---------------------	------------------------------

## H04W 88/10

### adapted for operation in multiple networks, e.g. multi-mode access points

#### Definition statement

*This place covers:*

Access points able to operate using at least two networks, communication technologies or standards, or different versions of a standard, e.g. packet-switched and circuit-switched operation, analog-digital, WLAN-cellular, GSM900-GSM1800.

Access points with at least two operational modes.

## H04W 88/12

### Access point controller devices

#### Definition statement

*This place covers:*

Equipments for controlling access points, e.g. Base Station Controller (BSC), Radio Network Controller (RNC), Femto base station controller (Home nodeB gateway).

## H04W 88/14

### Backbone network devices

#### Definition statement

*This place covers:*

Backbone network devices. Switching or routing equipments for a connection between a wireless user and a communication network, e.g. MSC/SGSN.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Data switching networks	<a href="#">H04L 12/00</a>
-------------------------	----------------------------

Selecting	<a href="#">H04Q</a>
-----------	----------------------

## H04W 88/16

### Gateway arrangements

#### Definition statement

*This place covers:*

Devices operating between different networks; Devices at the edge of one network interfacing to another network, e.g. between a wireless access network and a data network, or between a wireless access network and a wired network.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Inter-networking arrangements	<a href="#">H04W 92/02</a>
Arrangements for connecting between networks having differing types of switching systems, e.g. gateways	<a href="#">H04L 12/66</a>

## H04W 88/18

### Service support devices; Network management devices

#### Definition statement

*This place covers:*

- Wireless network equipments for providing services to users.
- Wireless network equipments for supporting the provision of services.
- Wireless network equipments for managing said networks.

#### References

##### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Supervisory, monitoring or testing arrangements	<a href="#">H04W 24/00</a>
---	----------------------------

## H04W 88/181

### {Transcoding devices; Rate adaptation devices}

#### Definition statement

*This place covers:*

- Network equipment for providing direct digital-to-digital data conversion from one encoding to another.
- Network equipment for adapting the rate of a communication.
- Arrangements for avoiding multiple transcoding, e.g. for tandem free operation.

## References

### Limiting references

*This place does not cover:*

Speech or audio signal analysis-synthesis techniques for redundancy reduction, e.g. in vocoders; Coding or decoding of speech or audio signals, e.g. for compression or expansion, source-filter models or psychoacoustic analysis	<a href="#">G10L 19/00</a>
--	----------------------------

## H04W 88/185

{Selective call encoders for paging networks, e.g. paging centre devices}

## References

### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Network addressing or numbering for mobility support	<a href="#">H04W 8/26</a>
--	---------------------------

## H04W 92/00

Interfaces specially adapted for wireless communication networks

### Definition statement

*This place covers:*

- Arrangements for interconnecting network components or networks.
- Special equipment or adaptations therefor.
- Control and signalling arrangements at interface.

### Special rules of classification

Classification symbols of this group should preferably only be allocated as "additional information".

## H04W 92/02

Inter-networking arrangements

### Definition statement

*This place covers:*

Arrangements for interconnecting a plurality of networks. The networks may be either physically or logically separated.

## References

### Informative references

*Attention is drawn to the following places, which may be of interest for search:*

Gateway arrangements	<a href="#">H04W 88/16</a>
----------------------	----------------------------

## H04W 92/04

### Interfaces between hierarchically different network devices

#### Definition statement

*This place covers:*

E.g. A-bis, luB, A, luCS, luPS.

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Master-slave arrangements in self-organizing networks	<a href="#">H04W 84/20</a>
---	----------------------------

## H04W 92/045

### {between access point and backbone network device}

#### Definition statement

*This place covers:*

Interface between access point and switching/routing equipment of the network e.g. S1, S1U

## H04W 92/06

### between gateways and public network devices

#### Definition statement

*This place covers:*

Interface between the wireless network and edge equipment of a public fixed telephone or data network.

## H04W 92/08

### between user and terminal device

#### Definition statement

*This place covers:*

E.g. Cu. (the Cu-interface is the interface between the "SIM card" and the terminal; the Cu-interface may be wireless).

#### References

##### *Informative references*

*Attention is drawn to the following places, which may be of interest for search:*

Mechanical arrangements for accommodating identification devices	<a href="#">H04B 1/3816</a>
--	-----------------------------

## H04W 92/10

**between terminal device and access point, i.e. wireless air interface**

### References

#### *Limiting references*

*This place does not cover:*

Radio transmission systems for communication between two or more posts, at least one of which is mobile	<a href="#">H04B 7/26</a>
---	---------------------------

## H04W 92/12

**between access points and access point controllers**

### Definition statement

*This place covers:*

Interface between controlled access points and wireless access controlling equipment, e.g. A-bis, IuB, IuR, S1MME.

## H04W 92/14

**between access point controllers and backbone network device**

### Definition statement

*This place covers:*

Interface between BSC/RNC and switching/routing equipment of the network e.g. A, IuCS, IuPS, Gb, IuH, S1MME.

## H04W 92/16

**Interfaces between hierarchically similar devices**

### Definition statement

*This place covers:*

E.g. among access points, between switching/routing equipments, between support/management equipments.

## H04W 92/20

**between access points**

### Definition statement

*This place covers:*

Interface between access points of the network e.g. X2

## **H04W 92/24**

### **between backbone network devices**

#### **Definition statement**

*This place covers:*

Interface between switching/routing equipments and support/management equipment e.g. HLR, VLR, AuC, SMS-C; B, D, F, Gf, Gr, Gc].