

CPC COOPERATIVE PATENT CLASSIFICATION

B PERFORMING OPERATIONS; TRANSPORTING

(NOTES omitted)

SHAPING

B23 MACHINE TOOLS; METAL-WORKING NOT OTHERWISE PROVIDED FOR (punching, perforating, making articles by processing sheet metal, tubes, or profiles [B21D](#); wire-working [B21F](#); making pins, needles, or nails [B21G](#); making chains [B21L](#); grinding [B24](#))
(NOTES omitted)

B23B TURNING; BORING (arrangements for copying or controlling [B23Q](#))

WARNINGS

1. The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:

| | | |
|-----------------------------|------------|---|
| B23B 3/18 | covered by | B23B 3/16 |
| B23B 3/20 | covered by | B23B 3/16 |
| B23B 3/28 | covered by | B23B 3/00 |
| B23B 5/22 | covered by | B23B 31/00 |
| B23B 5/24 | covered by | B23Q 27/00 ; B23B 35/00 |
| B23B 5/30 | covered by | B23Q 35/00 |
| B23B 5/34 | covered by | B23B 31/00 ; B23B 33/00 |
| B23B 5/42 | covered by | B23Q 35/00 |
| B23B 5/44 | covered by | B23Q 27/00 |
| B23B 7/08 | covered by | B23B 7/04 |
| B23B 7/14 | covered by | B23B 7/12 |
| B23B 7/16 | covered by | B23B 7/12 |
| B23B 9/04 | covered by | B23B 9/02 |
| B23B 9/06 | covered by | B23B 9/02 |
| B23B 9/10 | covered by | B23B 9/08 |
| B23B 9/12 | covered by | B23B 9/08 |
| B23B 15/00 | covered by | B23Q 7/00 |
| B23B 17/00 | covered by | B23Q 1/01 ; B23Q 1/03 ; B23Q 1/25 |
| B23B 19/00 | covered by | B23Q 1/70 |
| B23B 19/02 | covered by | B23Q 1/70 |
| B23B 21/00 | covered by | B23Q 1/00 |
| B23B 29/30 | covered by | B23B 29/28 |
| B23B 31/163 | covered by | B23B 31/16004 |
| B23B 31/165 | covered by | B23B 31/16045 |
| B23B 31/167 | covered by | B23B 31/16045 |
| B23B 31/169 | covered by | B23B 31/16083 |
| B23B 31/171 | covered by | B23B 31/1612 |
| B23B 31/173 | covered by | B23B 31/16158 |
| B23B 31/175 | covered by | B23B 31/16195 |
| B23B 31/177 | covered by | B23B 31/16233 |
| B23B 41/08 | covered by | F16L 41/04 |
| B23B 45/14 | covered by | B25H 1/0021 |
| B23B 45/16 | covered by | B25D 16/00 |
| B23B 47/02 | covered by | B23Q 5/00 |
| B23B 47/04 | covered by | B23Q 5/00 |
| B23B 47/06 | covered by | B23Q 5/00 |
| B23B 47/08 | covered by | B23Q 5/00 |
| B23B 47/10 | covered by | B23Q 5/00 |
| B23B 47/12 | covered by | B23Q 5/00 |
| B23B 47/14 | covered by | B23Q 5/00 |
| B23B 47/16 | covered by | B23Q 5/00 |
| B23B 47/18 | covered by | B23Q 5/00 |
| B23B 47/20 | covered by | B23Q 5/00 |
| B23B 47/22 | covered by | B23Q 5/00 |
| B23B 47/24 | covered by | B23Q 16/00 |

B23B
(continued) 2. In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

Turning

1/00 Methods for turning or working essentially requiring the use of turning-machines; Use of auxiliary equipment in connection with such methods

3/00 General-purpose turning-machines or devices, e.g. centre lathes with feed rod and lead screw; Sets of turning-machines

3/02 . Small lathes, e.g. for toolmakers (specially designed for watchmakers [G04D 3/00](#))

3/04 . Turning-machines in which the workpiece is rotated by means at a distance from the headstock

3/06 . Turning-machines or devices characterised only by the special arrangement of constructional units ([B23Q 37/00](#) takes precedence; structural features of details, see the relevant groups; such features of general applicability [B23Q](#))

3/065 . . {Arrangements for performing other machining operations, e.g. milling, drilling}

3/08 . Turning-machines characterised by the use of faceplates

3/10 . . with the faceplate horizontal, i.e. vertical boring and turning machines

3/12 . . with the faceplate vertical, i.e. face lathes

3/14 . . Mountings or drives of faceplates {(rotatable members, e.g. faceplates [B23Q 1/50](#))}

3/16 . Turret lathes for turning individually-chucked workpieces {(turrets [B23B 29/24](#))}

3/161 . . {lathe with one toolslide carrying one turret head}

3/162 . . . {Arrangements for performing other machining operations, e.g. milling, drilling}

3/164 . . {lathe with one toolslide carrying two or more turret heads}

3/165 . . . {Arrangements for performing other machining operations, e.g. milling, drilling}

3/167 . . {lathe with two or more toolslides carrying turrets}

3/168 . . . {Arrangements for performing other machining operations, e.g. milling, drilling}

3/22 . Turning-machines or devices with rotary tool heads {([B23B 5/08](#), [B23B 5/14](#) and [B23B 5/16](#) take precedence)}

3/24 . . the tools of which do not perform a radial movement; Rotary tool heads therefor

3/26 . . the tools of which perform a radial movement; Rotary tool heads thereof

3/265 . . . {Surfacing or grooving flanges}

3/30 . Turning-machines with two or more working-spindles, e.g. in fixed arrangement

3/32 . . for performing identical operations simultaneously on two or more workpieces

3/34 . Short turning-machines with one or multiple working-spindles attended from the end ([B23B 3/12](#) takes precedence)

3/36 . Associations of only turning-machines directed to a particular metal-working result (if the metal-working result is not essential [B23Q 39/00](#))

5/00 Turning-machines or devices specially adapted for particular work; Accessories specially adapted therefor

5/02 . for turning hubs or brake drums ([B23B 5/04](#) takes precedence)

5/04 . for reconditioning hubs or brake drums or axle spindles without removing same from the vehicle

5/06 . for turning valves or valve bodies {(turning conical surfaces in general [B23B 5/38](#); tools for working valve seats [B23B 51/106](#))}

5/08 . for turning axles, bars, rods, tubes, rolls, i.e. shaft-turning lathes, roll lathes; Centreless turning

5/10 . . for turning pilgrim rolls

5/12 . . for peeling bars or tubes by making use of cutting bits arranged around the workpiece (otherwise than by turning [B23D 79/12](#))

5/14 . Cutting-off lathes {([B23D 21/00](#) takes precedence) shearing [B23D](#)}

5/16 . for bevelling, chamfering, or deburring the ends of bars or tubes

5/161 . . {Devices attached to the workpiece}

5/162 . . . {with an internal clamping device}

5/163 . . . {with an external clamping device}

5/165 . . {Workpieces clamped on a bench, e.g. a vice}

5/166 . . {Devices for working electrodes}

5/167 . . {Tools for chamfering the ends of bars or tubes}

5/168 . . . {with guiding devices}

5/18 . for turning crankshafts, eccentrics, or cams, e.g. crankpin lathes

5/20 . . without removing same from the engine

5/26 . for simultaneously turning internal and external surfaces of a body

5/28 . for turning wheels or wheel sets or cranks thereon, i.e. wheel lathes

5/32 . . for reconditioning wheel sets without removing same from the vehicle; Underfloor wheel lathes for railway vehicles

5/36 . for turning specially-shaped surfaces by making use of relative movement of the tool and work produced by geometrical mechanisms, i.e. forming-lathes

5/365 . . {for toroidal surfaces}

5/38 . . for turning conical surfaces inside or outside, e.g. taper pins {(for turning valves or valve bodies [B23B 5/06](#))}

5/40 . . for turning spherical surfaces inside or outside

5/46 . . for turning helical or spiral surfaces (thread cutting [B23G](#))

5/48 . . . for cutting grooves, e.g. oil grooves of helicoidal shape

7/00 Automatic or semi-automatic turning-machines with a single working-spindle, e.g. controlled by cams; Equipment therefor; Features common to automatic and semi-automatic turning-machines with one or more working-spindles {(arrangements or accessories for enabling machine tools not specially designed only for thread cutting to be used for this purpose [B23G 3/00](#))}

7/02 . Automatic or semi-automatic machines for turning of stock

- 7/04 . . Turret machines
- 7/06 . . with sliding headstock
- 7/10 . . Accessories, e.g. guards [{\(guards B23Q 11/08 takes precedence\)}](#)
- 7/12 . Automatic or semi-automatic machines for turning of workpieces
- 9/00 Automatic or semi-automatic turning-machines with a plurality of working-spindles, e.g. automatic multiple-spindle machines with spindles arranged in a drum carrier able to be moved into predetermined positions; Equipment therefor (equipment applicable to single-spindle machines B23B 7/00)**
- 9/005 . [{Spindle carriers: constructional details, drives for the spindles, or the like}](#)
- 9/02 . Automatic or semi-automatic machines for turning of stock
- 9/08 . Automatic or semi-automatic machines for turning of workpieces
- 11/00 Automatic or semi-automatic turning-machines incorporating equipment for performing other working procedures, e.g. slotting, milling, rolling [{\(B23B 3/065 and B23B 3/16 take precedence; machines incorporating a plurality of sub-assemblies, each capable of performing a metal-working operation, the sub-assemblies being arranged to operate simultaneously at different stations B23Q 39/04\)}](#)**
- 13/00 Arrangements for automatically conveying or chucking or guiding stock**
- 13/02 . for turning-machines with a single working-spindle
- 13/021 . . [{Feeding device having intermittent movement}](#)
- 13/022 . . . [{being placed in the spindle}](#)
- 13/024 [{including two collets}](#)
- 13/025 . . [{with stock drum}](#)
- 13/027 . . [{Feeding by pistons under fluid-pressure}](#)
- 13/028 . . [{the material being fed from a reel}](#)
- 13/04 . for turning-machines with a plurality of working-spindles
- 13/06 . Arrangements for switching-off the drive of turning-machines after the stock has been completely machined
- 13/08 . Arrangements for reducing vibrations in feeding-passages or for damping noise [\(damping noise in general G10K\)](#)
- 13/10 . with magazines for stock
- 13/12 . Accessories, e.g. stops, grippers
- 13/121 . . [{Stops \(stops for equipment for precise positioning of tool or work into particular locations not otherwise provided for B23Q 16/00\)}](#)
- 13/123 . . [{Grippers, pushers or guiding tubes \(arrangements for reducing vibrations in feeding-passages or for damping noise B23B 13/08\)}](#)
- 13/125 . . . [{Feed collets \(feeding device having intermittent movement being placed in the spindle including two collets B23B 13/024; collet chucks B23B 31/20\)}](#)
- 13/126 . . [{Supports}](#)
- 13/128 . . [{Stock rest handling devices, e.g. ejectors}](#)

Components or accessories particularly for turning machines

- 23/00 Tailstocks; Centres [{\(for grinding machines B24B 41/062\)}](#)**
- 23/005 . [{the centres being adjustable}](#)
- 23/02 . Dead centres
- 23/025 . . [{the centres being adjustable}](#)
- 23/04 . Live centres
- 23/045 . . [{the centres being adjustable}](#)
- 25/00 Accessories or auxiliary equipment for turning-machines (for machine tools in general B23Q; cooling or lubricating B23Q 11/12)**
- 25/02 . Arrangements for chip-breaking in turning-machines [\(on cutting tools B23B 27/22\)](#)
- 25/04 . Safety guards specially designed for turning machines [{\(B23Q 11/08 takes precedence; in general F16P\)}](#)
- 25/06 . Measuring, gauging, or adjusting equipment on turning-machines for setting-on, feeding, controlling, or monitoring the cutting tools or work [\(measuring devices or gauges G01B\)](#)
- 25/065 . . [{Tool setting height gauges}](#)
- 27/00 Tools for turning or boring machines (for drilling machines B23B 51/00); Tools of a similar kind in general; Accessories therefor**
- NOTE**
- all subgroups except [B23B 27/12](#) relate to tools with a shank
- 27/002 . [{with vibration damping means}](#)
- 27/005 . [{Geometry of the chip-forming or the clearance planes, e.g. tool angles \[\\(B23B 27/141 and B23B 27/22 take precedence\\)}\]\(#\)}](#)
- 27/007 . [{for internal turning \(boring bars B23B 29/02, boring heads B23B 29/03; milling cutters B23C 5/00; reamers B23D 77/00\)}](#)
- 27/02 . Cutting tools with straight main part and cutting edge at an angle [\(B23B 27/04 - B23B 27/08 take precedence\)](#)
- 27/04 . Cutting-off tools [\(B23B 27/08 takes precedence \[{; toolholders for cutting-off inserts B23B 29/043}\]\(#\)\)}](#)
- 27/045 . . [{with chip-breaking arrangements}](#)
- 27/06 . Profile cutting tools, i.e. forming-tools
- 27/065 . . [{Thread-turning tools}](#)
- 27/08 . Cutting tools with blade- or disc-like main parts [{\(with disc-like main parts B23B 27/083\)}](#)
- 27/083 . . [{Cutting tools with disc-like main parts}](#)
- 27/086 . . [{with yieldable support for the cutting insert}](#)
- 27/10 . Cutting tools with special provision for cooling [{\(drills with lubricating or cooling equipment B23B 51/06; features relating to lubricating or cooling of milling cutters B23C 5/28; arrangements or devices for cooling or lubricating tools or work B23Q 11/10\)}](#)
- 27/12 . with a continuously-rotated circular cutting edge; Holders therefor
- 27/14 . Cutting tools of which the bits or tips [{or cutting inserts}](#) are of special material

- 27/141 . . {Specially shaped plate-like cutting inserts, i.e. length greater or equal to width, width greater than or equal to thickness ([with specially shaped plate-like exchangeable cutting inserts, e.g. chip-breaking groove, B23B 27/1603; with removable plate-like milling cutting inserts of special shape B23C 5/202](#))}
- 27/143 . . . {characterised by having chip-breakers}
- 27/145 . . . {characterised by having a special shape}
- 27/146 {Means to improve the adhesion between the substrate and the coating}
- 27/148 . . {Composition of the cutting inserts}
- 27/16 . . with exchangeable cutting bits {or cutting inserts}, e.g. able to be clamped
- 27/1603 . . . {with specially shaped plate-like exchangeable cutting inserts, e.g. chip-breaking groove ([B23B 27/1614 - B23B 27/1655 take precedence](#))}
- 27/1607 {characterised by having chip-breakers}
- 27/1611 {characterised by having a special shape}
- 27/1614 . . . {with plate-like cutting inserts of special shape clamped against the walls of the recess in the shank by a clamping member acting upon the wall of a hole in the insert ([B23B 27/1644 takes precedence](#))}
- 27/1618 {characterised by having chip-breakers}
- 27/1622 {characterised by having a special shape}
- 27/1625 . . . {with plate-like cutting inserts of special shape clamped by a clamping member acting almost perpendicularly on the chip-forming plane ([B23B 27/1644 takes precedence](#))}
- 27/1629 {in which the clamping member breaks the chips}
- 27/1633 {in which the chip-breaking clamping member is adjustable}
- 27/1637 {characterised by having chip-breakers}
- 27/164 {characterised by having a special shape}
- 27/1644 . . . {with plate-like cutting inserts of special shape clamped by a clamping member acting almost perpendicularly on the chip-forming plane and at the same time upon the wall of a hole in the cutting insert}
- 27/1648 {characterised by having chip-breakers}
- 27/1651 {characterised by having a special shape}
- 27/1655 . . . {Adjustable position of the plate-like cutting inserts of special form}
- 27/1659 . . . {with plate-like exchangeable cutting inserts ([B23B 27/1662 - B23B 27/1681 take precedence](#))}
- 27/1662 . . . {with plate-like cutting inserts clamped against the walls of the recess in the shank by a clamping member acting upon the wall of a hole in the cutting insert ([B23B 27/1677 takes precedence](#))}
- 27/1666 . . . {with plate-like cutting inserts clamped by a clamping member acting almost perpendicularly on chip-forming plane ([B23B 27/1677 takes precedence](#))}
- 27/167 {in which the clamping member breaks the chips}
- 27/1674 {in which the chip-breaking clamping member is adjustable}
- 27/1677 {with plate-like cutting inserts clamped by a clamping member acting almost perpendicularly on the chip-forming plane and at the same time upon the wall of a hole in the insert}
- 27/1681 {Adjustable position of the plate-like cutting inserts}
- 27/1685 {Adjustable position of the cutting inserts ([B23B 27/1655 and B23B 27/1681 take precedence](#))}
- 27/1688 {Height of the cutting tip adjustable}
- 27/1692 {Angular position of the cutting insert adjustable around an axis parallel to the chip-forming plane}
- 27/1696 {Angular position of the cutting insert adjustable around an axis generally perpendicularly to the chip-forming plane}
- 27/18 . . with cutting bits or tips {or cutting inserts} rigidly mounted, e.g. by brazing
- 27/20 . . . with diamond bits {or cutting inserts}
- 27/22 . Cutting tools with chip-breaking equipment {([B23B 27/045, B23B 27/143, B23B 27/16 take precedence; arrangements for chip-breaking B23B 25/02; for milling tools B23C 5/165](#))}
- 27/24 . Knurling tools
- 29/00 Holders for non-rotary cutting tools ([B23B 27/12 takes precedence](#)); Boring bars or boring heads; Accessories for tool holders**
- 29/02 . Boring bars
- 29/022 . . {with vibration reducing means}
- 29/025 . . {Boring toolholders fixed on the boring bar}
- 29/027 . . {Steadies for boring bars ([auxiliary devices, e.g. steadies, rests B23Q 1/76](#))}
- 29/03 . Boring heads
- 29/034 . . with tools moving radially, e.g. for making chamfers or undercuttings
- 29/03403 . . . {radially adjustable before starting manufacturing}
- 29/03407 {by means of screws and nuts}
- 29/0341 {Cartridges}
- 29/03414 {adjustment of the tool placed in the hole being possible}
- 29/03417 {by means of inclined planes}
- 29/03421 {by pivoting the tool carriers or by elastic deformation}
- 29/03425 {by means of gears and racks}
- 29/03428 {by means of an eccentric}
- 29/03432 . . . {radially adjustable during manufacturing}
- 29/03435 {by means of screws and nuts}
- 29/03439 {Boring and facing heads}
- 29/03442 {Grooving tool}
- 29/03446 {by means of inclined planes}
- 29/0345 {Boring and facing heads}
- 29/03453 {Grooving tool}
- 29/03457 {by pivoting the tool carriers or by elastic deformation}
- 29/0346 {Boring and facing heads}
- 29/03464 {Grooving tool}
- 29/03467 {by means of gears and racks}
- 29/03471 {Boring and facing heads}
- 29/03475 {Grooving tool}
- 29/03478 {by means of an eccentric}
- 29/03482 {Boring and facing heads}

| | | | |
|----------|--|--------------|--|
| 29/03485 | {Grooving tool} | 29/34 | . . Turrets equipped with triggers for releasing the cutting tools |
| 29/03489 | {Adjustment means not specified or not covered by the groups B23B 29/03435 - B23B 29/03478 } | 31/00 | Chucks {(allowing axial oscillation of percussion tool bits B25D 17/08); Expansion mandrels; Adaptations thereof for remote control (faceplates B23Q 1/50 ; devices for securing work or tools to spindles in general B23Q 3/12 ; rotary devices holding by magnetic and/or electrical force acting directly on work B23Q 3/152) |
| 29/03492 | {Boring and facing heads} | 31/001 | . {Protection against entering of chips or dust} |
| 29/03496 | {Grooving tool} | 31/003 | . {Work or tool ejection means} |
| 29/04 | . Tool holders for a single cutting tool | 31/005 | . {Cylindrical shanks of tools} |
| 29/043 | . . {with cutting-off, grooving or profile cutting tools, i.e. blade- or disc-like main cutting parts (B23B 29/14 takes precedence)} | 31/006 | . {Conical shanks of tools} |
| 29/046 | . . {with an intermediary toolholder} | 31/008 | . {with arrangements for transmitting torque} |
| 29/06 | . . Tool holders equipped with longitudinally-arranged grooves for setting the cutting tool | 31/02 | . Chucks |
| 29/08 | . . Tool holders equipped with grooves arranged crosswise to the longitudinal direction for setting the cutting tool | 31/021 | . . {Faceplates} |
| 29/10 | . . . with adjustable counterbase for the cutting tool | 31/023 | . . {for screw-threads} |
| 29/12 | . . Special arrangements on tool holders | 31/025 | . . {for gears} |
| 29/125 | . . . {Vibratory toolholders} | 31/026 | . . {the radial or angular position of the tool being adjustable (boring heads with tools moving radially B23B 29/034 ; holding tools yieldably B23B 31/08 ; with means for adjusting the chuck with respect to the working spindle B23B 31/36)} |
| 29/14 | . . . affording a yielding support of the cutting tool, e.g. by spring clamping {(cutting tools with yieldable support for the cutting insert B23B 27/086)} | 31/028 | . . {the axial positioning of the tool being adjustable (B23B 31/208 takes precedence; with means for adjusting the chuck with respect to the working spindle B23B 31/36)} |
| 29/16 | . . . for supporting the workpiece in a backrest | 31/06 | . . Features relating to the removal of tools; Accessories therefor |
| 29/18 | . . . for retracting the cutting tool | 31/07 | . . . Ejector wedges |
| 29/20 | . . . for placing same by shanks in sleeves of a turret | 31/08 | . . holding tools yieldably |
| 29/205 | {the tools being adjustable} | 31/083 | . . . {axially} |
| 29/22 | . . . for tool adjustment by means of shims or spacers | 31/086 | {having an overload clutch} |
| 29/24 | . Tool holders for a plurality of cutting tools, e.g. turrets {(indexing devices B23Q 16/00)} | 31/10 | . . characterised by the retaining or gripping devices or their immediate operating means |
| 29/242 | . . {Turrets, without description of the angular positioning device (turret lathes for turning individually-chucked workpieces B23B 3/16 ; turrets with manually operated angular positioning devices B23B 29/282 ; turrets with power operated angular positioning devices B23B 29/323)} | | NOTE |
| 29/244 | . . {Toolposts, i.e. clamping quick-change toolholders, without description of the angular positioning device (toolposts with manually operated angular positioning devices B23B 29/285 ; toolposts with power operated angular positioning devices B23B 29/326)} | 31/06 | . . . Group B23B 31/12 takes precedence over groups { B23B 31/101 , B23B 31/102 , B23B 31/103 - B23B 31/117 } |
| 29/246 | . . . {Quick-change tool holders} | 31/101 | . . . {Chucks with separately-acting jaws movable radially (B23B 31/1602 , B23B 31/16062 , B23B 31/161 , B23B 31/16137 , B23B 31/16175 , B23B 31/16212 , B23B 31/1625 and B23B 31/16283 take precedence; chucks with simultaneously-acting jaws moving radially B23B 31/16)} |
| 29/248 | . . {with individually adjustable toolholders} | 31/102 | . . . {Jaws, accessories or adjustment means (B23B 31/16008 , B23B 31/1605 , B23B 31/16087 , B23B 31/16125 , B23B 31/16162 , B23B 31/162 , B23B 31/16237 , B23B 31/1627 take precedence)} |
| 29/26 | . . Tool holders in fixed position | 31/103 | . . . Retention by pivotal elements, e.g. catches, pawls |
| 29/28 | . . Turrets manually adjustable about a vertical {or horizontal} pivot {(indexing devices B23Q 16/00)} | 31/107 | . . . Retention by laterally-acting detents, e.g. pins, screws, wedges; Retention by loose elements, e.g. balls |
| 29/282 | . . . {Turrets with manually operated angular positioning devices} | 31/1071 | {Retention by balls (balls acting as jaws B23B 31/22)} |
| 29/285 | . . . {Toolposts with manually operated angular positioning devices} | 31/1072 | {Retention by cylindrical elements (cylindrical elements acting as jaws B23B 31/22)} |
| 29/287 | . . . {Turret toolholder with manually operated angular positioning devices} | | |
| 29/32 | . . Turrets adjustable by power drive, i.e. turret heads {(indexing devices B23Q 16/00)} | | |
| 29/323 | . . . {Turrets with power operated angular positioning devices} | | |
| 29/326 | . . . {Toolposts with power operated angular positioning devices} | | |

| | | | |
|----------|---|----------|--|
| 31/1073 | {Retention by conical elements (conical elements acting as jaws B23B 31/22)} | 31/16029 | {using mechanical transmission through the spindle} |
| 31/1074 | {Retention by pins} | 31/16033 | {with a centre} |
| 31/1075 | {Retention by screws} | 31/16037 | {using mechanical transmission through the spindle (B23B 31/16029 takes precedence)} |
| 31/1076 | {with conical ends} | 31/16041 | {with locking arrangements (locking arrangements for chucks with simultaneously-acting jaws moving obliquely to the axis of the chuck in a plane containing this axis B23B 31/123)} |
| 31/1077 | {acting on a floating pin} | 31/16045 | {Jaws movement actuated by screws and nuts or oblique racks} |
| 31/1078 | {Retention by wedges} | 31/1605 | {Details of the jaws} |
| 31/11 | . . . Retention by threaded connection | 31/16054 | {Form of the jaws} |
| 31/1107 | {for conical parts} | 31/16058 | {Fixation on the master jaw} |
| 31/1115 | {using conical threads} | 31/16062 | {Individually adjustable jaws} |
| 31/1122 | {using cylindrical threads} | 31/16066 | {using fluid-pressure means to actuate the gripping means} |
| 31/113 | . . . Retention by bayonet connection | 31/1607 | {using mechanical transmission through the spindle} |
| 31/117 | . . . Retention by friction only, e.g. using springs, resilient sleeves, tapers | 31/16075 | {with a centre} |
| 31/1171 | {not used, see subgroups and B23B 31/117 } | 31/16079 | {using mechanical transmission through the spindle (B23B 31/1607 takes precedence)} |
| 31/1172 | {using fluid-pressure means to actuate the gripping means} | 31/16083 | {Jaws movement actuated by gears and racks} |
| 31/1173 | {using springs} | 31/16087 | {Details of the jaws} |
| 31/1174 | {using fluid-pressure means to actuate the gripping means} | 31/16091 | {Form of the jaws} |
| 31/1175 | {using elastomer rings or sleeves} | 31/16095 | {Fixation on the master jaw} |
| 31/1176 | {using fluid-pressure means to actuate the gripping means} | 31/161 | {Individually adjustable jaws} |
| 31/1177 | {using resilient metallic rings or sleeves} | 31/16104 | {using fluid-pressure means to actuate the gripping means} |
| 31/1178 | {using fluid-pressure means to actuate the gripping means} | 31/16108 | {using mechanical transmission through the spindle} |
| 31/1179 | {using heating and cooling} | 31/16112 | {with a centre} |
| 31/12 | . . . Chucks with simultaneously-acting jaws, whether or not also individually adjustable | 31/16116 | {using mechanical transmission through the spindle (B23B 31/16108 takes precedence)} |
| 31/1207 | {moving obliquely to the axis of the chuck in a plane containing this axis} | 31/1612 | {Jaws movement actuated by cam surface in a radial plane} |
| 31/1215 | {Details of the jaws} | 31/16125 | {Details of the jaws} |
| 31/1223 | {using fluid-pressure means in the chuck to actuate the gripping means} | 31/16129 | {Form of the jaws} |
| 31/123 | {with locking arrangements (locking arrangements for chucks with simultaneously-acting jaws moving radially actuated by one or more spiral grooves B23B 31/16041)} | 31/16133 | {Fixation on the master jaw} |
| 31/1238 | {Jaws movement actuated by a nut with conical screw-thread} | 31/16137 | {Individually adjustable jaws} |
| 31/1246 | {Jaws movement actuated by a bolt with conical screw-thread} | 31/16141 | {using fluid-pressure means to actuate the gripping means} |
| 31/1253 | {Jaws movement actuated by an axially movable member} | 31/16145 | {using mechanical transmission through the spindle} |
| 31/1261 | {pivotally movable in a radial plane} | 31/1615 | {with a centre} |
| 31/1269 | {Details of the jaws} | 31/16154 | {using mechanical transmission through the spindle (B23B 31/16145 takes precedence)} |
| 31/1276 | {using fluid-pressure means to actuate the gripping means} | 31/16158 | {Jaws movement actuated by coaxial conical surfaces} |
| 31/1284 | {with a centre} | 31/16162 | {Details of the jaws} |
| 31/1292 | {using mechanical transmission through the spindle} | 31/16166 | {Form of the jaws} |
| 31/14 | involving the use of a centrifugal force | 31/1617 | {Fixation on the master jaw} |
| 31/16 | moving radially | 31/16175 | {Individually adjustable jaws} |
| 31/16004 | {Jaws movement actuated by one or more spiral grooves} | 31/16179 | {using fluid-pressure means to actuate the gripping means} |
| 31/16008 | {Details of the jaws} | | |
| 31/16012 | {Form of the jaws} | | |
| 31/16016 | {Fixation on the master jaw} | | |
| 31/1602 | {Individually adjustable jaws} | | |
| 31/16025 | {using fluid-pressure means to actuate the gripping means} | | |

- 31/16183 {using mechanical transmission through the spindle}
- 31/16187 {with a centre}
- 31/16191 {using mechanical transmission through the spindle ([B23B 31/16183](#) takes precedence)}
- 31/16195 {Jaws movement actuated by levers moved by a coaxial control rod}
- 31/162 {Details of the jaws}
- 31/16204 {Form of the jaws}
- 31/16208 {Fixation on the master jaw}
- 31/16212 {Individually adjustable jaws}
- 31/16216 {using fluid-pressure means to actuate the gripping means}
- 31/1622 {using mechanical transmission through the spindle}
- 31/16225 {with a centre}
- 31/16229 {using mechanical transmission through the spindle ([B23B 31/1622](#) takes precedence)}
- 31/16233 {Jaws movement actuated by oblique surfaces of a coaxial control rod}
- 31/16237 {Details of the jaws}
- 31/16241 {Form of the jaws}
- 31/16245 {Fixation on the master jaw}
- 31/1625 {Individually adjustable jaws}
- 31/16254 {using fluid-pressure means to actuate the gripping means}
- 31/16258 {using mechanical transmission through the spindle}
- 31/16262 {with a centre}
- 31/16266 {using mechanical transmission through the spindle ([B23B 31/16258](#) takes precedence)}
- 31/1627 {Details of the jaws}
- 31/16275 {Form of the jaws}
- 31/16279 {Fixation on the master jaw}
- 31/16283 {Individually adjustable jaws}
- 31/16287 {using fluid-pressure means to actuate the gripping means}
- 31/16291 {with a centre}
- 31/16295 {with means preventing the ejection of the jaws}
- 31/18 pivotally movable in planes containing the axis of the chuck
- 31/185 {moving first parallel to the axis then pivotally in planes containing the axis of the chuck}
- 31/19 moving parallel to the axis of the chuck ([B23B 31/185](#) takes precedence)}
- 31/20 Longitudinally-split sleeves, e.g. collet chucks
- 31/201 {characterised by features relating primarily to remote control of the gripping means}
- 31/202 {Details of the jaws}
- 31/204 {using fluid-pressure means to actuate the gripping means}
- 31/205 {using mechanical transmission through the spindle}
- 31/207 {using mechanical transmission through the spindle ([B23B 31/205](#) takes precedence)}
- 31/208 {with a tool positioning stop (axial positioning of the tool being adjustable [B23B 31/028](#))}
- 31/22 Jaws in the form of balls {(retention by balls [B23B 31/1071](#))}
- 31/223 {Jaws in the form of cylindrical elements (retention by cylindrical elements [B23B 31/1072](#))}
- 31/226 {Jaws in the form of conical elements (retention by conical elements [B23B 31/1073](#))}
- 31/24 characterised by features relating primarily to remote control of the gripping means ([B23B 31/201](#) takes precedence)}
- 31/26 using mechanical transmission through the working-spindle ([B23B 31/16](#) and [B23B 31/40](#) take precedence)}
- 31/261 {clamping the end of the toolholder shank}
- 31/263 {by means of balls}
- 31/265 {by means of collets}
- 31/266 {using a threaded spindle}
- 31/268 {using a bayonet connection}
- 31/28 using electric or magnetic means in the chuck
- 31/30 using fluid-pressure means in the chuck ([B23B 31/10](#) and [B23B 31/40](#) take precedence)}
- 31/302 {Hydraulic equipment, e.g. pistons, valves, rotary joints}
- 31/305 {the gripping means is a deformable sleeve}
- 31/307 {Vacuum chucks}
- 31/32 with jaws carried by diaphragm
- 31/34 with means enabling the workpiece to be reversed or tilted
- 31/36 with means for adjusting the chuck with respect to the working-spindle
- 31/38 with overload clutches ([B23B 31/086](#) takes precedence)}
- 31/39 Jaw changers
- 31/40 Expansion mandrels
- 31/4006 {Gripping the work or tool by a split sleeve (collet chucks [B23B 31/20](#))}
- 31/4013 {Details of the jaws}
- 31/402 {using fluid-pressure means to actuate the gripping means}
- 31/4026 {using mechanical transmission through the spindle}
- 31/4033 {using mechanical transmission through the spindle ([B23B 31/4026](#) takes precedence)}
- 31/404 {Gripping the work or tool by jaws moving radially controlled by conical surfaces ([see also B23B 31/16158](#))}
- 31/4046 {Details of the jaws}
- 31/4053 {using fluid-pressure means to actuate the gripping means}
- 31/406 {using mechanical transmission through the spindle}
- 31/4066 {using mechanical transmission through the spindle ([B23B 31/406](#) takes precedence)}
- 31/4073 {Gripping the work or tool between planes almost perpendicular to the axis}
- 31/408 {Work or tool supported by two conical surfaces}
- 31/4086 {Work or tool gripped by a roller movable on an inclined plane}
- 31/4093 {Tube supporting means including a centerhole}

| | | | |
|--|---|--|--|
| 31/42 | . . characterised by features relating primarily to remote control of the gripping means | | |
| 33/00 | Drivers; Driving centres, Nose clutches, e.g. lathe dogs | | |
| 33/005 | . {Drivers with driving pins or the like} | | |
| Boring; Drilling (for surgical purposes A61B 17/16 ; in metal using electric current B23H 9/14 ; by laser beam B23K 26/00 ; earth or rock drilling E21B) | | | |
| 35/00 | Methods for boring or drilling, or for working essentially requiring the use of boring or drilling machines; Use of auxiliary equipment in connection with such methods | 41/00 | Boring or drilling machines or devices specially adapted for particular work {(surgical drilling machines A61B 17/16); Accessories specially adapted therefor |
| 35/005 | . {Measures for preventing splintering} | 41/003 | . {for drilling elongated pieces, e.g. beams} |
| 37/00 | Boring by making use of ultrasonic energy (essentially using abrasive material B24B, e.g. B24B 1/04) | 41/006 | . . {the machining device being moved along a fixed workpiece} |
| 39/00 | General-purpose boring or drilling machines or devices; Sets of boring and/or drilling machines | 41/02 | . for boring deep holes; Trepanning, e.g. of gun or rifle barrels |
| 39/003 | . {Drilling machine situated underneath the workpiece} | 41/04 | . for boring polygonal or other non-circular holes |
| 39/006 | . {Portal drilling machines} | 41/06 | . for boring conical holes |
| 39/02 | . Boring machines; Combined horizontal boring and milling machines | 41/10 | . for boring holes in steam boilers |
| 39/04 | . Co-ordinate boring or drilling machines; Machines for making holes without previous marking | 41/12 | . for forming working surfaces of cylinders, of bearings, e.g. in heads of driving rods, or of other engine parts |
| 39/06 | . . Equipment for positioning work | 41/14 | . for very small holes |
| 39/08 | . . Devices for programme control | 41/16 | . for boring holes with high-quality surface |
| 39/10 | . characterised by the drive, e.g. by fluid-pressure drive pneumatic power drive | 43/00 | Boring or drilling devices able to be attached to a machine tool, whether or not replacing an operative portion of the machine tool (if specially adapted for particular work B23B 41/00) |
| 39/12 | . Radial drilling machines | 43/02 | . to the tailstock of a lathe |
| 39/14 | . with special provision to enable the machine or the drilling or boring head to be moved into any desired position, e.g. with respect to immovable work | 45/00 | Hand-held or like portable drilling machines, e.g. drill guns; Equipment therefor (details or components, e.g. casings, bodies, of portable power-driven tools not particularly related to the operation performed B25F 5/00) |
| 39/16 | . Drilling machines with a plurality of working-spindles; Drilling automatons | 45/001 | . {Housing of the drill, e.g. handgrip} |
| 39/161 | . . {with parallel work spindles} | 45/003 | . {Attachments} |
| 39/162 | . . . {having gear transmissions} | 45/005 | . . {Flexible shafts} |
| 39/163 | . . . {having crank pin transmissions} | 45/006 | . {Keys for operating the chucks} |
| 39/165 | . . . {having universal joint transmissions} | 45/008 | . {Gear boxes, clutches, bearings, feeding mechanisms or like equipment} |
| 39/166 | . . . {having flexible shaft transmissions} | 45/02 | . driven by electric power |
| 39/167 | . . . {having belt and chain transmissions} | 45/04 | . driven by fluid-pressure or pneumatic power |
| 39/168 | . . {with the work spindles being oblique to each other} | 45/042 | . . {Turbine motors} |
| 39/18 | . . Setting work or tool carrier along a straight index line | 45/044 | . . {Rotary vane type motors} |
| 39/20 | . . Setting work or tool carrier along a circular index line; Turret head drilling machines | 45/046 | . . . {Internal combustion piston engines} |
| 39/205 | . . . {Turret head drilling machines} | 45/048 | . driven by man-power |
| 39/22 | . . with working-spindles in opposite headstocks | 45/08 | . . for drilling rails or profiled stock |
| 39/24 | . . designed for programme control | 45/10 | . . by using a fiddle bow or a belt |
| 39/26 | . in which the working position of tool or work is controlled by copying discrete points of a pattern (features of copying devices B23Q 35/02) | 45/12 | . . by using a ratchet brace |
| 39/28 | . Associations of only boring or drilling machines directed to a particular metal-working result (if not producing a particular metal-working result B23Q 39/00) | Components or accessories for boring or drilling machines | |
| | | 47/00 | Constructional features of components specially designed for boring or drilling machines; Accessories therefor (working-spindles, bearing sleeves therefor B23Q 1/70; for machine tools in general B23Q) |
| | | 47/26 | . Lifiable or lowerable drill heads or headstocks; Balancing arrangements therefor {(weight and flexion compensation B23Q 11/001)} |
| | | 47/28 | . Drill jigs for workpieces (equipment for setting or guiding the drill B23B 49/00) |
| | | 47/281 | . . {Jigs for drilling cylindrical parts} |
| | | 47/282 | . . {Jigs for drilling spherical parts} |
| | | 47/284 | . . {Jigs for drilling rivets or bolts} |
| | | 47/285 | . . {Jigs for drilling ski bindings} |
| | | 47/287 | . . {Jigs for drilling plate-like workpieces (templates for marking the position of fittings on wings or frames E05D 11/0009)} |

| | | | |
|--------------|--|----------------|--|
| 47/288 | . . . {involving dowelling} | 51/046 | {with exchangeable cutting inserts, e.g. able to be clamped} |
| 47/30 | . Additional gear with one or more working-spindles attachable to the main working-spindle and mounting the additional gear {(multi-spindle drilling machines B23B 39/16)} | 51/0466 | . . . {with exchangeable cutting inserts, e.g. able to be clamped} |
| 47/32 | . Arrangements for preventing the running-out of drills or fracture of drills when getting through | 51/0473 | . . . {details about the connection between the driven shaft and the tubular cutting part} |
| 47/34 | . Arrangements for removing chips out of the holes made; Chip- breaking arrangements attached to the tool {(chip-breaking in turning machines B23B 25/02 ; in turning tools B23B 27/22)} | 51/048 | . . {with exchangeable cutting inserts, e.g. able to be clamped (B23B 51/0493 takes precedence)} |
| 49/00 | Measuring or gauging equipment on boring machines for positioning or guiding the drill; Devices for indicating failure of drills during boring; Centering devices for holes to be bored (marking-out equipment B25H 7/00; measuring devices, gauges G01B) | 51/0486 | . . {with lubricating or cooling equipment (B23B 51/042 takes precedence)} |
| 49/001 | . {Devices for detecting or indicating failure of drills} | 51/0493 | . . . {with exchangeable cutting inserts, e.g. able to be clamped} |
| 49/003 | . {Stops attached to drilling tools, tool holders or drilling machines (B23B 51/104 takes precedence)} | 51/05 | . . for cutting discs from sheet |
| 49/005 | . . {Attached to the drill} | 51/06 | . Drills with lubricating or cooling equipment {(B23B 51/042 and B23B 51/0486 take precedence)} |
| 49/006 | . . {Attached to drilling machines} | 51/08 | . Drills combined with tool parts or tools for performing additional working {(B23G 5/20 takes precedence)} |
| 49/008 | . . . {Attached to the nose of the drilling machines} | 51/10 | . Bits for countersinking |
| 49/02 | . Boring templates or bushings | 51/101 | . . {Deburring tools (B23B 51/103 takes precedence)} |
| 49/023 | . . {Bushings and their connection to the template} | 51/102 | . . {Back spot-facing or chamfering} |
| 49/026 | . . {Boring bushing carriers attached to the workpiece by glue, magnets, suction devices or the like} | 51/103 | . . {Deburring or chamfering tools for the ends of tubes or rods} |
| 49/04 | . Devices for boring or drilling centre holes in workpieces | 51/104 | . . {with stops} |
| 49/06 | . Devices for drilling holes in brake bands or brake linings | 51/105 | . . {Deburring or countersinking of radial holes} |
| 51/00 | Tools for drilling machines {(for drilling wood B27G 15/00; for drilling stone or stone-like materials, e.g. brick, concrete, glass B28D 1/00; drill bits for earth or rock drilling E21B 10/00)} | 51/106 | . . {with a toolholder moving along a direction oblique to the axis} |
| 51/0009 | . {Spade drills} | 51/107 | . . {having a pilot} |
| 51/0018 | . {Drills for enlarging a hole} | 51/108 | . . {having a centering twist drill} |
| 51/0027 | . . {by tool swivelling} | 51/12 | . Adapters for drills or chucks; Tapered sleeves |
| 51/0036 | . . {by a tool-carrying eccentric} | 51/123 | . . {Conical reduction sleeves} |
| 51/0045 | . . {by expanding or tilting the toolhead} | 51/126 | . . {Tool elongating devices} |
| 51/0054 | . {Drill guiding devices} | 51/14 | . . Adapters for broken drills |
| 51/0063 | . {Centerdrills} | | |
| 51/0072 | . {Drills for making non-circular holes} | | |
| 51/0081 | . {Conical drills} | | |
| 51/009 | . {Stepped drills} | | |
| 51/02 | . Twist drills | | |
| 51/04 | . Drills for trepanning | | |
| 51/0406 | . . {Drills with a tubular body (saw cylinders, e.g. having their cutting rim equipped with abrasive particles, for working stone or glass B28D 1/041)} | | |
| 51/0413 | . . . {with core-cutting-off devices} | | |
| 51/042 | . . . {with lubricating or cooling equipment} | | |
| 51/0426 | . . . {with centering devices} | | |
| 51/0433 | {with exchangeable cutting inserts, e.g. able to be clamped} | | |
| 51/044 | . . . {with core holding devices} | | |
| 51/0446 | {with exchangeable cutting inserts, e.g. able to be clamped} | | |
| 51/0453 | . . . {with ejecting devices} | | |
| | | 2200/00 | Details of cutting inserts |
| | | 2200/04 | . Overall shape |
| | | 2200/0404 | . . Hexagonal |
| | | 2200/0409 | . . . irregular |
| | | 2200/0414 | . . . rounded |
| | | 2200/0419 | . . . trigonal |
| | | 2200/0423 | . . Irregular |
| | | 2200/0428 | . . Lozenge |
| | | 2200/0433 | . . . rounded |
| | | 2200/0438 | . . Octagonal |
| | | 2200/0442 | . . . rounded |
| | | 2200/0447 | . . Parallelogram |
| | | 2200/0452 | . . . rounded |
| | | 2200/0457 | . . Pentagonal |
| | | 2200/0461 | . . Round |
| | | 2200/0466 | . . Segment or sector of a circle |
| | | 2200/0471 | . . Square |
| | | 2200/0476 | . . . rounded |
| | | 2200/048 | . . Star form |
| | | 2200/0485 | . . Trapezium |
| | | 2200/049 | . . Triangular |
| | | 2200/0495 | . . . rounded |
| | | 2200/08 | . Rake or top surfaces |
| | | 2200/081 | . . with projections (chip breaking projections in general B23B 2200/321) |

- 2200/082 . . with elevated clamping surface
- 2200/083 . . curved
- 2200/085 . . discontinuous
- 2200/086 . . with one or more grooves
- 2200/087 . . . for chip breaking ([chip breaking depressions in general B23B 2200/323](#), [multiple chip breaking grooves B23B 2200/325](#))
- 2200/088 . . . for clamping
- 2200/12 . Side or flank surfaces
- 2200/121 . . with projections
- 2200/123 . . curved
- 2200/125 . . discontinuous
- 2200/126 . . . stepped
- 2200/128 . . with one or more grooves
- 2200/16 . Supporting or bottom surfaces
- 2200/161 . . with projections
- 2200/162 . . curved
- 2200/163 . . discontinuous
- 2200/164 . . ground
- 2200/165 . . with one or more grooves
- 2200/166 . . polygonal
- 2200/167 . . with serrations
- 2200/168 . . star form
- 2200/20 . Top or side views of the cutting edge
- 2200/201 . . Details of the nose radius and immediately surrounding area
- 2200/202 . . with curved cutting edge
- 2200/204 . . with discontinuous cutting edge
- 2200/205 . . with cutting edge having a wave form
- 2200/207 . . for cutting a particular form corresponding to the form of the cutting edge
- 2200/208 . . with wiper, i.e. an auxiliary cutting edge to improve surface finish
- 2200/24 . Cross section of the cutting edge
- 2200/242 . . bevelled or chamfered
- 2200/245 . . rounded
- 2200/247 . . sharp
- 2200/28 . Angles
- 2200/283 . . Negative cutting angles
- 2200/286 . . Positive cutting angles
- 2200/32 . Chip breaking or chip evacuation
- 2200/321 . . by chip breaking projections ([with projections on rake surface B23B 2200/081](#))
- 2200/323 . . by chip breaking depressions ([with one or more grooves on top surface for chip breaking B23B 2200/087](#), [with multiple chip breaking grooves B23B 2200/325](#))
- 2200/325 . . by multiple chip-breaking grooves ([with one or more grooves on top surface for chip breaking B23B 2200/087](#), [with chip breaking depression B23B 2200/323](#))
- 2200/326 . . by chip breaking-plates
- 2200/328 . . Details of chip evacuation
- 2200/36 . Other features of cutting inserts not covered by [B23B 2200/04](#) - [B23B 2200/32](#)
- 2200/3609 . . Chamfers
- 2200/3618 . . Fixation holes
- 2200/3627 . . Indexing ([with grooves on bottom surfaces B23C 2200/165](#), [with polygonal bottom surfaces B23B 2200/166](#), [with star form bottom surfaces B23C 2200/167](#))
- 2200/3636 . . . with cutting geometries differing according to the indexed position
- 2200/3645 . . Lands, i.e. the outer peripheral section of the rake face
- 2200/3654 . . . being variable ([negative lands of variable width B23B 2200/3672](#))
- 2200/3663 . . . having negative cutting angles ([with bevelled cutting edge B23C 2200/243](#))
- 2200/3672 being variable ([lands with variable width B23B 2200/3654](#))
- 2200/3681 . . Split inserts, i.e. comprising two or more sections roughly equal in size and having similar or dissimilar cutting geometries
- 2200/369 . . Mounted tangentially, i.e. where the rake face is not the face with the largest area
- 2205/00** **Fixation of cutting inserts in holders**
- 2205/02 . Fixation using an elastically deformable clamping member
- 2205/04 . Fixation screws, bolts or pins of particular form
- 2205/045 . . orientated obliquely to the hole in the insert or to the seating surface
- 2205/08 . using an eccentric
- 2205/10 . using two or more fixation screws
- 2205/12 . Seats for cutting inserts
- 2205/125 . . One or more walls of the seat being elastically deformable
- 2205/16 . Shims
- 2205/18 . Systems for indexing the cutting insert automatically
- 2205/21 . Systems for changing the cutting insert automatically
- 2205/215 . . using a magazine
- 2210/00** **Details of turning tools**
- 2210/02 . Tool holders having multiple cutting inserts
- 2210/022 . . Grooving tools
- 2210/025 . . . Grooving inserts arranged on a turret
- 2210/027 . . . Means for adjusting the grooving inserts
- 2210/04 . Self-sharpening tools
- 2210/06 . Chip breakers
- 2210/08 . Tools comprising intermediary toolholders
- 2210/12 . Tools comprising weakened spot on the tool at a preferred breakage location ([break points on shanks of tools B23B 2231/0212](#))
- 2215/00** **Details of workpieces**
- 2215/04 . Aircraft components
- 2215/08 . Automobile wheels
- 2215/10 . Ammunition cartridge cases
- 2215/12 . Bearing races
- 2215/16 . Camshafts
- 2215/20 . Crankshafts
- 2215/24 . Components of internal combustion engines ([B23B 2215/16](#) and [B23B 2215/20](#) take precedence)
- 2215/242 . . Cylinder liners
- 2215/245 . . Pistons
- 2215/247 . . Piston rings
- 2215/28 . Firearms, guns
- 2215/32 . Railway tracks
- 2215/36 . Railway wheels
- 2215/40 . Spectacles
- 2215/56 . Springs
- 2215/60 . Steel wool
- 2215/64 . Thin walled components
- 2215/68 . Threaded components

B23B

- 2215/72 . Tubes, pipes
- 2215/76 . Components for turbines
- 2215/81 . . Turbine blades
- 2220/00 Details of turning, boring or drilling processes**
- 2220/04 . Chamferring ([B23B 2220/28](#) takes precedence)
- 2220/08 . Deburring
- 2220/12 . Grooving
- 2220/123 . . Producing internal grooves
- 2220/126 . . Producing ring grooves
- 2220/24 . Finishing ([roughing and finishing B23B 2220/445](#))
- 2220/28 . Parting off and chamferring simultaneously
- 2220/32 . Drilling holes from both sides
- 2220/36 . Turning, boring or drilling at high speeds
- 2220/40 . Peeling
- 2220/44 . Roughing
- 2220/445 . . and finishing
- 2220/52 . Whirling
- 2222/00 Materials of tools or workpieces composed of metals, alloys or metal matrices**
- 2222/04 . Aluminium
- 2222/12 . Brass
- 2222/14 . Cast iron ([iron B23B 2222/44](#))
- 2222/16 . Cermet
- 2222/21 . Copper
- 2222/24 . Gold
- 2222/28 . Details of hard metal, i.e. cemented carbide
- 2222/32 . Details of high speed steel ([stainless steel B23B 2222/80](#), [steel B23B 2222/84](#))
- 2222/36 . Nickel chrome alloys, e.g. Inconel®
- 2222/41 . Nickel steel alloys, e.g. invar®
- 2222/44 . Iron ([cast iron B23B 2222/14](#))
- 2222/48 . Lead
- 2222/52 . Magnesium
- 2222/56 . Non-specified metals
- 2222/61 . Metal matrices with non-metallic particles or fibres
- 2222/64 . Nickel
- 2222/68 . Palladium
- 2222/72 . Platinum
- 2222/76 . Silver
- 2222/80 . Stainless steel ([high speed steel B23B 2222/32](#), [steel B23B 2222/84](#))
- 2222/84 . Steel ([high speed steel B23B 2222/32](#), [stainless steel B23B 2222/80](#))
- 2222/88 . Titanium
- 2222/92 . Tungsten
- 2222/98 . Zinc
- 2224/00 Materials of tools or workpieces composed of a compound including a metal**
- 2224/04 . Aluminium oxide
- 2224/08 . Aluminium nitride
- 2224/12 . Chromium carbide
- 2224/16 . Molybdenum disulphide
- 2224/20 . Tantalum carbide
- 2224/24 . Titanium aluminium nitride
- 2224/28 . Titanium carbide
- 2224/32 . Titanium carbide nitride (TiCN)
- 2224/36 . Titanium nitride
- 2224/40 . Tungsten disulphide
- 2226/00 Materials of tools or workpieces not comprising a metal**
- 2226/04 . Aromatic polyamides
- 2226/09 . Asbestos
- 2226/12 . Boron nitride
- 2226/125 . . cubic [CBN]
- 2226/15 . Cardboard
- 2226/18 . Ceramic
- 2226/27 . Composites
- 2226/275 . . Carbon fibre reinforced carbon composites
- 2226/31 . Diamond
- 2226/315 . . polycrystalline [PCD]
- 2226/33 . Elastomers, e.g. rubber
- 2226/36 . Epoxy
- 2226/39 . Foam
- 2226/42 . Gem, i.e. precious stone
- 2226/45 . Glass ([turning glass B28D 1/16](#), [drilling glass B28D 1/14](#))
- 2226/48 . Ice
- 2226/54 . Paper
- 2226/57 . Plasterboard, i.e. sheetrock
- 2226/61 . Plastics not otherwise provided for, e.g. nylon
- 2226/63 . Polyurethane
- 2226/66 . Polytetrafluoroethylene
- 2226/69 . Sapphire
- 2226/72 . Silicon carbide
- 2226/75 . Stone, rock or concrete ([working of stone B28D](#))
- 2226/78 . Textile
- 2228/00 Properties of materials of tools or workpieces, materials of tools or workpieces applied in a specific manner**
- 2228/04 . applied by chemical vapour deposition [CVD]
- 2228/08 . applied by physical vapour deposition [PVD]
- 2228/10 . Coatings
- 2228/105 . . with specified thickness
- 2228/12 . Abrasive
- 2228/16 . Shape memory alloys
- 2228/21 . Cast, i.e. In the form of a casting
- 2228/24 . Hard, i.e. after being hardened
- 2228/28 . Soft
- 2228/32 . Explosive
- 2228/36 . Multi-layered
- 2228/41 . Highly conductive
- 2228/44 . Materials having grain size less than 1 micrometre, e.g. nanocrystalline
- 2228/48 . Self-luminous, i.e. light-emitting, e.g. fluorescent
- 2228/52 . Solid lubricants
- 2228/56 . Two phase materials
- 2228/61 . Materials comprising whiskers
- 2229/00 Details of boring bars or boring heads**
- 2229/04 . Guiding pads
- 2229/08 . Cutting edges of different lengths or at different axial positions
- 2229/12 . Cutting inserts located on different radii
- 2229/16 . Boring, facing or grooving heads with integral electric motor
- 2231/00 Details of chucks, toolholder shanks or tool shanks**
- 2231/02 . Features of shanks of tools not relating to the operation performed by the tool
- 2231/0204 . . Connection of shanks to working elements of tools
- 2231/0208 . . Bores

B23B

- 2231/0212 . . Shanks of tools having a reduced cross section at a position where breakage of the tool is preferred ([break points on tools not in shank area B23B 2210/12](#), [shanks with reduced cross sections in general B23B 2231/0252](#))
- 2231/0216 . . Overall cross sectional shape of the shank ([not used](#))
- 2231/022 . . . Triangular
- 2231/0224 Rounded triangular
- 2231/0228 . . . Square
- 2231/0232 . . . Hexagonal
- 2231/0236 . . . Octagonal
- 2231/024 . . . Star form
- 2231/0244 . . . Special forms not otherwise provided for
- 2231/0248 . . Codes for diameters
- 2231/0252 . . Shanks having a section of reduced diameter ([to provide a preferred breaking point B23B 2231/0212](#))
- 2231/0256 . . Flats
- 2231/026 . . Grooves ([keyways B23B 2231/0276](#))
- 2231/0264 . . . Axial grooves
- 2231/0268 . . . Radial grooves
- 2231/0272 . . . Grooves on conical clamping surfaces
- 2231/0276 . . Keyways ([axial grooves B23B 2231/0264](#))
- 2231/028 . . Lugs
- 2231/0284 . . Notches
- 2231/0288 . . Conical shanks of tools in which the cone is not formed as one continuous surface
- 2231/0292 . . Flanges of conical shanks
- 2231/0296 . . Ends of conical shanks, e.g. pull studs, tangs
- 2231/04 . . Adapters
- 2231/06 . . Chucks for handtools having means for opening and closing the jaws using the driving motor of the handtool
- 2231/08 . . Chucks for shanks of tools having means for reducing the bending of the retained shanks
- 2231/10 . . Chucks having data storage chips
- 2231/12 . . Chucks having means to amplify the force produced by the actuating means to increase the clamping force
- 2231/14 . . Chucks with clamping force limitation means
- 2231/20 . . Collet chucks
- 2231/2002 . . Collets having blade-like jaws
- 2231/2005 . . Keys preventing rotation
- 2231/2008 . . Bores holding the collet having a slightly conical profile
- 2231/201 . . Operating surfaces of collets, i.e. the surface of the collet acted on by the operating means
- 2231/2013 . . . Non-cylindrical ([polygonal B23B 2231/2016](#))
- 2231/2016 . . . Polygonal
- 2231/2018 . . . with a saw-tooth profile
- 2231/2021 . . . comprising two different cones
- 2231/2024 . . Non-circular surfaces of collets for the transmission of torque
- 2231/2027 . . Gripping surfaces, i.e. the surface contacting the tool or workpiece
- 2231/2029 . . . Conical
- 2231/2032 . . . with non-cylindrical cross section
- 2231/2035 . . . Polygonal
- 2231/2037 . . . Roughened
- 2231/204 . . . with saw tooth profiles
- 2231/2043 . . . Discontinuous, interrupted or split
- 2231/2045 . . . comprising two or more diameters, e.g. stepped
- 2231/2048 . . Collets comprising inserts
- 2231/2051 . . . brazed in position
- 2231/2054 . . . glued in position
- 2231/2056 . . . where the insert forms part of the surface gripping the workpiece or tool
- 2231/2059 . . . Hard inserts
- 2231/2062 . . . Inserts mechanically clamped in the collet
- 2231/2064 . . . Inserts in the form of a roll
- 2231/2067 . . . Soft inserts
- 2231/207 . . . Inserts welded in position
- 2231/2072 . . Jaws of collets
- 2231/2075 . . . of special form
- 2231/2078 . . Jaw carriers, i.e. components retaining the collet itself
- 2231/2081 . . Keys, spanners or wrenches to operate the collet chuck
- 2231/2083 . . Collets comprising screw threads
- 2231/2086 . . Collets in which the jaws are formed as separate elements, i.e. not joined together
- 2231/2089 . . Slits of collets
- 2231/2091 . . . extending from both axial ends of the collet
- 2231/2094 . . . Helical
- 2231/2097 . . . having a special form not otherwise provided for
- 2231/22 . . Compensating chucks, i.e. with means for the compensation of irregularities of form or position
- 2231/24 . . Cooling or lubrication means
- 2231/26 . . Detection of clamping ([in general B23Q 17/006](#))
- 2231/28 . . Dust covers ([nose pieces in chucks B23B 2231/44](#), [dust covers for turning, boring or drilling in general B23B 2260/058](#))
- 2231/30 . . Chucks with four jaws
- 2231/32 . . Guideways for jaws
- 2231/34 . . Jaws
- 2231/345 . . Different jaws
- 2231/36 . . Sealed joints
- 2231/365 . . using O-rings
- 2231/38 . . Keyless chucks for hand tools
- 2231/40 . . Chucks having a pivotal retention element in the form of a laterally acting cam
- 2231/42 . . Chucks operated by a motor which is movable to engage with, or disengage from, the chuck operating means
- 2231/44 . . Nose pieces ([dust covers in chucks B23B 2231/28](#), [dust covers for turning, boring or drilling in general B23B 2260/058](#))
- 2231/46 . . Pins
- 2231/48 . . Polygonal cross sections
- 2231/50 . . Devices to counteract clamping forces exerted within the spindle in order to release the tool or workpiece
- 2231/52 . . Chucks with means to loosely retain the tool or workpiece in the unclamped position
- 2231/54 . . Chucks for taps
- 2233/00 Details of centres or drivers**
- 2233/04 . . Means to allow the facing of the axial end of the workpiece near the axis of rotation
- 2233/08 . . Centres or drivers comprising a ball
- 2233/12 . . Centres or drivers with a special arrangement of bearings or with special bearings
- 2233/16 . . Centres or drivers comprising chucks
- 2233/20 . . Centres or drivers with convex surfaces

B23B

- 2233/24 . Centres or drivers with inserts
- 2233/28 . Centres or drivers supporting the workpiece at three points around the circumference
- 2233/32 . Yieldable centres
- 2235/00 Turning of brake discs, drums or hubs**
- 2235/04 . Machining of brake discs
- 2235/045 . . Simultaneous machining of both sides of the brake disc
- 2235/12 . Machining of brake drums
- 2235/16 . Machining of hubs
- 2235/21 . Compensation of run out
- 2240/00 Details of connections of tools or workpieces**
- 2240/04 . Bayonet connections
- 2240/08 . Brazed connections
- 2240/11 . Soldered connections
- 2240/16 . Welded connections
- 2240/21 . Glued connections
- 2240/24 . Connections using hollow screws, e.g. for the transmission of coolant
- 2240/28 . Shrink-fitted connections, i.e. using heating and cooling to produce interference fits ([shrink fits chucks B23B 31/1179](#))
- 2240/32 . Press fits
- 2240/36 . Connections using a tongue and a hollow of corresponding prismatic form
- 2247/00 Details of drilling jigs**
- 2247/02 . Jigs for drilling spectacles ([machines for drilling spectacle lenses B28D 1/143](#))
- 2247/04 . Jigs using one or more holes as datums for drilling further holes
- 2247/06 . Jigs for drilling holes for lock sets for doors
- 2247/08 . Jigs for drilling overlapping or interfering holes
- 2247/10 . Jigs for drilling inclined holes
- 2247/12 . Drilling jigs with means to affix the jig to the workpiece
- 2247/14 . Jigs for drilling flanges
- 2247/16 . Jigs for drilling stairs and associated components, e.g. banisters or handrails
- 2247/18 . Jigs comprising V-blocks
- 2247/20 . Jigs for drilling holes for lock wires in bolts or nuts
- 2250/00 Compensating adverse effects during turning, boring or drilling**
- 2250/04 . Balancing rotating components ([vibration damping B23B 2250/16](#))
- 2250/08 . Compensation of centrifugal force ([use of centrifugal force B23B 2270/04](#))
- 2250/12 . Cooling and lubrication
- 2250/125 . . Improving heat transfer away from the working area of the tool by conduction
- 2250/16 . Damping of vibrations ([balancing rotating components B23B 2250/04](#))
- 2251/00 Details of tools for drilling machines**
- 2251/02 . Connections between shanks and removable cutting heads
- 2251/04 . Angles, e.g. cutting angles
- 2251/043 . . Helix angles
- 2251/046 . . . Variable
- 2251/08 . Side or plan views of cutting edges
- 2251/082 . . Curved cutting edges
- 2251/085 . . Discontinuous or interrupted cutting edges
- 2251/087 . . Cutting edges with a wave form
- 2251/12 . Cross sectional views of the cutting edges
- 2251/122 . . Bevelled cutting edges
- 2251/125 . . Rounded cutting edges
- 2251/127 . . Sharp cutting edges
- 2251/14 . Configuration of the cutting part, i.e. the main cutting edges
- 2251/18 . Configuration of the drill point
- 2251/20 . Number of cutting edges
- 2251/201 . . Single cutting edge
- 2251/202 . . Three cutting edges
- 2251/204 . . Four cutting edges
- 2251/205 . . Five cutting edges
- 2251/207 . . Six cutting edges
- 2251/208 . . Eight cutting edges
- 2251/24 . Overall form of drilling tools
- 2251/241 . . Cross sections of the diameter of the drill
- 2251/242 . . . increasing in a direction towards the shank from the tool tip
- 2251/244 . . . decreasing in a direction towards the shank from the tool tip
- 2251/245 . . . Variable cross sections
- 2251/247 . . Drilling tools having a working portion at both ends of the shank
- 2251/248 . . Drills in which the outer surface is of special form
- 2251/28 . Arrangement of teeth
- 2251/282 . . Unequal spacing of cutting edges in the circumferential direction
- 2251/285 . . Cutting teeth arranged at different heights
- 2251/287 . . Cutting edges having different lengths
- 2251/40 . Flutes, i.e. chip conveying grooves
- 2251/402 . . with increasing depth in a direction towards the shank from the tool tip
- 2251/404 . . with decreasing depth in a direction towards the shank from the tool tip
- 2251/406 . . of special form not otherwise provided for
- 2251/408 . . Spiral grooves
- 2251/42 . Types of drill
- 2251/422 . . Deep hole drills, e.g. ejector drills
- 2251/424 . . . Gun drills
- 2251/426 . . Microdrills
- 2251/428 . . Drills for cutting plugs of material
- 2251/44 . Margins, i.e. the area of the circumference following the axial cutting edge in the direction of rotation
- 2251/443 . . Double margin drills
- 2251/446 . . Drills with variable margins
- 2251/46 . Drills having a centre free from cutting edges or with recessed cutting edges
- 2251/48 . Chip breakers
- 2251/50 . Drilling tools comprising cutting inserts
- 2251/505 . . set at different heights
- 2251/52 . Depth indicators
- 2251/54 . Drilling tools having provision for drilling different diameters
- 2251/56 . Guiding pads
- 2251/58 . Guiding rolls
- 2251/60 . Drills with pilots
- 2251/603 . . Detachable pilots, e.g. in the form of a drill
- 2251/606 . . . being a twist drill

B23B

- 2251/62 . Drilling tools having means to reinforce the shank, e.g. drills having small shanks being gripped by devices having a larger shank
- 2251/64 . Drills operating in the reverse direction, i.e. in the unscrewing direction of a right-hand thread
- 2251/66 . Drills with provision to be used as a screwdriver
- 2251/68 . Drills with provision for suction ([use of suction in turning, boring or drilling in general B23B 2270/62](#))
- 2251/70 . Drills with vibration suppressing means
- 2260/00 Details of constructional elements**
- 2260/002 . Accumulators
- 2260/004 . Adjustable elements
- 2260/0045 . . Two elements adjustable relative to each other in three mutually perpendicular directions
- 2260/008 . Bearings
- 2260/0082 . . Sliding contact bearings
- 2260/0085 . . Needle roller bearings
- 2260/0087 . . Preloading of bearings
- 2260/016 . Bolts
- 2260/018 . Brushes
- 2260/02 . Cams
- 2260/022 . Balls
- 2260/024 . Batteries
- 2260/026 . Bushings, e.g. adapter sleeves
- 2260/028 . Chains
- 2260/03 . Clamps
- 2260/032 . Diaphragms
- 2260/034 . Drawbars
- 2260/036 . Cables
- 2260/038 . Cartridges
- 2260/04 . Centre drills of known configuration, e.g. the provision of a centre drill in centres or chucks
- 2260/042 . Collets of known configuration, i.e. devices using a collet
- 2260/044 . Clutches
- 2260/0445 . . Overload clutches
- 2260/048 . Devices to regulate the depth of cut
- 2260/0482 . . Depth controls, e.g. depth stops ([stops B23B 2260/12](#))
- 2260/0485 . . Depth gauges
- 2260/0487 . . Depth indicators ([indication scales B23B 2260/088](#))
- 2260/056 . Differential screw threads
- 2260/058 . Dust covers ([dust covers in chucks B23B 2231/28](#), [nose pieces in chucks B23B 2231/44](#))
- 2260/062 . Electric motors
- 2260/0625 . . Linear motors
- 2260/066 . Electrostrictive elements
- 2260/068 . Flexible members
- 2260/07 . Gears
- 2260/072 . Grooves
- 2260/0725 . . Spiral
- 2260/076 . Harmonic drive gearboxes, i.e. reduction gearing including wave generator, flex spline and a circular spline
- 2260/078 . Hand tools used to operate chucks or to assemble, adjust or disassemble tools or equipment used for turning, boring or drilling
- 2260/0785 . . for unclamping cutting inserts
- 2260/082 . Holes
- 2260/084 . Hirth couplings
- 2260/088 . Indication scales
- 2260/09 . Knurled surfaces
- 2260/092 . Lasers
- 2260/094 . Levels, e.g. spirit levels
- 2260/096 . Levers
- 2260/098 . Magazines
- 2260/10 . Magnets
- 2260/102 . Magnetostrictive elements
- 2260/104 . Markings, i.e. symbols or other indicating marks
- 2260/106 . Nuts
- 2260/108 . Piezoelectric elements
- 2260/11 . Planetary drives
- 2260/112 . Projections
- 2260/114 . Rings
- 2260/116 . Rollers or rolls
- 2260/118 . Suction pads or vacuum cups, e.g. for attachment of guides to workpieces
- 2260/12 . Stops ([depth controls B23B 2260/0482](#))
- 2260/122 . Safety devices
- 2260/124 . Screws
- 2260/126 . Seals
- 2260/128 . Sensors
- 2260/1285 . . Vibration sensors
- 2260/132 . Serrations ([cutting inserts with serrated bottom surfaces B23B 2200/167](#))
- 2260/134 . Spacers or shims ([shims for supporting cutting inserts B23B 2205/16](#))
- 2260/136 . Springs
- 2260/138 . Screw threads
- 2260/1381 . . Conical
- 2260/1383 . . with round thread profile
- 2260/1385 . . with square thread profile
- 2260/1386 . . with trapezoidal thread profile
- 2260/1388 . . with special profile not otherwise provided for
- 2260/142 . Valves
- 2260/144 . Wear indicators
- 2260/146 . Wedges
- 2260/158 . Worms and worm wheels
- 2265/00 Details of general geometric configurations**
- 2265/08 . Conical
- 2265/12 . Eccentric
- 2265/16 . Elliptical
- 2265/32 . Polygonal
- 2265/322 . . Square
- 2265/324 . . Pentagonal
- 2265/326 . . Hexagonal
- 2265/328 . . Octagonal
- 2265/34 . Round
- 2265/36 . Spherical
- 2270/00 Details of turning, boring or drilling machines, processes or tools not otherwise provided for**
- 2270/02 . Use of a particular power source
- 2270/022 . . Electricity
- 2270/025 . . Hydraulics
- 2270/027 . . Pneumatics
- 2270/04 . Use of centrifugal force ([compensating centrifugal force B23B 2250/08](#))
- 2270/06 . Use of elastic deformation
- 2270/08 . Clamping mechanisms; Provisions for clamping ([B23B 2210/00 takes precedence](#))
- 2270/09 . Details relating to unclamping
- 2270/10 . Use of ultrasound

B23B

- 2270/12 . Centering of two components relative to one another
- 2270/14 . Constructions comprising exactly two similar components
- 2270/16 . Constructions comprising three or more similar components
- 2270/20 . Internally located features, machining or gripping of internal surfaces
- 2270/205 . . Machining or gripping both internal and external surfaces
- 2270/22 . Externally located features, machining or gripping of external surfaces ([machining or gripping of both internal and external surfaces B23B 2270/205](#))
- 2270/24 . Tool, chuck or other device activated by the coolant or lubrication system of the machine tool
- 2270/26 . Burnishing
- 2270/28 . Cleaning
- 2270/30 . Chip guiding or removal ([use of suction B23B 2270/62, drilling tools with provision for suction B23B 2251/68](#))
- 2270/32 . Use of electronics
- 2270/34 . Means for guiding
- 2270/36 . Identification of tooling or other equipment
- 2270/38 . Using magnetic fields ([magnets B23B 2260/10](#))
- 2270/48 . Measuring or detecting
- 2270/483 . . Measurement of force
- 2270/486 . . Measurement of rotational speed
- 2270/54 . Methods of turning, boring or drilling not otherwise provided for
- 2270/56 . Turning, boring or drilling tools or machines with provision for milling
- 2270/58 . Oblique elements
- 2270/60 . Prevention of rotation
- 2270/62 . Use of suction ([suction pads or vacuum cups B23B 2260/118, drilling tools with provision for suction B23B 2251/68, chip removal B23B 2270/30](#))