

# CPC COOPERATIVE PATENT CLASSIFICATION

## B PERFORMING OPERATIONS; TRANSPORTING

(NOTES omitted)

### TRANSPORTING

#### B61 RAILWAYS

(NOTE omitted)

#### B61G COUPLINGS; DRAUGHT AND BUFFING APPLIANCES (vehicle connections in general [B60D](#))

##### WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

##### Couplings peculiar to railway vehicles

- |       |   |             |   |
|-------|---|-------------|---|
| 1/00  | <b>Couplings comprising interengaging parts of different shape or form and having links, bars, pins, shackles, or hooks as coupling means</b> | 1/34        | . . Operating devices therefor { <a href="#">(B61G 1/326 takes precedence)</a> }  |
| 1/02  | . having links or bars coupling or uncoupling by rotating around a transverse horizontal axis   | 1/36        | . with shackles and hooks, e.g. specially adapted for mine cars   |
| 1/04  | . . Operating devices therefor ( <a href="#">B61G 1/08 takes precedence</a> )   | 1/38        | . . rotatable about line of traction, e.g. for cars which are tiltable when coupled   |
| 1/06  | . . and coupling when the coupling halves are pushed together   | 1/40        | . with coupling bars having an enlarged or recessed end which slips into the opposite coupling part and is gripped thereby, e.g. arrow-head type; with coupling parts having a tong-like gripping action  |
| 1/08  | . . . Control devices therefor  | 1/42        | . . Operating devices therefor  |
| 1/10  | . having links or bars coupling or uncoupling by rotating around a vertical axis  | <b>3/00</b> | <b>Couplings comprising mating parts of similar shape or form which can be coupled without the use of any additional element or elements</b>  |
| 1/12  | . . Operating devices therefor ( <a href="#">B61G 1/16 takes precedence</a> )   | 3/02        | . with interengaging movably-mounted hooks or links guided into alignment by a gathering device, e.g. "Dowty" type  |
| 1/14  | . . and coupling when the coupling halves are pushed together   | 3/04        | . with coupling head having a guard arm on one side and a knuckle with angularly-disposed nose and tail portions pivoted to the other side thereof, the nose of the knuckle being the coupling part, and means to lock the knuckle in coupling position, e.g. "A.A.R." or "Janney" type |
| 1/16  | . . . Control devices therefor  | 3/06        | . . Knuckle-locking devices   |
| 1/18  | . having links or bars coupling or uncoupling by rotating axially   | 3/08        | . . . Control devices, e.g. for uncoupling  |
| 1/183 | . . {and coupling when the coupling halves are pushed together}   | 3/10        | . with coupling heads in the form of hook-like interengaging rigid jaws, e.g. "Willison" type   |
| 1/186 | . . . {Control devices therefor}  | 3/12        | . . Jaw-locking devices   |
| 1/20  | . . Operating devices therefor { <a href="#">(B61G 1/186 takes precedence)</a> }  | 3/14        | . . Control devices, e.g. for uncoupling  |
| 1/22  | . having screws incorporated in the links for lengthening or shortening the couplings   | 3/16        | . with coupling heads rigidly connected by rotatable hook plates or discs and balancing links, the coupling members forming a parallelogram, e.g. "Scharfenberg" type   |
| 1/24  | . . Operating devices therefor ( <a href="#">B61G 1/26 takes precedence</a> )   | 3/18        | . . Locking devices   |
| 1/26  | . . and coupling when the coupling halves and pushed together; Control devices therefor   | 3/20        | . . Control devices, e.g. for uncoupling  |
| 1/265 | . . . {Control devices therefor}  | 3/22        | . with coupling heads rigidly connected by locks consisting of pivoted latches  |
| 1/28  | . with vertical bolt or pin   | 3/24        | . . Latch-locking devices   |
| 1/283 | . . {and coupling when the coupling halves are pushed together}   | 3/26        | . . Control devices, e.g. for uncoupling  |
| 1/286 | . . . {Control devices therefor}  | 3/28        | . with coupling heads rigidly connected by locks consisting of slidable pins  |
| 1/30  | . . Operating devices therefor { <a href="#">(B61G 1/286 takes precedence)</a> }  |             |   |
| 1/32  | . with horizontal bolt or pin   |             |   |
| 1/323 | . . {and coupling when the coupling halves are pushed together}   |             |   |
| 1/326 | . . . {Control devices therefor}  |             |   |

- |             |   |       |  |
|-------------|---|-------|--|
| 3/30        | . with coupling heads rigidly connected by pins having locking noses which are brought into locking position by rotating the pins   | 11/14 | . absorbing shocks by mechanical friction action; Combinations of mechanical shock-absorbers and springs ( <a href="#">B61G 11/06 takes precedence</a> ) |
| <b>5/00</b> | <b>Couplings for special purposes not otherwise provided for</b>  | 11/16 | . absorbing shocks by permanent deformation of buffer element  |
| 5/02        | . for coupling articulated trains, locomotives and tenders or the bogies of a vehicle; Coupling by means of a single coupling bar; Couplings preventing or limiting relative lateral movement of vehicles | 11/18 | . Details  |
| 5/04        | . for matching couplings of different types, i.e. transitional couplings  |       |  |
| 5/06        | . for, or combined with, couplings or connectors for fluid conduits or electric cables  |       |  |
| 5/08        | . . for fluid conduits  |       |  |
| 5/10        | . . for electric cables   |       |  |
| <b>7/00</b> | <b>Details or accessories</b>   |       |  |
| 7/02        | . Hand tools for coupling or uncoupling   |       |  |
| 7/04        | . Coupling or uncoupling by means of trackside apparatus  |       |  |
| 7/06        | . Coupling heads constructed to facilitate alignment  |       |  |
| 7/08        | . Adjustable coupling heads   |       |  |
| 7/10        | . Mounting of the couplings on the vehicle  |       |  |
| 7/12        | . . Adjustable coupling bars, e.g. for centralisation purposes  |       |  |
| 7/14        | . Safety devices  |       |  |

#### Draught or buffing appliances peculiar to railway or tramway vehicles

- |              |  |
|--------------|--|
| <b>9/00</b>  | <b>Draw-gear</b>   |
| 9/02         | . Draw-gear and non-integral buffing appliances with combined action or acting on the same spring  |
| 9/025        | . . {with only metal springs}  |
| 9/04         | . Draw-gear combined with buffing appliances ( <a href="#">continuous B61G 9/12</a> )              |
| 9/045        | . . {with only metal springs}  |
| 9/06         | . . with rubber springs  |
| 9/08         | . . with fluid springs or fluid shock-absorbers; Combinations thereof                              |
| 9/10         | . . with separate mechanical friction shock-absorbers  |
| 9/12         | . Continuous draw-gear combined with buffing appliances, e.g. incorporated in a centre sill        |
| 9/125        | . . {with only metal springs}  |
| 9/14         | . . with rubber springs  |
| 9/16         | . . with fluid springs or fluid shock-absorbers; Combinations thereof                              |
| 9/18         | . . with separate mechanical friction shock-absorbers  |
| 9/20         | . Details; Accessories   |
| 9/22         | . . Supporting framework, e.g. cradles; Spring housings  |
| 9/24         | . . Linkages between draw-bar and framework ( <a href="#">adjustable coupling bars B61G 7/12</a> ) |
| <b>11/00</b> | <b>Buffers (<a href="#">springs F16F</a>)</b>  |
| 11/02        | . with metal springs   |
| 11/04        | . . with helical springs   |
| 11/06        | . . . arranged to damp each other by mutual friction   |
| 11/08        | . with rubber springs  |
| 11/10        | . with combined rubber and metal springs   |
| 11/12        | . with fluid springs or shock-absorbers; Combinations thereof                                      |