CPC COOPERATIVE PATENT CLASSIFICATION

B PERFORMING OPERATIONS; TRANSPORTING

(NOTES omitted)

TRANSPORTING

B62 LAND VEHICLES FOR TRAVELLING OTHERWISE THAN ON RAILS

B62K CYCLES; CYCLE FRAMES; CYCLE STEERING DEVICES; RIDER-OPERATED TERMINAL CONTROLS SPECIALLY ADAPTED FOR CYCLES; CYCLE AXLE SUSPENSIONS; CYCLE SIDE-CARS, FORECARS, OR THE LIKE

NOTES

- 1. In this subclass, each of the main groups $\underline{B62K\ 7/00}$ $\underline{B62K\ 15/00}$ takes precedence over all the preceding main groups, e.g. a child's bicycle is classified in $\underline{B62K\ 9/00}$ and not in $\underline{B62K\ 3/00}$.
- {"Cycles" includes a single or plural wheeled straddle type vehicles having a handlebar, self-balancing vehicles and kid scooters}

WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Unicycles	5/027	Motorcycles with three wheels (specially adapted
3/00 3/002 3/005 3/02	 Bicycles {without a seat, i.e. the rider operating the vehicle in a standing position, e.g. non-motorized scooters; non-motorized scooters with skis or runners} {Recumbent-type bicycles} Frames (tandem frames B62K 3/14) 	5/05 5/06 5/08 5/10	 for disabled riders B62K 5/023) characterised by a single rear wheel Frames for tricycles with steering devices acting on two or more wheels with means for inwardly inclining the vehicle body on bends
3/04	 having a substantially horizontal top bar 	7/00	Freight- or passenger-carrying cycles
3/06	• of open type	7/02	Frames
3/08	having crossing members	7/04	having a carrying platform (article-carrying)
3/10	of single-beam type, i.e. connecting steering head to rear axle		accessories <u>B62J 7/00</u> - <u>B62J 11/00</u>)
3/12	. Tandems	9/00	Children's cycles (toy vehicles A63H 17/00)
2003/125	{Tandems with side-by-side seating}	9/02	• Tricycles
3/14	Frames	11/00	Motorcycles, engine-assisted cycles or motor
3/16	 specially adapted for disabled riders (invalid multi- track cycles <u>A61G 5/00</u>) 	11/00	scooters with one or two wheels (fairings or streamlining parts not forming part of the frame B62J; transmission of drive from engines to wheels B62M)
5/00	Cycles with handlebars, equipped with three or more main road wheels (cycle supports or stands equipped with additional wheels for ride stabilisation B62H 1/12)	11/007	 {Automatic balancing machines with single main ground engaging wheel or coaxial wheels supporting a rider}
2005/001	Suspension details for cycles with three or more	11/02	• Frames (motorcycles or cycles with auxiliary engines characterised by position of engine <u>B62M</u>)
2005/002	main road wheels} • {with adaptations to be used as golf carts}	11/04	• • characterised by the engine being between front
5/003	 • {with adaptations to be used as gon carts} • Cycles with four or more wheels, specially adapted 		and rear wheels
3/003	for disabled riders, e.g. personal mobility type	11/06	the frame being of single-beam type
	vehicles with four wheels (wheelchairs A61G 5/00)	11/08	the beam being fabricated from sheet metal,
5/007	• • power-driven	11/10	e.g. forming fuel tank walls
5/01	• Motorcycles with four or more wheels (specially adapted for disabled riders <u>B62K 5/003</u>)	11/10	• characterised by the engine being over or beside driven rear wheel
5/02	• Tricycles (children's tricycles <u>B62K 9/02</u>)	11/12	Steering wheel forks characterised by the
5/023	 specially adapted for disabled riders, e.g. personal mobility type vehicles with three wheels (wheelchairs <u>A61G 5/00</u>) 	11/14	 association therewith of engine Handlebar constructions, or arrangements of controls thereon, specially adapted thereto (hand controls per se B62K 23/02)
5/025	power-driven		

CPC - 2023.02

13/00	Cycles convertible to, or transformable into, other	21/06	Bearings specially adapted for steering heads
	types of cycles or land vehicle (cycle supports or		(bearings in general <u>F16C</u>)
	stands equipped with additional wheels for ride	21/08	• Steering dampers (dampers in general F16F)
12/02	stabilisation <u>B62H 1/12</u>)	21/10	Mechanisms for restoring steering device to
13/02	• to a tandem	21/12	straight-ahead position
13/025	• • {from two or more cycles}	21/12	Handlebars; Handlebar stems
13/04	• to a tricycle	21/125	• • {Extensions; Auxiliary handlebars}
13/06	• to a quadricycle, e.g. by coupling together two	21/14	 having resilient parts therein
12/00	bicycles side by side	21/145	• • • {the handlebar itself being flexible}
13/08	• Frames	21/16	having adjustable parts therein
15/00	Collapsible or foldable cycles	21/18	Connections between forks and handlebars or
2015/001	• {Frames adapted to be easily dismantled}	24/20	handlebar stems
2015/003	• {having a foldable crank or pedal}	21/20	. resilient
2015/005	• {having additional wheels for use when folded or	21/22	adjustable
	collapsed}	21/24	. readily releasable
15/006	• {the frame being foldable}	21/26	• Handlebar grips (twist grips <u>B62K 23/04</u>)
15/008	• • {foldable about 2 or more axes}	23/00	Rider-operated controls specially adapted for
17/00	Cycles not otherwise provided for		cycles, i.e. means for initiating control operations, e.g. levers, grips (specially adapted to cycle brake
19/00	Cycle frames (cycle frames specially adapted for		mechanisms <u>B62L 3/00</u>)
	one particular kind of cycle specified in groups	23/02	 hand actuated (arrangements of controls on handle-
	<u>B62K 1/00</u> - <u>B62K 17/00</u> , <u>see</u> the relevant group)		bars of engine-driven cycles <u>B62K 11/14</u>)
19/02	 characterised by material or cross-section of frame 	23/04	Twist grips
	members	23/06	Levers
19/04	• • the material being wholly or mainly metallic, e.g.	23/08	 foot actuated
	of high elasticity	25/00	Axle suspensions (for vehicles in general <u>B60G</u>)
19/06	tubular	25/005	• {characterised by the axle being supported at one
19/08	made from sheet	23/003	end only}
19/10	Combinations of tube and sheet	25/02	 for mounting axles rigidly on cycle frame or fork,
19/12	having cast members		e.g. adjustably
19/14	the material being wholly or mainly wood	2025/025	• . {Hinged axle clamps}
19/16	• the material being wholly or mainly of plastics	25/04	for mounting axles resiliently on cycle frame or fork
19/18	Joints between frame members		(for sidecars, forecars or the like <u>B62K 27/06</u>)
19/20	• • welded, soldered, or brazed	2025/041	• • {the cycle frame being made of a flexible
19/22	. Adhesive joints		material }
19/24	Screwed joints	2025/042	• • {Suspensions with sprung hubs}
19/26	. Riveted joints	2025/044	• • {Suspensions with automatic adjustment}
19/28	. Means for strengthening joints	2025/045	• • {Suspensions with ride-height adjustment}
19/30	• Frame parts shaped to receive other cycle parts or	2025/047	• • {with suspension locking means}
10/22	accessories (axle suspensions <u>B62K 25/00</u>)	2025/048	• • {with suspension manual adjustment details}
19/32	Steering heads (bearings therefor <u>B62K 21/06</u>) Between heads (bearings therefor <u>B62K 21/06</u>)	25/06	with telescopic fork, e.g. including auxiliary
19/34 19/36	. Bottom brackets. for attaching saddle pillars, e.g. adjustable during		rocking arms
19/30	ride	25/08	for front wheel
19/38	• for attaching brake members	25/10	for rear wheel
19/40	 for attaching accessories, e.g. article carriers, 	25/12	• with rocking arm pivoted on each fork leg (in
19/40	lamps	25/14	combination with telescopic fork <u>B62K 25/06</u>)
19/42	for tyre pumps (attachment devices not forming	25/14	with single arm on each fork leg
-27, 1-	part of frame B62J 11/02)	25/16	for front wheel
19/44	Chain-guards forming part of frame (chain-guards)	25/18	• • • • the arm being pivoted intermediate its ends
	per se <u>B62J 13/00</u>)	25/20	for rear wheel
19/46	 Luggage carriers forming part of frame (luggage 	25/22	with more than one arm on each fork leg
	carriers per se B62J 7/00)	25/24	for front wheel
19/48	Fairings forming part of frame	25/26	for rear wheel
21/00	Steering devices (steering devices appointly adopted	25/28	• with pivoted chain-stay
21/00	Steering devices (steering devices specially adapted for one particular kind of cycle specified in groups	25/283	• • • {for cycles without a pedal crank, e.g. motorcycles}
21/005	B62K 1/00 - B62K 17/00, see the relevant group) (Steering pivot axis erronged within the wheel a g	25/286	• • • {the shock absorber being connected to the
21/005	 {Steering pivot axis arranged within the wheel, e.g. for a hub center steering arrangement} 	25/20	chain-stay via a linkage mechanism}
21/02	• Front wheel forks or equivalent, e.g. single tine	25/30	pivoted on pedal crank shelf (<u>B62K 25/32</u> takes precedence)
21/02	Fork crowns	25/32	the chain-stay forming a chain-guard
21/07	· Long of Office	23132	• • • the chain-stay forming a chain-guard

CPC - 2023.02

27/00	Sidecars; Forecars; {Trailers or the like specially adapted to be attached to cycles}(trailers <u>B60P</u> ; <u>B62D</u> ; characterised by carrying propulsion engine { <u>B62M 7/14</u> })
27/003	• {Trailers}
27/006	• • {having a single wheel}
27/02	. Frames
27/04	 Car bodies; Fairings
27/06	 Resilient axle suspension
27/08	 Resilient car-body suspension on frame
27/10	 Other component parts or accessories
27/12	• Coupling parts for attaching cars or the like to cycle; Arrangements thereof
27/14	Resilient coupling parts
27/16	Hoods; Weather-guards, e.g. windscreens
2201/00	Springs used in cycle frames or parts thereof
2201/02	Rubber springs
2201/04	Helical springs
2201/06	• Leaf springs
2201/08	• Fluid springs
2202/00	Motorised scooters
2204/00	Adaptations for driving cycles by electric motor (for driving electrically assisted bicycles <u>B62M 6/00</u>)
2206/00	Quick release mechanisms adapted for cycles

CPC - 2023.02