

CPC COOPERATIVE PATENT CLASSIFICATION

B PERFORMING OPERATIONS; TRANSPORTING

(NOTES omitted)

TRANSPORTING

B67 OPENING, CLOSING {OR CLEANING} BOTTLES, JARS OR SIMILAR CONTAINERS; LIQUID HANDLING

B67B APPLYING CLOSURE MEMBERS TO BOTTLES JARS, OR SIMILAR CONTAINERS; OPENING CLOSED CONTAINERS (opening or closing devices attached to, or incorporated in, containers or container closures [B65D](#))

WARNINGS

1. The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:

B67B 7/46	covered by	B67B 7/30-B67B 7/385
B67B 7/48-B67B 7/52	covered by	B67B 7/24, B67B 7/26, B67B 7/28
B67B 7/54-B67B 7/90	covered by	B67B 7/30-B67B 7/385

2. In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Closing bottles, jars or similar containers by applying stoppers (stoppers per se B65D 39/00)	3/064	. . . from a hopper {(B67B 3/061 takes precedence)}
1/005	. {Feeding stoppers (in general B65G)}	3/0645 {with means for orientating the caps to a position ready to be applied to the container}
1/03	. Pretreatment of stoppers, e.g. cleaning, steaming, heating, impregnating or coating; Applying resilient rings to stoppers (mechanical working of cork B27J 5/00)	3/10	. . Capping heads for securing caps {(B67B 3/023 takes precedence)}
1/04	. by inserting threadless stoppers, e.g. corks	3/12	. . . characterised by being movable axially relative to cap to deform flanges thereof, e.g. to press projecting flange rims inwardly
1/045	. . {using hand operated devices}	3/14	. . . characterised by having movable elements, e.g. hinged fingers, for applying radial pressure to the flange of the cap (B67B 3/16, B67B 3/18 take precedence)
1/06	. by inserting and rotating screw stoppers	3/16	. . . characterised by having resilient deforming elements, e.g. resilient sleeves or collars (B67B 3/18 takes precedence)
1/08	. Securing stoppers, e.g. swing stoppers, which are held in position by associated pressure-applying means coating with the bottle neck	3/18	. . . characterised by being rotatable, e.g. for forming screw threads <i>in situ</i>
1/10	. by inserting disc closures	3/20	. by applying and rotating preformed threaded caps (forming threads <i>in situ</i> by resilient deforming means B67B 3/16 , by rotary capping heads B67B 3/18)
3/00	Closing bottles, jars or similar containers by applying caps (caps per se B65D 41/00)	3/2006	. . {using manually-controlled or manually operated devices}
3/003	. {Pretreatment of caps, e.g. cleaning, steaming, heating or sterilizing}	3/2013	. . {by carousel-type capping machines}
3/006	. {Applying date marks, code marks, or the like, to caps during capping (applying marks to labels B65C 9/46)}	3/202	. . . {using friction means for screwing the caps, e.g. belts or guides (B67B 3/2026, B67B 3/2033 take precedence)}
3/02	. by applying flanged caps, e.g. crown caps, and securing by deformation of flanges	3/2026	. . . {comprising stationary capping heads}
3/023	. . {using additional means for securing the cap, e.g. adhesives}	3/2033	. . . {comprising carousel co-rotating capping heads}
3/026	. . {the caps being made of thermoplastic material (B67B 3/023 takes precedence)}	3/204	. . {Linear-type capping machines}
3/04	. . Cutting caps from strip material in capping machines (devices for registering moving strip material B65H 23/00)	3/2046	. . . {using friction means for screwing the caps, e.g. belts or wheels (B67B 3/2053 takes precedence)}
3/06	. . Feeding caps to capping heads	3/2053	. . . {comprising capping heads}
3/061	. . . {the caps having an asymmetric footprint, e.g. comprising a gripping lip}		
3/062	. . . from a magazine {(B67B 3/061 takes precedence)}		

- 3/206 . . {Means for preventing rotation of the container or cap}
- 3/2066 . . {Details of capping heads ([B67B 3/2073](#) takes precedence)}
- 3/2073 . . {comprising torque limiting means (torque limiters in wrenches or screwdrivers [B25B 23/14](#); couplings or clutches [per se F16D](#))}
- 3/208 . . . {Electrical means responsive to the torque applied and acting on motor control means, e.g. strain gauges or power measurement means ([B67B 3/2093](#) takes precedence)}
- 3/2086 . . . {Magnetic or electromagnetic clutches}
- 3/2093 . . . {whereby the applied torque limit is varied}
- 3/22 . by applying snap-on caps
- 3/24 . Special measures for applying and securing caps under vacuum
- 3/26 . Applications of control, warning, or safety devices in capping machinery
- 3/261 . . {Devices for controlling the tightening of threaded caps, e.g. testing the release torque (torque testers in general [G01L 5/00](#))}
- 3/262 . . {Devices for controlling the caps}
- 3/264 . . . {positioning of the caps}
- 3/265 . . . {presence of a cap}
- 3/267 . . . {positioning of the cap-label}
- 3/268 . . {devices for avoiding damage to the closing machine}
- 3/28 . Mechanisms for causing relative movement between bottle or jar and capping head
- 5/00 Applying protective or decorative covers to closures; Devices for securing bottle closures with wire (infant feeding teats with means for fastening to bottles [A61J 11/04](#))**
- 5/03 . Applying protective or decorative covers to closures, e.g. by forming *in situ*
- 5/032 . . {Dies for securing overcaps}
- 5/034 . . {the covers being elastic}
- 5/036 . . {the covers being heat-shrinkable}
- 5/038 . . {the covers being applied wet, whereby shrinkage occurs on drying}
- 5/05 . . by applying liquids, e.g. by dipping
- 5/06 . Devices for securing bottle closures with wire ([B67B 1/08](#) takes precedence)
- 6/00 Closing bottles, jars or similar containers by applying closure members, not provided for in groups [B67B 1/00](#) - [B67B 5/00](#)**
- 7/00 Hand- or power-operated devices for opening closed containers (nail pullers or extractors [B25C 11/00](#); attached to, or incorporated in, containers or container closures {[B65D 75/58](#), [B65D 77/30](#))}**
- 7/02 . for removing stoppers
- 7/04 . . Cork-screws
- 7/0405 . . . {Power-operated cork-screws, e.g. operated by an electric motor}
- 7/0411 . . . {without supporting means for assisting the pulling action}
- 7/0417 . . . {with supporting means for assisting the pulling action}
- 7/0423 {of wine-waiter, i.e. sommelier type}
- 7/0429 {having means for varying the effective lever arm length}
- 7/0435 {with a pantograph extracting mechanism}
- 7/0441 {whereby the supporting means abut around the whole periphery of the neck of the bottle}
- 7/0447 {whereby the supporting means abut around parts of the periphery of the neck of the bottle}
- 7/0452 . . . {adapted to be mounted on walls}
- 2007/0458 . . . {Means for cutting sealing capsules}
- 2007/0464 . . . {Means for counting}
- 2007/047 . . . {Means for reducing friction}
- 2007/0476 {by coating the screw}
- 2007/0482 {by using roller-bearings}
- 2007/0488 . . . {Means for measuring temperature}
- 2007/0494 . . . {Means for varying the lever arm}
- 7/06 . . Other cork removers
- 7/063 . . . {using one or more blades to be inserted between the cork and the inner surface of the bottle neck}
- 7/066 . . . {specially adapted for opening pressurised bottles, e.g. champagne or sparkling wine bottles}
- 7/08 . . . using air or gas pressure
- 7/10 . . with means for retrieving stoppers from the interior of the container
- 7/12 . for removing disc-closures
- 7/14 . for removing tightly-fitting lids or covers, e.g. of shoe-polish tins, by gripping and rotating
- 7/15 . . finger grapple type
- 7/16 . for removing flanged caps, e.g. crown caps
- 7/162 . . {the removing device being formed by at least two articulated parts, e.g. pliers ([B67B 7/164](#) takes precedence)}
- 7/164 . . {Power-operated devices}
- 2007/166 . . {Means for attaching the opener to fingers}
- 2007/168 . . {Means for counting}
- 7/18 . for removing threaded caps ([B67B 7/14](#) takes precedence; wrenches [B25B 13/00](#))
- 7/182 . . {power-operated}
- 7/184 . . {by use of a flexible loop gripping the cap skirt or the container body by friction}
- 7/186 . . . {the loop having an adjustable length}
- 2007/188 . . {Means for attaching the opener to fingers}
- 7/20 . for breaking vacuum seals between lids or covers and bodies of preserving jars, e.g. by wedge action
- 7/22 . . incorporating loops, e.g. of wire, which are tightened around seal
- 7/24 . {Hole-piercing devices}
- 7/26 . . {combined with spouts}
- 7/28 . . . {and associated with receptacle hodlers}
- 7/30 . {Hand-operated cutting devices}
- 2007/303 . . {can openers}
- 2007/306 . . . {Means for counting}
- 7/32 . . {propelled by rotary gears or wheels around periphery of container}
- 7/34 . . {with rotatable cutters}
- 7/36 . . {adapted to be mounted on walls}
- 7/38 . {Power-operated cutting devices ([machines for domestic use with a plurality of interchangeable units \[A47J 43/06\]\(#\), \[A47J 44/00\]\(#\)](#))}
- 7/385 . . {specially adapted to be hand-held}
- 7/40 . Devices for engaging tags, strips, or tongues for opening by tearing, e.g. slotted keys for opening sardine tins

B67B

- 7/403 . . {adapted for engaging the ring of a pull tab for opening an aperture}
- 7/406 . . . {and subsequently tearing off the top of the can}
- 7/42 . Devices for removing barrel bungs
- 7/44 . Combination tools, e.g. comprising cork-screws, can piercers, crown cap removers (combinations of opening devices with cutting tools [B26](#); with devices serving other purposes, see appropriate subclasses, e.g. [B25F](#); [B43K 29/00](#))
- 7/92 . by breaking, e.g. for ampoules

2201/00 Indexing codes relating to constructional features of closing machines

- 2201/01 . Orienting closure means
- 2201/012 . . Stoppers
- 2201/015 . . . Cylindrical stoppers
- 2201/017 . . Caps
- 2201/03 . applying two closures on a container
- 2201/06 . Details of cap feeding devices
- 2201/065 . . Use of magnets
- 2201/08 . Aseptic features
- 2201/10 . Quick or easy connection means for connecting a capping head to a spindle
- 2201/12 . Details related to spray caps, i.e. caps comprising a pump and a tube for dispensing content from a container