

CPC COOPERATIVE PATENT CLASSIFICATION

E FIXED CONSTRUCTIONS

BUILDING

E05 LOCKS; KEYS; WINDOW OR DOOR FITTINGS; SAFES

(NOTE omitted)

E05Y INDEXING SCHEME RELATING TO HINGES OR OTHER SUSPENSION DEVICES FOR DOORS, WINDOWS OR WINGS AND DEVICES FOR MOVING WINGS INTO OPEN OR CLOSED POSITION, CHECKS FOR WINGS AND WING FITTINGS NOT OTHERWISE PROVIDED FOR, CONCERNED WITH THE FUNCTIONING OF THE WING

2201/00	Constructional elements; Accessories therefore	2201/42	. . . for locking
2201/10	. Covers; Housings	2201/422	. . . for opening
2201/11	. . Covers	2201/424 for the final opening movement
2201/20	. Brakes; Disengaging means, e.g. clutches; Holders, e.g. locks; Stops; Accessories therefore	2201/426 for the initial opening movement
2201/21	. . Brakes	2201/428	. . . for suspending or supporting
2201/212	. . . Buffers	2201/43	. . Motors
2201/214	. . Disengaging means	2201/434	. . . Electromotors; Details thereof
2201/216	. . . Clutches	2201/438 Rotors
2201/218	. . Holders	2201/442 Stators
2201/22	. . . Locks	2201/446 Windings
2201/222	. . . Stabilizers, e.g. anti-rattle devices	2201/448	. . . Fluid motors; Details thereof
2201/224	. . Stops	2201/454 Cylinders
2201/23	. . Actuation thereof	2201/456 Pistons
2201/232	. . . by automatically acting means	2201/458 Valves
2201/234 direction dependent	2201/46	. . Magnets
2201/236 using force or torque	2201/462	. . . Electromagnets
2201/238 reaction force or torque	2201/47	. . Springs; Spring tensioners
2201/24 using lost motion	2201/474	. . . Compression springs
2201/242 using threshold speed	2201/476	. . . Disk springs
2201/244	. . . by manual operation	2201/478	. . . Gas springs
2201/246	. . . by motors, magnets, springs or weights	2201/48	. . . Leaf springs
2201/248	. . . characterised by the transmission	2201/482	. . . Ribbon springs
2201/25	. . Force or torque adjustment therefore (E05Y 2400/21 takes precedence)	2201/484	. . . Torsion springs
2201/252	. . characterised by type of friction	2201/486 Torsion rods
2201/254	. . . Fluid or viscous friction	2201/488	. . . Traction springs
2201/256 with pistons or vanes	2201/49	. . . Wrap springs
2201/258	. . . Magnetic or electromagnetic friction	2201/492	. . . Spring tensioners, tension sensors
2201/26	. . . Mechanical friction	2201/496	. . . Double acting springs
2201/262	. . characterised by type of motion	2201/50	. . Weights
2201/264	. . . linear	2201/502	. . . Wing weights
2201/266	. . . rotary	2201/60	. Suspension or transmission members; Accessories therefore
2201/40	. Motors; Magnets; Springs; Weights; Accessories therefore	2201/602	. . Suspension members
2201/404	. . characterised by the function	2201/604	. . Transmission members
2201/406	. . . for additional wing movements only	2201/606	. . Accessories therefore
2201/408	. . . for braking	2201/608	. . . Back-drive
2201/41	. . . for closing	2201/61	. . . Cooperation between suspension or transmission members
2201/412 for the final closing movement	2201/612 between carriers and rails
2201/414 for the initial closing movement	2201/614 Anti-derailing means
2201/416	. . . for counterbalancing	2201/616 to ensure mutual engagement, e.g. counter-rollers
2201/418	. . . for holding	2201/618	. . . Transmission ratio variation

E05Y

2201/62	. . . Synchronisation of transmission members	2400/302	. . . during electromotoric braking
2201/622	. . Suspension or transmission members elements	2400/31	. . . Force or torque control
2201/624	. . . Arms	2400/315 Curve setting or adjusting
2201/626 Levers	2400/32	. . . Position control, detection or monitoring
2201/628	. . . Bearings	2400/322 by using absolute position sensors (sensors for electronic control of hinges, wings, windows as such E05Y 2400/44)
2201/63 Races	2400/324 Switches
2201/632 Sleeves	2400/326 of the angular type
2201/636 Universal or ball joints	2400/328 of the linear type
2201/638	. . . Cams; Ramps	2400/33 by using load sensors (sensors for electronic control of hinges, wings, windows as such E05Y 2400/44)
2201/64	. . . Carriers	2400/332 Switches
2201/642 Trackless carriers	2400/334 by using pulse generators
2201/644	. . . Flexible elongated pulling elements; Members cooperating with flexible elongated pulling elements	2400/336 of the angular type
2201/646 continuous, e.g. closed loops	2400/337 Encoder wheels
2201/648 having teeth (toothed gearing E05Y 2201/71)	2400/338 of the linear type
2201/652 Belts	2400/34 Pulse count limit setting
2201/654 Cables	2400/342 Pulse count value setting or correcting
2201/656 Chains	2400/35 related to specific positions
2201/658 Members cooperating with flexible elongated pulling elements	2400/354 End positions
2201/66 Deflectors; Guides	2400/356 Predefined intermediate positions
2201/662 Cable sheaths	2400/358 in the proximity of end positions
2201/664 Drums	2400/36	. . . Speed control, detection or monitoring
2201/666 Magazines	2400/40	. . . Control units therefore
2201/668 Pulleys; Wheels	2400/41 for multiple motors
2201/67 in tackles	2400/415 for multiple wings
2201/672 Tensioners, tension sensors	2400/42 for multiple openings
2201/674	. . . Friction wheels	2400/44	. . Sensors therefore (E05Y 2400/322 , E05Y 2400/33 , E05Y 2400/55 , E05Y 2400/56 , E05Y 2400/852 take precedence)
2201/676	. . . Transmission of human force	2400/445	. . . Switches
2201/678 Hand chains	2400/45	. . Control modes
2201/68 Handles, cranks	2400/452	. . . for saving energy
2201/682	. . . Pins	2400/454	. . . for accommodating handicapped users
2201/684	. . . Rails	2400/456	. . . for programming
2201/686	. . . Rods, links	2400/458	. . . for generating service signals
2201/688	. . . Rollers	2400/50	. . Fault detection
2201/69 having inclined axes	2400/502	. . . of components
2201/692 having vertical axes	2400/504	. . . of control
2201/694	. . . Scissor mechanisms	2400/506	. . . of counterbalance
2201/696	. . . Screw mechanisms	2400/508	. . . of detection
2201/70 Nuts	2400/51	. . . of position, of back drive
2201/702 Spindles; Worms	2400/512	. . . of electric power
2201/704 Worm wheels	2400/514	. . . of speed
2201/706	. . . Shafts	2400/52	. . Safety arrangements (Safety means for manual wing operation E05Y 2800/116)
2201/708	. . . Sliders (E05Y 2201/64 takes precedence)	2400/522	. . . Back-drive prevention
2201/71	. . . Toothed gearing	2400/525	. . . Car-jacking prevention
2201/712 with incomplete toothing	2400/53	. . . Wing impact prevention or reduction
2201/716 Pinions	2400/532 Emergency braking
2201/718 Bevelled pinions	2400/54 Obstruction or resistance detection
2201/72 Planetary gearing	2400/55 by using load sensors (sensors for electronic control of hinges, wings, windows as such E05Y 2400/44)
2201/722 Racks	2400/552 Switches
2201/724 Flexible	2400/554 sensing motor load
2201/726 Ring gears; Internal gears	2400/56 by using speed sensors (sensors for electronic control of hinges, wings, windows as such E05Y 2400/44)
2400/00	Electronic control; Power supply; Power or signal transmission; User interfaces	2400/562 Switches
2400/10	. Electronic control		
2400/20	. . of brakes, disengaging means, holders or stops		
2400/202	. . . Force or torque control (mechanical aspects E05Y 2201/25)		
2400/21 by controlling the viscosity		
2400/30	. . of motors		

2400/564	sensing motor speed
2400/57	Disabling thereof
2400/58	Sensitivity setting or adjustment
2400/59	. . .	Travel display
2400/60	.	Power supply; Power or signal transmission
2400/61	. .	Power supply
2400/612	. . .	Batteries
2400/614	charging thereof
2400/616	. . .	Generators
2400/628	Solar cells
2400/65	. .	Power or signal transmission
2400/652	. . .	by bus
2400/654	. . .	by electrical cables
2400/656	. . .	by travelling contacts
2400/658	with current rails
2400/66	. . .	Wireless transmission
2400/662	by optical waves
2400/664	by radio waves
2400/80	.	User interfaces
2400/81	. .	User displays
2400/812	. . .	with acoustic display
2400/814	Sound emitters, e.g. speakers
2400/816	Voice emitters
2400/818	. . .	with visual display
2400/82	Images, Symbols
2400/822	Light emitters, e.g. LEDs
2400/85	. .	User input means
2400/852	. . .	Sensors
2400/854	Switches
2400/856	Actuation thereof
2400/858	by body parts
2400/86	by hand
2600/00		Mounting or coupling arrangements for elements provided for in this subclass
2600/10	.	Adjustable or movable
2600/11	. .	by automatically acting means
2600/12	. .	by manual operation
2600/13	. .	by motors, magnets, springs, weights
2600/14	. .	with position retaining means
2600/20	. .	characterised by the movement transmission
2600/30	. .	characterised by the type of motion
2600/31	. . .	Linear motion
2600/312	Horizontal motion
2600/314	Vertical motion
2600/32	. . .	Rotary motion
2600/322	around a horizontal axis
2600/324	around a vertical axis
2600/33	. . .	Stepwise motion
2600/40	.	Mounting location; Visibility of the elements
2600/41	. .	Concealed
2600/412	. . .	in the rabbet
2600/45	. .	in or on the fixed frame
2600/452	. .	in or on the floor or wall
2600/454	. .	in or on the motor
2600/456	. .	in or on a suspension member
2600/458	. .	in or on a transmission member
2600/46	. .	in or on the wing
2600/50	.	Mounting methods; Positioning
2600/502	. .	Clamping
2600/504	. .	Expansion
2600/506	. .	Plastic deformation
2600/508	. . .	Riveting (in general B21J)
2600/51	. .	Screwing or bolting
2600/52	. .	Toolless
2600/522	. . .	Axial stacking
2600/524	. . .	Friction
2600/526	. . .	Glueing or cementing
2600/528	. . .	Hooking, e.g. using bayonets; Locking
2600/53	. . .	Snapping
2600/54	. .	Welding (in general B23K , B29C 65/02)
2600/56	. .	Positioning or pre-mounting
2600/60	.	Mounting or coupling members (devices for fastening or securing constructional elements or machine parts together, e.g. nails, bolts, in general F16B); Accessories therefore
2600/61	. . .	Threaded members
2600/62	. .	Bolts
2600/622	. .	Dowels; Pins
2600/624	. .	Nuts
2600/626	. .	Plates or brackets
2600/628	. .	Profiles
2600/63	. .	Retainers
2600/632	. .	Screws
2600/634	. .	Spacers
2600/636	. . .	Washers
2800/00		Details, accessories and auxiliary operations not otherwise provided for
2800/10	.	Additional functions
2800/102	. .	Additional wing movements
2800/104	. .	Heating
2800/106	. .	Lighting
2800/108	. .	Lubrication
2800/11	. .	Manual wing operation
2800/112	. . .	Back driving the transmission or motor
2800/113	Power assistance
2800/114	Overriding existing wing movement
2800/116	. . .	Safety means therefore
2800/12	. .	Sealing
2800/122	. .	Telescopic action
2800/15	.	Applicability
2800/16	. .	applicable on combinations of fixed and movable wings
2800/162	. . .	the wings being coplanar when the movable wing is in the closed position
2800/17	. .	Universally applicable
2800/172	. . .	on different wing or frame locations
2800/174	on the left or right side
2800/176	. . .	on different wing types
2800/178	. . .	on wings having different thicknesses
2800/20	.	Combinations of elements
2800/205	. .	forming a unit
2800/21	. .	of identical elements, e.g. of identical compression springs
2800/22	. .	of not identical elements of the same category, e.g. combinations of not identical springs
2800/23	. .	of elements of different categories
2800/232	. . .	of motors and transmissions
2800/234	. . .	of motors and brakes
2800/236	. . .	of motors and springs
2800/238	. . .	of springs and transmissions
2800/24	. . .	of springs and brakes
2800/242	. . .	arranged in parallel relationship

E05Y

- 2800/244 . . arranged in serial relationship
- 2800/246 . . with at least one element being redundant
- 2800/25 . Emergency conditions
- 2800/252 . . the elements functioning only in case of emergency
- 2800/254 . . the elements not functioning in case of emergency
- 2800/26 . Form, shape
- 2800/262 . . column shaped
- 2800/264 . . compact
- 2800/266 . . curved
- 2800/268 . . cylindrical
- 2800/27 . . profiles
- 2800/272 . . . hollow
- 2800/276 U-shaped
- 2800/278 C-shaped
- 2800/28 . . tubular
- 2800/29 . . forming a unitary piece with another element
- 2800/292 . . having apertures
- 2800/296 . . . Slots
- 2800/298 . . having indentations
- 2800/33 . . having protrusions
- 2800/34 . Form stability
- 2800/342 . . Deformable
- 2800/344 . . . elastically
- 2800/35 . . . of specific parts
- 2800/352 . Frames; Posts
- 2800/353 . . fixed
- 2800/356 . . . horizontal frame members
- 2800/358 . . . vertical frame members or posts
- 2800/36 . . Movable frames
- 2800/362 . . . horizontal frame members
- 2800/364 . . . vertical frame members
- 2800/37 . Length, width adjustment
- 2800/372 . . Telescopic
- 2800/40 . Protection ([E05Y 2400/50](#), [E05Y 2400/52 take precedence](#))
- 2800/402 . . against corrosion
- 2800/404 . . against component faults or failure
- 2800/406 . . against deformation
- 2800/407 . . . plastic deformation
- 2800/409 . . against faulty mounting or coupling
- 2800/41 . . against finger injury
- 2800/412 . . against friction
- 2800/414 . . against high or low temperatures
- 2800/416 . . . against fire
- 2800/42 . . against smoke or gas
- 2800/422 . . against vibration or noise
- 2800/424 . . against unintended use
- 2800/426 . . . against unauthorised use ([E05Y 2400/51](#), [E05Y 2400/522 take precedence](#))
- 2800/428 . . against water
- 2800/43 . . against wear
- 2800/45 . Manufacturing
- 2800/455 . . Extrusion ([in general B29C 48/00](#), [B21C 23/00](#))
- 2800/46 . . Injection moulding ([in general B29C 45/00](#))
- 2800/465 . . Pressing
- 2800/67 . Materials; Strength alteration thereof
- 2800/672 . . Glass
- 2800/674 . . Metal
- 2800/676 . . Plastics
- 2800/678 . . . Elastomers
- 2800/68 . . Combinations of materials
- 2800/682 . . Strength alteration by reinforcing, e.g. by applying ribs
- 2800/684 . . Strength alteration by weakening, e.g. by applying grooves
- 2800/69 . Permanence of use
- 2800/692 . . Temporary use
- 2800/694 . . during manufacturing
- 2800/696 . . during transport or storage
- 2800/70 . Retrofitting of elements
- 2800/71 . Secondary wings, e.g. pass doors
- 2800/72 . Sets of mutually exchangeable elements
- 2800/73 . Single use of elements
- 2800/74 . Specific positions ([E05Y 2400/35 takes precedence](#))
- 2800/742 . . abnormal
- 2800/744 . . . cleaning or service
- 2800/746 . . . emergency or extended
- 2800/748 . . . end
- 2800/75 . . intermediate
- 2900/00 Application of doors, windows, wings or fittings thereof**
- 2900/10 . for buildings or parts thereof
- 2900/102 . . for cold-rooms
- 2900/104 . . for elevators
- 2900/106 . . for garages
- 2900/108 . . for hangars
- 2900/11 . . for industrial buildings
- 2900/112 . . for restrooms
- 2900/114 . . for showers
- 2900/116 . . for sluices
- 2900/13 . . characterised by the type of wing
- 2900/131 . . . Access panels
- 2900/132 . . . Doors
- 2900/134 Fire doors
- 2900/136 Insect doors
- 2900/14 Doors disappearing in pockets of a wall, e.g. so-called pocket doors
- 2900/142 . . . Partition walls
- 2900/144 . . . Security grills
- 2900/146 . . . Shutters
- 2900/148 . . . Windows
- 2900/15 Balcony glazing
- 2900/152 Roof windows
- 2900/154 Skylights
- 2900/20 . for furnitures, e.g. cabinets
- 2900/202 . . for display cabinets
- 2900/204 . . for display counters
- 2900/208 . . for metal cabinets
- 2900/21 . . for safety cabinets
- 2900/212 . . Doors disappearing in pockets in the furniture body
- 2900/30 . for domestic appliances
- 2900/302 . . for built-in appliances
- 2900/304 . . for dishwashers
- 2900/306 . . for freezers
- 2900/308 . . for ovens
- 2900/31 . . for refrigerators
- 2900/312 . . for washing machines
- 2900/40 . for gates
- 2900/402 . . for cantilever gates
- 2900/404 . . for railway platform gates

E05Y

- 2900/50 . for vehicles
- 2900/502 . . for aircraft
- 2900/504 . . for armored vehicles
- 2900/506 . . for buses
- 2900/508 . . for convertibles
- 2900/51 . . for railway cars or mass transit vehicles
- 2900/512 . . for recreational vehicles
- 2900/514 . . for ships
- 2900/516 . . for trucks or trailers
- 2900/518 . . for working vehicles
- 2900/53 . . characterised by the type of wing
 - 2900/531 . . . Doors
 - 2900/532 Back doors or end doors
 - 2900/534 Fuel lids
 - 2900/536 Hoods
 - 2900/538 Interior lids
 - 2900/54 Luggage compartment lids for buses
 - 2900/542 Roof panels
 - 2900/544 Tailboards or sideboards
 - 2900/546 Tailgates
 - 2900/548 Trunk lids
 - 2900/55 Windows
- 2900/60 . for other use
- 2900/602 . . for containers
 - 2900/604 . . . for large containers
- 2900/606 . . for electronic devices
- 2900/608 . . for machines
- 2900/612 . . for manhole covers
- 2900/614 . . for toilet seats or covers