

CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINES OR PUMPS

F01 MACHINES OR ENGINES IN GENERAL; ENGINE PLANTS IN GENERAL; STEAM ENGINES

F01C ROTARY-PISTON OR OSCILLATING-PISTON MACHINES OR ENGINES (internal-combustion aspects [F02B 53/00](#), [F02B 55/00](#))

NOTES

1. This subclass covers:
 - rotary-piston or oscillating-piston engines for elastic fluids, e.g. steam;
 - rotary-piston or oscillating-piston engines for liquids and elastic fluids;
 - rotary-piston or oscillating-piston machines for elastic fluids;
 - rotary-piston or oscillating-piston machines for liquids and elastic fluids.
2. In this subclass, the following expression is used with the meaning indicated:
 - "rotary-piston machine" includes the German expressions "Drehkolbenmaschinen", "Kreiskolbenmaschinen" and "Umlaufkolbenmaschinen".
3. Attention is drawn to the Notes preceding class [F01](#), especially as regards the definitions of "rotary-piston machine", "oscillating-piston machine", "rotary piston", "co-operating members", "movement of co-operating members", "teeth or tooth-equivalents" and "internal-axis".

WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Rotary-piston machines or engines (with axes of co-operating members non parallel F01C 3/00; with the working-chamber walls at least partly resiliently deformable F01C 5/00; with fluid ring or the like F01C 7/00; rotary-piston machines or engines in which the working fluid is exclusively displaced by, or exclusively displaces, one or more reciprocating pistons F01B 13/00)	1/0292 {Ports or channels located in the wrap}
		1/04	. . . of internal-axis type
		1/045 {having a C-shaped piston}
		1/06	. . . of other than internal-axis type (F01C 1/063 takes precedence)
		1/063	. . . with coaxially-mounted members having continuously-changing circumferential spacing between them
		1/067 having cam-and-follower type drive
		1/07 having crankshaft-and-connecting-rod type drive
		1/073 having pawl-and-ratchet type drive
		1/077 having toothed-gearing type drive
1/02	. . . of arcuate-engagement type, i.e. with circular translatory movement of co-operating members, each member having the same number of teeth or tooth-equivalents	1/08	. . . of intermeshing engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing
1/0207	. . . {both members having co-operating elements in spiral form}	1/082	. . . {Details specially related to intermeshing engagement type machines or engines}
1/0215 {where only one member is moving}	1/084 {Toothed wheels}
1/0223 {with symmetrical double wraps}	1/086 {Carter}
1/023 {where both members are moving}	1/088 {Elements in the toothed wheels or the carter for relieving the pressure of fluid imprisoned in the zones of engagement}
1/0238 {with symmetrical double wraps}		
1/0246 {Details concerning the involute wraps or their base, e.g. geometry}	1/10	. . . of internal-axis type with the outer member having more teeth or tooth-equivalents, e.g. rollers, than the inner member
1/0253 {Details concerning the base}		
1/0261 {Details of the ports, e.g. location, number, geometry}	1/101 {Moineau-type}
1/0269 {Details concerning the involute wraps}	1/102 {with a crescent shaped filler element located between the intermeshing elements}
1/0276 {Different wall heights}		
1/0284 {Details of the wrap tips}		

- 1/103 . . . {the two members rotating simultaneously around their respective axes}
- 1/104 . . . {one member having simultaneously a rotational movement about its own axis and an orbital movement}
- 1/105 {and having an articulated driving shaft}
- 1/107 . . . with helical teeth
- 1/113 . . . the inner member carrying rollers intermeshing with the outer member
- 1/12 . . of other than internal-axis type
- 1/123 . . . {with tooth-like elements, extending generally radially from the rotor body cooperating with recesses in the other rotor, e.g. one tooth}
- 1/126 . . . {with elements extending radially from the rotor body not necessarily cooperating with corresponding recesses in the other rotor, e.g. lobes, Roots type}
- 1/14 . . . with toothed rotary pistons
- 1/16 with helical teeth, e.g. chevron-shaped, screw type {(for non-parallel axes of movement [F01C 3/00](#))}
- 1/165 {having more than two rotary pistons with parallel axes}
- 1/18 with similar tooth forms ([F01C 1/16](#) takes precedence)
- 1/20 with dissimilar tooth forms ([F01C 1/16](#) takes precedence)
- 1/22 . . of internal-axis type with equidirectional movement of co-operating members at the points of engagement, or with one of the co-operating members being stationary, the inner member having more teeth or tooth- equivalents than the outer member
- 1/24 . . of counter-engagement type, i.e. the movement of co-operating members at the points of engagement being in opposite directions
- 1/26 . . of internal-axis type
- 1/28 . . of other than internal-axis type
- 1/30 . . having the characteristics covered by two or more groups [F01C 1/02](#), [F01C 1/08](#), [F01C 1/22](#), [F01C 1/24](#) or having the characteristics covered by one of these groups together with some other type of movement between co-operating members
- 1/32 . . having both the movement defined in group [F01C 1/02](#) and relative reciprocation between the co-operating members
- 1/321 . . . {with vanes hinged to the inner member and reciprocating with respect to the inner member}
- 1/322 . . . {with vanes hinged to the outer member and reciprocating with respect to the outer member}
- 1/324 . . . with vanes hinged to the inner member and reciprocating with respect to the outer member
- 1/328 and hinged to the outer member
- 1/332 . . . with vanes hinged to the outer member and reciprocating with respect to the inner member
- 1/336 and hinged to the inner member
- 1/34 . . having the movement defined in group [F01C 1/08](#) or [F01C 1/22](#) and relative reciprocation between the co-operating members
- 1/344 . . . with vanes reciprocating with respect to the inner member
- 1/3441 {the inner and outer member being in contact along one line or continuous surface substantially parallel to the axis of rotation}
- 1/3442 {the surfaces of the inner and outer member, forming the working space, being surfaces of revolution}
- 1/3443 {with a separation element located between the inlet and outlet opening}
- 1/3445 {the vanes having the form of rollers, slippers or the like}
- 1/3446 {the inner and outer member being in contact along more than one line or surface}
- 1/3447 {the vanes having the form of rollers, slippers or the like}
- 1/3448 {with axially movable vanes}
- 1/348 the vanes positively engaging, with circumferential play, an outer rotatable member
- 1/352 the vanes being pivoted on the axis of the outer member
- 1/356 . . . with vanes reciprocating with respect to the outer member
- 1/3562 {the inner and outer member being in contact along one line or continuous surface substantially parallel to the axis of rotation}
- 1/3564 {the surfaces of the inner and outer member, forming the working space, being surfaces of revolution}
- 1/3566 {the inner and outer member being in contact along more than one line or surface}
- 1/3568 {with axially movable vanes}
- 1/36 . . having both the movements defined in sub-groups [F01C 1/22](#) and [F01C 1/24](#)
- 1/38 . . having the movement defined in group [F01C 1/02](#) and having a hinged member ([F01C 1/32](#) takes precedence)
- 1/39 . . . with vanes hinged to the inner as well as to the outer member
- 1/40 . . having the movement defined in group [F01C 1/08](#) or [F01C 1/22](#) and having a hinged member
- 1/44 . . . with vanes hinged to the inner member
- 1/46 . . . with vanes hinged to the outer member
- 3/00 Rotary-piston machines or engines with non-parallel axes of movement of co-operating members (with the working-chamber walls being at least partly resiliently deformable [F01C 5/00](#))**
- 3/02 . . the axes being arranged at an angle of 90 degrees
- 3/025 . . . {of intermeshing engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing}
- 3/04 . . with axially sliding vanes
- 3/06 . . the axes being arranged otherwise than at an angle of 90 degrees
- 3/08 . . of intermeshing-engagement type, i.e. with engagement of co-operating members similar to that of toothed gearing
- 3/085 . . . {the axes of cooperating members being on the same plane}
- 5/00 Rotary-piston machines or engines with the working-chamber walls at least partly resiliently deformable**
- 5/02 . . the resiliently-deformable wall being part of the inner member, e.g. of a rotary piston
- 5/04 . . the resiliently-deformable wall being part of the outer member, e.g. of a housing

5/06	• the resiliently-deformable wall being a separate member	19/085	• • {Elements specially adapted for sealing of the lateral faces of intermeshing-engagement type machines or engines, e.g. gear machines or engines}
5/08	• • of tubular form, e.g. hose		
7/00	Rotary-piston machines or engines with fluid ring or the like	19/10	• Sealings for working fluids between radially and axially movable parts
9/00	Oscillating-piston machines or engines	19/12	• for other than working fluid
9/002	• {the piston oscillating around a fixed axis}	19/125	• • {Shaft sealings specially adapted for rotary or oscillating-piston machines or engines}
9/005	• {the piston oscillating in the space, e.g. around a fixed point (rotary piston machines or engines with non-parallel axes of rotation between co-operating members F01C 3/00)}	20/00	Control of, monitoring of, or safety arrangements for, machines or engines
9/007	• {the points of the moving element describing approximately an alternating movement in axial direction with respect to the other element}	20/02	• specially adapted for several machines or engines connected in series or in parallel
11/00	Combinations of two or more machines or engines, each being of rotary-piston or oscillating-piston type (F01C 13/00 takes precedence; combinations of two or more pumps F04; fluid gearing F16H)	20/04	• specially adapted for reversible machines or engines
11/002	• {of similar working principle}	20/06	• specially adapted for stopping, starting, idling or no-load operation
11/004	• • {and of complementary function, e.g. internal combustion engine with supercharger}	20/08	• characterised by varying the rotational speed
11/006	• {of dissimilar working principle}	20/10	• characterised by changing the positions of the inlet or outlet openings with respect to the working chamber
11/008	• • {and of complementary function, e.g. internal combustion engine with supercharger}	20/12	• • using sliding valves
	NOTE	20/125	• • • {with sliding valves controlled by the use of fluid other than the working fluid}
	Multi-stage steam engines or similar machines are not considered as having complementary function	20/14	• • using rotating valves
13/00	Adaptations of machines or engines for special use; Combinations of engines with devices driven thereby	20/16	• • using lift valves
13/02	• for driving hand-held tools or the like	20/18	• characterised by varying the volume of the working chamber (by changing the positions of inlet or outlet openings F01C 20/10)
13/04	• for driving pumps or compressors	20/185	• • {by varying the useful pumping length of the cooperating members in the axial direction}
17/00	Arrangements for drive of co-operating members, e.g. for rotary piston and casing	20/20	• • by changing the form of the inner or outlet contour of the working chamber
17/02	• of toothed-gearing type (F01C 1/077 takes precedence)	20/22	• • by changing the eccentricity between cooperating members
17/04	• of cam-and-follower type (F01C 1/067 takes precedence)	20/24	• characterised by using valves for controlling pressure or flow rate, e.g. discharge valves (F01C 20/10 takes precedence)
17/06	• using cranks, universal joints or similar elements (F01C 1/07 takes precedence)	20/26	• • using bypass channels
17/063	• • {with only rolling movement}	20/265	• • • {being obtained by displacing a lateral sealing face}
17/066	• • {with an intermediate piece sliding along perpendicular axes, e.g. Oldham coupling}	20/28	• Safety arrangements; Monitoring
19/00	Sealing arrangements in rotary-piston machines or engines (sealings in general F16J)	21/00	Component parts, details or accessories not provided for in groups F01C 1/00 - F01C 20/00
19/005	• {Structure and composition of sealing elements such as sealing strips, sealing rings and the like; Coating of these elements (vane construction F01C 21/0809 ; piston rings and ring sealings of similar construction in general F16J 9/00)}	21/001	• {Injection of a fluid in the working chamber for sealing, cooling and lubricating (sealing only F01C 17/00 ; lubrication only F01C 21/04 ; cooling only F01C 21/06 ; injecting water or steam in internal combustion engines F02B 47/02 , F02D 21/00 , F02M 25/00)}
19/02	• Radially-movable sealings for working fluids	21/002	• • {with control systems for the injection of the fluid}
19/025	• • {Radial sealing elements specially adapted for intermeshing engagement type machines or engines, e.g. gear machines or engines}	21/003	• {Systems for the equilibration of forces acting on the elements of the machine (interstice adjustment other than by fluid pressure F01C 21/102)}
19/04	• • of rigid material	21/005	• • {Internal leakage control}
19/06	• • of resilient material	21/006	• • {Equalization of pressure pulses (silencing for compressors F04C 29/06)}
19/08	• Axially-movable sealings for working fluids	21/007	• {General arrangements of parts; Frames and supporting elements}
		21/008	• {Driving elements, brakes, couplings, transmissions specially adapted for rotary or oscillating-piston machines or engines (brakes, couplings, transmissions per se F16 , B60)}

F01C

- 21/02 . Arrangements of bearings ([bearing constructions F16C](#))
- 21/04 . Lubrication ([of machines or engines in general F01M](#))
- 21/045 . . {Control systems for the circulation of the lubricant}
- 21/06 . Heating; Cooling ([of machines or engines in general F01P](#)); Heat insulation ([heat insulation in general F16L](#))
- 21/08 . Rotary pistons ([reciprocating pistons in general F16J](#))
 - 21/0809 . . {Construction of vanes or vane holders}
 - 21/0818 . . . {Vane tracking; control therefor}
 - 21/0827 {by mechanical means}
 - 21/0836 {comprising guiding means, e.g. cams, rollers}
 - 21/0845 {comprising elastic means, e.g. springs}
 - 21/0854 {by fluid means}
 - 21/0863 {the fluid being the working fluid}
 - 21/0872 {the fluid being other than the working fluid}
 - 21/0881 . . . {the vanes consisting of two or more parts}
 - 21/089 . . . {for synchronised movement of the vanes}
- 21/10 . Outer members for co-operation with rotary pistons; Casings ([casings for rotary engines or machines in general F16M](#))
 - 21/102 . . {Adjustment of the interstices between moving and fixed parts of the machine by means other than fluid pressure}
 - 21/104 . . {Stators; Members defining the outer boundaries of the working chamber}
 - 21/106 . . . {with a radial surface, e.g. cam rings}
 - 21/108 . . . {with an axial surface, e.g. side plates}
- 2021/12 . {Control of working fluid admission or discharge}
- 2021/125 . . {Arrangements for supercharging the working space}
 - 2021/14 . . {for variable fluid distribution}
 - 2021/16 . {Other regulation or control}
 - 2021/1606 . . {Variation of the working chamber}
 - 2021/1612 . . . {by changing the eccentricity of an element with respect to another element}
 - 2021/1618 . . . {by changing the positions of the inlet and outlet openings with respect to the working chambers}
 - 2021/1625 {with sliding or rotating valves, adjustable in position}
 - 2021/1631 {with sliding valves controlled by the use of fluid other than the working fluid}
 - 2021/1637 . . . {by changing the form of the radially inner or the radially outer contour of the working chamber}
 - 2021/1643 . . {by using valves regulating pressure and flow rate, e.g. discharge valves}
 - 2021/165 . . . {using a by-pass channel}
 - 2021/1656 {being obtained by displacing a lateral sealing face}
 - 2021/1662 . . . {with venting means}
 - 2021/1668 . . {with several machines or engines connected in series or in parallel}
 - 2021/1675 . . {with reversible machines or engines}
 - 2021/1681 . . {by varying the rotational speed}
 - 2021/1687 . . {Safety arrangements}
 - 2021/1693 . . {Stopping or starting, idling or no-load operation}
 - 21/18 . Arrangements for admission or discharge of the working fluid, e.g. constructional features of the inlet or outlet
 - 21/183 . . {Arrangements for supercharging the working space ([similar arrangements for internal combustion engines F02B 33/00, F02B 27/00](#))}
 - 21/186 . . {for variable fluid distribution}