

CPC COOPERATIVE PATENT CLASSIFICATION

F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

ENGINEERING IN GENERAL

F16 ENGINEERING ELEMENTS AND UNITS; GENERAL MEASURES FOR PRODUCING AND MAINTAINING EFFECTIVE FUNCTIONING OF MACHINES OR INSTALLATIONS; THERMAL INSULATION IN GENERAL

F16B DEVICES FOR FASTENING OR SECURING CONSTRUCTIONAL ELEMENTS OR MACHINE PARTS TOGETHER, e.g. NAILS, BOLTS, CIRCLIPS, CLAMPS, CLIPS, WEDGES, JOINTS OR JOINTING (couplings for transmitting rotation [F16D](#))

NOTES

1. Attention is drawn to:
 - a. the Note following group [E04B 1/38](#);
 - b. the following places:

A44B	Buckles, slide fasteners
A47G 3/00	Ornamental heads for nails, screws, or the like
B42F 3/00	Means, not using staples, for attaching sheets temporarily together
{C14B 17/08}	{Fastening devices, e.g. clips for leather-stretching used in apparatus or machines for manufacturing or treating skins, hides, leathers or furs}
E01B 9/10	Screws or bolts for railway sleepers
E01B 11/00	Rail joints
E04	Connections for building
E04D 13/08	Clamping means for down pipes for roof drainage
E04G 5/04	Fastening scaffolds against buildings
E04G 7/00	Scaffolding couplings
E05C	Bolts for fasteners for wings, specially for doors or windows
F16C 29/10	Locking bearings for parts moving only linearly
F16G 17/00	Hooks as integral parts of chains
F16L	Pipe joints
F16L 3/00	Supports for pipes, cables or protective tubing, e.g. hangers, holders, clamps, cleats, clips, brackets
F16L 33/02	Clips for connecting hoses to rigid members
H01F 7/00	Magnetic holding devices
H02N 13/00	Electrostatic holding devices.
2. Groups [F16B 2/00](#) - [F16B 47/00](#) take precedence over group [F16B 1/00](#).
3. {In this main group, it is desirable to add the indexing codes of [F16B 2200/00](#)}

WARNINGS

1. The following IPC groups are not in the CPC scheme. The subject matter for these IPC groups is classified in the following CPC groups:

F16B 7/08	covered by	F16B 5/12 , F16B 7/04 , F16L 3/00
F16B 7/12	covered by	F16B 7/105
F16B 13/13	covered by	F16B 13/002 , F16B 13/12
F16B 25/02	covered by	F16B 25/103
F16B 25/04	covered by	F16B 25/00 , F16B 25/106
F16B 25/06	covered by	F16B 25/00 , F16B 25/106
F16B 25/08	covered by	F16B 25/00 , F16B 25/106
F16B 37/10	covered by	F16B 37/0842 , F16B 37/0871
2. {In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.}

1/00 **Devices for securing together, or preventing relative movement between, constructional elements or machine parts**

[2001/0007](#) . {Fasteners made by sintering powders}

[1/0014](#) . {by the use of a shape-memory material}

[2001/0021](#) . {Friction-reducing coatings}

[2001/0028](#) . {by the use of a material of the hooks-and-loops type}

F16B

- 2001/0035 . {by the use of a magnetic material}
 - 2001/0042 . {by the use of an explosive charge ([F16B 19/125](#), [F16B 31/005](#) take precedence)}
 - 1/005 . {by the use of a hydraulic action}
 - 1/0057 . {by the use of a pneumatic action}
 - 2001/0064 . {and establishing a good electrical connection}
 - 1/0071 . {with markings, colours, indicators or the like (for indicating tensile load [F16B 31/02](#))}
 - 2001/0078 . {having differing thermal expansion coefficients}
 - 2001/0085 . {Ceramic-to-metal-connections}
 - 2001/0092 . {with means for avoiding incorrect assembly or positioning}
 - 1/02 . Means for securing elements of mechanisms after operation (means for bringing members to rest [F16D](#))
 - 1/04 . . disengaged by movement of the actuating member of the element (locking of actuators [G05G](#), e.g. [G05G 5/00](#))
- Fastenings for constructional elements or machine parts in general** (couplings for transmitting rotation [F16D](#))
- 2/00 Friction-grip releasable fastenings** (for cables or ropes, e.g. cleats [F16G 11/00](#)){(connections of rods or tubes, e.g. of non-circular section, mutually, including resilient connections [F16B 7/00](#))}
 - 2/005 . {Means to increase the friction-coefficient}
 - 2/02 . Clamps, i.e. with gripping action effected by positive means other than the inherent resistance to deformation of the material of the fastening
 - 2/04 . . internal, i.e. with spreading action ([F16B 2/14](#) - [F16B 2/18](#) take precedence)
 - 2/06 . . external, i.e. with contracting action ([F16B 2/14](#) - [F16B 2/18](#) take precedence)
 - 2/065 . . . {using screw-thread elements ([F16B 2/08](#) - [F16B 2/12](#) take precedence)}
 - 2/08 . . . using bands
 - 2/10 . . . using pivoting jaws
 - 2/12 . . . using sliding jaws
 - 2/14 . . using wedges
 - 2/16 . . using rollers or balls {(clamps for rods or tubes telescopically engaged [F16B 7/1409](#); used in anti-theft monitors, e.g. as used for articles of clothing in shops [E05B 73/0017](#))}
 - 2/18 . . using cams, levers, eccentrics, or toggles {(for connections of rods or tubes engaged telescopically [F16B 7/1418](#), [F16B 7/1427](#), [F16B 7/1454](#))}
 - 2/185 . . . {using levers}
 - 2/20 . Clips, i.e. with gripping action effected solely by the inherent resistance to deformation of the material of the fastening
 - 2/205 . . {with two stable positions}
 - 2/22 . . of resilient material, e.g. rubbery material {([F16B 2/205](#) takes precedence)}
 - 2/24 . . . of metal
 - 2/241 {of sheet metal}
 - 2/243 {internal, i.e. with spreading action}
 - 2/245 {external, i.e. with contracting action}
- 2/246 {the clip being released by tilting the clip or a part thereof to a position in which the axis of the openings surrounding the gripped elements is parallel to, or coincides with, the axis of the gripped elements}
 - 2/248 {of wire}
 - 2/26 . . of pliable, non-resilient material, e.g. plant tie
 - 3/00 Key-type connections; Keys** ([F16B 2/00](#) takes precedence; for rods or tubes mutually [F16B 7/00](#))
 - 3/005 . {the key being formed by solidification of injected material (joining of preformed parts by applying molten plastics [B29C 65/40](#); non-disconnectible pipe joints obtained using a hardenable filler [F16L 13/11](#))}
 - 3/04 . using keys formed of wire or other flexible material, to be inserted through an opening giving access to grooves in the adjacent surfaces of the parts to be connected
 - 3/06 . using taper sleeves
 - 4/00 Shrinkage connections, e.g. assembled with the parts at different temperature; Force fits** (restricted to metal parts or objects [B23P 11/02](#)); **Non-releasable friction-grip fastenings** ([F16B 2/00](#) takes precedence; {using members with a shape-memory material [F16B 1/0014](#))}
 - 4/002 . {engaging or disengaging by means of fluid pressure}
 - 4/004 . {Press fits, force fits, interference fits, i.e. fits without heat or chemical treatment ([F16B 4/002](#) takes precedence)}
 - 4/006 . {Shrinkage connections, e.g. assembled with the parts being at different temperature}
 - 4/008 . . {using heat-recoverable, i.e. shrinkable, sleeves}
 - 5/00 Joining sheets or plates {, e.g. panels,} to one another or to strips or bars parallel to them** (([F16B 17/00](#) takes precedence;) by sticking together [F16B 11/00](#); dowel connections [F16B 13/00](#); pins, including deformable elements [F16B 19/00](#); covering of walls [E04F 13/00](#); fastening signs, plates, panels or boards to a supporting structure, fastening readily-detachable elements, e.g. letters to signs, plates, panels, or boards, [G09F 7/00](#))
 - 5/0004 . {Joining sheets, plates or panels in abutting relationship ([F16B 5/01](#) takes precedence)}
 - 5/0008 . . {by moving the sheets, plates or panels substantially in their own plane, perpendicular to the abutting edge}
 - 5/0012 . . . {a tongue on the edge of one sheet, plate or panel co-operating with a groove in the edge of another sheet, plate or panel}
 - 5/0016 {with snap action}
 - 5/002 . . . {both sheets, plates or panels having a groove, e.g. with strip-type connector}
 - 5/0024 . . . {the sheets, plates or panels having holes, e.g. for dowel- type connections}
 - 5/0028 . . . {using I-shaped connectors (with flanges moving towards each other [F16B 5/0068](#))}
 - 5/0032 . . {by moving the sheets, plates, or panels or the interlocking key parallel to the abutting edge}
 - 5/0036 . . . {and using hook and slot or keyhole-type connections}
 - 5/004 . . . {and using C-shaped clamps}

- 5/0044 . . . {and using interlocking keys of circular, square, rectangular or like shape}
- 5/0048 {hinge-like}
- 5/0052 . . . {the interlocking key acting as a dovetail-type key}
- 5/0056 . . {by moving the sheets, plates or panels or the interlocking key perpendicular to the main plane}
- 5/006 . . . {and using ring-shaped clamps}
- 5/0064 . . . {and using C-shaped clamps}
- 5/0068 . . . {and using I-shaped clamps with flanges moving towards each other}
- 5/0072 {and using screw-thread}
- 5/0076 . . . {and using expanding clamps}
- 5/008 . . {by a rotating or sliding and rotating movement}
- 5/0084 . . {characterised by particular locking means}
- 5/0088 . . . {with locking means moving substantially perpendicular to the main plane, e.g. pins, screws}
- 5/0092 . . . {with locking means rotating about an axis parallel to the main plane and perpendicular to the abutting edge, e.g. screw, bayonet}
- 5/0096 . {by using permanent deformation}
- 5/01 . by means of fastening elements specially adapted for honeycomb panels
- 5/02 . by means of fastening members using screw-thread ([F16B 5/0004](#) takes precedence); construction of screw-threaded connections [F16B 25/00](#) - [F16B 39/00](#))
- 5/0208 . . {using panel fasteners, i.e. permanent attachments allowing for quick assembly}
- 5/0216 . . {the position of the plates to be connected being adjustable}
- 5/0225 . . . {allowing for adjustment parallel to the plane of the plates}
- 5/0233 . . . {allowing for adjustment perpendicular to the plane of the plates}
- 5/0241 . . {with the possibility for the connection to absorb deformation, e.g. thermal or vibrational}
- 5/025 . . {specially designed to compensate for misalignment or to eliminate unwanted play}
- 5/0258 . . {using resiliently deformable sleeves, grommets or inserts ([F16B 43/001](#) takes precedence)}
- 5/0266 . . {using springs}
- 5/0275 . . {the screw-threaded element having at least two axially separated threaded portions ([F16B 5/0283](#) takes precedence)}
- 5/0283 . . {with an externally threaded sleeve around the neck or the head of the screw-threaded element for adjustably fastening a plate or frame or the like to a fixed element}
- 5/0291 . . {the threaded element being driven through the edge of a sheet plate with its axis in the plane of the plate}
- 5/04 . by means of riveting ([rivets F16B 19/04](#))
- 5/045 . . {without the use of separate rivets}
- 5/06 . by means of clamps or clips ([F16B 5/0004](#) takes precedence); friction-grip releasable fastenings in general [F16B 2/00](#))
- 5/0607 . . {joining sheets or plates to each other ([F16B 5/0692](#), [F16B 21/082](#) take precedence)}
- 5/0614 . . . {in angled relationship}
- 5/0621 . . . {in parallel relationship (fastened by a drive-pin [F16B 19/1081](#); fastened by a device locking by rotation [F16B 21/02](#))}
- 5/0628 {allowing for adjustment parallel or perpendicular to the plane of the sheets or plates}
- 5/0635 {fastened over the edges of the sheets or plates}
- 5/0642 {the plates being arranged one on top of the other and in full close contact with each other}
- 5/065 {the plates being one on top of the other and distanced from each other, e.g. by using protrusions to keep contact and distance}
- 5/0657 {at least one of the plates providing a raised structure, e.g. of the doghouse type, for connection with the clamps or clips of the other plate}
- 5/0664 {at least one of the sheets or plates having integrally formed or integrally connected snap-in-features}
- 2005/0671 {with unlocking by rotation}
- 2005/0678 . . . {in abutting relationship}
- 5/0685 . . {Joining sheets or plates to strips or bars ([F16B 5/0692](#) takes precedence)}
- 5/0692 . . {joining flexible sheets to other sheets or plates or to strips or bars (tent fastenings [E04H 15/64](#); coping elements for swimming pools with fixing means for sealing foil [E04H 4/142](#); greenhouses of flexible synthetic material [A01G 9/1407](#); end or aperture-closing arrangements or devices for sacks or bags [B65D 33/16](#))}
- 5/07 . by means of multiple interengaging protrusions on the surfaces, e.g. hooks, coils,
- 5/08 . by means of welds or the like ([welding B23K](#))
- 5/10 . by means of bayonet connections ([F16B 5/0092](#) takes precedence); fastening devices locking by rotation [F16B 21/02](#))
- 5/12 . Fastening strips or bars to sheets or plates, e.g. rubber strips, decorative strips for motor vehicles, by means of clips ([friction- grip releasable fastenings in general F16B 2/00](#); fastening rods or tubular parts to flat surfaces at an angle [F16B 9/00](#))
- 5/121 . . {fastened over the edge(s) of the sheet(s) or plate(s)}
- 5/123 . . {Auxiliary fasteners specially designed for this purpose}
- 5/125 . . . {one of the auxiliary fasteners is comprising wire or sheet material or is made thereof}
- 5/126 . . {at least one of the sheets, plates, bars or strips having integrally formed or integrally connected snap-in-features}
- 5/128 . . {a strip with a C- or U-shaped cross section being fastened to a plate such that the fastening means remain invisible, e.g. the fastening being completely enclosed by the strip}
- 7/00 Connections of rods or tubes, e.g. of non-circular section, mutually, including resilient connections** ([F16B 11/008](#), [F16B 17/00](#) take precedence); umbrella frames [A45B 25/02](#); welding or soldering of connections [B23K](#); vehicle connections in general [B60D](#); railway couplings [B61G](#); bicycle frames [B62K](#); couplings for transmitting rotation [F16D](#); couplings for tubes conveying fluids [F16L](#))
- 7/02 . with conical parts

- 7/025 . . {with the expansion of an element inside the tubes due to axial movement towards a wedge or conical element (for rods or tubes telescopically engaged [F16B 7/1463](#))}
- 7/04 . Clamping or clipping connections (friction-grip releasable fastenings in general [F16B 2/00](#))
- 7/0406 . . {for rods or tubes being coaxial ([F16B 7/10](#) takes precedence)}
- 7/0413 . . . {for tubes using the innerside thereof ([F16B 7/025](#) takes precedence)}
- 7/042 {with a locking element, e.g. pin, ball or pushbutton, engaging in a hole in the wall of at least one tube}
- 7/0426 . . . {for rods or for tubes without using the innerside thereof}
- 7/0433 . . {for rods or tubes being in parallel relationship}
- 7/044 . . {for rods or tubes being in angled relationship}
- 7/0446 . . . {for tubes using the innerside thereof ([F16B 7/025](#) takes precedence)}
- 7/0453 {the tubes being drawn towards each other ([F16B 7/0473](#) takes precedence)}
- 7/046 {by rotating an eccentric-mechanism}
- 7/0466 {by a screw-threaded stud with a conical tip acting on an inclined surface}
- 7/0473 {with hook-like parts gripping, e.g. by expanding, behind the flanges of a profile}
- 7/048 . . . {for rods or for tubes without using the innerside thereof}
- 7/0486 {forming an abutting connection of at least one tube}
- 7/0493 {forming a crossed-over connection}
- 7/06 . Turnbuckles (for cables, ropes, or wire [F16G 11/12](#))
- 7/10 . Telescoping systems ({for vertically adjustable chairs [A47C 3/20](#); telescopic steering columns [B62D 1/18](#)}; for scaffolding [E04G 25/04](#); {telescopic masts, poles or the like [E04H 12/182](#); telescopic door or window holders [E05C 17/30](#)}; telescope props for mining [E21D 15/14](#) - [E21D 15/46](#); stands or trestles as supports for apparatus or articles placed thereon ([F16M 11/26](#))}
- 7/105 . . {locking in discrete positions, e.g. in extreme extended position}
- 7/14 . . locking in intermediate {non-discrete} positions {(the rod or tube being locked by a tilting clip [F16B 2/246](#))}
- 7/1409 . . . {with balls or rollers urged by an axial displacement of a wedge or a conical member}
- 7/1418 . . . {with a clamping collar or two split clamping rings tightened by a screw or a cammed latch member}
- 7/1427 . . . {with cammed or eccentric surfaces co-operating by relative rotation of the telescoping members or by rotation of an external collar}
- 7/1436 {with rollers or balls}
- 7/1445 . . . {with a rubber bushing gripping inside the outer telescoping member by a radial expansion due to its axial compression ([F16B 7/1463](#) takes precedence)}
- 7/1454 . . . {with a clamp locking the telescoping members by swinging a handle provided with a locking cam ([F16B 7/1418](#) takes precedence)}
- 7/1463 {with the expansion of an element inside the outer telescoping member due to the axial movement towards a wedge or a conical member}
- 7/1472 . . . {with a clamping screw perpendicular to the axis of the telescoping members}
- 7/1481 . . . {with a gripping helical spring}
- 7/149 . . . {with a sleeve or ring having a tapered or conical surface ([F16B 7/1463](#) takes precedence)}
- 7/16 . . . locking only against movement in one direction
- 7/18 . using screw-thread elements {([F16B 7/025](#) takes precedence; for turnbuckles [F16B 7/06](#))}
- 7/182 . . {for coaxial connections of two rods or tubes}
- 7/185 . . {with a node element}
- 7/187 . . {with sliding nuts or other additional connecting members for joining profiles provided with grooves or channels (channel nuts [per se](#) [F16B 37/045](#))}
- 7/20 . using bayonet connections
- 7/22 . using hooks or like elements
- 9/00** **Connections of rods or tubular parts to flat surfaces at an angle** ({with a part of or on one member entering a hole in the other and involving plastic deformation [F16B 17/006](#)}; friction-grip releasable fastenings in general [F16B 2/00](#); making press-fit connections [B23P 11/00](#), [B23P 19/00](#); fluid-tight connecting of pipes to reservoirs, sheets, or the like [F16L](#), e.g. joining pipes {or rods conveying fluids} to walls [F16L 41/00](#))
 - 9/01 . {Welded or bonded connections}
 - 9/02 . Detachable connections {([F16B 9/05](#) – [F16B 9/09](#) take precedence)}
 - 9/05 . {by way of an intermediate member}
 - 9/052 . . {the intermediate member having a radial flange secured to the flat surface}
 - 9/054 . . {the intermediate member being threaded}
 - 9/056 . . {the intermediate member extending through the flat surface; the rod or tubular part extending through the flat surface}
 - 9/058 . . {the intermediate member being secured to the rod by transverse fasteners}
 - 9/07 . {involving plastic or elastic deformation when assembling (involving plastic deformation with a part of or on one member entering a hole in the other [F16B 17/006](#))}
 - 9/09 . {rods and flat surfaces interengaging by projections and mating sockets}
- 11/00** **Connecting constructional elements or machine parts by sticking or pressing them together, e.g. cold pressure welding (non-electric welding in general [B23K](#); methods of using adhesives independently of the form of the surfaces joined [C09J 5/00](#))**
 - 11/002 . {by pressing the elements together so as to obtain plastic deformation (shrinkage connections, force fits [F16B 4/00](#); pin-and-hole connections involving plastic deformation [F16B 17/00](#))}
 - 11/004 . {by cold pressure welding}
 - 11/006 . {by gluing (gluing of plastics material [B29C 65/48](#))}
 - 11/008 . . {of tubular elements or rods in coaxial engagement}

- 12/00 Jointing of furniture or the like, e.g. hidden from exterior** (F16B 2/00 - F16B 11/00 take precedence; fastening means per se F16B 13/00 - F16B 47/00; wood-working B27)
- 12/02 . Joints between panels and corner posts
- 12/04 . Non-loosenable joints for non-metal furniture parts, e.g. glued
- 2012/043 . . {using carpentry joints other than mortise and tenon joints, e.g. using multiple tenons}
- 2012/046 . . {using mortise and tenon joints}
- 12/06 . Non-loosenable joints for metal furniture parts
- 12/08 . . without use of separate connecting elements
- 12/10 . using pegs, bolts, tenons, clamps, clips, or the like (glued F16B 12/04; fastening means per se F16B 15/00 - F16B 47/00)
- 2012/103 . . {Sleeves or dowels for connection fittings}
- 2012/106 . . {Connection bolts for connection fittings}
- 12/12 . . for non-metal furniture parts, e.g. made of wood, of plastics
- 12/125 . . . {using mortise and tenon joints}
- 12/14 . . . using threaded bolts or screws
- 2012/145 {Corner connections}
- 12/16 using self-tapping screws
- 12/18 using drawing bars
- 12/20 . . . using clamps, clips, wedges, sliding bolts, or the like
- 12/2009 {actuated by rotary motion}
- 2012/2018 {pin and drum securing device; drum has cam surface to engage the head of the pin}
- 12/2027 {with rotating excenters or wedges}
- 12/2036 {with rotating excenters or wedges acting on a head of a pin or screw}
- 2012/2045 {pin and drum securing device; drum has screw to engage the head of the pin}
- 12/2054 {with engaging screw threads as securing means for limiting movement}
- 12/2063 {with engaging screw threads as tightening means}
- 2012/2072 {Pin and drum securing devices; Drums having lever with cam surface to engage the head of the pin}
- 2012/2081 {having a fitting providing slanted access for a screwdriver as actuator}
- 2012/209 {having an integrated lever as actuator}
- 12/22 . . . using keyhole-shaped slots and pins
- 12/24 . . . using separate pins, dowels, or the like
- 12/26 . . . using snap-action elements
- 12/28 . . for metal furniture parts
- 12/30 . . . using threaded bolts
- 12/32 . . . using clamps, clips, wedges, sliding bolts, or the like
- 12/34 . . . using keyhole-shaped slots and pins
- 12/36 . . . using separate pins, dowels or the like
- 12/38 . . . using snap-action elements
- 12/40 . Joints for furniture tubing
- 2012/403 . . {with inserts for joining tubes coaxially}
- 2012/406 . . {Cove joints for joining two cylindrical members}
- 12/42 . . connecting furniture tubing to non-tubular parts {(connecting table tops to underframes A47B 13/003)}
- 12/44 . Leg joints; Corner joints
- 2012/443 . . {with two-dimensional corner element, the legs thereof being inserted in hollow frame members}
- 2012/446 . . {with three-dimensional corner element, the legs thereof being inserted in hollow frame members}
- 12/46 . . Non-metal corner connections
- 2012/463 . . . {for wooden members without additional elements}
- 2012/466 . . . {using mortise and tenon joints}
- 12/48 . . Non-metal leg connections (F16B 12/46 takes precedence)
- 12/50 . . Metal corner connections
- 2012/505 . . . {having a corner insert which is inserted in mitered profiled members}
- 12/52 . . Metal leg connections (F16B 12/50 takes precedence)
- 12/54 . Fittings for bedsteads or the like
- 12/56 . . Brackets for bedsteads; Coupling joints consisting of bolts or the like; Latches therefor
- 12/58 . . Tapered connectors for bed rails
- 12/60 . . Fittings for detachable side panels
- 13/00 Dowels or other devices fastened in walls or the like by inserting them in holes made therein for that purpose** (nails F16B 15/00; self-locking pins or bolts in general, stud-and-socket releasable fastenings F16B 21/00; dowels or bolts for railroad sleepers E01B 9/00; ans means for anchoring structural elements or bulkheads specially adapted to foundation engineering E02D 5/74; bolts or dowels used while laying bricks or casting concrete sleepers E04B 1/38; setting anchoring bolts in shafts, tunnels or galleries E21D 20/00; anchoring bolts for shafts, tunnels or galleries E21D 21/00)
- 13/001 . {with means for preventing rotation of the dowel}
- 13/002 . {self-cutting}
- 13/003 . . {with a separate drilling bit attached to or surrounded by the dowel element}
- 13/004 . . {with a drilling sleeve driven against a tapered or spherical plug}
- 13/005 . {formed in integral series but easily separable}
- 2013/006 . {with sealing means}
- 2013/007 . {to be fastened in undercut holes}
- 2013/008 . {used for mining purposes}
- 2013/009 . {Double sleeve dowels, i.e. the first sleeve is fixed in a hole by the action of a second sleeve and one of the sleeves receives a nail, a screw or the like}
- 13/02 . in one piece with protrusions or ridges on the shaft
- 13/025 . . {of rolled sheet material}
- 13/04 . with parts gripping in the hole or behind the reverse side of the wall after inserting from the front ((F16B 13/002 and F16B 13/12 take precedence;) friction-grip releasable fastenings in general F16B 2/00)
- 13/045 . . {having axially compressing parts allowing the clamping of an object tightly to the wall}
- 13/06 . . combined with expanding sleeve {(F16B 13/045 and F16B 13/08 take precedence)}
- 13/061 . . . {of the buckling type}
- 13/063 . . . {by the use of an expander}
- 13/065 {fastened by extracting the screw, nail or the like}
- 13/066 {fastened by extracting a separate expander-part, actuated by the screw, nail or the like}
- 13/068 {expanded in two or more places}

- 13/08 . . with separate {or non-separate} gripping parts moved into their final position in relation to the body of the device without further manual operation
- 13/0808 . . . {by a toggle-mechanism}
- 13/0816 . . . {with a wedging drive-pin}
- 13/0825 . . . {with a locking element, e.g. sleeve, ring or key co-operating with a cammed or eccentric surface of the dowel body}
- 13/0833 . . . {with segments or fingers expanding or tilting into an undercut hole ([F16B 13/0858](#) takes precedence)}
- 13/0841 . . . {with a deformable sleeve member driven against the abutting surface of the head of the bolt or of a plug}
- 13/085 . . . {with a drive-nail deflected by an inclined surface in the dowel body ([nails with spreading shaft F16B 15/04](#))}
- 13/0858 . . . {with an expansible sleeve or dowel body driven against a tapered or spherical expander plug ([F16B 13/004](#) takes precedence)}
- 13/0866 . . . {with prongs penetrating into the wall of the hole by a retractile movement of a threaded member}
- 13/0875 . . . {with elastic discs or spring washers anchoring in the hole}
- 13/0883 . . . {with split rings or wire between the threads of the dowel body or in grooves near a conical surface ([F16B 13/0825](#) takes precedence)}
- 13/0891 . . . {with a locking element, e.g. wedge, key or ball moving along an inclined surface of the dowel body ([F16B 13/0816](#), [F16B 13/0825](#), [F16B 13/0883](#) take precedence)}
- 13/10 . . with separate gripping parts moved into their final position in relation to the body of the device by a separate operation ([F16B 13/06](#) takes precedence)
- 13/12 . Separate metal {or non-separate or non-metal} dowel sleeves fastened by inserting the screw, nail or the like {([F16B 13/0808](#) takes precedence)}
- 13/122 . . {made from a sheet-metal blank}
- 13/124 . . {fastened by inserting a threaded element, e.g. screw or bolt ([F16B 13/122](#), [F16B 13/128](#) take precedence)}
- 13/126 . . {fastened by inserting an unthreaded element, e.g. pin or nail ([F16B 13/122](#), [F16B 13/128](#) take precedence)}
- 13/128 . . {with extending protrusions, e.g. discs, segments, ridges, fingers or tongues ([F16B 13/122](#) takes precedence)}
- 13/14 . Non-metallic plugs or sleeves {(not used, [see F16B 13/002- F16B 13/12](#))}; Use of liquid, loose solid or kneadable material therefor
- 13/141 . . {Fixing plugs in holes by the use of settable material}
- 13/142 . . . {characterised by the composition of the setting material or mixture ([F16B 13/143](#) takes precedence)}
- 13/143 . . . {using frangible cartridges or capsules containing the setting components}
- 13/144 {characterised by the shape or configuration or material of the frangible cartridges or capsules}
- 13/145 {characterised by the composition of the setting agents contained in the frangible cartridges or capsules}
- 13/146 . . . {with a bag-shaped envelope or a tubular sleeve closed at one end, e.g. with a sieve-like sleeve, or with an expandable sheath}
- 2013/147 . . . {Grout with reinforcing elements or with fillers, e.g. fibres, flakes, balls, wires}
- 2013/148 . . . {Means for inhibiting adhesion between dowel or anchor bolt parts and the surrounding grouting composition}
- Fastening means without screw-thread (horseshoe nails [A01L 7/10](#); nails for footwear [A43B 23/20](#); thumb-tacks [B43M 15/00](#); for building constructions [E04B 1/38](#); for hand railings [E04F 11/18](#); for fencing [E04H 17/00](#))**
- 15/00 Nails; Staples (surgical staples [A61B 17/064](#); manufacture of nails or staples [B21G](#) {}; drawing-pins, thumb-tacks [B43M 15/00](#)); railway spikes [E01B 9/06](#))**
- 15/0007 . {with two nail points extending in opposite directions, in order to fix two workpieces together}
- 15/0015 . {Staples}
- 15/0023 . {Nail plates (claw dowels for building structures [E04B 1/49](#); machines for driving in nail plates [B27F 7/15](#))}
- 15/003 . . {with teeth cut out from the material of the plate}
- 15/0038 . . . {only on the perimeter of the plate}
- 15/0046 . . . {from the body of the plate}
- 15/0053 . . {with separate nails attached to the plate}
- 2015/0061 . . {Multipiece-plates}
- 2015/0069 . . {with nails on both sides}
- 2015/0076 . . {with provisions for additional fastening means, e.g. hooks, holes for separate screws or nails, adhesive}
- 2015/0084 . . {with marks to indicate where to strike with the hammer}
- 15/0092 . {Coated nails or staples}
- 15/02 . with specially-shaped heads, e.g. with enlarged surfaces ([ornaments for furniture A47B 95/04](#); [removable ornamental heads for nails A47G 3/00](#))
- 15/04 . with spreading shaft {(dowels with a drive-nail deflected by an inclined surface in the dowel body [F16B 13/085](#))}
- 15/06 . with barbs, e.g. for metal parts; Drive screws
- 15/08 . formed in integral series but easily separable
- 17/00 Connecting constructional elements or machine parts by a part of or on one member entering a hole in the other {and involving plastic deformation}(riveting [F16B 19/04](#))**
- 17/004 . {of rods or tubes mutually}
- 17/006 . {of rods or tubes to sheets or plates}
- 17/008 . {of sheets or plates mutually (joining sheets by riveting without the use of separate rivets [F16B 5/045](#))}
- 19/00 Bolts without screw-thread; Pins, including deformable elements (in screwed connections [F16B 29/00](#)); Rivets (means for preventing withdrawal [F16B 21/00](#))**
- 19/002 . {Resiliently deformable pins ([F16B 21/06](#) takes precedence)}
- 19/004 . . {made in one piece ([F16B 21/084](#) takes precedence)}
- 2019/006 . . {made in a plurality of pieces}
- 19/008 . {with sealing means}

19/02	• Bolts or sleeves for positioning of machine parts, e.g. notched taper pins, fitting pins, sleeves, eccentric positioning rings	21/00	Means for preventing relative axial movement of a pin, spigot, shaft or the like and a member surrounding it (riveted or deformable spigots F16B 19/04; for gudgeon pins F16J 1/18); Stud-and-socket releasable fastenings
19/04	• Rivets; Spigots or the like fastened by riveting (lead seals G09F 3/00)	21/02	• Releasable fastening devices locking by rotation (with snap-action F16B 21/06 ; studs or coupling pins with resilient protrusions F16B 21/08)
2019/045	• • {Coated rivets}	21/04	• • with bayonet catch
19/05	• • Bolts fastening by swaged-on collars (F16B 19/08 takes precedence)	21/06	• Releasable fastening devices with snap-action ((quickly-detachable or mountable nuts to threaded bolts F16B 37/0842))
2019/055	• • • {deformed by an electro-magnetic action}	21/065	• • {with an additional locking element}
19/06	• • Solid rivets made in one piece	21/07	• • in which the socket has a resilient part ({ F16B 21/065 takes precedence})
19/08	• • Hollow rivets; Multi-part rivets	21/071	• • • {the socket being integrally formed with a component to be fasted, e.g. a sheet, plate or strip}
19/083	• • • {Self-drilling rivets}	21/073	• • • {the socket having a resilient part on its inside}
19/086	• • • {Self-piercing rivets}	21/075	• • • • {the socket having resilient parts on its inside and outside}
19/10	• • • fastened by expanding mechanically	21/076	• • • {the socket having a resilient part on its outside (F16B 21/075 takes precedence)}
	NOTES	21/078	• • • {the socket having a further molded-in or embedded component, e.g. a ring with snap-in teeth molded into it (F16B 21/065 takes precedence)}
	1. Subject matter relating to hollow or single-part rivets fastened by a pull-through mandrel is classified in F16B 19/1045	21/08	• • in which the stud, pin, or spigot has a resilient part ((F16B 21/065 , F16B 21/125 , F16B 21/165 , F16B 37/043 take precedence); wall-dowels F16B 13/00)
	2. Subject matter relating to hollow or single-part rivets fastened by a drive pin is classified in F16B 19/1081	21/082	• • • {the stud, pin or spigot having two resilient parts on its opposite ends in order to connect two elements}
2019/1009	• • • • {hollow or single-part rivets fastened by a pull-through mandrel}	21/084	• • • {with a series of flexible ribs or fins extending laterally from the shank of the stud, pin or spigot, said ribs or fins deforming predominantly in a direction parallel to the direction of insertion of the shank}
2019/1018	• • • • {hollow or single-part rivets fastened by a drive pin}	21/086	• • • {the shank of the stud, pin or spigot having elevations, ribs, fins or prongs intended for deformation or tilting predominantly in a direction perpendicular to the direction of insertion}
19/1027	• • • • {Multi-part rivets}	21/088	• • • {the stud, pin or spigot being integrally formed with the component to be fastened, e.g. forming part of the sheet, plate or strip}
19/1036	• • • • • {Blind rivets}	21/09	• Releasable fastening devices with a stud engaging a keyhole slot
19/1045	• • • • • {fastened by a pull - mandrel or the like (F16B 19/109 takes precedence)}	21/10	• by separate parts ((F16B 21/06 takes precedence); key-type connection F16B 3/00 ; locking screws or nuts against rotation by such means F16B 39/04)
19/1054	• • • • • • {the pull-mandrel or the like being frangible}	21/12	• • with locking-pins or split-pins thrust into holes
19/1063	• • • • • • {with a sleeve or collar sliding over the hollow rivet body during the pulling operation}	21/125	• • • {radially resilient or with a snap-action member, e.g. elastic tooth, pawl with spring, resilient coil or wire}
19/1072	• • • • • • {the pull-mandrel or the like comprising a thread and being rotated with respect to the rivet, thereby mechanically expanding and fastening the rivet (nuts fastened by riveting F16B 37/067)}	21/14	• • • Details of locking-pins or split-pins
19/1081	• • • • • • {fastened by a drive-pin (F16B 19/109 takes precedence)}	21/16	• • with grooves or notches in the pin or shaft
19/109	• • • • • • {Temporary rivets, e.g. with a spring-loaded pin (special clamping devices for workpieces to be riveted together, e.g. operating through the rivet holes B21J 15/42 ; hand tools for temporarily connecting sheets before or during assembly operations B25B 31/005)}	21/165	• • • {with balls or rollers (for connections of rods or tubes engaged telescopically F16B 7/1409)}
19/12	• • • fastened by fluid pressure, including by explosion (bolts shot by means of detonation-operated nailing tools into concrete constructions, metal walls or the like F16B 19/14)	21/18	• • • with circlips or like resilient retaining devices, {i.e. resilient in the plane of the ring or the like}; Details (spring-washers for locking nuts F16B 39/24 ; adjusting rings F16B 43/00)
19/125	• • • • {fastened by explosion}	21/183	• • • • {internal, i.e. with spreading action}
19/14	• Bolts or the like for shooting into concrete constructions, metal walls or the like by means of detonation-operated nailing tools (tools therefor B25C , B27E)		

- 21/186 {external, i.e. with contracting action}
- 21/20 . . for bolts or shafts without holes, grooves, or notches for locking members {(by rings resilient in their plane [F16B 21/18](#))}
- 21/205 . . . {the connecting means having gripping edges in the form of a helix}

Fastening means using screw-thread (wall-dowels [F16B 13/00](#); manufacture of threaded fastening means [B21H](#), [B21K](#), [B23G](#); screws or bolts for railway sleepers [E01B 9/10](#); screw mechanisms [F16H](#))

23/00 Specially shaped {nuts or} heads of bolts or screws for rotations by a tool {(detachable ornamental heads for screws [A47G 3/00](#); screwdrivers, wrenches [B25B](#))}

- 23/0007 . {characterised by the shape of the recess or the protrusion engaging the tool ([F16B 23/0069](#) and [F16B 23/0076](#) take precedence)}
- 23/0015 . . {substantially rectangular, e.g. one-slot head}
- 23/0023 . . {substantially cross-shaped}
- 23/003 . . {star-shaped or multi-lobular, e.g. Torx-type, twelve-point star}
- 23/0038 . . {substantially prismatic with up to six edges, e.g. triangular, square, pentagonal, Allen-type cross-sections}
- 23/0046 . . {having one eccentric circular or polygonal recess or protrusion}
- 23/0053 . {with a conical or prismatic recess for receiving a centering pin of the tool apparatus}
- 23/0061 . {with grooves, notches or splines on the external peripheral surface designed for tools engaging in radial direction ([F16B 23/003](#) takes precedence)}
- 23/0069 . {with holes to be engaged with corresponding pins on the tool or protruding pins to be engaged with corresponding holes on the tool}
- 23/0076 . {causing slipping of the tool in loosening rotation, i.e. disabling unscrewing unless another tool is used ([F16B 31/027](#) takes precedence)}
- 23/0084 . {with a threaded engagement between the head of the bolt or screw and the tool}
- 23/0092 . {with a head engageable by two or more different tools ([F16B 23/0076](#) takes precedence)}

25/00 Screws that cut thread in the body into which they are screwed, e.g. wood screws {([F16B 35/065](#) takes precedence; joining sheets or plates using screws with two separate threads [F16B 5/0275](#), using screws with adjustment sleeves [F16B 5/0283](#))}

- 25/0005 . {of the helical wire type (threaded wire-inserts [F16B 37/12](#))}
- 25/001 . {characterised by the material of the body into which the screw is screwed}
- 25/0015 . . {the material being a soft organic material, e.g. wood or plastic ([F16B 25/0031](#) takes precedence)}
- 25/0021 . . {the material being metal, e.g. sheet-metal or aluminium ([F16B 25/0031](#) takes precedence)}
- 25/0026 . . {the material being a hard non-organic material, e.g. stone, concrete or drywall ([F16B 25/0031](#) takes precedence)}
- 25/0031 . . {the screw being designed to be screwed into different materials, e.g. a layered structure or through metallic and wooden parts}
- 25/0036 . {characterised by geometric details of the screw}

- 25/0042 . . {characterised by the geometry of the thread, the thread being a ridge wrapped around the shaft of the screw}
- 25/0047 . . . {the ridge being characterised by its cross-section in the plane of the shaft axis}
- 25/0052 . . . {the ridge having indentations, notches or the like in order to improve the cutting behaviour}
- 25/0057 . . . {the screw having distinct axial zones, e.g. multiple axial thread sections with different pitch or thread cross-sections}
- 25/0063 {with a non-threaded portion on the shaft of the screw}
- 25/0068 . . . {with multiple-threads, e.g. a double thread screws}
- 25/0073 . . . {characterised by its pitch, e.g. a varying pitch}
- 25/0078 . . {with a shaft of non-circular cross-section or other special geometric features of the shaft}
- 25/0084 . . {characterised by geometric details of the tip}
- 25/0089 . . {the screw having wings}
- 25/0094 . . {the screw being assembled or manufactured from several components, e.g. a tip out of a first material welded to shaft of a second material}
- 25/10 . Screws performing an additional function to thread-forming, e.g. drill screws {or self-piercing screws}
- 25/103 . . {by means of a drilling screw-point, i.e. with a cutting and material removing action}
- 25/106 . . {by means of a self-piercing screw-point, i.e. without removing material}

27/00 Bolts, screws, or nuts formed in integral series but easily separable, particularly for use in automatic machines {(arrangements for feeding screws or nuts in spanners, wrenches or screw-drivers with built-in magazines [B25B 23/06](#))}

29/00 Screwed connection with deformation of nut or auxiliary member while fastening {(Nuts fastened to surfaces by riveting [F16B 37/065](#); members deformed for locking screws, bolts or nuts [F16B 39/22](#))}

31/00 Screwed connections specially modified in view of tensile load; Break-bolts (shape of thread [F16B 33/02](#); in couplings [F16D 9/00](#))

- 2031/002 . {Breakbolts loosening due to an electromagnetic action}
- 31/005 . {Breakbolts loosening due to the action of an explosive charge}
- 31/007 . {Break-bolts loosening at high temperature}
- 31/02 . for indicating {the attainment of a particular tensile load} or limiting tensile load {(apparatus for, or method of, determining value of torque or twisting moment for tightening a nut or other member similarly stressed [G01L 5/24](#))}
- 31/021 . . {by means of a frangible part ([F16B 31/025](#), [F16B 31/028](#) take precedence; break members in torque limiters or torque indicators in wrenches or screwdrivers [B25B 23/1415](#))}
- 2031/022 . . {using an ultrasonic transducer}
- 31/024 . . {with the bottom of the nut or of the head of the bolt having gaps which close as the bolt tension increases, e.g. with lips or with a load-indicating flange}
- 31/025 . . {with a gauge pin in a longitudinal bore in the body of the bolt}

- 31/027 . . {with a bolt head causing the fastening or the unfastening tool to lose the grip when a specified torque is exceeded}
- 31/028 . . {with a load-indicating washer or washer assembly}
- 31/04 . for maintaining {a} tensile load
- 31/043 . . {Prestressed connections tensioned by means of liquid, grease, rubber, explosive charge, or the like (hydraulic bolt tensioners [B25B 29/02](#))}
- 2031/046 . . . {by means of an explosive charge}
- 31/06 . having regard to possibility of fatigue rupture
- 33/00 Features common to bolt and nut**
- 33/002 . {Means for preventing rotation of screw-threaded elements ([F16B 39/00](#) takes precedence)}
- 33/004 . {Sealing; Insulation (by means of washers [F16B 43/001](#))}
- 33/006 . {Non-metallic fasteners using screw-thread}
- 33/008 . {Corrosion preventing means}
- 33/02 . Shape of thread; Special thread-forms ({[F16B 25/00](#) takes precedence; used to remove paint or dirt layers [F16B 35/007](#), [F16B 37/002](#)}; used as screw-locking device [F16B 39/30](#))}
- 2033/025 . . {with left-hand thread}
- 33/04 . . in view of tensile load
- 33/06 . Surface treatment of parts furnished with screw-thread, e.g. for preventing seizure {or fretting (corrosion preventing means [F16B 33/008](#); settable coatings for locking threaded members [F16B 39/225](#); deformable coatings for locking threaded members [F16B 39/34](#))}
- 35/00 Screw-bolts; Stay-bolts; Screw-threaded studs; Screws; Set screws** ({[F16B 33/008](#) takes precedence; joining sheets or plates using screws with two separate threads [F16B 5/0275](#); using screws with adjustment sleeves [F16B 5/0283](#)}; thread cutting screws [F16B 25/00](#))
- NOTE**
- The fastening of heads of screws or heads of bolts to surfaces is classified in [F16B 37/04](#)
- 35/002 . {onto which threads are cut during screwing ([F16B 37/002](#) takes precedence)}
- 35/005 . {Set screws; Locking means therefor}
- 35/007 . {Removing paint or dirt layers covering the threaded part of nut-like members}
- 35/02 . divided longitudinally
- 35/04 . with specially-shaped head or shaft in order to fix the bolt on or in an object (locking the bolt against turning in the object by the use of accessory parts [F16B 39/00](#))
- 35/041 . . {Specially-shaped shafts (shape of thread [F16B 33/02](#))}
- 35/042 . . . {for retention or rotation by a tool, e.g. of polygonal cross-section}
- 35/044 . . . {Specially-shaped ends}
- 35/045 {for retention or rotation by a tool (specially shaped heads of bolts or screws for rotation by a tool [F16B 23/00](#))}
- 35/047 {for preventing cross-threading, i.e. preventing skewing of bolt and nut}
- 35/048 . . . {Specially-shaped necks ([F16B 35/06](#) takes precedence)}
- 35/06 . . Specially-shaped heads (special shape in order to rotate the bolt [F16B 23/00](#) {; separate hook adaptors for bolts [F16B 43/025](#)})
- 35/065 . . . {with self-countersink-cutting means}
- 37/00 Nuts or like thread-engaging members** ({specially shaped for rotations by a tool [F16B 23/00](#))}
- 37/002 . {cutting threads during screwing; removing paint or dirt layers covering threaded shanks}
- 37/005 . {into which threads are cut during screwing}
- 2037/007 . {with a blind hole}
- 37/02 . made of thin sheet material (fastening to surfaces [F16B 37/04](#) {; used as lock-nuts [F16B 39/14](#)})
- 37/04 . Devices for fastening nuts to surfaces, e.g. sheets, plates {(nuts fastened behind a wall by a toggle-mechanism [F16B 13/0808](#); threaded inserts [F16B 37/122](#); measures against loss of bolts, nuts or pins [F16B 41/002](#))}
- 37/041 . . {Releasable devices ([F16B 37/044](#), [F16B 37/045](#) take precedence)}
- 37/042 . . . {locking by rotation}
- 37/043 . . . {with snap action}
- 37/044 . . {Nut cages}
- 37/045 . . {specially adapted for fastening in channels, e.g. sliding bolts, channel nuts}
- 37/046 . . . {with resilient means for urging the nut inside the channel}
- 37/047 . . . {Barrel nuts}
- 37/048 . . {Non-releasable devices ([F16B 37/044](#), [F16B 37/045](#) and [F16B 37/06](#) take precedence)}
- 37/06 . . by means of welding or riveting
- 37/061 . . . {by means of welding}
- 37/062 . . . {by means of riveting}
- 37/064 {with the use of separate rivets}
- 37/065 {by deforming the material of the nut}
- 37/067 {the material of the nut being deformed by a threaded member generating axial movement of the threaded part of the nut, e.g. blind rivet type}
- 37/068 {by deforming the material of the support, e.g. the sheet or plate}
- 37/08 . Quickly-detachable {or mountable} nuts, e.g. consisting of two or more parts; Nuts movable along the bolt after tilting the nut
- 37/0807 . . {Nuts engaged from the end of the bolt, e.g. axially slidable nuts}
- 37/0814 . . . {movable along the bolt after tilting the nut}
- 37/0821 . . . {in two halves pivotally connected}
- 37/0828 . . . {with a longitudinal slit through the annular wall of the nut for enabling expansion of the nut, e.g. for easy removal}
- 37/0835 . . . {with balls engaging threads or grooves on the shaft of the bolt}
- 37/0842 . . . {fastened to the threaded bolt with snap-on-action, e.g. push-on nuts for stud bolts ([F16B 37/0857](#) takes precedence; snap-on-action of a pin, spigot, shaft or the like and a member surrounding it [F16B 21/06](#))}
- 37/085 . . . {with at least one unthreaded portion in both the nut and the bolt}

- 37/0857 . . . {with the threaded portions of the nut engaging the thread of the bolt by the action of one or more springs or resilient retaining members ([F16B 37/0821](#) and [F16B 37/0835](#) take precedence)}
- 37/0864 . . . {with the threaded portions of the nut engaging the thread of the bolt by pressing or rotating an external retaining member such as a cap, a nut, a ring or a sleeve ([F16B 37/0835](#) takes precedence)}
- 37/0871 . . {engaging the bolt laterally, i.e. without the need to engage the end of the bolt}
- 37/0878 . . . {in one piece, e.g. C-shaped nuts}
- 37/0885 . . . {in two halves hingedly connected}
- 37/0892 . . . {in two or more pieces, e.g. assemblies made by two C-shaped nuts mutually interlocked, or retained by an additional member ([F16B 37/0885](#) takes precedence)}
- 37/12 . with thread-engaging surfaces formed by inserted coil-springs, discs, or the like; Independent pieces of wound wire used as nuts; Threaded inserts for holes {(mounting devices [B25B 27/143](#))}
- 37/122 . . {Threaded inserts, e.g. "rampa bolts"}
- 37/125 . . . {the external surface of the insert being threaded}
- 37/127 {and self-tapping}
- 37/14 . Cap nuts; Nut caps or bolt caps
- 37/145 . . {Sleeve nuts, e.g. combined with bolts}
- 37/16 . Wing-nuts ([F16B 37/14](#) takes precedence)
- 39/00** **Locking of screws, bolts or nuts** ({[F16B 35/005](#) takes precedence}; locking of bottle closures [B65D](#); locking of rail-fastening bolts for permanent ways [E01B 9/12](#); locking of fastening means for railway fishplates [E01B 11/38](#); locking devices for valves or cocks [F16K](#))
- NOTE**
- In this group, heads of screws or bolts are put on a par with nuts as far as pertains to locking; an object into which a screw is threaded is put on a par with a nut.
- 39/01 . specially adapted to prevent loosening at extreme temperatures
- 39/02 . in which the locking takes place after screwing down ([F16B 39/01](#) takes precedence; split-pins, circlips, or the like for preventing relative axial movement only [F16B 21/10](#); fastening nuts by welding or riveting [F16B 37/06](#))
- 39/021 . . {by injecting a settable material after the screwing down}
- 39/023 . . {by driving a conic or wedge-shaped expander through the threaded element}
- 39/025 . . {by plastic deformation of a part of one of the threaded elements into a notch or cavity of the other threaded element ([F16B 39/103](#) and [F16B 39/106](#) take precedence)}
- 39/026 . . {by swaging the nut on the bolt, i.e. by plastically deforming the nut}
- 39/028 . . {by means of an auxiliary bolt or threaded element whose action provokes the deformation of the main bolt or nut and thereby its blocking}
- 39/04 . . with a member penetrating the screw-threaded surface of at least one part, e.g. a pin, a wedge, cotter-pin, screw
- 39/06 . . . with a pin or staple parallel to the bolt axis
- 39/08 . . with a cap interacting with the nut, connected to the bolt by a pin or cotter pin
- 39/10 . . by a plate, {spring, wire} or ring immovable with regard to the bolt or object {and mainly perpendicular to the axis of the bolt}([F16B 39/08](#) takes precedence)
- 39/101 . . . {with a plate, spring, wire or ring holding two or more nuts or bolt heads which are mainly in the same plane}
- 39/103 . . . {with a locking cup washer, ring or sleeve surrounding the nut or bolt head and being partially deformed on the nut or bolt head, or on the object itself}
- 39/105 {locking the bolt head or nut into a hole or cavity, e.g. with the cup washer, ring or sleeve deformed into a dimple in the cavity}
- 39/106 . . . {with a deformable locking element, e.g. disk or pin above the bolt head or nut, flattened into a hole or cavity within which the bolt head or nut is positioned}
- 39/108 . . . {with a locking washer under the nut or bolt head having at least one tongue or lug folded against the nut or bolt head, or against the object itself ([F16B 39/103](#) takes precedence)}
- 39/12 . . by means of locknuts
- 39/122 . . . {foreseen with mating surfaces inclined, i.e. not normal, to the bolt axis}
- 39/124 {with helically inclined mating surfaces}
- 39/126 . . . {causing radial forces on the bolt-shaft ([F16B 39/36](#) takes precedence)}
- 39/128 {by means of eccentric or spiral interengaging parts}
- 39/14 . . . made of thin sheet material or formed as spring-washers (locknuts *per se* made of thin sheet metal [F16B 37/02](#))
- 39/16 . . . in which the screw-thread of the locknut differs from that of the nut
- 39/18 in which the locknut grips with screw-thread in the nuts as well as on the bolt
- 39/20 . . by means of steel wire or the like ([F16B 39/10](#) takes precedence)
- 39/22 . in which the locking takes place during screwing down or tightening ([F16B 39/01](#) takes precedence)
- 39/225 . . {by means of a settable material}
- 39/24 . . by means of washers, spring washers, or resilient plates that lock against the object (locking to the screw-thread [F16B 39/14](#) {, [F16B 39/34](#)}, [F16B 39/36](#))
- 39/26 . . . with spring washers fastened to the nut or bolt-head
- 39/28 . . by special members on, or shape of, the nut or bolt ([F16B 39/26](#) takes precedence; locknuts [F16B 39/12](#))
- 39/282 . . . Locking by means of special shape of work-engaging surfaces, e.g. notched or toothed nuts
- 39/2825 {causing the bolt to tilt}
- 39/284 . . . Locking by means of elastic deformation ({[F16B 39/2825](#), [F16B 39/36](#),} [F16B 39/38](#) take precedence)
- 39/286 caused by saw cuts
- 39/30 . . . Locking exclusively by special shape of the screw-thread

- 39/32 . . . Locking by means of a pawl or pawl-like tongue
- 39/34 . . . Locking by deformable inserts or like parts
- 39/36 . . . with conical locking parts, which may be split, including use of separate rings co-operating therewith
- 39/38 . . . with a second part of the screw-thread which may be resiliently mounted ([F16B 39/30](#) takes precedence)
- 41/00 Measures against loss of bolts, nuts, or pins; Measures against unauthorised operation of bolts, nuts or pins** ({locking of screws, bolts or nuts [F16B 39/00](#);} seals [G09F 3/00](#))
- 41/002 . {Measures against loss of bolts, nuts or pins (devices for fastening nuts to surfaces [F16B 37/04](#))}
- 41/005 . {Measures against unauthorised operation of bolts, nuts or pins ([F16B 23/0007](#), [F16B 23/0061](#), [F16B 23/0069](#), [F16B 23/0076](#) and [F16B 31/02](#) take precedence; locks, keys [E05B](#); for valves, taps or cocks [F16K 35/00](#); for pipe-joints with swivel-nuts [F16L 19/005](#))}
- 41/007 . . {by means of two housings hingedly connected which enclose the bolt head}
- 43/00 Washers or equivalent devices; Other devices for supporting bolt-heads or nuts** (circlips [F16B 21/18](#); {for indicating tensile load [F16B 31/02](#); forming a whole with the bolt or nut [F16B 33/00](#); locking bolts or nuts by means of a fixed plate or ring, or washer-like resilient plates [F16B 39/10](#), [F16B 39/24](#))}
- 43/001 . {for sealing or insulation}
- 43/002 . {with special provisions for reducing friction}
- 43/003 . {with a special hole shape in order to allow a quick mounting or dismounting of the washer, e.g. with a keyhole slot ([F16B 43/005](#) takes precedence)}
- 43/004 . {with a radial cut in order to improve elasticity of the washer ([F16B 43/005](#) takes precedence)}
- 43/005 . {engaging the bolt laterally to allow a quick mounting or dismounting of the washer, i.e. without the need to engage over the end of the bolt ([F16B 43/009](#) takes precedence)}
- 43/006 . . {in two or more parts hingedly connected}
- 43/007 . . {in two or more parts}
- 2043/008 . {with a cavity for receiving the bolt head in order to make a flush surface}
- 43/009 . {with a wedging effect in order to adjust the height of the washer}
- 43/02 . with special provisions for engaging surfaces which are not perpendicular to a bolt axis or do not surround the bolt
- 43/025 . . {for surfaces not surrounding the bolt, e.g. hook adaptors for bolts}

45/00

Hooks; Eyes (if the attaching parts or means are concerned, groups [F16B 13/00](#), [F16B 15/00](#), [F16B 19/00](#), [F16B 25/00](#), [F16B 35/00](#), [F16B 47/00](#) take precedence; for hanging pictures or the like [A47G 1/16](#); towing hooks for ships [B63B 21/58](#); for hoisting or hauling purposes [B66C](#); hooks or eyes with integral parts designed to facilitate quick attachment to cables or ropes at any point [F16G 11/14](#))

WARNING

Group [F16B 45/00](#) is impacted by reclassification into groups [F16B 45/002](#), [F16B 45/005](#), [F16B 45/008](#), [F16B 45/012](#) and [F16B 45/015](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/002 . {Eyes}

WARNING

Group [F16B 45/002](#) is incomplete pending reclassification of documents from group [F16B 45/00](#).

Groups [F16B 45/00](#) and [F16B 45/002](#) should be considered in order to perform a complete search.

- 45/005 . {characterised by the material}

WARNING

Groups [F16B 45/005](#), [F16B 45/008](#), [F16B 45/012](#), and [F16B 45/015](#) are incomplete pending reclassification of documents from groups [F16B 45/00](#), [F16B 45/02](#), [F16B 45/021](#) and [F16B 45/04](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/008 . . {plastics}
- 45/012 . . {wire}
- 45/015 . . {sheet metal}
- 45/02 . Hooks with pivoting {or elastically bending} closing member

WARNING

Group [F16B 45/02](#) is impacted by reclassification into groups [F16B 45/005](#), [F16B 45/008](#), [F16B 45/012](#), [F16B 45/015](#), [F16B 45/021](#), [F16B 45/022](#), [F16B 45/023](#), [F16B 45/024](#), [F16B 45/026](#), [F16B 45/027](#), [F16B 45/028](#), [F16B 45/029](#), [F16B 45/031](#), [F16B 45/032](#), [F16B 45/033](#), [F16B 45/034](#), [F16B 45/035](#), [F16B 45/036](#) and [F16B 45/037](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/021 . . {the closing member being operable remotely, e.g. by cables, chains or rods}

WARNING

Group [F16B 45/021](#) is incomplete pending reclassification of documents from groups [F16B 45/02](#).

Group [F16B 45/021](#) is also impacted by reclassification into groups [F16B 45/005](#), [F16B 45/008](#), [F16B 45/012](#), [F16B 45/015](#), [F16B 45/022](#), [F16B 45/023](#), [F16B 45/024](#), [F16B 45/026](#), [F16B 45/027](#), [F16B 45/028](#), [F16B 45/029](#), [F16B 45/031](#), [F16B 45/032](#), [F16B 45/033](#), [F16B 45/034](#), [F16B 45/035](#), [F16B 45/036](#) and [F16B 45/037](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/022 . . {the closing member pivoting about an axis lying in the plane of the hook}

WARNING

Group [F16B 45/022](#) is incomplete pending reclassification of documents from group [F16B 45/02](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/023 . . {the closing member pivoting about an axis perpendicular to the plane of the hook}

WARNING

Group [F16B 45/023](#) is incomplete pending reclassification of documents from group [F16B 45/02](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/024 . . {and having means biasing the closing member about the pivot}

WARNING

Groups [F16B 45/024](#) and [F16B 45/026](#) are incomplete pending reclassification of documents from group [F16B 45/02](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/026 . . . {and including a coil type spring}

- 45/027 . . {and having position-locking means for the closing member}

WARNING

Groups [F16B 45/027](#), [F16B 45/028](#) and [F16B 45/029](#) are incomplete pending reclassification of documents from group [F16B 45/02](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/028 . . . {the position-locking means being pivotally connected}

- 45/029 . . . {the position-locking means being slidably mounted}

- 45/031 . . {the closing member closing when a structure to be secured is tensioned}

WARNING

Group [F16B 45/031](#) is incomplete pending reclassification of documents from group [F16B 45/02](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/032 . . {whereby the closing member is slidable relative to the pivot}

WARNING

Group [F16B 45/032](#) is incomplete pending reclassification of documents from group [F16B 45/02](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/033 . . {the closing member being revolvably mounted and having a disc shape}

WARNING

Group [F16B 45/033](#) is incomplete pending reclassification of documents from group [F16B 45/02](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/034 . . {the closing member constituting the hook shaped portion of the hook}

WARNING

Group [F16B 45/034](#) is incomplete pending reclassification of documents from group [F16B 45/02](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/035 . . {the hook forming a loop or ring when interlocked with the closing member, i.e. the entire structure of the hook being loop shaped}

WARNING

Group [F16B 45/035](#) is incomplete pending reclassification of documents from group [F16B 45/02](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/036 . . {with an elastically bending closing member}

WARNING

Group [F16B 45/036](#) is incomplete pending reclassification of documents from group [F16B 45/02](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/037 . . {Multiple locking cavities, each having a pivoting closing member}

WARNING

Group [F16B 45/037](#) is incomplete pending reclassification of documents from group [F16B 45/02](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/04 . . Hooks with sliding closing member

WARNING

Group [F16B 45/04](#) is impacted by reclassification into groups [F16B 45/005](#), [F16B 45/008](#), [F16B 45/012](#), [F16B 45/015](#), [F16B 45/043](#), [F16B 45/045](#), [F16B 45/047](#), [F16B 45/049](#), [F16B 45/051](#), [F16B 45/053](#), [F16B 45/055](#), [F16B 45/057](#) and [F16B 45/059](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/043 . . {the closing member being operable remotely, e.g. by cables, chains or rods}

WARNING

Group [F16B 45/043](#) is incomplete pending reclassification of documents from group [F16B 45/04](#).

All groups listed in this Warning should be considered in order to perform a complete search.

- 45/045 . . {provided with position-locking means for the closing member}

WARNING

Groups [F16B 45/045](#) and [F16B 45/047](#) are incomplete pending reclassification of documents from group [F16B 45/04](#).

Groups [F16B 45/04](#) and [F16B 45/045](#) should be considered in order to perform a complete search.

- 45/047 . . . {in the form of a threaded closing member}

- 45/049 . . {provided with means biasing the closing member}

WARNING

Group [F16B 45/049](#) is incomplete pending reclassification of documents from group [F16B 45/04](#).

Groups [F16B 45/04](#) and [F16B 45/049](#) should be considered in order to perform a complete search.

- 45/051 . . {provided with a guide of the closing member encircling a shank of the hook}

WARNING

Group [F16B 45/051](#) is incomplete pending reclassification of documents from group [F16B 45/04](#).

Groups [F16B 45/04](#) and [F16B 45/051](#) should be considered in order to perform a complete search.

- 45/053 . . {provided with a cavity in a shank of the hook forming a track or way for the closing member}

WARNING

Group [F16B 45/053](#) is incomplete pending reclassification of documents from group [F16B 45/04](#).

Groups [F16B 45/04](#) and [F16B 45/053](#) should be considered in order to perform a complete search.

- 45/055 . . {the closing member constituting the hook-shaped portion of the hook}

WARNING

Group [F16B 45/055](#) is incomplete pending reclassification of documents from group [F16B 45/04](#).

Groups [F16B 45/04](#) and [F16B 45/055](#) should be considered in order to perform a complete search.

- 45/057 . . {the hook forming a loop or ring when interlocked with the closing member, i.e. the entire structure of the hook being loop shaped}

WARNING

Group [F16B 45/057](#) is incomplete pending reclassification of documents from group [F16B 45/04](#).

Groups [F16B 45/04](#) and [F16B 45/057](#) should be considered in order to perform a complete search.

- 45/059 . . {Multiple locking cavities, each having a sliding closing member}

WARNING

Group [F16B 45/059](#) is incomplete pending reclassification of documents from group [F16B 45/04](#).

Groups [F16B 45/04](#) and [F16B 45/059](#) should be considered in order to perform a complete search.

- 45/06 . Hooks with two symmetrically-pivoting hook parts {within the same locking cavity ([F16B 45/035](#) takes precedence)}
- 47/00 Suction cups for attaching purposes; Equivalent means using adhesives** {(devices using adhesives, suction or magnetism for hanging or supporting pictures or the like [A47G 1/17](#); vacuum work holders [B25B 11/005](#); anchoring of ships using suction [B63B 21/27](#); suction cups for handling glass [B65G 49/061](#); load-engaging elements for cranes using suction means [B66C 1/02](#)}
- 47/003 . {using adhesives for attaching purposes (using adhesives for connecting constructional elements [F16B 11/006](#))}
- 47/006 . {the suction cups being activated by the rotation of a cranked lever arm}
- 2200/00 Constructional details of connections not covered for in other groups of this subclass**
- 2200/10 . Details of socket shapes
- 2200/20 . Connections with hook-like parts gripping behind a blind side of an element to be connected
- 2200/205 . . the hook being a separate retainer
- 2200/30 . Dovetail-like connections
- 2200/40 . Clamping arrangements where clamping parts are received in recesses of elements to be connected
- 2200/403 . . Threaded clamping parts
- 2200/406 . . Clamping parts being collars, bushings or wedges
- 2200/50 . Flanged connections
- 2200/503 . . the flange being separate from the elements to be connected
- 2200/506 . . bolted or riveted
- 2200/509 . . clamped