

# CPC COOPERATIVE PATENT CLASSIFICATION

## F MECHANICAL ENGINEERING; LIGHTING; HEATING; WEAPONS; BLASTING (NOTE omitted)

### LIGHTING; HEATING

#### F23 COMBUSTION APPARATUS; COMBUSTION PROCESSES (NOTE omitted)

#### F23R GENERATING COMBUSTION PRODUCTS OF HIGH PRESSURE OR HIGH VELOCITY, e.g. GAS-TURBINE COMBUSTION CHAMBERS (using such products for specific purposes, [see the relevant classes for the purposes](#); chemical aspects of gas production [C06D 5/00](#); gas-turbine plants characterised by the arrangement of the combustion chamber in the plant [F02C 3/14](#); arrangement of afterburners in jet-propulsion plants [F02K 3/10](#); combustion chambers of rocket-engine plants [F02K 9/00](#))

<b>3/00</b>	<b>Continuous combustion chambers using liquid or gaseous fuel</b>	3/346	. . . {for staged combustion}
3/002	. {Wall structures ( <a href="#">F23R 3/02</a> and <a href="#">F23R 3/007</a> take precedence)}	3/36	. . . Supply of different fuels
3/005	. {Combined with pressure or heat exchangers}	3/38	. . . comprising rotary fuel injection means
3/007	. {constructed mainly of ceramic components}	3/40	. characterised by the used of catalytic means
3/02	. characterised by the air-flow or gas-flow configuration (reverse- flow combustion chambers <a href="#">F23R 3/54</a> ; cyclone or vortex type combustion chambers <a href="#">F23R 3/58</a> )	3/42	. characterised by the arrangement or form of the flame tubes or combustion chambers
3/04	. . Air inlet arrangements	3/425	. . {Combustion chambers comprising a tangential or helicoidal arrangement of the flame tubes}
3/045	. . . {using pipes}	3/44	. . Combustion chambers comprising a {single} tubular flame tube within a tubular casing ( <a href="#">reverse-flow combustion chambers F23R 3/54</a> )
3/06	. . . Arrangement of apertures along the flame tube	3/46	. . Combustion chambers comprising an annular arrangement of {several essentially tubular} flame tubes within a common annular casing or within individual casings
3/08	. . . . between annular flame tube sections, e.g. flame tubes with telescopic sections	3/48	. . . Flame tube interconnectors, e.g. cross-over tubes
3/10	. . . for primary air ( <a href="#">F23R 3/06</a> , <a href="#">F23R 3/045</a> take precedence)	3/50	. . Combustion chambers comprising an annular flame tube within an annular casing ( <a href="#">toroidal combustion chambers F23R 3/52</a> )
3/12	. . . . inducing a vortex	3/52	. . Toroidal combustion chambers
3/14	. . . . by using swirl vanes	3/54	. . Reverse-flow combustion chambers
3/16	. . with devices inside the flame tube or the combustion chamber to influence the air or gas flow	3/56	. . Combustion chambers having rotary flame tubes
3/18	. . . Flame stabilising means, e.g. flame holders for after-burners of jet-propulsion plants	3/58	. . Cyclone or vortex type combustion chambers
3/20	. . . . incorporating fuel injection means	3/60	. . Support structures; Attaching or mounting means
3/22	. . . . movable, e.g. to an inoperative position; adjustable, e.g. self-adjusting	<b>5/00</b>	<b>Continuous combustion chambers using solid or pulverulent fuel</b>
3/24	. . . . of the fluid-screen type	<b>7/00</b>	<b>Intermittent or explosive combustion chambers</b>
3/26	. . Controlling the air flow	<b>2900/00</b>	<b>Special features of, or arrangements for continuous combustion chambers; Combustion processes therefor</b>
3/28	. characterised by the fuel supply ( <a href="#">burners F23D</a> )	2900/00001	. Arrangements using bellows, e.g. to adjust volumes or reduce thermal stresses
3/283	. . {Attaching or cooling of fuel injecting means}	2900/00002	. Gas turbine combustors adapted for fuels having low heating value [LHV]
3/286	. . {having fuel-air premixing devices ( <a href="#">F23R 3/30</a> takes precedence)}	2900/00004	. Preventing formation of deposits on surfaces of gas turbine components, e.g. coke deposits
3/30	. . comprising fuel prevapourising devices	2900/00005	. Preventing fatigue failures or reducing mechanical stress in gas turbine components
3/32	. . . being tubular		
3/34	. . Feeding into different combustion zones		
3/343	. . . {Pilot flames, i.e. fuel nozzles or injectors using only a very small proportion of the total fuel to insure continuous combustion (ignition in gas-turbine plants <a href="#">F02C 7/264</a> ; pilot flame igniters <a href="#">F23Q 9/00</a> )}		

## F23R

- 2900/00006 . Using laser for starting or improving the combustion process
- 2900/00008 . Combustion techniques using plasma gas ([plasma torches F23R 2900/00009](#))
- 2900/00009 . Using plasma torches for igniting, stabilizing, or improving the combustion process
- 2900/00012 . Details of sealing devices
- 2900/00013 . Reducing thermo-acoustic vibrations by active means
- 2900/00014 . Reducing thermo-acoustic vibrations by passive means, e.g. by Helmholtz resonators ([silence apparatus using resonance F01N 1/023](#))
- 2900/00015 . Trapped vortex combustion chambers
- 2900/00016 . Retrofitting in general, e.g. to respect new regulations on pollution
- 2900/00017 . Assembling combustion chamber liners or subparts
- 2900/00018 . Manufacturing combustion chamber liners or subparts
- 2900/00019 . Repairing or maintaining combustion chamber liners or subparts
- 2900/03041 . Effusion cooled combustion chamber walls or domes
- 2900/03042 . Film cooled combustion chamber walls or domes
- 2900/03043 . Convection cooled combustion chamber walls with means for guiding the cooling air flow ([means for creating turbulence F23R 2900/03045](#))
- 2900/03044 . Impingement cooled combustion chamber walls or subassemblies
- 2900/03045 . Convection cooled combustion chamber walls provided with turbulators or means for creating turbulences to increase cooling
- 2900/03281 . Intermittent fuel injection or supply with plunger pump or other means therefor
- 2900/03282 . High speed injection of air and/or fuel inducing internal recirculation
- 2900/03341 . Sequential combustion chambers or burners
- 2900/03342 . Arrangement of silo-type combustion chambers
- 2900/03343 . Pilot burners operating in premixed mode