CPC COOPERATIVE PATENT CLASSIFICATION

G PHYSICS

(NOTES omitted)

NUCLEONICS

5/06

5/08

G21 NUCLEAR PHYSICS; NUCLEAR ENGINEERING

. . with engine working medium circulating through

with engine working medium heated in a heat

exchanger by the reactor coolant

reactor core

G21D NUCLEAR POWER PLANT

1/00 1/003	Details of nuclear power plant (control G21D 3/00) • {Nuclear facilities decommissioning arrangements (decontamination arrangements, treating	5/10	Liquid working medium partially heated by reactor and vaporised by heat source external to the core, e.g. with oil heating
	radioactively contaminated material G21F 9/00)}	5/12	Liquid working medium vaporised by reactor
1/006	• {primary side of steam generators (secondary side		coolant
	of steam generators <u>F22B 1/00</u> , <u>F22B 35/00</u> or	5/14	and also superheated by reactor coolant
1 /02	<u>F22B 37/00</u>)}	5/16	• • • superheated by separate heat source
1/02	. Arrangements of auxiliary equipment	7/00	Arrangements for direct production of electric
1/04	• Pumping arrangements (within the reactor pressure vessel <u>G21C 15/24</u> ; electrodynamic pumps		energy from fusion or fission reactions (obtaining
	<u>H02K 44/02</u>)	7/00	electric energy from radioactive sources <u>G21H 1/00</u>)
3/00	Control of nuclear power plant (control of nuclear	7/02	 using magneto-hydrodynamic generators {(MHD-generators with thermodynamic cycles <u>F02C 7/00</u>;
5/00	reaction in general G21C 7/00)		magneto-hydrodynamic generators <u>H02K 44/08</u>)}
3/001	• {Computer implemented control}	7/04	• using thermoelectric elements {or thermoionic
3/002	• • {Core design; core simulations; core		converters} (structural combination of fuel
	optimisation}		element with thermoelectric element {or with
3/004	• • {Fuel shuffle simulation; fuel shuffle		thermoionic converters} $\underline{G21C3/40}$ {, $\underline{G21H1/10}$ };
	optimisation}		thermoelectric elements <u>per se H01L 35/00</u> , H01L 37/00)
3/005	• • {Thermo-hydraulic simulations}		<u>1101L 37/00</u>)
3/007 3/008	• {Expert systems}	9/00	Arrangements to provide heat for purposes other
3/008	{Man-machine interface, e.g. control room layout} Manual control		than conversion into power, e.g. for heating
3/04	Safety arrangements (emergency protection of		buildings
3/04	reactor G21C 9/00)		
3/06	• responsive to faults within the plant (in the reactor <u>G21C 9/00</u>)		
3/08	 Regulation of any parameters in the plant 		
3/10	 by a combination of a variable derived from neutron flux with other controlling variables, e.g. derived from temperature, cooling flow, pressure 		
3/12	by adjustment of the reactor in response only to changes in engine demand		
3/14	Varying flow of coolant		
3/16	Varying reactivity		
3/18	• • by adjustment of plant external to the reactor only in response to change in reactivity		
5/00	Arrangements of reactor and engine in which reactor-produced heat is converted into mechanical energy		
5/02	Reactor and engine structurally combined, e.g. portable		
5/04	 Reactor and engine not structurally combined 		
F 10 C	tage to the second of the seco		

CPC - 2019.02