

CPC COOPERATIVE PATENT CLASSIFICATION

H ELECTRICITY

(NOTE omitted)

H03 BASIC ELECTRONIC CIRCUITRY

H03L AUTOMATIC CONTROL, STARTING, SYNCHRONISATION, OR STABILISATION OF GENERATORS OF ELECTRONIC OSCILLATIONS OR PULSES (of dynamo-electric generators [H02P](#))

NOTES

- This subclass covers:
 - automatic control circuits for generators of electronic oscillations or pulses;
 - starting, synchronisation, or stabilisation circuits for generators where the type of generator is irrelevant or unspecified.
- This subclass does not cover stabilisation or starting circuits specially adapted to only one specific type of generator, which are covered by subclasses [H03B](#), [H03K](#).
- In this subclass, the following expression is used with the meaning indicated:
 - "automatic control" covers only closed loop systems.

WARNING

In this subclass non-limiting references (in the sense of paragraph 39 of the Guide to the IPC) may still be displayed in the scheme.

1/00	Stabilisation of generator output against variations of physical values, e.g. power supply (automatic control H03L 5/00, H03L 7/00)	7/04	. . wherein the frequency-determining element comprises distributed inductance and capacitance
1/02	. against variations of temperature only	7/06	. using a reference signal applied to a frequency- or phase-locked loop
1/021	. . {of generators comprising distributed capacitance and inductance}	7/07	. . using several loops, e.g. for redundant clock signal generation (for indirect frequency synthesis H03L 7/22)
1/022	. . {by indirect stabilisation, i.e. by generating an electrical correction signal which is a function of the temperature (H03L 1/021 takes precedence)}	7/08	. . Details of the phase-locked loop
1/023	. . . {by using voltage variable capacitance diodes}	7/0802	. . . {the loop being adapted for reducing power consumption (H03L 7/14 takes precedence)}
1/025 {and a memory for digitally storing correction values}	7/0805	. . . {the loop being adapted to provide an additional control signal for use outside the loop}
1/026	. . . {by using a memory for digitally storing correction values (H03L 1/025 takes precedence)}	7/0807	. . . {concerning mainly a recovery circuit for the reference signal}
1/027	. . . {by using frequency conversion means which is variable with temperature, e.g. mixer, frequency divider, pulse add/subtract logic circuit (H03L 1/023 , H03L 1/026 take precedence)}	7/081	. . . provided with an additional controlled phase shifter {(H03L 7/0998 takes precedence)}
1/028	. . {of generators comprising piezo-electric resonators (H03L 1/021 and H03L 1/022 take precedence; oscillation generators with a piezo-electric resonator <i>per se</i> H03B 5/32)}	7/0812 {and where no voltage or current controlled oscillator is used}
1/04	. . Constructional details for maintaining temperature constant		WARNING
3/00	Starting of generators		Group H03L 7/0812 is impacted by reclassification into groups H03L 7/0816 and H03L 7/0818 .
5/00	Automatic control of voltage, current, or power		Groups H03L 7/0812 , H03L 7/0816 and H03L 7/0818 should be considered in order to perform a complete search.
5/02	. of power		
7/00	Automatic control of frequency or phase; Synchronisation (tuning of resonant circuits in general H03J; synchronising in digital communication systems, see the relevant groups in class H04)		
7/02	. using a frequency discriminator comprising a passive frequency-determining element		

- 7/0814 {the phase shifting device being digitally controlled}
WARNING
Group [H03L 7/0814](#) is impacted by reclassification into groups [H03L 7/0816](#) and [H03L 7/0818](#). Groups [H03L 7/0814](#), [H03L 7/0816](#) and [H03L 7/0818](#) should be considered in order to perform a complete search.
- 7/0816 {the controlled phase shifter and the frequency- or phase-detection arrangement being connected to a common input}
WARNING
Groups [H03L 7/0816](#) and [H03L 7/0818](#) are incomplete pending reclassification of documents from groups [H03L 7/0812](#) and [H03L 7/0814](#). Until reclassification is complete, groups [H03L 7/0816](#), [H03L 7/0818](#), [H03L 7/0812](#) and [H03L 7/0814](#) should be considered in order to perform a complete search.
- 7/0818 {the controlled phase shifter comprising coarse and fine delay or phase-shifting means}
WARNING
Groups [H03L 7/0816](#) and [H03L 7/0818](#) are incomplete pending reclassification of documents from groups [H03L 7/0812](#) and [H03L 7/0814](#). Until reclassification is complete, groups [H03L 7/0816](#), [H03L 7/0818](#), [H03L 7/0812](#) and [H03L 7/0814](#) should be considered in order to perform a complete search.
- 7/083 . . . the reference signal being additionally directly applied to the generator (direct frequency synchronisation without loop [H03L 7/24](#))
- 7/085 . . . concerning mainly the frequency- or phase-detection arrangement including the filtering or amplification of its output signal ([H03L 7/10](#) takes precedence; frequency or phase detection comparison in general [H03D 3/00](#), [H03D 13/00](#))
- 7/087 using at least two phase detectors or a frequency and phase detector in the loop
- 7/089 the phase or frequency detector generating up-down pulses ([H03L 7/087](#) takes precedence)
- 7/0891 {the up-down pulses controlling source and sink current generators, e.g. a charge pump}
- 7/0893 {the up-down pulses controlling at least two source current generators or at least two sink current generators connected to different points in the loop}
- 7/0895 {Details of the current generators ([H03L 7/0893](#) takes precedence)}
- 7/0896 {the current generators being controlled by differential up-down pulses}
- 7/0898 {the source or sink current values being variable ([H03L 7/0896](#) takes precedence)}
- 7/091 the phase or frequency detector using a sampling device ([H03L 7/087](#) takes precedence)
- 7/093 using special filtering or amplification characteristics in the loop ([H03L 7/087](#) - [H03L 7/091](#) take precedence)
- 7/095 using a lock detector ([H03L 7/087](#) takes precedence)
- 7/097 using a comparator for comparing the voltages obtained from two frequency to voltage converters
- 7/099 . . . concerning mainly the controlled oscillator of the loop
- 7/0991 {the oscillator being a digital oscillator, e.g. composed of a fixed oscillator followed by a variable frequency divider ([H03L 7/0995](#) takes precedence; fixed oscillators with means for selecting among various phases [H03L 7/0814](#))}
- 7/0992 {comprising a counter or a frequency divider}
- 7/0993 {and a circuit for adding and deleting pulses}
- 7/0994 {comprising an accumulator}
- 7/0995 {the oscillator comprising a ring oscillator}
- 7/0996 {Selecting a signal among the plurality of phase-shifted signals produced by the ring oscillator}
- 7/0997 {Controlling the number of delay elements connected in series in the ring oscillator}
- 7/0998 {using phase interpolation}
- 7/10 . . . for assuring initial synchronisation or for broadening the capture range
WARNING
Group [H03L 7/10](#) impacted by reclassification into groups [H03L 7/102](#), [H03L 7/103](#), [H03L 7/104](#) and [H03L 7/105](#). Groups [H03L 7/10](#), [H03L 7/102](#), [H03L 7/103](#), [H03L 7/104](#) and [H03L 7/105](#) should be considered in order to perform a complete search.
- 7/101 {using an additional control signal to the controlled loop oscillator derived from a signal generated in the loop ([H03L 7/113](#), [H03L 7/187](#) take precedence)}
- 7/102 {the additional signal being directly applied to the controlled loop oscillator}
WARNING
Group [H03L 7/102](#) is incomplete pending reclassification of documents from group [H03L 7/10](#). Until reclassification is complete, groups [H03L 7/102](#) and [H03L 7/10](#) should be considered in order to perform a complete search.

- 7/103 {the additional signal being a digital signal}
WARNING
 Group [H03L 7/103](#) is incomplete pending reclassification of documents from group [H03L 7/10](#).
 Until reclassification is complete, groups [H03L 7/103](#) and [H03L 7/10](#) should be considered in order to perform a complete search.
- 7/104 {using an additional signal from outside the loop for setting or controlling a parameter in the loop ([H03L 7/107](#), [H03L 7/12](#) take precedence)}
WARNING
 Group [H03L 7/104](#) is incomplete pending reclassification of documents from group [H03L 7/10](#).
 Until reclassification is complete, groups [H03L 7/104](#) and [H03L 7/10](#) should be considered in order to perform a complete search.
- 7/105 {Resetting the controlled oscillator when its frequency is outside a predetermined limit}
WARNING
 Group [H03L 7/105](#) is incomplete pending reclassification of documents from group [H03L 7/10](#).
 Until reclassification is complete, groups [H03L 7/105](#) and [H03L 7/10](#) should be considered in order to perform a complete search.
- 7/107 using a variable transfer function for the loop, e.g. low pass filter having a variable bandwidth
WARNING
 Group [H03L 7/107](#) impacted by reclassification into groups [H03L 7/1072](#), [H03L 7/1075](#) and [H03L 7/1077](#).
 Groups [H03L 7/107](#), [H03L 7/1072](#), [H03L 7/1075](#) and [H03L 7/1077](#) should be considered in order to perform a complete search.
- 7/1072 {by changing characteristics of the charge pump, e.g. changing the gain}
WARNING
 Group [H03L 7/1072](#) is incomplete pending reclassification of documents from group [H03L 7/107](#).
 Until reclassification is complete, groups [H03L 7/1072](#) and [H03L 7/107](#) should be considered in order to perform a complete search.
- 7/1075 {by changing characteristics of the loop filter, e.g. changing the gain, changing the bandwidth ([H03L 7/1072](#) takes precedence)}
WARNING
 Group [H03L 7/1075](#) is incomplete pending reclassification of documents from group [H03L 7/107](#).
 Until reclassification is complete, groups [H03L 7/1075](#) and [H03L 7/107](#) should be considered in order to perform a complete search.
- 7/1077 {by changing characteristics of the phase or frequency detection means ([H03L 7/1072](#) takes precedence)}
WARNING
 Group [H03L 7/1077](#) is incomplete pending reclassification of documents from group [H03L 7/107](#).
 Until reclassification is complete, groups [H03L 7/1077](#) and [H03L 7/107](#) should be considered in order to perform a complete search.
- 7/113 using frequency discriminator
- 7/12 using a scanning signal ([tuning circuits with automatic scanning over a band of frequencies H03J 7/18](#))
- 7/14 for assuring constant frequency when supply or correction voltages fail {or are interrupted}
- 7/141 {the phase-locked loop controlling several oscillators in turn}
- 7/143 {by switching the reference signal of the phase-locked loop}
- 7/145 {the switched reference signal being derived from the controlled oscillator output signal}
- 7/146 {by using digital means for generating the oscillator control signal ([H03L 7/141](#), [H03L 7/143](#) take precedence)}
- 7/148 {said digital means comprising a counter or a divider}
- 7/16 Indirect frequency synthesis, i.e. generating a desired one of a number of predetermined frequencies using a frequency- or phase-locked loop
- 7/18 using a frequency divider or counter in the loop ([H03L 7/20](#), [H03L 7/22](#) take precedence)
- 7/1803 {the counter or frequency divider being connected to a cycle or pulse swallowing circuit}
- 7/1806 {the frequency divider comprising a phase accumulator generating the frequency divided signal}
- 7/181 a numerical count result being used for locking the loop, the counter counting during fixed time intervals {([H03L 7/1806](#) takes precedence)}
- 7/183 a time difference being used for locking the loop, the counter counting between fixed numbers or the frequency divider dividing by a fixed number {([H03L 7/1806](#) takes precedence)}

H03L

- 7/185 using a mixer in the loop
([H03L 7/187](#) - [H03L 7/195](#) take precedence)
- 7/187 using means for coarse tuning the voltage controlled oscillator of the loop ([H03L 7/191](#) - [H03L 7/195](#) take precedence)
- 7/189 comprising a D/A converter for generating a coarse tuning voltage
- 7/191 using at least two different signals from the frequency divider or the counter for determining the time difference ([H03L 7/193](#), [H03L 7/195](#) take precedence)
- 7/193 the frequency divider/counter comprising a commutable pre-divider, e.g. a two modulus divider ([pulse counters/frequency dividers H03K 21/00](#) - [H03K 29/00](#))
- 7/195 in which the counter of the loop counts between two different non zero numbers, e.g. for generating an offset frequency ([H03L 7/193](#) takes precedence; [pulse counters for predetermined counting H03K 21/00](#) - [H03K 29/00](#))
- 7/197 a time difference being used for locking the loop, the counter counting between numbers which are variable in time or the frequency divider dividing by a factor variable in time, e.g. for obtaining fractional frequency division {([H03L 7/1806](#) takes precedence)}
- 7/1972 {for reducing the locking time interval ([H03L 7/1974](#), [H03L 7/199](#) take precedence)}
- 7/1974 {for fractional frequency division}
- 7/1976 {using a phase accumulator for controlling the counter or frequency divider}
- 7/1978 {using a cycle or pulse removing circuit}
- 7/199 with reset of the frequency divider or the counter, e.g. for assuring initial synchronisation
- 7/20 using a harmonic phase-locked loop, i.e. a loop which can be locked to one of a number of harmonically related frequencies applied to it ([H03L 7/22](#) takes precedence)
- 7/22 using more than one loop
- 7/23 with pulse counters or frequency dividers
- 7/235 {Nested phase locked loops}
- 7/24 using a reference signal directly applied to the generator
- 7/26 using energy levels of molecules, atoms, or subatomic particles as a frequency reference

9/00 Automatic control not provided for in other groups of this subclass

2207/00 Indexing scheme relating to automatic control of frequency or phase and to synchronisation

- 2207/04 Modifications for maintaining constant the phase-locked loop damping factor when other loop parameters change
- 2207/05 Compensating for non-linear characteristics of the controlled oscillator

- 2207/06 Phase locked loops with a controlled oscillator having at least two frequency control terminals
- 2207/08 Modifications of the phase-locked loop for ensuring constant frequency when the power supply fails or is interrupted, e.g. for saving power
- 2207/10 Indirect frequency synthesis using a frequency multiplier in the phase-locked loop or in the reference signal path
- 2207/12 Indirect frequency synthesis using a mixer in the phase-locked loop
- 2207/14 Preventing false-lock or pseudo-lock of the PLL
- 2207/18 Temporarily disabling, deactivating or stopping the frequency counter or divider
- 2207/50 All digital phase-locked loop