

2	COMBINED WRENCHES AND PUMPS OR OILERS	7	.Jewel setters'
3.05	SHELL, PROJECTILE, OR WAD EXTRACTORS	7.5	.Mainspring winders
3.07	RECEPTACLE CLOSURE REMOVER	8	.Ruby pin setters
3.08	.Having discrete retainer or receptacle for removed closure	8.1	PACKING
3.09	.Combined or plural	9.2	STYLUS
3.15	..Attached to receptacle or closure	9.21	STAMP SCARIFIER
3.2	.Power-, vacuum-, or fluid pressure-operated	9.22	PERFORATOR AND INKER
3.25	.Wall or surface mounted or supported	9.24	TAPPET ADJUSTER
3.31	..With receptacle supporting or grasping means	9.26	PLOWSHARE HOLDER
3.32	...With bottom support	9.3	HOSE-CLAMP APPLIERS
3.33	..Rotary remover device, gear or lever actuated	9.4	WIRE STRIPPER
3.27	..Lever or prying type	9.51	.Bench tools
3.35	.Movable into or over handle	9.41	.Having relatively movable clamp and blade
3.36	.With additional receptacle-engaging means	9.42	..Clamp and blade move relative to supporting structure
3.37	..Lever- or gear-translated closure remover	9.43	..Blade moves relative to handle to remove insulation
3.29	..For engaging receptacle about closure (e.g., socket type)	9.44	.Pivoted blade
3.39	..Bottom support	10	NUT LOCK
3.4	.Gripping type	13	BOLT HOLDERS
3.41	..Finger grapple type	15.2	REPAIR TOOLS FOR RESILIENT TIRES
3.42	..With reciprocating closure-engaging	15.3	.Holders for spread tire casings
3.43	..With deformable strip-tightening means	15.4	.Deflating tools
3.44	..With pivoted closure-engaging parts	15.5	.Combined cement injectors and plug or patch inserters
3.45	.Screw type	15.6	.Cement injectors
3.55	.Levering or prying type	15.7	.Plug or patch inserters
3.47	..With impaling or inserting remover	15.8	SKID CHAIN APPLYING TOOLS FOR LOCK OR LATCH
3.56	..Having discrete relatively movable portions	15.9	CHUCK KEY
3.57	..Having handle, intermediate hook, and end fulcrum	16	HOLDER, PUSHER, OR SETTER FOR DRIVEN-TYPE FASTENERS
3.48	.Impaling or inserting type	44	SHINGLE TOOL
3.49	..With lateral projection or abutment	45	WOODEN FLOORING TOOL
3.5	SPECTACLE	46	TOOL JAW(S) POSITIONED BY RELATIVELY MOVABLE PLURAL HANDLES (E.G., PLIERS)
3.6	.Plier	300	.Including hydraulic features
3.7	LEAF-SPRING SPREADERS	301	.Antipodal jaw surfaces move apart as handles approach (e.g., outwardly expanding jaws)
3.8	FUSE PULLERS	302	.With three or more jaws
4	ENGRAVERS' CLAMPS	303	..With single pair of handles
6	WATCHMAKERS'	304	...Double pair Janus-jawed
		305	...With jaws fixed to handle(s)
		306	...With intermediate jaw(s) in line with and between outer jaws
		307	...With three jaws only
		308	...Two pivoted jaws and one sliding jaw
		309	

310Three coacting pivoted jaws	344	...Predetermined and discrete member of leverage selections
311	...With separate jaw pairs	345	..Axial motion of handle-attached actuators(s)
312Parallel jaws perpendicularly spaced	346	..Pivotal motion about axis of parallel actuator rod(s)
313	..With means requiring a completion of travel of jaw movement	347	..With means to articulate and/or slide both jaws
314	..With means for step-by-step jaw movement	348	...With means for arcuate motion of both jaws
315	..With means to immobilize handles against relative angular movement and means to move jaw(s) thereafter	349Cam actuator
316	..With plural selective handle positions	350Dual pivoted actuator levers
317	..With means for relative longitudinal handle movement	351With jaws pivoted together
318	..With means to immobilize jaws	352	...With means for parallel movement of work-engaging surfaces
319	..With lock-release means	353Longitudinal guide means
320	..With lock-disabling means	354Lateral guide means
321	..Including spring-urged handles or jaws	355	..With means for sliding jaw actuation
322	...And spring-urged latch	356	...With adjustment means
323	..Spring-urged latch element(s)	357Pivoted pawl type
324	..Positive lock means	358	...Pinion and rack
325	..With plural selective jaw positions	359	...Claw lever and rack or notch
326Threaded lock means	360Plural teeth on claw
327With threaded jaw adjustment means	361	...Grip lever and cam
328Interdigitated lock means	362	...Grip lever and link
329	..With means (nontoggle) to hold jaws against only retrograde movement	363Toggle link
330	..With plural preselective jaw positions	364	..Including claw lever and rack or notch means
331	..Manipulated lock member	365	...With adjustment means
332	...Pivoted bail	366	...Plural teeth on claw
333	...Sliding yoke	367	..Including toggle means
334	...Threaded member	368	...With toggle release
335Nut	369By means acting on intermediate pivot
336	...Pivoted rack	370Release means carried by grip lever
337	...Pivoted pawl	371Mounted on intermediate pivot
338	..Rack and pawl means	372	...With means to limit movement of intermediate pivot
339	..Coacting friction means	373	...With means for relative parallel movement of jaws
340	...Serrated surfaces	374	...With pitman between grip lever and intermediate pivot
341	..With means to vary range limit(s) of jaw movement	375	...With toggle linkage and actuated jaw mounted on carrier
342	..Jaw-actuating means (handle-manipulation conversion)	376	...With connecting rod between grip lever and actuated jaw
343	..With means to choose one of a plurality of actuator leverages	377	...With connecting rod between grip lever and handle member

378	...With actuated jaw pivoted on handle member	411	...With pivot pin fulcrum in notched slot
379With means for resiliently biasing jaw and/or toggle	412	...With flattened cross section pin
380Extension coil spring between jaw and handle member	413	...With toothed-member fulcrum on notched handle
381	..Including grip lever actuator and pivoted jaw (e.g., tandem levers)	414	...With opposed interdigitated concentric segmental annular portions
382	..With adjustment means	415	.Crossed handles
383	..With link connecting jaw and grip lever	416	..Joint detail
383.5	..Including cam actuator and pivoted jaw	417	..Resiliently urged
384	..With adjustment means	418	.Jaw features
385	..Adjustable relationship between jaw(s) and/or handle(s)	419	..Tined or digitated jaws
386	..By relative positioning of jaw(s) only	420	..Jaws extend laterally beyond side edge plane of handle(s)
387	...Both jaws adjustable	421	..Jaw attachment and/or inserts
388	...By threaded elements	422	...Selective
389Rotatable screw type	423	...By detachment
390Rotatable nut type	424	...Articulated
391	..Maintained by detent and rack	424.5	..Nonplanar jaw face
392	..Maintained by locked interdigitated members	426	...And diversely shaped face
393	..By angular orientation of one handle portion relative to other	426.5	...Work conforming face
394	..By selection of pivot hole(s) in each handle	427	.Resiliently urged
395	..By threaded adjustment means	427.5	.Handle
396	...Worm and rack type	463	INCLUDING TOOL DRIVING BY IMPACT DELIVERING COMPONENT OR COOPERATING ANVIL
397	...Peripherally threaded handle manipulated for travel relative to other handle	464	.Motor or gear driven
398	...Threaded element travels relative to both handles	465	.Structurally constrained to arcuate movement
399	...Rotatable screw in nut	466	..About turning axis of work engaging portion
400Screw attached to joint	52	WRENCH, SCREWDRIVER, OR DRIVER THEREFOR
401Nut attached to joint	53.1	.With elongated hot line stick
402	...Rotatable nut on screw	53.11	..Globe manipulator
403Screw attached to joint	53.12	...Rotatable grasper
404Nut attached to joint	53.2	.Stud-removal and implacement
405	..By manipulation of pivot-carrying member	429	.Responsive to movement of work
406	...With angular orientation of eccentric pivots joining handles	467	.Responsive to torque on work
407	..By relative sliding or slipping of handles	468	..With marking mechanism
408	..With fulcrum-carrying member	469	..Means for regulating motor
409With positive lock for member	470	...Fluid motor
409.5With spring urged lock for member	471	..Permanently deformable component
		472	..Relatively movable work contacting components
		473	..Rotatable, coaxial, clutching components
		474	...Having intermediate, disparate, interlock element
		475	...Having complementary formations

476	...Having friction type contact surfaces	432	...Including vibratory work supporting member
477	..Work engaging portion attached to and turned by resilient member	433	...Including revolvably driven work contacting member
478	..Work engaging portion pivotally or rotatably connected to handle	434	...Including driven, flexible, work supporting strip
479	...With electric signal device	435	...Including driven, reciprocating, conveying member
480	...Axis of connection coaxial to rotational axis of work	57.38	..With tensioning means
481	...With arm extending from portion	57.39	..Step by step
482	...With pivoted locking pawl	57.4	..With support
483	...With arm extending from portion and through connection	57.41	...Vehicular
54	.Machine	57.42	..Direct drive
55	..Bolt-holding	57.43	...Flexible
56	...Gear-operated	57.44	...Fluid
57	..Gear-operated	57.45	...Oblique angle
57.11	...With motor	57.46	...Tangential engagement
57.12	...Oblique angle drive	57.5	.Turret head
57.13	...Right angle drive	74	.Wheel or endless track operated
57.14	...Parallel axis drive	75	..Hub-rim grasp
57.15	...Round work	76	...Internal
57.16	...With additional work-engaging means	58	.Handle clutched to head
57.17	...Flexible jaw	58.1	..With additional head-turning means
57.18	...Cam-operated jaw	58.2	..Radially slotted or open end head
57.19	...Fluid-operated jaw	58.3	..Axially movable clutching parts
57.2	...Pivoted jaw	58.4	..Positive two-way drive (e.g., dog clutch)
57.21	...Sliding jaw	58.5	..Radially extending eccentrically movable handle
57.22	..Multiple drive or driven means	59.1	..Ball or roller wedge
57.23	...With magazine	60	..One-way detent drive, e.g., ratchet
57.24	...With support	61	...Pivoted pawl
57.25	...Vehicular	62	...Reversing
57.26	..Adjustable angle drive	63Single
57.27	...Flexible shaft	63.1	...Reversing
57.28	...Oblique angle drive	63.2	...Single pawl
57.29	...Right angle drive	436	.Having work engaging and force exerting portion inserted into cavity (e.g., allen wrench, screwdriver)
57.3	...Parallel axis drive	437	..Combined with or usable as diverse-type wrench
57.31	..Common axis drive	438	..Having structure adapting portion or tool for separation
57.32	..Double or duplex	439	..Including discrete, separately usable inserted portions
57.33	..Round work	440	...Pivotally or rotatably mounted
57.34	...With additional work-engaging means	441	..Inserted portion cuts into or deforms cavity
57.35	...With support	442	..Inserted portion having relatively movable components
57.36	..Multiple work-engaging means		
57.37	..With feed or magazine means		
430	...Utilizing fluid to convey work		
431	...Including chute having longitudinal axis collinear with rotational axis of work turning portion		

443	...Having camming or wedging element for moving components	90.1	.Plural pivoted jaws and handle-lever
444Axially shiftable element located between and wedging against components	90.2	..Cam or gear operated
		90.3	..Jaws enclose work
445With threaded surface for cooperating with mating tool structure	90.4	...Including latch to connect jaw to handle-lever
		90.5At least three jaws enclose work
446Rotatable element located between and camming against components	90.6	...Including latch to connect pivoted jaws
447	..Having cooperating threaded element type actuating means	90.7At least three jaws enclose work
448	...Having resilient or spring biased component	90.8Two jaw pairs connected by latch
449Biased component rotated about axis collinear to rotational axis of tool	90.9	..Including means to adjust or to secure jaw in adjusted position
450	..Inserted portion mounted to pivot or swivel relative to longitudinal axis of handle	91.1	..Slidable pivot
		91.2	..First jaw pivoted directly to handle and to second jaw
451	..With separate means for guiding or gripping work	91.3	..Two jaws pivoted directly to intermediate member
452	...Having resilient, relatively movable, work gripping members	92	.Pivoted inner jaw
		93	..Nut or screw fulcrum
453With camming or wedging element for moving members	94	..Pin fulcrum
		95	...Roller jaw
454	...Having pivoted, relatively movable, work gripping members	96Pinion
		97	...Spring-pressed
455With camming or wedging element for moving members		.Pivoted outer jaw
			..Fixed fulcrum
456	...Having member with work underlying portion	98	...Nontraveling jaw
		99Spring-pressed
457Member spring biased for axial movement	100	...Traveling jaw
		101Nut fulcrum
458Resilient member	102Rocking sleeve
459	..Inserted portion having threaded periphery	103Spring-pressed
		104Fulcrum washer
460	..Inserted portion having plural, noncollinear blades (e.g., Phillips)	105Sleeve-enclosed nut
		106	..Traveling fulcrum
461	..Inserted portion having plural, separate, work-engaging projections	107	...Threaded handlebar
		108Axillary rotating
		109	...Slotted guide
64	.Flexible	110	...Fulcrum tooth and rack
65	..Threaded adjustment	111	.Pivoted side jaw
65.2	..Link	112	..Bevel-closing
68	...Handle jaw	113	...Cammed into socket by axial nut or screw
69Pivoted	114Sleeve socket nut
70Duplex	115	...Rotating ring
65.4	...Toothed adjustment	116	...Wedge
73	.U-crank arm	117	..Rocking link
77	.Double-ended, simultaneous adjustment	118	..Transverse screw clamp
		126	.Sliding jaw, handle-lever grip
		127	..Claw

128	.Sliding jaw, cam-closing	176.15	..Having means to engage work axially
129	.Slidable jaw adjustments	176.2	...And means to engage peripheral face of work
129.5	..Rack	176.3	..Having relatively movable jaws
131	...Interlocking jaw handles	119	.Rigid jaws
132	...Locking set screw or nut	120	..Round work
133	...Pinion lock	121.1	..Enclosed (e.g., socket)
134	...Pivoted rack catch	122	...Watch and clock keys
135Nontraveling	123Dust protectors
136Intermediate fulcrum	124.1	...With nut ejectors
137Transverse	125	...Work-holding
138Cam-seated	124.2	...Slotted socket
139Indirectly operated	124.3	...Through socket and perpendicular handle
140Intermediate fulcrum	124.4	...Plural sockets
141	...Shank-engaged cam	124.5Slidably or pivotally connected to handle or each other
142	...Sliding rack catch	124.6	...Having axial opening for removable handle
143Cam-seated	124.7	...Having perpendicular handle
144Screw- or nut-seated	125.1	..Double-ended
145Spring-seated	177.1	.Handle or shank
146	...Spring-seated jaw frame	177.8	..Angularly adjustable handle
147Integral frame and teeth	177.9	...With yieldable one-way detent
148	...Wedge lock	177.2	..Extensible handle or handle extension
149	...Wedge pusher	177.3	..Having finger opening
150	..Shank grip	177.4	..Having means to store parts
151	...Side jaw	177.5	..Having terminal cross arm
152	...Clutch yoke	177.6	..Foldable or flexible
153	...Roller clutch	177.7	..Having pivoted handle section
154	...Locking incline	177.75	...Universal joint
155	..Thread	177.85	..Including socket and boss type connecting means
156	...Displaceable half nut	178	.Reversible jaws
157	...Displaceable nut or screw	179	.Sliding jaw face
158Traveling screw, shank rack	462	.Having stationary structure for supporting wrench or screwdriver
159	...Interrupted	180.1	.Attachment, or including adjunct or replaceable portion
160Nut set	181	..Cutters
161Traveling nut	182	...Rotary
162Traveling screw, shank rack	183	..Roller clutch
163	...Right and left threads	184	..Shank-embracing
164	...Rotatable threaded handle shank	185	..Socket reducers
165	...Sliding side jaw	185.1	..Removable jaw face
166	..Nontraveling rotatable nut	185.2	..Movably mounted
167Intermediate	186	.Jaw faces
168Causing outer jaw to slide	19	DEFORMABLE HEAD MALLET
169Terminal	20	HAMMER
170Causing outer jaw to slide		
171	...Nontraveling rotatable screw		
172Bracket-bearing		
173Spiral groove engaged by slidable actuator		
174	...Traveling and rotating nut		
175Threaded handlebar		
176	...Traveling and rotating screw		
176.1Shank rack		
176.1	.Spanner		

21	.Having work protector surrounding face	DIG 2	SPIRAL DRIVE FOR WRENCHES
22	.Having shock absorbing means	DIG 3	WRENCHES, THREAD-ADJUSTMENT LOCK
23	.Having nail placer	DIG 4	DOUBLE ADJUSTMENTS, SLIDING JAW
24	..Magnetic	DIG 5	WRENCH SCALES AND INDICIA
25	.Having replaceable striking face	DIG 6	SPRING MEANS BIASING WRENCH JAWS
26	.Having plural striking faces	DIG 7	BICYCLE SPOKE OR NIPPLE WRENCH
27	.Rod encircling type	DIG 8	CROWFOOT-TYPE WRENCHES
28	BIT STOCK HAVING MANUAL DRIVE MEANS (E.G., BRACE)	DIG 9	PIVOTED JAW LATCH MEANS
29	.Having ratchet mechanism	DIG 10	IRIS-TYPE WRENCH HEAD
30	..Straight crank arm	DIG 11	ADAPTERS FOR DIFFERENT-SIZED FASTENERS
31	..Adjustable pawl	DIG 12	POWER HAMMER
32	..Pivoted pawl		
33	..Sliding pawl		
34	.Straight stock having side driving gear		
35	.Having U-shaped crank arm		
36	..Speeding gear		
37	..Bit shaft inclined relative to crank		
484	FOR ADJUSTING VARIABLE POSITIONED PARTS		
485	SPREADER		
486	RESILIENT ARTICLE TENSIONER OR COMPRESSOR		
489	HANDLE FOR TOOL		
490	.Having storage compartment		
491	.Having discrete relatively movable tool clamp		
492	.Having cap or reinforcing means		
487	HAND HELD HOLDER OR HAVING CLAMP		
488	MISCELLANEOUS		

CROSS-REFERENCE ART COLLECTIONS

900	WRENCH OR SCREWDRIVER CONSTRUCTED FROM SPECIFIC MATERIAL
901	WRENCH OR SCREWDRIVER ADAPTED TO TURN EYE SCREW

FOREIGN ART COLLECTIONSFOR 000 **CLASS-RELATED FOREIGN DOCUMENTS****DIGESTS**DIG 1 **TOOL-SUPPORT ADJUNCTS**