200	STAIRWAY ASSIST FOR INDIVIDUAL OR MINOR BARRIER (E.G., CURB) LIFT FOR IMPAIRED INDIVIDUAL	222	<pre>INDUSTRIAL LIFT TRUCK OR REQUIRED COMPONENT THEREOF (E.G., FORKLIFT)</pre>
201	.Mounted adjacent stairway for	223	.Having safety cutoff control
201	travel parallel thereto	224	.Having control for load support
202	-		drive-means
202	Having specific means	225	.Having foldable vertical guide
	contacting or on load support	226	
	for stopping thereof	226	.Having extensible vertical guide
203	STATIONARY LIFT FOR ROADWAY	000	for load support
	VEHICLE OR REQUIRED COMPONENT THEREOF	227	Guide or drive-means therefor positioned to enhance operator
204	.With distinct jack on vehicle	000	visibility
	support	228	And guiding means for fluid
205	.With floor pit opening for		drive line
	support and safety cover	229	Extended by single fluid ram
	therefor	230	Specific vertical guide
206	.With safety prop or braking rod	231	.Having structure allowing
	for support		propulsion or steering by
207	.Having position lock for		walking attendant
207	engaging sustaining drive	232	With stabilizing outrigger
		233	.Having specific drive-means for
	means or guide means of	233	load support
0.00	support	224	
208	Ratchet bar and latching pawl-	234	Including fluid ram
	type lock	235	Including cable accumulating-
209	.With safety cutoff for drive		type drum
	means	236	Including gear and mating rack
210	.Having specific drive means for		or chain
	support	237	.Having specific load support
211	Includes plural sustaining		structure (e.g., forks)
	levers (e.g., scissored	238	.Having specific guide means for
	levers)		load support
212	Powered by vehicle being lifted	239	MOUNTED ON EXTERIOR OF BUILDING
213	Includes driven sustaining	240	TRANSPORTABLE ELEVATOR
213	columns on opposite sides of	-	
	11	241	.Nonself-supporting-type (e.g.,
014	support	0.40	leaned against building)
214	Having threaded rider and mating screw	242	.Knockdown or collapsible for transport
215	Includes sustaining fluid ram	243	Wheel supported
216	.Having specific vehicle support	244	.Wheel supported
	structure (e.g., trackways)	245	INCLINED ELEVATOR
217	With movable stop engaging	246	.Having linking cable tension
	vehicle wheel		change actuated stopping means
218	Includes portion positioned or		for load support
	shaped to engage axle or	247	HAVING COMPUTER CONTROL OF
	undercarriage	21,	ELEVATOR
219	Portion adjusts to plural use	240	
217		248	.Includes redundant circuitry
220	positions	249	HAVING INDEPENDENT SUPPORTS
220	Portion moves from use to		CARRYING DISTINCT LOADS AND
	nonuse configuration (e.g.,		SHARING COMMON PATH
	alternate supports)	250	HAVING SPECIFIC LOAD SUPPORT
221	Includes auxiliary or		DRIVE-MEANS OR ITS CONTROL
	adjustably spaced trackway	251	.Includes linking support cable
			(e.g., rope, chain) in drive- means

187 - 2 $\,$ CLASS 187 ELEVATOR, INDUSTRIAL LIFT TRUCK, OR STATIONARY LIFT FOR VEHICLE

252	And reciprocatingly shifted pulley wheel pulling thereon	282	Actuated by load support contacting trip in shaft
253	Shifted by fluid ram	283	Having trip at each of plural
254	And rotatably driven drum		landings
	pulling thereon	284	And means for final leveling
255	With projections or apertures	285	For fluid-type power source
	for engaging complementary	286	Actuated by load support
	formations on cable (e.g.,		speed sensor or governor
	sprocket)	287	Includes safety cut off switch
256	Plural driven drums		actuated by load support speed
257	Each moves distinct load		sensor or governor
	support	288	Control actuates mechanical
258	Having distinct drive motors		braking means for power source
259	Cable accumulating-type drums	289	For electric power source
260	Different size drums	290	With auxiliary supply of
261	Cable accumulating-type drum		electricity
262	Having cable guiding pulley	291	Having means for final
	wheel spaced therefrom		leveling
263	With structure adapting drum	292	With means for stopping
	for manual drive		vibration or bump start
264	With separate biasing means	293	Controls power source speed
	maintaining cable tension	294	Actuated near terminus of
265	Includes spring supported		shaft
	pulley	295	Having control signal
266	Having cable guiding pulley		pattern generator
	wheel spaced therefrom	296	Limited to power source
267	.Includes threaded rider mating		(i.e., motor) utilizing A.C.
	with support screw in drive-		power
	means	297	Limited to power source
268	Driven rider		(i.e., motor) utilizing D.C.
269	.Includes scissored supporting		power
	levers in drive-means	298	Actuated by human operator
270	.Includes gear on support mating		engaging specific input part
	with stationary rack or chain	299	With means locking input
271	Worm-type gear		part of control against
272	.Includes fluid supporting ram in		movement
	drive-means	300	Actuated by presence of
273	Pneumatic (e.g., steam)		obstruction in shaft
274	Plural fluid rams having	301	Actuated by location of access
	interrelated operation		barrier or its lock
275	With fluid flow controlling	302	Actuated by load support
	means		contacting trip in shaft
276	.Includes control for power	303	Having trip at each of plural
	source of drive-means	0.04	landings
277	With specific electrical	304	Trip supported on or formed
	component	205	by cable
278	Actuated by movement of	305	Actuated by load support speed
	building (e.g., seismic	206	sensor or governor
	activity)	306	Actuated by human operator
279	Actuated by presence of	205	engaging specific input part
0.00	obstruction in shaft	307	With means for locking input
280	Actuated by location of access		part of control against
0.01	barrier or its lock		movement by operator
281	Actuated by excessive load		

308	Actuated by position or movement of access barrier or	334	.Including slideably mounted barrier on load support
	its position lock	335	With position lock therefor
309	Having barrier position lock	336	WITH CLOSURE MEANS FOR SHAFT
	operable only when load		OPENING THROUGH LANDING
	support or control input part	337	.Including pivoted closure
	safely positioned	338	Shifted by drive-means powered
310	With common actuation of		by load support motion
	barrier position lock and	339	With closure latching means
	input part locking means	340	.Including transversely sliding
311	Using cable to transmit input		closure
312	Running cable type	341	Shifted by drive-means powered
313	WITH BARRIER FOR REGULATING		by load support motion
	ACCESS TO LOAD SUPPORT	342	.Including closure bodily carried
314	.Operation variable for		along shaft by load support
	emergency, maintenance, or	343	HAVING MEANS CUSHIONING CONTACT
0.4.5	abnormal condition		OF LOAD SUPPORT WITH TERMINUS
315	.Includes motor or motor driven		OF SHAFT
24.5	linkage for shifting barrier	344	.Fluid resistance or shock
316	With specific electrical		absorber-type means
245	control therefor	345	HAVING FLUID DAMPENING MEANS
317	Includes object detecting		REGULATING LOAD SUPPORT
210	sensor or switch on barrier		MOVEMENT
318	Shifts barrier mounted at	346	.With fluid coacting portion
210	landing		carried by load support
319	Through coupling with barrier	347	.Includes piston and cylinder
320	on load support		attached to support by cable
320	Plural interconnected motors	348	WITH EMERGENCY RUNNING SUSPENSION
	shift barriers at different	2.40	CABLE FOR LOAD SUPPORT
321	landings	349	WITH CONDITION ACTUATED MEANS
321	landingsMotor stationarily mounted and	349	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM
321	<pre>landingsMotor stationarily mounted and linkable to barriers on</pre>		WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS
	<pre>landingsMotor stationarily mounted and linkable to barriers on different landings</pre>	349 350	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE
321 322	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft		WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR
	<pre>landingsMotor stationarily mounted and linkable to barriers on different landings</pre>		WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD
322 323	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landings	350	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT
322	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motor		WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING
322 323	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load	350	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT
322 323 324	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support	350 351	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF
322 323 324	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landing	350	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating
322 323 324 325	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means	350 351	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF
322 323 324 325	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landing	350 351 352	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rack
322 323 324 325	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load	350 351 352 353	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear
322 323 324 325 326	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load support	350 351 352 353	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier
322 323 324 325 326	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in	350 351 352 353 354	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movement
322 323 324 325 326	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-means	350 351 352 353 354	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact
322 323 324 325 326	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum	350 351 352 353 354 355	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support
322 323 324 325 326	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding	350 351 352 353 354 355	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having
322 323 324 325 326 327 328	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-means	350 351 352 353 354 355	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact
322 323 324 325 326 327 328	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding	350 351 352 353 354 355 356	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact component
322 323 324 325 326 327 328 329 330	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding pulley therefor in drive-means	350 351 352 353 354 355 356	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact componentMounted only at landings or
322 323 324 325 326 327 328 329 330 331	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding pulley therefor in drive-meansWith means to couple to barrier on load supportWith position lock therefor	350 351 352 353 354 355 356	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact componentMounted only at landings or terminus of shaft
322 323 324 325 326 327 328 329 330 331 332	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding pulley therefor in drive-meansWith means to couple to barrier on load supportWith position lock thereforCollapsible or rollable type	350 351 352 353 354 355 356	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact componentMounted only at landings or terminus of shaftHaving drive-means for
322 323 324 325 326 327 328 329 330 331	landingsMotor stationarily mounted and linkable to barriers on different landingsIncludes rotating shaft extending between landingsNonelectric motorShifts sliding barrier on load support .Including barrier mounted at landingBarrier shifted by drive-means powered by motion of load supportHaving endless driving belt in drive-meansHaving rotatably driven drum and cable pulled thereby in drive-meansHaving cable and guiding pulley therefor in drive-meansWith means to couple to barrier on load supportWith position lock therefor	350 351 352 353 354 355 356	WITH CONDITION ACTUATED MEANS RELEASING LOAD SUPPORT FROM DRIVE-MEANS HAVING MEANS ENGAGING CABLE ATTACHED TO LOAD SUPPORT, OR ITS GUIDE, TO SLOW LOAD SUPPORT HAVING SPECIFIC MEANS CONTACTING OR ON LOAD SUPPORT FOR STOPPING OR SLOWING THEREOF .Includes gear on support mating with stationary rackWorm-type gear .Means actuated by access barrier movementAnd having movable contact component carried by support .Stationarily mounted and having disparate movable contact componentMounted only at landings or terminus of shaftHaving drive-means for component powered by load

187 - 4 $\,$ CLASS 187 ELEVATOR, INDUSTRIAL LIFT TRUCK, OR STATIONARY LIFT FOR VEHICLE

359	.Includes movable contact	384	Having security or priority
	component on support for		preemption feature
	engaging shaft structure	385	Dispatches load supports from
360	Interlocking only with		designated landing
	structure of landings or	386	Frequency based on interval of
	terminus of shaft		time
361	Actuated by change in	387	Assigns calls to load supports
	suspension or counterweight		on predetermined basis
	cable tension	388	.Also directs response
362	And shaped to cut into	389	.Includes specific floor selector
	cooperating structure	390	ALARM SYSTEM
363	And interlocking with	391	
5 0 5	complementary stationary	391	WITH MONITORING, SIGNALLING, AND
	formation (e.g., catches)	200	INDICATING MEANS
364	Slidably mounted contact	392	.Monitors passengers
304	component	393	.Monitors operational parameter
365	Slides perpendicular to path	394	Load support position
303		395	HAVING CALL BUTTON WITH INDICATOR
266	of support	396	GENERAL INFORMATION DISPLAY
366	Plural pivotally attached		(E.G., STORE DIRECTORIES)
	gripping contact components	397	WITH VISUAL INDICATOR OF MOVEMENT
2.60	engaging common rail		OF LOAD SUPPORT
367	Pivotally attached contact	398	.Indicates particular one of
	component		plural load supports
368	With eccentric camming face		responding
369	Having similar contact	399	.Indicates existing location
	component cooperating to grip	400	WITH SAFETY OR SEALING MEANS FOR
	common rail		GAP BETWEEN LOAD SUPPORT AND
370	Plural gripping contact		LANDING
	components engaging common	401	HAVING SPECIFIC LOAD SUPPORT
	rail		STRUCTURE OR ARRANGEMENT
371	Slidably mounted contact		(E.G., CAR FRAMING)
	component	402	.Arranged to carry masonry hod
372	Having wedge shape or sliding	403	.With means for engaging wheels
	along incline	403	of carried vehicle
373	Actuated by load support speed	404	HAVING SPECIFIC COUNTERBALANCE
	governor or sensor	404	MEANS FOR LOAD SUPPORT
374	Pivotally attached contact	405	
	component		.Includes variable weight
375	Plural gripping contact	406	HAVING SPECIFIC STATIONARY
373	components engaging common		GUIDING STRUCTURE FOR
	rail		COUNTERBALANCE MEANS OR LOAD
376	Slidable contact component	407	SUPPORT
3.0	having wedge shape or sliding	-	.Formed from cable
	along incline	408	.And mounting means therefor
377	Actuated by human operator	409	HAVING SPECIFIC GUIDE SHOE
378	And interlocking with	410	.With roller
370		411	HAVING SPECIFIC FORCE
	complementary stationary formation		TRANSMITTING CONNECTION FOR
270			COUNTERWEIGHT OR LOAD SUPPORT
379	Pivotally attached contact	412	.Equalizes tension in, or length
200	component		of, plural linking cables
380	WITH CALL REGISTRATION MEANS	413	HAVING SPECIFIC ARRANGEMENT OR
381	.Having call cancel or refuse		CONNECTION OF ELECTRICAL OR
	feature		FLUID SERVICE LINE
382	.Shared by plural load supports	414	MISCELLANEOUS
383	Assigns load supports to zones		
	3		

CROSS-REFERENCE ART COLLECTIONS

900	TEMPORARY CONSTRUCTION ELEVATOR
	FOR BUILDING
901	CONTROL MODIFIED FOR USE BY
	DISABLED INDIVIDUAL
902	CONTROL FOR DOUBLE-DECKER CAR

FOREIGN ART COLLECTIONS

FOR 000 CLASS-RELATED FOREIGN DOCUMENTS

187 - 6 $\,$ CLASS 187 ELEVATOR, INDUSTRIAL LIFT TRUCK, OR STATIONARY LIFT FOR VEHICLE