1	PROCESSES OF DISPENSING	28	With common operating means
590	.Molten metal	29	.Plural scale
2	CHECK CONTROL	30	.Recorder
3	GAS OR VAPOR DISPENSING	31	.With motion ratio adjusting
4	.With nongaseous material dispensing		<pre>means and/or relatively adjustable scale and pointer</pre>
5	.With cutter or punch	32	.With zero-setting mechanism
6	.Parallel connected, serially used	33	Operating cycle including reset to zero
591	MOLTEN METAL DISPENSING	34	With means to prevent zero
592	.With heating or cooling		setting during discharge
593	Heating	35	With means to prevent discharge prior to zero setting
594	.Flow controllers or assists	36	.Totalizer for successive
595	Fluid pressure assist	30	dispenser cycles
596	Piston displacement	37	
597	Closure	3 /	Varying cycles or quantities
598	Movable about an axis	2.0	per cycle
599	Perpendicular to flow	38	Reciprocating (including oscillating) dispenser part
600	Reciprocating transverse to	39	.Audible
601	flow	40	.Flow and/or overflow type
601	Stopper operator structure	41	.Position or extent of motion
602	beneath receptacle		indicator
602	Stopper operator structure above receptacle	42	Selection from plural outlets,
603	.Gaseous fluid engages molten	4.2	valves or traps
629	metal .Submersible dipper or trap	43	Comprising an adjustable stop or stops
029	chamber	44	Scale and pointer, with detents
604	.Tilting receptacle	45	Flexibly connected indicator
605	Teakettle type		and dispenser element
606	.With subjacent flow guide	46	Common screw means for
607	Unattached		indicator element and
14	CUTOFF OPERATED BY SELECTIVELY	4.77	dispenser part
	PRESET VOLUME OR RATE OF FLOW- RESPONSIVE MECHANISM	47	Indicating element rigidly carried by movable dispenser element
15	.With means to prevent change of	48	Pivoted or rotary dispensing
	setting during discharge		part
16	.Operating cycle including reset	49	Slidable indicator element
4.5	to starting position		projecting from container
17	.Moving cutoff operating element	50	Scale or container
	with variable initial position	51	.Float-level indicators
18	Having plural revolutions	52	AUTOMATIC CONTROL
19	Plural dials	53	.Involving conveying conduit
20	Cutoff by valve closing		jacket and/or inert atmosphere
21	.Cutoff by single trapped volume		(including vacuum) providing
22	.Cutoff set after discharge begins	- 4	means
23	WITH RECORDER, REGISTER,	54	.Temperature responsive or
	INDICATOR, SIGNAL OR EXHIBITOR		soluble controller
24	Register with shutter	55	.Constant weight, volume or
25	.Plural		pressure control by output
26	Two or more volume devices	56	.Delivery from source controlled
27	Register and signal		by quantity in discharging
۷ /	register and signar		receiver

57	.By weight, volume or pressure of	78	SIMULATIONS
	a second dispensed material	79	.Firearms
58	.By the weight of the material in	80	WITH CUTTER AND/OR PUNCH
	the supply container	81	.To form dispensing opening in
59	.Cutoff operated by rate of flow		container
	responsive mechanism	82	With discharge assistant
60	Single complete revolution of	83	Mounted for relative motion
C 1	controller element	83.5	With sleeve or rest for
61	.Of dispensers with fluid	0.5	container cut
(1)	pressure discharge assistance	85	For cutting plural openings
62	Float-controlled pressure liquid	86	With sleeve or rest for container cut.
63	.Motor control	87	With container-destroying means
64	.Material level control	88	With sleeve or rest for
65	Full and/or empty interlock	00	container cut
66	Empty container cutoff	89	With nonfriction fit means to
67	Float-operated flow controllers	0,5	secure discharge guide to
68	Plural		container
69	For vent only	90	Abutment for container
638	INCLUDING TIMER		interior
639	.For timing dispensing period	91	Screw
640	Of beverage or beverage	92	COLLAPSIBLE WALL-TYPE CONTAINER
	component dispenser	93	.With additional article-holding
641	Including electrical timing		means
	circuit	94	.Plural container and/or
642	Of discharge assistant		compartment
643	Rotary	95	.With wall-collapsing means
644	And means for timing the period	96	With interconnected flow
6.45	between dispensing cycles		controller or closure
645	Of aerosol dispenser	97	operating means
646	Including electrical timing	98	Plural typesWinding and roller types
647	circuitAnd mechanical timing	99	Winding type
047	element	100	With casing or support
648	And battery power supply	101	Roller type
649	.For aerosol dispenser	102	Plural roller
650	.For plant or animal feed	103	Clamping type
	dispenser	104	Twisting type
651	.For wash cycle ingredient	105	.With casing or support
	dispenser	106	.Combined
652	Movably mounted ingredient	107	.Nonmetallic
	container	108	DRIP, LEAKAGE OR WASTE CATCHING
71	VOLUME OR RATE OF FLOW METERING		OR DISPOSAL
72	.With meter bypass, gas	109	.Return to main supply
	separation, antisyphon priming	110	Valved
73	.With hose pressure relief or	111	With enclosing cover
5 .4	maintenance	113	WITH ILLUMINATOR OR BURNER
74	HOSE OR OTHER MOVABLE DISCHARGE	576	INKWELL
	GUIDE INTERLOCKS AND INTERCONNECTIONS	577	.With support (i.e., inkstand)
75	.Switch or motor control and	578	.Including nongravity feed to dip
15	discharge controller actuator	570	well
77	WEIGHING	579	Spillover type

580	Including discharge assistant supporting and movable with dip well	142.4	Selection as a result of container shape, configuration or arrangement
581	Diaphragm-type discharge	142.5	Container within container concentrically arranged
582	Biased for resetting	142.6	With common selector
583	.Including dip well filled by	142.7	Interconnected relatively
303	immersion into supply	142.7	movable closures
584	.Tiltable to fill dip well	142.8	Bodily slidable closure
585	.Barometric	142.9	Axially rotary closure for
586	Including base supporting	142.5	axial outlets
300	removable inverted container	143	.Packing or stacking arrangements
587	And valve or base-opened	144	.Rotatably mounted assembly
367	closure	144.5	.With selecting means
588	Dip opening below peak level of	144.5	.With common discharge
300	supply	145.1	Including discharge path
589	Including closure or valve for	143.2	cleaning discharge path
309	dip well outlet	145.3	
129	PLURAL SOURCES, COMPARTMENT,	143.3	Dispensed product retains identity of individual
129	CONTAINERS AND/OR SPACED		material (e.g., striped
	JACKET		toothpaste)
129.1	.Cabinet-type dispenser for	145.4	Movable material discharge
127.1	single mixed drinks	143.4	guide
129.2	One ingredient operates	145.5	Having mixing chamber
129.2	dispensing means for another	145.6	Including mixing means
129.3	With ingredient charge	145.7	Having variable flow control
129.9	measuring	145.8	For common path
129.4	Plural measured charges in	146.1	WITH HEATING OR COOLING MEANS
127.4	single drink	146.2	.Heating only
130	.At least one nondispensing	146.3	Having an aerosol
131	Jacketed	146.4	By steam
132	.Three or more diverse sources	146.5	By electrical energy
133	.Measured discharge from one and	146.6	.Cooling only
133	indeterminate flow from	140.0	WITH REFILL PREVENTING MEANS
	another	148	WITH CLEANING MEANS
134	.Interconnected discharge volume	149	Element extending through
	varying means	147	dispenser outlet
135	.With discharge assistant for	150	Operated by resilient container
	each source	130	walls
136	Single, operable on material	151	Extending inwardly through
	from all sources	1 31	container outlet
137	Unitary reciprocating	152	WITH CONVEYING CONDUIT JACKET
138	Two or more rotary or swinging	132	AND/OR INERT ATMOSPHERE
139	Co-axial		(INCLUDIND VACUUM) PROVIDING
140	Vertical axis		MEANS
141	Single plane	153.01	WITH LOCK OR FASTENING SEAL
142	Parallel axes	153.02	.Plural
142.1	.Hand manipulable shaker type	153.03	.Lock actuated by key or tool
142.2	Selection by relative movement	153.04	.Lock operation dependent upon
	between containers or		dispenser position
	containers and casing	153.05	.Single-use fastening seal
142.3	Containers removable from base	153.06	Frangible
	or casing	153.07	Pull tab
		153.08	Cord
		153.09	.Inhibiting disassembly
		22.02	5

152 1		C1 F	*****
153.1	Overcap	615	With variable transmission
153.11	.For a fluid pressure discharge	616	With clutch
	assistant	617	Fluid flow discharge
153.12	Maintain dispenser in open	618	Plural ground wheel driven
	position		discharge assistants in series
153.13	.Inhibiting actuation of	619	Ground wheel driven vibrator
	discharge assistant		or jarring means
153.14	.Inhibiting operation of flow	620	Rotary motion of ground wheel
	controller or closure		to reciprocating, oscillating,
154	INSPECTION DEVICES		or linear motion
155		621	Fluid pump
	External gauge tubes	622	
156	.Sight openings	-	Endless conveyer
157	Graduated for level	623	Ground wheel driven rotary
	determination		discharge assistant or rotary
158	.Graduated transparent container		agitator
	or trap	624	With adjustable discharge
159	.Transparent flow-line section		controller
160	MOVABLY MOUNTED SUPPLY CONTAINER	625	Sliding gate or shutter
161	.Vibratory (i.e., for agitation	626	Motor operated dispensing means
	of container contents)	627	Power take off
162	.Moving relatively to trap,	628	Manually actuated fluid pump
	impeller or valve to cause	179	.With pedal-controlled discharge
	discharge		means
163	.Adjustable relatively to	179.5	.Removable for discharge
	discharge assistant to vary	180	.Bracket or suspension supported
	the discharge volume	181.1	For bottom discharge
164	.Tiltable	181.2	Suspension supported
165	For refilling or changing	181.3	Supported on vertical wall by
103	cartridges or containers	101.5	container integral with wall
166	•		•
	For gravity discharge	100	or by a plate support means
167	Rotatable	182	.Enclosing cover for actuating
168	Vertical axis		parts of discharging means
168.5	Circumferentially arranged	183	.Jacketed
	measuring or trap chambers	184	.Extended sidewall base
169	Peripheral discharge	185.1	.For bottom discharge dispenser
170	With trap chambers		supported on horizontal
171	With sleeve-type discharge		surface
	controller	186	.Foot piece or rest
172	With annular outlet	187	WITH WICK OR ABSORBENT MATERIAL
173	WITH CASING OR SUPPORT		FEED
174	.Pole or extension	188	WITH FLUID TRAP SEAL FOR INLETS
175	.Body carried and/or operated		OR OUTLETS (E.G., VENTS)
-	type	189.01	WITH FLAME ARRESTER
608	.Ambulant	189.02	WITH SIFTER
609	With assembly or disassembly	189.03	.Integral with container
003	feature	189.04	.Plural
610	Dispensing means detachably	189.05	.Including moving mechanism
010	carried upon vehicle	189.06	WITH FILTER (E.G., STRAINER)
611.1	_	189.00	.Portable drainer
	With guide or guide line marker		
611.2	Mortar applying machine	189.08	Plural
612	With height adjustment	189.09	.Associated with vent passage
613	Dispensing means driven or	189.1	.Internally extended outlet pipe
	controlled by surface contact		(e.g., diptube)
614	Ground wheel operated	189.11	.With discharge assistant
	discharge controller		

190 WITH MATERIAL TREATMENT OR 216 AGITATOR AND/OR EJEC CONDITIONING MEANS ON MATERIAL IN EI	
191 WITH TOOL OR IMPLEMENT HANDLE CONVEYER TYPE DIS	
192 COMBINED ASSISTANTS HAVING	
630 FLUID FLOW DISCHARGE CHAMBERS OR TRANS	
631 .Fluid flow generated by manually GROOVES, OR (2) M	MOVABLE TRAP
actuated working member CHAMBERS	
632Flexible working member 217 .Mounted on or in co	onveyer or
633Bellows or bulb movable trap cham	mber
634Telescoping supply container 218Radially movable 6	ejector in
635 .Pressurized aerosol container rotary conveyer o	or trap
636 .From movable trap chamber chamber	
637 Open blast 219Double-ended ejec	
195 WITH GAS AGITATION 220 . Meshing conveyer to	
196 JARRING AND/OR VIBRATING and ejector rotor	
196.1 .Hand manipulable shaker type 221 .Cam-operated agitat	tor or ejector
196.2 Movable outlet element 222 .Pivoted ejector	
196.3Pattern-type outlet with hole 223With pivoted strik	
clearers 224 .Ball or roller form	m agitator or
196.4 Caged outlet element	
196.5Guided or restrained internal 225 .Resilient ejector	
element 226 AGITATOR FOLLOWED BY	Y DISCHARGE
197 .Movable or conveyer-type trap	
chamber CONTROLLER	ISCHARGE
198 .Single outlet bounded by plural 227 .Three or more in se	oriog
vibrating members 228 Flexible or pivoted	
199 .Bottom forming member carried by assist	
reciprocable (including controller movabl	
oscillatable)	ic about all
200 .Member reciprocable (including 229 .Axially aligned, wi	ith axially
oscillatable) transversely of rotary and longit	-
material flow movement	-
201 .Discharge rotor is actuator for 230 .Biasing means const	titutes
vibratable wall agitator	
202 .Supply container wall flexing 231 .Free engagement-type	pe connection
203 Flexible wall 204 SIPHON COMBINED WITH DISCHARGE 232 Connection through	eccentric
204 SIPHON COMBINED WITH DISCHARGE carried by rotary ASSISTANT	assistant or
ASSISTANT controller 205 NONGRAVITY FEED TO TRAP OF	
VACUUM, GRAVITY, OR MANUAL 233 .One rotary and one in the control of the control	reciprocating
REMOVAL TYPE (including oscill	lating)
206 RESTITENT WALL. 234Reciprocating, nor	npivoted
207 Supply container delivering to 235Rotary agitator	
receiving chamber 236 .All rotary	
209 Fluid pressure generating pump 23/Relatively rotatal	ble rings and/
or pulsator and/or removable	
flexible wall closures 238Parallel axes	
210 .With container handle or	
handgrip 240Helix or vane agi	itator and
211 .Internally extending outlet pipe terminal element	
212 .With flow controllers or haling an arms	minal screw,
closures helix, or vane	
213Resilient wall actuated 242Agitator rigidly succeeding device	
214 .Wall deflecting means	=
215 .Nonmetallic	

243	.All reciprocating (including	276	Unitary
	oscillating)	277	Pivoted
244	Relatively movable in parallel	278	Alternatively usable
	planes, nonpivoted	279	Movable or removable baffles
245	Pivoted and nonpivoted		or covers for nonused
	reciprocating elements		assistant
246	Reciprocable axially of outlet	280	Single outlet formed by plural
247	Pivoted only		discharge assistants
248	Unitary	281	Parallel rolls
249	FLOATING PISTON WITH PLURAL OR	282	.With discharge volume varying
217	ALTERNATE DISCHARGE	202	means
250	.With discharge volume varying	283	Plural
	means	284	Trap chambers in series
251	WITH DISCHARGE ASSISTANT (E.G.,	285	Source and assistant relatively
231	IMPELLER, PUMP, CONVEYER,	203	adjustable axially of source
	MOVABLE TRAP CHAMBER, ETC.)		outlet
252	.Plural	286	Sleeve-type discharge
253	With material-operated	200	controller for outlet
233	differential piston	287	Adjustment in relatively
254	Three or more in series	207	movable actuator
255		288	Interchangeable, removable or
	Pumps only	200	<i>y</i> ,
256	Follower combined with casing		selectively usable discharge assistant or element thereof
0.55	enclosed impeller	200	
257	Interconnected with movable	289	Reversible
	nozzle	290	Adjustable deflector for
258	Utilizing fluid pressure and/		conveyer-type discharge
	or motor	0.01	assistant
259	Follower and impeller coaxial	291	Retractable projections
	or parallel and interconnected	292	Interconnected radially movable
260	Follower and impeller coaxial		adjusting means for plural
	or parallel and interconnected		rotor projection or traps
261	Utilizing fluid pressure and/	293	Rotor having plural adjustable
	or motor		parts of rotor form
262	Utilizing fluid pressure and/	294	Substantially coextensive
	or motor		disks and/or rings, axially
263	Utilizing fluid pressure and/or		rotary adjustment
	motor	295	Axially adjustable
264	Rotors with concentrically	296	Disk with axially projecting
	arranged sets of axial trap		pins
	chambers	297	Cup rotor with horizontal
265	In sets		axis
266	With selecting means	298	Groove or trap rotor slidable
267	With common discharge volume		through discharge channel
	varying means	299	With channel blocking means
268	Variable capacity rotors	300	With nonrotary sleeve
269	Container wall sections	301	Rose washer bearing
200	carrying set units	302	Material passage parallel to
270	With interior material		axis of rotation
<u> </u>	discharge guides between units	303	Groove or trap blocking means
271		304	Axial pocket trap
	Rotary	305	Axiai pocket trapMovable or conveyer-type trap
272	Opppositely directed	505	
273	Coaxial only		chamber with capacity varying means
274	Spaced units	306	
275	Reciprocating (including	500	Single inlet-outlet,
	oscillating)		adjustable bottom

307	Wall with straight line	332	.With vent passage for movable
307	movements	332	trap chamber
308	Screw adjusting means	333	.Motor operated
309	Adjustable stroke pump piston,	334	Fluid motor
	pulsator or follower	335	.Actuated by pressure of or
310	With discharge controller		suction on material to be
311	Rotor with discharge		dispensed
311	controller	336	.With biasing means for discharge
312	Discharge passage between		assistant and/or its casing
311	drum-type rotor and controller	337	Joint sealing bias only
313	Biased controller	338	Movable encasing wall
314	Reciprocating nonpivoted	339	For oscillating discharge
	controller		assistant
315	Cup rotor with horizontal	340	For reciprocating piston on
	axis		follower-type impeller
316	Sectional discharge	341	Biasing means within material
	controller		chamber or passage
317	On container side of rotor	342	.With scraper or wiper for or
318	.With bypass or return to supply		carried by discharge assistant
319	.Displacement type	343	.With retractable projections
320	.With movable nozzle	344	.Movable or conveyer-type trap
	interconnected therewith		chamber
321.1	With material supply container	345	With striking or clearing means
	and discharge assistant casing	346	Not part of the supply
321.2	With precompression		container outlet
321.3	With antileak or antisiphon	347	Plural and/or interconnected
	means		with gate at point of trap
321.4	With plural-point inlet to		reentry to supply
	casing	348	Sectional
321.5	Inlet trap (e.g., sump)	349	Yielding
321.6	Aligned discharge assistant,	350	Pivoted
	actuator, container and nozzle	351	Reciprocating
321.7	Container-mounted pump	352	Brush
321.8	With relatively movable	353	Barometric or angle of repose
	actuator	354	With relatively movable cutoff
321.9	Pump casing within supply		carried by trap chamber
	container	355	With cutoff interconnected with
322	.Movable element actuator		trap chamber for operation
	projection through outlet	356	Dipping trap chamber,
323	.With container handle or		nonrotary, nonendless belt
323	handgrip	357	Compound movement
324	With material supply container	358	Oscillating
321	and discharge assistant casing	359	With relatively movable
325	.Insertable cartridge or	333	actuator
323	removable container	360	Intermittent rotary
326	With follower	361	Reciprocating (including
327	Part of cartridge or removable	301	oscillating) conveyer-type
J 2 1	container		trap chamber
328	.With material discharge guide on	362	Oscillating
320	container side of discharge	363	Single inlet-outlet
	assistant	364	Pivot lying in chamber rim
329	Removable or movable depending	365	Plural concentric enlargements
527	cups for rotors	505	on stem
330	.With plural material outlets	366	Single inlet-outlet
331	Of different types	500	Dindre inter-outter
$\supset \supset \bot$	··or arrrerent clabes		

367	Rotary conveyer-type trap chamber	400.5	Simultaneously operative material discharge valve and
368			pump or pulsator operating
	Single inlet-outlet		member
369	Scoop type	400 7	Unitary mounting for fluid
370	Axial inlet and outlet	400.7	1 9
371	Endless belt carried		pressure inlet and material
372	.With material supply container		outlet
	and discharge assistant with	400.8	With pump or pulsator
	casing (e.g., supply container	401	Container-mounted fluid
	and pump)		pressure generating pump or
373	Fluid pressure discharge		pulsator
375	With antileak or antisiphon	402	With piston or pulsator
	means or full-stroke mechanism		holding means
376	With plural-point inlet to	402.1	Valve actuated by nozzle or
	casing		through valve outlet
377	Inlet trap (e.g., sump)	402.11	With actuation disabling means
378		402.12	With discharge orifice
3/6	Aligned discharge assistant,	102.12	contamination quard
250	actuator, container and nozzle	402.13	With container end overcap
379	Telescopic outlet and/or	402.13	-
	discharge-assistant casing	400 14	having actuator
	inlet	402.14	With means to hold valve open
380	Valve outlet	402.15	With container-carried
381	Movable discharge assistant		actuating lever
	casing	402.16	With bypass for filling or
382	Internally extending outlet		charging
	pipe	402.17	With external selector of
383.1	Container-mounted pump		flowpath
383.2	Rotary pump	402.18	Separate inlets for gas and
383.3	Movable material discharge		material in duct to valve
33313	quide	402.19	Alternative flowpath to valve
384	With piston holding means		when inverted
385		402.2	Pressure lock trap chamber
303	Pump or pulsator casing within	402.21	Tilting nozzle
206	supply container	402.21	Nozzle inner end valve headed
386	.Container with follower		
386.5	Nonrigid follower	402.23	Valve stem in nozzle
387	Valved outlet, movable	402.24	Nozzle sliding in or flexing
	discharge guide and/or gas		seal ring
	vent	402.25	Rod actuator pushed through
388	With side wall filling opening		valve outlet
389	Fluid pressure actuated	403	.Film accumulating type
390	Screw actuated	404	.Compound motions
391	Intermittent grip-type actuator	405	.Discharge of material from top
392	Ribbon-type follower and/or		of supply
332	stand actuator	406	.Deformable discharging elements
393	Scoop type	407	Biased
394	.Fluid pressure	408	.Conveyer type with deflector
	-	408.5	
395	Liquid pressure	400.3	.Agitator rigidly mounted on
396	With pressure limiting means	400	movable closure
397	With pressure fluid relieving	409	.Reciprocating (including
	means	44.0	oscillating)
398	Telescopic container and/or	410	.Rotary
	outlet	411	Central discharge
399	With gas pressure supplying	412	Helically arranged projections
	reservoir		(e.g., screws)

413	Screw with terminal outlet only	451	Rigidly interconnected or unitary cutoffs
414	Peripheral surface material	452	Rotary and/or pivoted only
	contact	453	Axially slidable only
415	.Endless belt	454	.With tiltable container trap
416	SIPHON		only
420	DROP FORMERS	455	Supplementary trap
421	.Grooved closure and/or container	456	Single discharge passage
	neck or outlet		forming trap
422	.With valve	457	.Barometric or angle of repose
423	WITH FILM ACCUMULATING MATERIAL		trap chamber
	REMOVERS	457.5	HAND MANIPULABLE SHAKER WITH
424	WITH MATERIAL RETURN TO SUPPLY		REVERSE OUTLET PASSAGE
424.5	SUPPLY CONTAINERS WITH TRAPS	459	STATIONARY AGITATOR
425	.With trap chamber cutoffs	460	FUNNEL-TYPE OUTLET
426	Plural traps, nonserial	461	.Movably interconnected
427	Single rotary cutoff member	462	.Integral
428	Interconnected discharge	463	ROCKABLE OR WEIGHTED
	controllers	464.1	INTERNALLY EXTENDING OUTLET PIPE
429 430	For simultaneous discharge0f different capacities	464.2	.Porous or having plural apertures
431	With plural discharge	464.3	.Movable
432	Plural level discharge volume	464.4	Weighted
102	varying	464.5	Telescopic
433	Independent discharge	464.6	Float
	controllers	464.7	.Including sump
434	With discharge volume varying	465.1	WITH CONTAINER HANDLE OR
	means		HANDGRIPS
435	With means to prevent	466	.Plural handles
	adjustment during discharge	467	Detachable
436	Trap chambers in series	468	.Vent in handle
437	Barometric or angle of repose	469	.Movable handle interconnected
438	With means to change trap chamber volume		with flow controller or closure
439	Movable cutoff of cutoff seat	470	.Handle and actuator for flow
	carrying elements		controller or closure
440	Having straight-line motion		juxtaposed for one handed
441	With container handle or		manipulation
	handgrip	471	Nonpivoted actuator
442	With vent passage for trap		reciprocable lengthwise of
443	With bypass or free-flow		handle
	adjustment	472	Pivoted actuator
444	Single inflow-outflow trap	473	On handle
	passage	474	Generally lengthwise of handle
445	Nonrigidly interconnected	475	.Handle as spout, spout holder or guard
110	cutoffs	475.1	.Handle and spout for hot liquid
446	Free engaging element carried by one cutoff	4/3.1	decanters (e.g., coffee
447	Both reciprocating, nonpivoted	170	servers)
448	With relatively movable	476	SPACED, ALTERNATELY SEATED FLOW
	actuator		CONTROLLERS OR CLOSURES FOR
449	With biasing means	477	SINGLE OUTLET RETARDED OR DELAYED ACTION FLOW
450	For both inlet and outlet		

478	WITH PLURAL OPENINGS OR DISCHARGE GUIDES	507	.Annular, outlet surrounding actuator
479	.Coterminous (barometric)	508	.For swingable elements in
480	.Hand-manipulable shaker,		receptacle interior
100	diverse-type openings (e.g.,	509	.For nonrotary outlet element
	dredge top)		reciprocable axially of
481	.Having flow controllers or		discharge opening
_	closures	510	OUTLET ELEMENT IN ONE WALL, ROD
481.5	With movable flexible or		ACTUATOR THROUGH CONTAINER
	remotely connected vent pipes		INTERIOR AND ANOTHER WALL
482	Plural and/or single for plural	511	WITH RESILIENT BIASING MEANS FOR
-	openings		OUTLET ELEMENT
483	Interlocked controllers and/or	512	.Joint sealing bias only
	closures	513	.For movable tubes, sleeves, or
484	Interconnected for operation		apertured caps
	and/or integral	514	Axially slidable only
485	For plural dispensing outlets	515	.For elements having plural,
486	Variable number exposed and/		diverse motions
	or variably opened	516	.For rotary elements
487	Nonrigidly interconnected	517	.For pivoted and swingable
488	For single passage into which		elements
	plural passages merge	518	.For elements reciprocable
489	Screw-type flow controller or		axially of discharge opening
	closure	519	AXIALLY ROTARY AND LONGITUDINALLY
490	SLITTED RESILIENT DIAPHRAGM OR		MOVABLE TUBES, SLEEVES, OR
	NIPPLE		APERTURED CAPS
491	OUTLET ELEMENT OPERATED BY	520	.Axial discharge
	PRESSURE OF CONTENTS	521	Axial sationary closure plug
492	.Axially slidable tube, sleeve,	522	AXIALLY SLIDABLE TUBES, SLEEVES,
-	or apertured cap		OR APERTURED CAPS
493	Axial discharge	523	.Sectional, telescoping
494	.Spring form, resilient or	524	.With telescopic guide pin
	compressible flow controller	525	.Axial discharge
	or closure	526	MOVABLE MATERIAL DISCHARGE GUIDE
495	.Reciprocable, nonpivoted	527	.Foldable, bendable, collapsible
496	With biasing means		or flexible
497	With additional means to hold	528	Closure type
	against motion	529	With flow controller or closure
498	SNAP-ACTING OUTLET ELEMENT	530	Nonuse securing means
499	.Axially movable tube, sleeve, or	531	.Closure type
	apertured cap	532	With additional flow
500	GRAVITY OR INERTIA OPERATED		controller, closure or seal
	MOVABLE OUTLET ELEMENTS	533	.Swingable
501	MOVABLE OUTLET ELEMENT ACTUATOR	534	Into container recess
	PROJECTING THROUGH DISCHARGE	535	From container interior
	GUIDE	536	With flow controller or closure
502	SECTIONAL FLOW CONTROLLER OR	537	.With flow controller or closure
	CLOSURE	538	NONUSE HOUSING OR SECURING MEANS
503	.Interconnected for relative		FOR DISCHARGE GUIDES
	motion	539	Reversible to extend into or out
504	MOTOR OPERATED OUTLET ELEMENT		of container
505	WITH RELATIVELY MOVABLE ACTUATOR	540	OUTLET SEATED IN CONTAINER RECESS
	FOR OUTLET ELEMENT	541.1	WITH FRANGIBLE CLOSURE FOR OUTLET
506	.Plural flow controllers or		
	closures		

CLASS 222 DISPENSING 222 - 11

541.2	.With cutting or punching or with	572	.Integral with container walls
	cutter or puncher	573	.Reinforced or with container-
	accommodating means		connected brace
541.3	.Closure or closure portion	574	.With folded seam
	broken by pressure of	575	MISCELLANEOUS (E.G., OUTLET
E 4.1 . 4	container content		SHAPES)
541.4	About line or point of weakness		
541.5	.Having reusable closure		
541.6	.About line or point of weakness		
541.7	Adapted for engagement with special tool (e.g., slotted	FOREIGN	ART COLLECTIONS
	key)	FOR 000	CLASS-RELATED FOREIGN DOCUMENTS
541.8	Tool serves as closure		
541.9	<pre>With integral gripping means (e.g., pull tab)</pre>		
542	WITH PACKING-TYPE SEAL FOR OUTLET		
543	WITH SINGLE STRAND, CORD OR WIRE	DIGESTS	
	CONNECTOR FOR REMOVABLE OUTLET ELEMENTS	DIG 1	XEROGRAPHY
544	WITH FLOW CONTROLLER OR CLOSURE		
545	.Plural and/or carried by separably attached element		
546	Cap carried axial plug		
547	.With interior material guide or restrictor		
548	.Rotary, axially		
549	With axial longitudinal motion		
550	And additional pivotal motion		
551	Nonapertured screw cap		
552	Screw plug or disc		
553	Apertured sleeve or cap, nonaxial discharge		
554	Plug		
555	Between fixed plates or flanges		
556	.Pivoted		
557	Pivot axis parallel to axis of		
0	outlet opening		
558	Bail type		
559	.Reciprocatory		
560	Arcuate path		
561	Between fixed plates or flanges		
562	.Cap		
563	.Plug		
564	WITH INTERIOR MATERIAL GUIDE OR RESTRICTOR		
565	SIFTER, SPRINKLER OR PLURAL OPENING PATTERNS		
566	NOZZLES, SPOUTS AND POURING		
	DEVICES		
567	.With separable attaching means		
568	Screw		
569	Abutment for container interior		
570	Rim mounted, interengaging groove and bead or flange		
571	.Antidrip		
	-		