1	CATHODE RAY TUBE CIRCUITS	5.37	Device has particular grid structure
3	.Combined cathode ray tube and circuit element structure	5.38	With particular collector or
3.5	Traveling wave tube with delay-		anode structure
	type transmission line	5.39	Plural hollow devices
3.6	Line with plural	5.41	Accelerating or decelerating
	characteristics or plural lines		the ray between the hollow devices
4	Inductor or distributed	5.42	Devices excited to
-	parameter-type inductive		accelerate the ray across their gaps; e.g., synchrotrons
_	structure	5.43	Devices of different
5	Ray passes in or through a	3.43	resonance frequency
	hollow distributed parameter	5.44	Feedback connection between
- 44	device	3.44	the hollow devices
5.11	With a secondary emission	5.45	Three hollow devices
- 10	stage	5.46	Device tunable
5.12	Secondary emission passes		
	through or in the hollow	5.47	Gang tuned hollow devices
	device	5.48	Device has a flexible wall
5.13	With a magnetron	5.49	Three hollow devices
5.14	Plural rays pass through or in the hollow device	5.51	Plural gaps in the hollow device
5.15	Rays merged at the hollow	5.52	Device has a re-entrant
	device		portion surrounding the ray
5.16	Plural hollow devices	5.53	Device tunable
5.17	Feedback by ray	5.54	Device has a flexible wall
5.18	Ray returns to the hollow device; e.g., reflex type	7	Connected to the deflecting electrodes
5.19	By same path and/or to same	8	.Compensating for stray
	aperture		deflecting fields
5.21	Device tunable	8.51	.Pulse storing
5.22	Device has a flexible wall	8.61	Plural cathode-ray tubes or
5.23	Thermally controlled		ray-type tubes
5.24	Deflecting or reflecting the	9	.Plural cathode-ray tubes in the
	ray		circuit
5.25	Ray sweeps over an aperture or slot in the hollow device	10	.With radiant energy sensitive control means
5.26	Device deflects the ray	11	With secondary emission stage
5.27	Plural hollow devices		in the cathode-ray tube
5.28	Plural hollow devices	11.5	Color convergence controlled
5.29	Ray has appreciable		by photodetector
J • Z J	transverse electrical	12.1	.With secondary emission stage in
	dimension and/or significant		the cathode-ray tube
	shape	13.1	.Plural ray-type tube
5.31	Hollow ray	13.11	Storage tubes
5.32	Disk-shaped ray	14	.Plural concentrating,
5.33	Device also a ray anode or		accelerating, and/or de-
J.JJ	cathode		accelerating stages
5.34	Focusing and/or concentrating	15	Three or more stages
· - -	the ray	16	Intermediate stage at lower
5.35	By magnetic field		potential
5.36	Device removable from its		
	grids		

17	With ray-deflecting stage interposed between plural	376	With post deflection phosphor selection
	concentrating or accelerating	377	With marker
	<pre>and/or de-accelerating stage or co-extensive with one such</pre>	378	Circular, spiral, or radial sweeps
364	stage .Cathode-ray deflections circuits	379	With additional control of cathode ray
365	Symbol generator	380	Control only at turn-on or
366	For flat cathode-ray tube		turnoff of circuit
368.11	Including color convergence control	381	Circuits control grid-cathode circuit of tube
368.12	Including specified signal	382	With focusing of ray
	storage (e.g., memory,	382.1	For television
	register, etc.)	383	Intensity control of ray
368.13	Interpolation	384	Ray blanking
368.15	Including electrostatic	385	Ray unblanking
	element (e.g., electrode,	386	With ray control responsive
	lens, etc.)		to deflection circuit
368.16	Offset apertures in plural	387	Including feedback circuit
	sequential electrodes	388	Plural feedback circuits
368.17	Including signal delay	389	Negative feedback
	circuitry	390	Tube-type circuit
368.18	Including specified waveform	391	Plural deflection circuits
	generating circuitry	392	Plural waveform display
368.19	By nonlinear device (e.g.,		circuits
	square law device, diode,	393	Interconnected sweep circuits
	etc.)	394	Plural deflections in one
368.21	Parabolic waveform		plane
368.22	By integrating of signal	395	Plural potentials or currents
368.23	By multiplying of signal		applied to deflection member
368.24	Static convergence feature	396	Push-pull deflection circuit
368.25	Including core or winding	397	Coil-type circuit
	structure	398	With cathode-ray centering
368.26	Adjacent to or integral with	399	Deflection coil circuit
	deflection winding or housing	400	Including a saturable element
260 07	structure therefor	401	Including a temperature
368.27	Including particular magnetic		responsive element
260 20	field distribution	402	Including a voltage dependent
368.28	Including plural cores or		resistor
267	coils	403	Including an amplifier
367	Including a digital-to-analog device	404	Tube-type amplifier
369		405	With transformer connecting
369	Target controls deflection circuit		amplifier to coil
370		406	With power recovery circuit
370	With ray deflection distortion correction or reduction	407	With diode or amplifier
371	By modulation of deflection		across coil
3/1	_	408	Including solid-state switch
372	waveform	409	Including a discharge device
J 1 Z	For cathode-ray tube having	410	With device discharging a
373	plural targets Targets radially about cathode		condenser
374	Targets radially about cathode	30	.Ray modulation
	Targets in single plane	411	.Power supply from deflection
375	For plural phosphor target tube		circuit source

500	HIGH ENERGY PARTICLE ACCELERATOR TUBE	40	.Electrode formed as inductive impedance
501	.Magnetic field acceleration means	41	.Inductive impedance connected between electrodes of a
502	Cyclotron		discharge device load
503	Synchrotron	42	Connected to plural anodes or
504	Betatron		plural cathodes
505	Linear accelerator (Linac)	43	Connected to control electrode
506	.Electrostatic accelerator means	44	With capacitive impedance
507	.With injection or extraction means		connected to the control electrode
32	COMBINED LOAD DEVICE OR LOAD	45	With diverse-type impedance
	DEVICE TEMPERATURE MODIFYING	46	.Filament, electric heater, or
	MEANS AND ELECTRICAL CIRCUIT DEVICE STRUCTURE		resistance in shunt with the discharge electrodes of a
33	.Portable self-contained	4.5	discharge device load
34	.With antenna	47	Automatic switch in the shunt
35	.Plural discharge device loads		circuit
36	Series connected discharge devices	48	Cathode or cathode heater in the shunt circuit
37	Cathode-anode circuit connected	49	.Filament or electric heater in
	to the discharge control		series with a discharge device
	electrode of another discharge		load
	device load (e.g., cascade)	50	.Load device temperature-
38	Corresponding electrodes		modifying means combined with
	connected by a circuit		or forming circuit impedance
	<pre>impedance (e.g., push-pull)</pre>		means
39	.Discharge device load with	51	.Plural circuit elements
	distributed parameter-type	52	Plural impedance elements
	transmission line (e.g., wave-	53	Diverse types of impedances
	guide, coaxial cable)	54	Plural inductive impedances
39.3	Traveling wave type with delay-	55	.Electric generator or
	type transmission line		piezoelectric device
39.51	.Distributed parameter resonator-	56	.Discharge device load
	type magnetron	57	Discharge device and
39.53	With output-coupling means		transformer
39.55	Variable tuning	58	Discharge device and circuit
39.57	Electron emission type		impedance
39.59	Thermal or magnetic actuator	59	Impedance connected between
39.61	Movable tuning element (e.g.,		two electrodes
03101	slug)	60	Impedance connected to an
39.63	With control electrode,		auxiliary starting electrode
33.03	secondary emitter, or	61	Discharge control discharge
	auxiliary anode or cathode	V =	device
39.65	Having diverse size resonators	62	Inductive impedance
39.67	Tubular anode with eccentric or	63	Discharge control discharge
	axially displaced cathode	03	load
39.69	With strapping for resonant	64	.Multiple filament load devices
	structure	65	Automatic substitution of the
39.71	Magnetic field generating and		filament
	pole structure	66	Series connected filaments
39.73	Interdigital electrode	67	Diverse resistance filaments
39.75	Anode with plural cavities	68	Three or more controlled
39.77	With resonant cavity coupled to		filament circuits
	anode		

69	Plural filaments energized in parallel	98	.Plural cathodes or heaters in the load device
70	.Load device and transformer	99	Series connected cathodes or
71	.Load device and impedance		heaters
72	.Load device and periodic	100	Thermostatic switch in the
7 4	electric switch	100	series circuit
73	.Electric switch inside evacuated	101	.Discharge device and/or
7 3	or gas filled envelope	101	rectifier in the cathode or
74	.Automatic shunt circuit closing		heater circuit
/ 4	or cut-out switch	102	.Delayed application of the
75	Shunt circuit closing	102	discharge potential
76	SPECIAL APPLICATION	103	With surge generator in the
77	.Vehicle	_00	discharge circuit
78	Vehicle motor or vehicle motion	104	Thermostatic controlled
70	driven generator	104	delaying means
79	5	105	.Pulsating or A.C. supply to the
19	Vehicle or engine speed	103	cathode or heater circuit
0.0	controlled	106	Automatic cut-out or voltage
80	Load device controller combined	100	regulator in the cathode or
0.1	with vehicle controller		heater circuit
81	Steering mechanism controlled	107	.Automatic cut-out or voltage
82	Head light systems	107	regulator in the cathode or
83	Alternate circuit closing		heater circuit
84	.Door or closure controlled load	108	CONFINED GAS OR VAPOR-TYPE LOAD
0.4.54	device	100	DEVICE WITH PRESSURE
84.51	PULSE STORING SYSTEMS OF THE		REGULATING MEANS
	GASEOUS DISCHARGE-TUBE TYPE	109	.Auxiliary discharge type
84.61	.With plural cathode or anode	110	.Valve controlled
	+1160	$\pm \pm 0$	· vaive controlled
	tube	_	
85	WITH ELECTROMAGNETIC WAVE	111.01	DISCHARGE DEVICE LOAD WITH FLUENT
85	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR	_	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE
	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS	111.01	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE
85	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE	_	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material
86	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY	111.01	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply
	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode	111.01 111.11 111.21	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating
86 87	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution	111.01 111.11 111.21 111.31	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode
86	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE	111.01 111.11 111.21 111.31 111.41	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic field
86 87 88	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE	111.01 111.11 111.21 111.31 111.41 111.51	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction type
86 87	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load	111.01 111.11 111.21 111.31 111.41 111.51 111.61	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAcceleration
86 87 88 89	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment
86 87 88	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion source
86 87 88 89	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion source .Gas ionization type (e.g., ion
86 87 88 89 90	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion source .Gas ionization type (e.g., ion pump or gauge source)
86 87 88 89	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion source .Gas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE
86 87 88 89 90	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion source .Gas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER
86 87 88 89 90	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systems
86 87 88 89 90 91	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load
86 87 88 89 90 91 92 93	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices
86 87 88 89 90 91	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generating .With extraction electrode .With magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load
86 87 88 89 90 91 92 93 94	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER SUPPLY CIRCUIT	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112 113 114 115	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load device
86 87 88 89 90 91 92 93 94 95	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER SUPPLY CIRCUIT .Plural load device systems	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load deviceAutomatic cut-out or voltage
86 87 88 89 90 91 92 93 94	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER SUPPLY CIRCUIT .Plural load device systemsSeries connected cathodes or	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112 113 114 115	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load deviceAutomatic cut-out or voltage regulator for the heater
86 87 88 89 90 91 92 93 94 95 96	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER SUPPLY CIRCUIT .Plural load device systemsSeries connected cathodes or heaters	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112 113 114 115 116	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load deviceAutomatic cut-out or voltage regulator for the heater circuit
86 87 88 89 90 91 92 93 94 95	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER SUPPLY CIRCUIT .Plural load device systemsSeries connected cathodes or heatersPulsating or A.C. supply to the	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112 113 114 115	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load deviceAutomatic cut-out or voltage regulator for the heater circuit .Automatic control of the
86 87 88 89 90 91 92 93 94 95 96	WITH ELECTROMAGNETIC WAVE RADIATION PREVENTING OR SHIELDING MEANS AUTOMATIC SUBSTITUTION OF THE POWER SUPPLY .With load device or electrode substitution AUTOMATIC SUBSTITUTION OF THE LOAD DEVICE OR ELECTRODE .Plural substitution of load devices or electrodes .Plural load devices with selective substitution of load device or electrode .Over-voltage or over-current controlled substitution .Diverse-type load device or electrode substituted .With current shifting switch WITH CATHODE OR CATHODE HEATER SUPPLY CIRCUIT .Plural load device systemsSeries connected cathodes or heaters	111.01 111.11 111.21 111.31 111.41 111.51 111.61 111.71 111.81 111.91 112 113 114 115 116	DISCHARGE DEVICE LOAD WITH FLUENT MATERIAL SUPPLY TO THE DISCHARGE SPACE .With tangential fluent material supply .Plasma generatingWith extraction electrodeWith magnetic fieldInduction typeAccelerationPlasma containment .Electron or ion sourceGas ionization type (e.g., ion pump or gauge source) WITH LOAD DEVICE TEMPERATURE MODIFIER .Plural load device systemsElectric heater for the load devices .Electric heater for the load deviceAutomatic cut-out or voltage regulator for the heater circuit

118	.Load device circuit controlled	151	.Load device irradiating the
	by the temperature modifying		radiant energy responsive
	medium		device
119	WITH AUTOMATIC SHUNT AND/OR	152	.Plural load devices
	CUTOUT	153	Selective energization of the
120	.Combined with signal, indicator,		load devices
	or alarm	154	Selective electric switch
121	.Plural load device systems		controlled by the radiant
122	Series connected load devices		energy responsive device
123	.Plural shunts and/or cut-outs	155	.Plural radiant energy responsive
124	.Auxiliary electrode controlled		devices
125	.Shunt circuit closing	156	.Radiant energy control of an
126	With compensating impedance		electric discharge device in
127	.Supply circuit current and/or		the supply circuit of the load
	potential actuated switch		device
128	Plural switch operating means	157	.Discharge control discharge
129	WITH SIGNAL, INDICATOR, OR ALARM		device load controlled by the
130	.Plural load device systems		radiant energy responsive
131	Selective indication of the		device
	load device	158	.Radiant energy controlled
132	Plural signals, indicators, or		regulation of the current
	alarms		supply for the load device
133	.Plural signals, indicators, or	159	.Electric switch controlled by
133	alarms		the radiant energy responsive
134	.Radiant energy responsive		device
131	control type	160	PLURAL POWER SUPPLIES
135	.Discharge device and/or	161	.Plural load devices
133	rectifier in the signal	162	Diverse type load devices
	circuit	163	Simultaneous application of
136	.Electrically operated switch		diverse type current supplies
130	controlling the signal circuit		to a load device
137	POLYPHASE A.C. SUPPLY	164	Series connected current
138	.M phase to N phase (e.g., phase		supplies
130	splitters)	165	Diverse type current supplies
139	_	166	Simultaneous application to a
140	Polyphase supply circuitPhase multiplying		load device
141	1 1 3	167	.Plural cathode and/or anode load
141	.Transformer in the supply		device
142	circuit	168	Diverse type current supplies
142	With interphase transformer in		to auxiliary and principal
1 1 2	the supply circuit		electrodes
143	Convertible transformer	169.1	Diverse-type energizing or bias
1 1 1	connections		supplies to different
144	Plural load devices		electrodes
145	Plural cathode and/or anode	169.2	Including shifting of
4.6	load device		register, counter, or display
146	.Plural discharge control	169.3	Electroluminescent device
4.45	discharge device load devices	169.4	Gas display panel device
147	.Plural cathode and/or anode	170	.Series connected current
4.4.6	discharge device load	-	supplies
148	Discharge control discharge	171	.Discharge device and/or
4.45	device	· -	rectifier in one of the supply
149	WITH RADIANT ENERGY SENSITIVE		circuits
	CONTROL MEANS	172	.Periodic switch in one of the
150	.Radiant energy responsive load		supply circuits
	device		

173	.Condenser in one of the supply circuits	200 R	DISCHARGE DEVICE AND/OR RECTIFIER IN THE SUPPLY CIRCUIT
174	.Plural diverse pulsating or A.C.	201	.Plural load device systems
	supplies	202	.Plural cathode and/or anode
175	.Diverse-type current supplies		discharge device load
176	Simultaneous application to the	203	Discharge device or rectifier
	load device		in the auxiliary starting
177	LOAD DEVICE IN THE PRIMARY AND		electrode circuit
	SECONDARY CIRCUIT OF THE	204	Discharge control discharge
	SUPPLY TRANSFORMER		device in the auxiliary
178	PLURAL DIVERSE-TYPE LOAD DEVICES		electrode circuit
179	.Series connected diverse-type load devices	205	.Plural discharge devices and/or rectifiers in the supply
180	Plural diverse discharge device		circuit
	load	206	.Discharge device and/or
181	Asymmetrical discharge device		rectifier in the primary
	load		circuit of the supply
182	.Electric discharge device load		transformer
183	Plural diverse discharge device	207	.Discharge device and/or
	loads		rectifier in shunt to the load
184	THREE OR MORE LOAD DEVICES	0.00	device
	CONNECTED BETWEEN DIVERSE	208	.Discharge control discharge
	PAIRS OF PAIRED CONDUCTORS	000 7	device in the supply circuit
185 R	PLURAL SERIES CONNECTED LOAD	200 A	.Flashers
	DEVICES	209 R	PERIODIC SWITCH IN THE SUPPLY
186	.Periodic switch in the supply	210	CIRCUIT
100	circuit	210	.Plural load device systemsDistributor type periodic
187	.Condenser in the supply circuit	211	switch means
188	Condenser in shunt to load and	212	Transformer in the supply
100	supply	212	circuit
189	.Discharge device loads	213	Distributor switch means in
190	Asymmetrical discharge device loads	213	the primary circuits of plural
191	.Convertible to parallel		transformers
191	connected	214	With additional periodic
192	.Combined with parallel connected		switch in the primary circuit
172	load device	215	With additional periodic
193	.Electric switch controlled load		switch in the distributor
100	device		switch means circuit
185 S	.Christmas lights	216	Plural electrically operated
194	REGULATION OF THE CONTROL CURRENT		switches
	AND/OR POTENTIAL APPLIED TO	217	Periodic switch selectively
	DISCHARGE CONTROL DISCHARGE		connectable to plural load
	DEVICE LOADS BY PHASE SHIFTING		device circuits
	MEANS	218	.Magnetoelectric generator supply
195	.Plural load device systems	219	.Periodic switch in the primary
196	Inverse parallel connected		circuit of the supply
	asymmetric load devices		transformer
197	Discharge control discharge	220	Plural transformers in the
	device in the control circuit	0.04	supply circuit
198	Discharge control discharge	221	Secondary conductively
	device in the control circuit	222	connected to the primary
199	.Discharge control discharge	222	Plural interrupted transformer
	device in the control circuit		coil circuits

223	Condenser or inductance in the primary circuit	245	Resistance in the condenser
224	.Impedance or current regulator	227 A	.Arc machining
	in the supply circuit	246	PULSATING OR A.C. SUPPLY
225	.Periodic switch cut-out	247	.With power factor control device
226	.Plural periodic switches or	248	.Induction-type discharge device
	multiple contact periodic		load
	switch	249	.Potential node-type discharge
209 Т	.Transistorized ignition systems	-	device load
209 CD	.Capacitor dischargeneous	250	.Plural load device systems
	ignition systems	251	Inverse parallel connected
209 M	.Miscellaneous ignition systems		asymmetrical discharge device
209 PZ	.Piezoelectric ignition systems		loads
209 SC	.Silicon controlled rectifier	252	Discharge control discharge
	ignition		device loads
227 R	CONDENSER IN THE SUPPLY CIRCUIT	253	Full wave systems with
228	.Plural load device systems		asymmetrical discharge device
229	Condenser connected to plural		loads
	cathodes or anodes of	254	Transformer in the supply
	asymmetrical discharge device		circuit
	loads	255	Plural transformers in the
230	Discharge control discharge		supply circuit
	device loads	256	Primaries in series
231	Plural series connected	257	With plural secondary or
	condenser and load device		tapped secondary
	circuits	258	Inductance in the supply
232	Condenser in shunt to load and		circuit
	supply	259	Variable inductance
233	.Plural cathode and/or anode	260	.Plural cathode and/or anode
	discharge device load		discharge device load
234	Condenser in the auxiliary	261	Auxiliary starting electrode-
	starting electrode circuit		type discharge device load
235	Condenser connected to plural	262	Transformer or auxiliary
	cathodes or anodes		winding in the auxiliary
236	.Electromagnetic influenced		electrode circuit
	discharge device load	263	Inductance or potential surge
237	.Discharge control discharge		generator in the auxiliary
000	device load	0.6.4	electrode circuit
238	Condenser in the control	264	Impedance in the auxiliary
220	circuit	265	electrode circuit
239	.Transformer in the condenser	265	Full wave-type system
0.40	load device circuit	266	Transformer in the supply
240	.Electric switch in the condenser circuit	267	circuit
0.41 D		267	.Electromagnetic influenced
241 R	.Condenser in shunt to the load	260	discharge device load
242	device and the supplyWith an inductance in the	268	.Discharge control discharge device load
242	circuit	269	
243	Inductance in series with the	209	With plural discharge control devices
243		270	
241 P	load device and the supplyPhotoflash	270	Plural control potentialsPlural pulsating and/or A.C.
241 F 241 S	Strobe lights	211	potentials
241 5	.Inductance in the condenser	272	Rectifier and/or discharge
277	circuit	2 / 2	device in the control circuit

273	With condenser in the control circuit	308	Regulator responsive to plural conditions
274	Transformer in the control	309	Thermal responsive regulator
	circuit	310	Shunted impedance-type
275	Condenser in the control		regulator
	circuit	311	Variable impedance-type
276	.Transformer in the supply		regulator
	circuit	312	PLURAL LOAD DEVICE SYSTEMS
277	Plural transformers in the	313	.Electric switch in the supply
0.77.0	supply circuit	0.4.4	circuit
278	Three or more coil-type	314	Pre-selectable switching
279	transformers	315	systems
213	Current regulator in the primary circuit	313	Electrically controlled load device switch
280	Convertible to inductance	316	Keyboard or pattern controlled
281	Relatively movable core and	310	switch
202	coil-type transformer	317	Three or more controlled load
282	Regulating transformer		device circuits
283	.Inductance in the supply circuit	318	Group control systems
284	Variable inductance	319	Four or more groups
285	Relatively movable core and	320	Plural switches
203	coil-type inductance	321	Master circuit closing switch
286		322	<u> </u>
200	Biased movable part with supply current controlled	323	Alternate circuit closing
	movement	323	.Sequential starting .Plural discharge device loads
287		_	5
207	.Periodic-type current and/or voltage regulator in the	325	Discharge control discharge
	supply circuit	326	device loads DISCHARGE DEVICE LOAD
	buppiy circuit		
200			
288	THREE OR MORE WIRE DISTRIBUTION SYSTEMS	327	.Discharge drawing-type discharge device
288 289	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN		.Discharge drawing-type discharge
289	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT	327	.Discharge drawing-type discharge device
	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the	327 328 329	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tilting
289	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit	327 328	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled
289 290 291	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION	327 328 329 330	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode type
289	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern	327 328 329	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting
289 290 291 292	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator	327 328 329 330 331	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrode
289 290 291 292 293	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems	327 328 329 330	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the
289 290 291 292 293 294	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation	327 328 329 330 331	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device
289 290 291 292 293	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively	327 328 329 330 331 332	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuit
289 290 291 292 293 294 295	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuits	327 328 329 330 331	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the
289 290 291 292 293 294 295	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuitsInverse control of load devices	327 328 329 330 331 332	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device
289 290 291 292 293 294 295 296 297	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulation	327 328 329 330 331 332	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit
289 290 291 292 293 294 295	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected	327 328 329 330 331 332	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuitPlural cathode and/or anode
289 290 291 292 293 294 295 296 297 298	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected regulators	327 328 329 330 331 332 333	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device load
289 290 291 292 293 294 295 296 297 298	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected regulators .Plural regulators	327 328 329 330 331 332	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrode-
289 290 291 292 293 294 295 296 297 298 299 300	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuits .Inverse control of load devices .Automatic regulation .Mechanically connected regulators .Plural regulators .Current generator control	327 328 329 330 331 332 333 334 335	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge device
289 290 291 292 293 294 295 296 297 298 299 300 301	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuits .Inverse control of load devices .Automatic regulation .Mechanically connected regulators .Plural regulators .Current generator control .Plural automatic regulators	327 328 329 330 331 332 333	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge devicePlural auxiliary starting
289 290 291 292 293 294 295 296 297 298 299 300 301 302	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuits .Inverse control of load devices .Automatic regulation .Mechanically connected regulators .Plural regulators .Current generator control .Plural automatic regulators .Current generator control	327 328 329 330 331 332 333 334 335 336	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge devicePlural auxiliary starting electrode
289 290 291 292 293 294 295 296 297 298 299 300 301 302 303	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuits .Inverse control of load devicesAutomatic regulation .Mechanically connected regulators .Plural regulators .Current generator control .Plural automatic regulators .Current generator control .Control of the prime mover	327 328 329 330 331 332 333 334 335	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge devicePlural auxiliary starting electrodeDiverse potentials for the
289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuits .Inverse control of load devicesAutomatic regulation .Mechanically connected regulators .Plural regulators .Current generator control .Plural automatic regulators .Current generator control .Control of the prime mover .Plural field-type generator	327 328 329 330 331 332 333 334 335 336 337	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge devicePlural auxiliary starting electrodePlural auxiliary starting electrodeDiverse potentials for the discharge electrodes
289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulation .Regulator selectively connectable to plural circuits .Inverse control of load devicesAutomatic regulation .Mechanically connected regulators .Plural regulators .Current generator control .Plural automatic regulators .Current generator control .Control of the prime mover	327 328 329 330 331 332 333 334 335 336	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge devicePlural auxiliary starting electrodePlural starting electrodesElectromagnetic influenced
289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected regulators .Plural regulatorsCurrent generator controlPlural automatic regulators .Current generator controlControl of the prime moverPlural field-type generatorThree or more fields .Regulator in shunt to the load	327 328 329 330 331 332 333 334 335 336 337 338	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge devicePlural auxiliary starting electrodePlural starting electrodesDiverse potentials for the discharge electrodesElectromagnetic influenced discharge device
289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected regulators .Plural regulatorsCurrent generator controlPlural automatic regulators .Current generator controlControl of the prime moverPlural field-type generatorThree or more fields	327 328 329 330 331 332 333 334 335 336 337	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrode-type discharge devicePlural auxiliary starting electrodeDiverse potentials for the discharge electrodesElectromagnetic influenced discharge deviceDischarge control discharge
289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305	THREE OR MORE WIRE DISTRIBUTION SYSTEMS SURGE GENERATOR OR INDUCTANCE IN THE SUPPLY CIRCUIT .Circuit interrupter in the inductance circuit CURRENT AND/OR VOLTAGE REGULATION .Keyboard operated or pattern controlled regulator .Pre-selectable regulator systems .Plural load device regulationRegulator selectively connectable to plural circuitsInverse control of load devicesAutomatic regulationMechanically connected regulators .Plural regulatorsCurrent generator controlPlural automatic regulators .Current generator controlControl of the prime moverPlural field-type generatorThree or more fields .Regulator in shunt to the load	327 328 329 330 331 332 333 334 335 336 337 338	.Discharge drawing-type discharge deviceTilting discharge deviceElectrically controlled tiltingAuxiliary starting electrode typeMovable auxiliary starting electrodeAutomatic switch in the electrode moving device circuitAutomatic cut-out for the electrode moving device circuit .Plural cathode and/or anode discharge device loadAuxiliary starting electrodetype discharge devicePlural auxiliary starting electrodePlural starting electrodesDiverse potentials for the discharge electrodesElectromagnetic influenced discharge device

340	.With de-ionizing means in the cathode-anode circuit	DIG 1	1	FLUORESCENT LAMP CIRCUITS WITH MORE THAN TWO PRINCIPLE
341	.With plural discharge control			ELECTRODES
	devices	DIG 2	2	HIGH FREQUENCY STARTING OPERATION
342	Diverse types			FOR FLUORESCENT LAMP
343	Plural electromagnetic devices	DIG 3	3	CIRCUIT FOR ION GAUGES AND
344	.Electromagnetic influenced			PRESSURE GAUGES
	discharge device	DIG 4	4	DIMMING CIRCUIT FOR FLUORESCENT
345	Rail-type discharge device load			LAMPS
346	Plural current supply to the	DIG 5	5	STARTING AND OPERATING CIRCUIT
	electromagnet			FOR FLUORESCENT LAMP
347	Series connected with the load device	DIG '	7	STARTING AND CONTROL CIRCUITS FOR GAS DISCHARGE LAMP USING
348	Pulsating or A.C. supply to the electromagnet			TRANSISTORS
349	.Discharge control discharge device load			
350	Plural control currents and/or potentials			
351	Plural pulsating or A.C. currents and/or potentials			
352	Rectifier and/or discharge device in the control circuit			
353	With condenser in the control circuit			
354	Transformer in the control circuit			
355	Condenser in the control circuit			
356	Inductance in the control circuit			
357	.Movable electrode discharge device			
358	.Plural gases or vapors in the discharge device			
359	PYRO-ELECTRIC DEVICE LOAD			
360	TIME-CONTROLLED			
361	PLURAL CONTROL STATIONS			
362	ELECTRIC SWITCH IN THE SUPPLY			
	CIRCUIT			
363	MISCELLANEOUS SYSTEMS			

FOREIGN ART COLLECTIONS

FOR 000 CLASS-RELATED FOREIGN DOCUMENTS

DIGESTS